Position-Faithful Merge Tree Maps: Certified Bounds and Optimal Layouts

Category: Research




Figure 1: North Atlantic pressure minima (ERA5, 118 half-day steps). (a) One time step with five minima A–E, lettered from west to east; their positions along the reference axis are their references q_i. (b) A layout that optimizes hierarchy and time, in the style of TMTM, draws all five near the middle of the axis; triangles mark the references and lines connect them to the drawn positions. (c) Our layout keeps the merge tree exactly and stays as close to the references as the hierarchy allows: the worst displacement in this step falls from 55.4% to 22.6% of the canvas. Only C is displaced: it joins the other four minima only at the top of the tree, so an exact map must place it outside their block, and the hierarchy forces an order error of at least 20.6% (Sect. 5).

Abstract

Merge tree maps summarize a time-varying scalar field in one image: every time step becomes a one-dimensional profile whose basins are the features of the field, stacked along time. Existing maps keep the merge hierarchy and temporal coherence, but the axis then carries little spatial meaning, so a storm in the west may be drawn east of one in the east. We ask how close such a map can stay to a fixed spatial reference, such as longitude, without misrepresenting the hierarchy. We prove closed-form lower bounds on the displacement that any map preserving the merge tree must incur, with and without feature widths, and chain-aware bounds for maps whose merge levels may err by a declared budget ε. These bounds hold for every method, including TMTM and ST-MTM. We give layouts that attain them: a midpoint ordering, a width-aware search, and a budgeted ordering whose exact merge-level error is checked, combined with optimal barriers and a capped quadratic placement. A cross-method comparison on 917 frames from five planar and two volumetric sequences shows that most of the order error of existing maps is avoidable, that sorting by reference alone changes merge levels by up to 59% of the scalar range, and that our exact maps lower the motion error of both previous methods on every sequence, while ST-MTM keeps the better distance preservation. Each of our maps reports two certified numbers, how far it moves features and how far it changes the hierarchy, and marks every changed merge on the map.

Index Terms: Merge trees, temporal scalar fields, topology-based visualization, one-dimensional layout, lower bounds.

1 Introduction

Static summaries of time-varying scalar fields show a whole sequence at once, without relying on memory across animation frames [1, 43, 47]. Merge tree maps build such summaries from topology [11, 31]. At each time step the merge tree of the field is linearized into a one-dimensional profile whose basins are the extrema and whose barriers are their merge levels; the profiles are stacked along time, so every feature becomes a band and the nesting of bands shows how features connect.

The cost of this compression is the meaning of the axis. Temporal Merge Tree Maps (TMTM) order features by a tree traversal aligned across time [31]; Spatiotemporal Merge Tree Maps (ST-MTM) add pairwise distances [11]. Neither ties a feature to a coordinate the analyst already knows, and in Fig. 1b five pressure systems spread over the whole North Atlantic are drawn within a fifth of the axis. Hovmöller diagrams make the opposite choice [26]: the axis is longitude, which is immediately readable, but the hierarchy is lost. This paper asks how close a merge tree map can come to both.

The question has a precise answer. If the merge tree is kept intact, every subtree occupies one contiguous block of the axis; two sibling subtrees whose reference ranges overlap cannot both stay at their references. We show that this conflict determines the unavoidable displacement in closed form, that it is attainable, and that most of the displacement of existing maps lies above it (Fig. 1c). When the analyst accepts a bounded change of merge levels, the same reasoning bounds how much position can be recovered, and the change is shown on the map.

Our contributions are:

- **Certified lower bounds** on the displacement of any merge tree map that keeps the hierarchy: a closed-form bound on the order error and a width-aware bound on the worst displacement, valid for every method including TMTM and ST-MTM, and chain-aware bounds for maps with a merge-level budget ε (Sect. 5).

- **Layouts that attain them**: midpoint ordering, a width-aware

search and a budgeted ordering with exact merge-cost checks, combined with optimal barriers and a capped quadratic placement; every map reports its position and merge-level errors and marks changed merges (Sect. 6).

- **One formulation** with explicit position and topology budgets, in which TMTM and ST-MTM are exact-topology instances; given their own leaf orders, their layouts are reproduced exactly (Sect. 3).

- **A cross-method comparison** of five methods on 917 frames from seven sequences, including two volumetric ones, and a case study with error disclosure (Sect. 7).

We study faithfulness, not readability; a perceptual study is future work.

2 Related Work

Linearizing space and time. Space–time cubes and their flattenings organize temporal visualization [2]. Hovmöller diagrams keep one spatial coordinate [26]; space-filling curves, geographic orderings and data-driven projections linearize the whole domain [10,19,21,51,56], and MotionRugs and related summaries order moving entities [7,44,48,53]. None of them represents the merge hierarchy. Storyline layouts solve a related time×1D problem, minimizing crossings and wiggles, partly by quadratic programming [12,33,45]; their entities have neither a fixed coordinate nor nesting.

Drawing merge and contour trees. Topology-based visualization is surveyed by Heine et al. [22]. Contour trees have been drawn in the plane [23], as terrains [49], with geometry-preserving terrain layouts [4], and as one-dimensional landscape profiles [40], which Herick et al. make temporally coherent [24]. Mergemaps argue that nesting is hard to read in profiles and use treemaps [28]. TMTM introduced the time×1D merge tree map [31] and ST-MTM made it geometry-aware [11] (Fig. 2). Tracking graphs show feature evolution without a spatial axis [30,34,35,39,52]. We keep the TMTM/ST-MTM map and its renderer and change what the layout optimizes; our bounds apply to all such profile layouts.

Ordering the leaves of a tree. Optimal leaf ordering selects one of the 2^{n-1} tree-consistent orders to minimize adjacent dissimilarity [3,16]. Closest to our question are reordering a tree towards a given leaf order [8] and one-sided tanglegrams [13,18,27]; geophylogenies combine tree constraints with map positions [29]. These works count inversions, crossings or summed displacement; minimizing the number of inversions against a target order is NP-complete for trees of unbounded degree [8]. We measure the *maximum* displacement in reference units, which has a closed form, and extend it to interval widths, anchor slack and controlled violations of the tree.

Ordered merge trees and distances. A merge tree with a leaf order is equivalent to a one-dimensional curve; Beurskens et al. define a monotone interleaving distance for such ordered merge trees [6], visualized by ParkView [5]. For labelled merge trees, the ℓ_∞ distance between cophenetic matrices is an interleaving distance [38], used as the labelled interleaving distance [20]; it bounds the unlabelled interleaving distance [20], which bounds the bottleneck distance of persistence diagrams [37]. Geometry-aware and Wasserstein comparisons extend these distances [41,54,55]. Fitting an ultrametric under ℓ_∞ error has a closed form [17]; our optimal barriers are such a fit under a fixed leaf order.

3 Background and Problem

Merge tree maps. A sequence of scalar fields f_t on a two- or three-dimensional domain gives, per time step, a merge tree T_t of its sublevel (or superlevel) sets. Its leaves are the n_t retained extrema; V_{ij} is the level at which leaves i and j merge, the value of $\mathrm{lca}(i,j)$, and Δ_F is the scalar range. Features are matched across time by support overlap. Figure 2 shows the two existing pipelines. TMTM linearizes the augmented merge tree by a depth-first traversal and flips subtrees greedily to maximize the overlap of subtree intervals between adjacent steps [31]. ST-MTM orders leaves by spatial proximity, places a one-dimensional skeleton by a quadratic program on pairwise distances, and fills it hierarchically [11]. A map frame is $M_t = (\pi_t, x_t, \psi_t)$: a leaf order, anchor positions and a profile $\psi_t : [0,L] \to \mathbb{R}$. As in ST-MTM, leaf i occupies an interval of width $W_i = s\,m_i$ proportional to its support measure m_i, intervals are separated by a gap g, and the anchor (the basin extremum) lies within $H_i = \rho W_i/2$ of the interval centre.

References. Each leaf has a reference coordinate $q_i \in [0,L]$, the projection of its location onto a fixed world direction, constant over time; L is the canvas length in world units. On Storms the direction is west–east (Fig. 1a). Any fixed one-dimensional quantity, such as distance to a site, can serve.

Errors. *Position*: the displacement $|x_i - q_i|/L$, pooled over leaves and frames (E_{pool}) and its maximum (E_∞). *Order*: the reference-order error of a leaf order,

$$\mathrm{NROE}(\pi) = \frac{1}{2L} \max_k \Big(\max_{j \le k} q_{\pi(j)} - q_{\pi(k)} \Big), \tag{1}$$

the smallest worst displacement of any monotone placement in that order with zero widths; it is scale-free and therefore also compares maps without a world canvas. *Topology*: in the profile, leaves i, j merge at the highest value of ψ_t between their anchors, V^{ψ}_{ij}, and

$$d_{\mathrm{top}}(\psi_t, T_t) = \max_{i,j} \big| V^{\psi}_{ij} - V_{ij} \big|, \qquad \mathrm{NMLE} = d_{\mathrm{top}}/\Delta_F. \tag{2}$$

Labelling every extremum and its anchor by its feature, V and V^{ψ} are the cophenetic matrices of two labelled merge trees (diagonal $V_{ii} = f(i)$, which the profile keeps), so d_{top} is their labelled interleaving distance [20,38]. It requires the labels to cover all leaves, i.e., no unlabelled extremum in the profile; every rendered column we checked satisfies this. Hence $d_B \le d_I \le d_{\mathrm{top}}$ [20,37]: a map with $d_{\mathrm{top}} \le \varepsilon\Delta_F$ displays a tree, and a persistence diagram, within $\varepsilon\Delta_F$ of the source. For superlevel sets all statements apply to $-f$.

One problem. All maps we consider solve, per sequence,

$$\begin{aligned} \min_{\{M_t\}} \; & \textstyle\sum_t \lambda_O E_O + \lambda_G E_G + \lambda_M E_M + \lambda_R E_R + \lambda_W E_W \\ \text{s.t. } & M_t \in \mathscr{L}(\pi_t), \quad \|x_t - q_t\|_\infty \le B_t, \\ & d_{\mathrm{top}}(\psi_t, T_t) \le (\varepsilon_0 + \varepsilon)\Delta_F, \end{aligned} \tag{3}$$

with the TMTM overlap term E_O, the stress E_G of anchor distances against source distances, a temporal term E_M on matched anchors, the reference error E_R, the width deviation E_W and layout model $\mathscr{L}$ (notation in Table 1). The data resolution ε_0 treats merge levels closer than $\varepsilon_0\Delta_F$ as ties (float32 round-off); ε is the budget the analyst spends and B_t a position cap. Table 2 lists the methods we compare as instances. Given their native leaf orders, both previous layouts are reproduced exactly on all five planar sequences: the TMTM linearization equals the official implementation in all 3127 arc intervals and anchors, and the ST-MTM anchors satisfy the optimality conditions of its quadratic programs (relative KKT residuals below 10^{-6}, below 10^{-10} on the volumetric sequences). Both methods are heuristic in the order: ST-MTM's leaf ordering exceeds the exhaustive optimum of its own objective on 10 frames, and TMTM's greedy choice is optimal at 434 of 463 enumerated steps but up to 85.5% above the per-step optimum elsewhere. The bounds below depend only on the shared constraints.




Figure 2: Existing merge tree map pipelines on a shared augmented merge tree. (a) TMTM linearizes each tree and aligns adjacent steps by subtree overlap. (b) ST-MTM orders leaves by spatial proximity, places a one-dimensional skeleton and fills it hierarchically. Neither uses an absolute spatial reference.




Figure 3: Our pipeline on one Storms step (17 Dec 1999, 12 UTC). (a) Extrema and references. (b) Merge tree; the root's children $\{C\}$ and $\{A,B,D,E\}$ have overlapping reference hulls (bars below), which certifies $\nu^* = 20.6\%$ for every exact map. (c) Leaf orders at $\varepsilon = 0$ and 10% with their exact merge cost δ^*. (d) Profile with optimal barriers (ticks; orange where the merge level was changed), intervals (bars), anchors (dots) and references (triangles). (e) Map around this step with marked barriers and the per-step merge error.

4 Overview

Figure 3 follows one Storms time step through our pipeline. (a) The extrema of the field are projected onto the reference axis. (b) Their merge tree is fixed by the data. Minimum C joins the other four only at the root, so any exact map keeps A, B, D, E in one block and places C at one of its ends; since C's reference lies inside the range of that block, the order error is at least $\nu^* = 20.6\%$ (Theorem 1). (c) With a budget $\varepsilon = 10\%$, the budgeted ordering moves C next to D, near its reference, at an exact merge cost $\delta^* = 4.7\%$. (d) Optimal barriers realize this order with the smallest possible merge error, and a capped quadratic program places the anchors. (e) The stacked map marks every barrier whose displayed merge level was changed, and a strip reports the merge error spent per step.

5 Certified Bounds

All bounds follow from one lemma about where a leaf may sit.

Lemma 1 (Separation)**.** *Let u be a node of T_t with level $f(u)$, and let leaf k lie strictly between two leaves i, j of u in a map with $d_{\text{top}} \leq$*

Table 1: Notation.

Symbol	Meaning
T_t, V_{ij}, Δ_F	merge tree of step t, merge level of leaves i, j, scalar range
q_i, L	reference coordinate of leaf i, canvas length
W_i, g, H_i	interval width, gap between intervals, anchor slack $\rho W_i/2$
π_t, x_i, ψ_t	leaf order, anchor position, profile of step t
NROE, τ	reference-order error (Eq. 1); attained worst displacement
d_{top}, NMLE	labelled merge error (Eq. 2); d_{top}/Δ_F
ν^*	lower bound on NROE for exact maps (Theorem 1)
ε, ε_0, B_t	merge-level budget, data resolution, position cap
$\delta^*(\pi)$	smallest merge error of order π (optimal barriers)

Table 2: Methods compared, as instances of problem (3).

Method	ε	B	objective	solver
TMTM [31]	0	∞	E_O	greedy subtree flips
ST-MTM [11]	0	∞	$E_G + \lambda E_M$; E_W	leaf order, then QP
κ R20 (earlier)	uncapped	–	$E_R + E_G + E_M$	candidate pool + QP
Projection	∞	$\tau_t + \beta$	–	sort by q + QP
Ours	0 or ε	$\tau_t + \beta$	$E_R + E_G + E_M$	Algorithm 1

ε. *Then* $V_{ik} \le f(u) + 2\varepsilon$.

Proof. The displayed merge of i, j is the highest profile value between them, which is at least the displayed merge of i, k. Hence $V_{ik} - \varepsilon \le V^{\psi}_{ik} \le V^{\psi}_{ij} \le V_{ij} + \varepsilon \le f(u) + \varepsilon$. □

With $\varepsilon = 0$, a leaf outside u merges with u strictly above $f(u)$, so *every subtree is contiguous*: the children of a node occupy disjoint blocks. Let $[m_X, M_X]$ be the reference hull of a subtree X.

Theorem 1 (Order bound)**.** *Every map with* $d_{\text{top}} = 0$ *satisfies*

$$\begin{aligned} \mathrm{NROE}(\pi_t) &\ge \nu^*(T_t) \\ &= \frac{1}{2L} \max_{\nu} \max_{X \ne Y \in \mathrm{ch}(\nu)} \left[\min(M_X - m_Y,\, M_Y - m_X) \right]^+, \end{aligned} \tag{4}$$

and sorting the children of every node by hull midpoint attains the bound in $O(n \log n)$.

Proof. If X precedes Y, the leaf of X at M_X precedes the leaf of Y at m_Y, which by (1) costs at least $(M_X - m_Y)/2L$; the other orientation costs $(M_Y - m_X)/2L$. In a midpoint order every inverted pair lies in sibling blocks $X \prec Y$ of its lowest common ancestor, and $m_X + M_X \le m_Y + M_Y$ is exactly $M_X - m_Y \le M_Y - m_X$. □

The bound is geometric (Fig. 4): siblings pay in proportion to how deeply their reference hulls overlap. It holds for any width rule, layout model or solver, hence for TMTM and ST-MTM.

Widths. A wide feature pushes its neighbours away. The attained interval cost $\tau(\pi) = \min_{x \in \mathscr{L}(\pi)} \max_i |x_i - q_i|$ has a closed form over the packed intervals. With $\ell_k = q_k - W_k/2 - H_k$, $h_k = q_k + W_k/2 + H_k$, $s_k = W_k + g$ and, for a leaf set S,

$$A(S) = \max_{\alpha} \left[\alpha + \sum_{k \in S,\ \ell_k \ge \alpha} s_k \right], \quad B(S) = \max_{\beta} \left[\sum_{k \in S,\ h_k \le \beta} s_k - \beta \right], \tag{5}$$

Theorem 2 (Width-aware bound)**.** *If block* X *precedes block* Y*, then* $\tau \ge (A(X) + B(Y) - g)/2$*. Hence every exact map has* $\tau(\pi_t) \ge \max_{\nu} \max_{X \ne Y \in \mathrm{ch}(\nu)} \frac{1}{2}[\min(A(X) + B(Y), A(Y) + B(X)) - g]$*, and every map has* $\tau \ge B(all) - g$ *and* $\tau \ge A(all) - g - L$ *at the canvas ends.*




Figure 4: Theorem 1 on sibling subtrees X (blue) and Y (orange). With exact topology one block must precede the other; the cheaper orientation costs $\min(M_X - m_Y, M_Y - m_X)/2$ and is chosen by sorting hull midpoints.




Figure 5: (a) Reference order A–C–B splits the subtree A–B. (b) Filling barriers with the original lowest-common-ancestor levels errs by the full gap γ. (c) Optimal barriers balance the error at $\gamma/2$, the minimum for this order.

Proof sketch. For $S_X \subseteq X$, $S_Y \subseteq Y$, the first interval of S_X and the last of S_Y enclose all of $S_X \cup S_Y$; their anchors are thus at least $\sum_{S_X \cup S_Y} s_k - g - W_a/2 - W_b/2 - H_a - H_b$ apart, and τ is at least half the shortfall against $q_a - q_b$. Upper sets of ℓ and lower sets of h separate the maximization into A and B, computed by sorting and prefix sums. The full proof is in the supplement. □

With zero widths and gap, Theorem 2 reduces to $L\nu^*$.

A merge-level budget. With $d_{\text{top}} \le \varepsilon$, Lemma 1 still forbids a leaf between two leaves of u unless it merges with u within 2ε of $f(u)$. Let $A_\varepsilon(u)$ be the highest ancestor of u with level at most $f(u) + 2\varepsilon$.

Theorem 3 (Chain bounds)**.** *In a map with* $d_{\text{top}} \le \varepsilon$*, every leaf outside* $A_\varepsilon(u)$*, and every node* w *with* $w \notin A_\varepsilon(u)$ *and* $u \notin A_\varepsilon(w)$*, lies entirely on one side of* u*. Applying the argument of Theorem 1 (resp. 2) to these separated pairs bounds NROE (resp.* τ*) from below.*

A coarser bound flattens every node within 2ε of its parent and applies Theorems 1 and 2; the chain bound charges a chain of small gaps by their sum and is never weaker. All bounds use $\varepsilon_0 + \varepsilon$ when a data resolution is declared. Full proofs are in the supplement; every bound was checked against exhaustive enumeration on random trees.

6 Certified Layouts

Algorithm 1 computes one map frame; frames are processed in time order so that the temporal term refers to the previous frame.




Figure 6: Cross-method comparison on seven sequences (left of the grey line: planar; right: volumetric). Order error with the certified lower bound ν^* (black ticks; no exact map can go below), worst merge error, motion error, and the two distance measures of ST-MTM. Exact-topology methods (TMTM, ST-MTM, ours at $\varepsilon = 0$) have zero merge error; the projection has zero order error but up to 59% merge error. Values are in the supplement.




Figure 7: Maps of daily outgoing longwave radiation (OLR, 60 days) and the synthetic Ring sequence (40 steps) that differ only in the layout objective. Each column is one time step; black dots mark the reference of each feature. Layouts that optimize hierarchy and time (TMTM-type) or pairwise distance (ST-MTM-type) place features far from their references; ours follows them.

Ordering. For $\varepsilon = 0$, midpoint ordering attains ν^*. With widths, a local search over the child permutations of each node minimizes τ; the sum of squared positive pair terms breaks plateaus of the minimax objective. Every child permutation of the exact tree keeps $d_{\text{top}} = 0$. For $\varepsilon > 0$, candidate trees flatten nodes either by threshold or by repeatedly releasing the sibling pair that sets the order cost when Theorem 3's chain condition allows; every candidate and every search move is checked with the exact merge cost δ^* and rejected if it exceeds the budget. The best previous order is always kept, so refinement never increases τ.

Search details. Threshold candidates use one tree per distinct parent gap up to $2(\varepsilon_0 + \varepsilon)$. The conflict-driven candidate starts from the exact tree, finds the sibling pair with the largest order cost and flattens one or both of its nodes when the chain condition holds and the exact δ^* of the new midpoint order stays within the budget; it repeats while the order error does not increase. The four candidates with the lowest initial τ, together with the exact tree, are refined. A move reinserts one child block at another position among its siblings, over all positions for nodes with up to eight children and within distance three otherwise, for at most eight passes. On 300 random trees with random widths and budgets, this search reached the exhaustive optimum of τ on 296; the point-model order alone on 250.

Algorithm 1 Certified map frame t

Require: tree T_t, references q, widths W, budget ε, resolution ε_0, slack β, previous anchors x_{t-1}
$\mathscr{S} \leftarrow \{T_t\} \cup \{T_t^{(s)} : s \le 2(\varepsilon_0+\varepsilon)\} \cup \{\text{conflict-driven flattening}\}$ ▷ candidate trees
for $S \in \mathscr{S}$ **do**
  $\pi \leftarrow$ midpoint order of S; **skip** if $\delta^*(\pi) > (\varepsilon_0+\varepsilon)\Delta_F$
  repeat ▷ width-aware local search
    move one child block of a node of S if it lowers $(\tau, \sum \text{positive terms}^2)$ and $\delta^* \le (\varepsilon_0+\varepsilon)\Delta_F$
  until no move improves
$\pi_t \leftarrow$ best order by (τ, NROE) ▷ includes the point-model order
barriers $\leftarrow$ optimal barriers of π_t, attaining $\delta^*(\pi_t)$
$x_t \leftarrow \arg\min E_R + E_G + E_M$ s.t. $\mathscr{L}(\pi_t)$, $\|x-q\|_\infty \le \tau(\pi_t)+\beta$
report lower bound, $\tau(\pi_t)$, $\delta^*(\pi_t)$; mark barriers changed by more than $10^{-3}\Delta_F$

Table 3: Sequences. Leaves: retained extrema per frame.

Sequence	Scalar field	Frames	Leaves	Tree
Storms	ERA5 mean sea-level pressure, 2-D	118	1–8	join
Wildfires	$\log(1+\text{FRP})$, 2-D	30	6–11	split
OLR	outgoing longwave radiation, 2-D	60	2–8	join
$PM_{2.5}$	$PM_{2.5}$ concentration, 2-D	366	1–7	split
Ring	synthetic ring intensity, 2-D	40	1–7	split
Tangaroa	velocity magnitude, 3-D	201	18–93	join
Cylinder	Q criterion, 3-D	102	4–75	split

Optimal barriers. For a fixed order, the barrier between consecutive basins determines every displayed merge. The smallest achievable error $\delta^*(\pi)$ has a closed form: each pair is limited by the lowest true merge level among the pairs it separates, an ℓ_∞ ultrametric fit under a fixed leaf order [17]. Figure 5 shows the effect: keeping original merge levels doubles the error that a balanced barrier needs. The profile is filled from the source arc samples with the renderer of ST-MTM [11].

Capped placement. The anchors solve the convex quadratic program of (3) with widths, gaps, canvas and anchor slack. The cap $B_t = \tau(\pi_t) + \beta$ is feasible because τ is attained by the order, and it bounds E_∞; without it the geometry term can pull single anchors far from their references.

Cost. Bounds cost $O(n \log n)$ to $O(n^2 \log n)$, δ^* $O(n^3)$ per order. On an Apple M2 Pro (single Python process; NumPy 2.0, SciPy 1.13), all bounds take at most 0.6 ms per planar frame (1–11 leaves) and 5.5 ms per volumetric frame (up to 93 leaves), the ordering at most 3.7 ms and 103 ms, and the capped QP (SciPy SLSQP) 2.3–9.0 ms and 0.25–0.50 s. All 917 frames take 94 s at $\varepsilon = 0$ and at most 137 s with a budget.

7 Evaluation

7.1 Setup

Data. Table 3 lists seven sequences, 917 frames in total [9, 14, 19, 25, 31, 32, 42, 50]. All methods share the processed fields, extrema, supports, matches and references; preprocessing follows prior work.

Methods and metrics. We compare native TMTM and ST-MTM outputs, the earlier uncapped κ construction (R20), the projection baseline, which sorts every frame by reference and uses the same optimal barriers and capped QP, and our layouts at $\varepsilon = 0$ and 10% (Table 2), with $\varepsilon_0 = 10^{-7}$. Metrics are the order error NROE, the worst merge error, and, with the protocol of ST-MTM [11], scale-normalized stress (SNS) and trustworthiness (TW, $k = 1$) of anchor distances against support-centroid distances, and the motion error (ME): the fraction of clear approach or separation events between two features over two steps that the map shows in the wrong direction or not at all. Recomputing the stored baseline values from their saved anchors reproduces SNS and TD to a relative 10^{-5} and TW and ME to the third decimal or one event.

7.2 Cross-method comparison

Exact-topology maps can be far more position-faithful than existing ones; the remaining error is certified, and distance preservation is a different trade-off.

Figure 6 compares all methods on all sequences. *Order*: no method falls below ν^* on any of the 917 frames. Most of the order error of TMTM and ST-MTM is avoidable: on Storms, TMTM's 19.2% contains 3.8% that the hierarchy forces and ST-MTM's 16.3% contains 12.5% that it does not. Our exact layouts lie within 0.03 percentage points of ν^* on every planar sequence; on Tangaroa and Cylinder the width-aware order trades a little NROE (9.67% against 9.24% on Tangaroa) for a lower worst displacement. On all 637 frames with at most eight leaves, the budgeted order matches exhaustive enumeration at nine budgets from 0 to 100%. *Topology*: the projection has zero order error but changes merge levels by up to 58.66% of the scalar range on Storms, 52.58% on Wildfires, 33.56% on OLR and 31.02% on Tangaroa, where no frame keeps its tree; the uncapped κ construction reached the same worst values on OLR and Tangaroa. Our budgeted maps never exceed their budget. *Motion*: our exact maps make fewer motion errors than both TMTM and ST-MTM on all seven sequences, e.g., 5.4% against 21.4% on OLR and 52.2% against 70.0% on Tangaroa, because a feature that moves along the reference moves on the map; the projection, which follows the references exactly, is lowest on most sequences. *Distance*: ST-MTM, which optimizes pairwise distances, has the best TW on all seven sequences and the best SNS on five; on Cylinder our budgeted map (0.041) and the κ construction (0.040) are far below ST-MTM's 0.135.

Figure 7 shows the planar sequences OLR and Ring with the same renderer and widths. On Ring, the TMTM-type objective keeps all features near the centre of the axis and the ST-MTM-type objective spreads them by pairwise distance; both place them far from their references, whereas our exact layout follows them and a 10% budget changes the map only locally. On OLR, our exact map already places the low-radiation basins near their references, which makes it comparable to a time–longitude plot while keeping each basin's nesting.

7.3 The position–topology frontier

Small budgets can recover most of the position, but not on every sequence; the frontier shows where.

Figure 8 places every layout by its measured worst merge error and its displacement, from $\varepsilon = 0$ to the projection. On Cylinder a 1% budget reaches the lowest worst displacement of the whole curve (27.00% to 5.27%), below the projection's 5.73%, because sorting by reference ignores widths. On Wildfires 1% reduces E_∞ from 20.48% to 8.71%, and on $PM_{2.5}$ 5% reaches the projection result. Storms needs much more: its worst displacement stays above 18% up to $\varepsilon = 20\%$, and OLR keeps $E_\infty = 17.14\%$ up to 10% because one frame needs a larger change. Mean merge errors are far below the maxima (Storms at 10%: 0.90% mean, 8.51% maximum), so the budget is spent on few frames. Compared with the uncapped κ construction at similar positions, the worst merge error is now bounded (Storms: 26.07% to 8.51%; Wildfires: 19.56% to 8.35%).

7.4 Wide features

Ordering for the point model is not enough when features are large; the width-aware bound and search close the gap.

On Tangaroa, ordering by NROE alone gave a worst displacement of 20.69%, above the κ construction's 16.86%. Ordering by τ lowers it to 15.10% at $\varepsilon = 0$ and to 14.55% at $\varepsilon = 2\%$, where the




Figure 8: Position–topology frontier per sequence. Each point is one layout of all frames at budget ε (labels, in percent), placed by its measured worst merge error and its worst (dark) and mean (light) displacement. Stars: projection ($\varepsilon = \infty$). Grey crosses: earlier candidate-pool QP, planar only.




Figure 9: Tangaroa, 201 time steps: interval cost τ_t/L of the point-model order (orange), the width-aware order (blue) and the κ construction (dashed, mostly hidden under the blue line), with the certified lower bound (grey area, the larger of Theorems 2 and 3).

worst frame meets the lower bound; on Cylinder $\varepsilon \geq 2\%$ lowers E_∞ from 5.73% to 5.27%, again at the bound. The chain bound makes these certificates informative for large trees: at $\varepsilon = 5\%$ the coarse bound averages 0.38% on Tangaroa, the chain width bound 7.40% against an attained 8.10%. The remaining gap of about one percentage point also appears at $\varepsilon = 0$, which suggests that the bound, not the ordering, is loose. Figure 9 shows where the gain comes from: the point-model order lies far above the bound in the first 30 steps, and the width-aware order removes most of this excess. Table 4 lists both volumetric sequences. The κ construction keeps lower mean jumps on Tangaroa (2.59% against 2.82%) and a lower pooled displacement than our 2% map (4.16% against 4.55%); its merge error, however, has no cap.

7.5 Case study: Storms with error disclosure

A budgeted map shows where, and by how much, the hierarchy was changed.

Figure 10 compares maps on Storms, where minima of sea-level pressure are low-pressure systems crossing the North Atlantic. Within the same layout model, the TMTM-type and ST-MTM-type objectives place features on average 37.3% and 50.7% of the canvas from their references in the worst case of each step; our exact map has a median of 0.8% and a mean of 5.1%, with peaks of up to 26.2% in a few steps. A 10% budget lowers the mean to 2.7%. It is spent in 31 of 118 steps, at most 8.51% and 0.90% on average, and the 89 barriers whose merge level changed by more than 0.1% of the scalar range are marked. At $\varepsilon = 0$ no mark appears.

Reading the map. The teaser step (Fig. 1) shows how an analyst uses these maps. In the exact map, the western minima A and B sit at the bottom of the axis and the eastern minimum E near the top, as in the field; only C is out of place, and ν^* tells the analyst that no exact map could do better than an order error of 20.6% in this step. Switching to the 10% map moves C next to D, at its reference, and the marks on this step show that all four barriers were changed, by at most $\delta^* = 4.7\%$ of the pressure range. Across the sequence, the




Figure 10: Storms, 118 half-day steps. Top: maps that differ only in the layout objective; dots mark references. On the $\varepsilon = 10\%$ map, yellow ticks mark barriers whose displayed merge level differs from the source by more than 0.1% of the scalar range. Bottom left: worst displacement per step. Bottom right: merge error spent per step at $\varepsilon = 10\%$, always below the cap.

Table 4: Volumetric sequences (percent). κ P (exact) and R2 (relaxed, no merge-error cap) are the earlier construction; N1 orders by NROE only. Jump: mean $|\Delta x - \Delta q|/L$ of matched features.

	Layout	E_{pool}	E_∞	NROE	jump	NMLE max
Tangaroa	κ P	5.01	16.86	9.61	2.59	0
Tangaroa	N1, $\varepsilon = 0$	4.92	20.69	9.24	2.73	0.00
Tangaroa	Ours, $\varepsilon = 0$	5.01	15.10	9.67	2.82	0.00
Tangaroa	κ R2	4.16	14.65	8.56	2.49	no cap
Tangaroa	N1, $\varepsilon = 2\%$	4.49	20.69	8.23	2.60	2.00
Tangaroa	Ours, $\varepsilon = 2\%$	4.55	14.55	8.60	2.76	2.00
Cylinder	κ P	5.40	32.08	12.26	5.87	0
Cylinder	N1, $\varepsilon = 0$	3.76	27.00	8.01	3.83	0.00
Cylinder	Ours, $\varepsilon = 0$	3.76	27.00	8.01	3.89	0.00
Cylinder	κ R2	0.62	5.27	0.25	0.47	no cap
Cylinder	N1, $\varepsilon = 2\%$	0.64	5.73	0.17	0.46	1.84
Cylinder	Ours, $\varepsilon = 2\%$	0.64	5.27	0.19	0.47	1.67

merge-error strip shows that such changes are concentrated in 31 steps, so the analyst knows which steps to read with care and which keep the exact hierarchy. Rendering does not weaken the guarantees: rendered barriers differ from the computed ones by at most $1.6 \cdot 10^{-6}$ of the scalar range and anchors are rounded by at most $2.4 \cdot 10^{-4}$ of the canvas.

8 Discussion and Limitations

What a budget changes. A budget never removes a feature, changes an extremum value or moves the data; it changes displayed merge levels by at most $\varepsilon\Delta_F$, and the displayed tree and its persistence diagram stay within that distance of the source. Where a subtree is split, its band is no longer contiguous and the reading "one band, one component" fails locally, which is why we mark such barriers. Persistence simplification spends a comparable budget differently, removing features below 2ε [15, 46]. Open refinements are a one-sided error that never shows an earlier connection and a constraint that keeps barriers inside the data range. We recommend $\varepsilon = 0$ as the default and a budget only where the frontier shows a clear gain.

Choosing the budget. The data resolution ε_0 should match the precision of the data; with float32 fields we used 10^{-7} of the range. On Cylinder, whose saddles are nearly degenerate, the bound ν^* is 12.24% when only exactly equal levels are merged and 6.15% at $\varepsilon_0 = 10^{-6}$, which shows that part of its hierarchy lies below data precision. The budget ε is a choice of the analyst: the frontier of Fig. 8 shows its effect on position before any map is read, and the disclosure strip shows where it was spent.

Limits of one dimension. Projecting onto one direction loses the other coordinates; features at the same longitude compete for the same position, and ν^* quantifies exactly this conflict for the chosen direction. Our metrics of position are defined against the reference the layout optimizes; the comparison therefore also reports the scale-free order error of native outputs and the distance and motion measures of ST-MTM, on which ST-MTM keeps the better distance preservation. Readability was not tested: whether analysts read position and nesting together, and whether disclosure marks prevent misreading [28, 36], requires a user study.

Reproducibility. All results are computed from saved experiment records by scripts that we will release with the paper; every figure and table of this paper and the supplement is regenerated by one script, and 68 unit tests, among them checks of the bounds and orders against exhaustive enumeration, cover the implementation.

Bounds. The order bound is attained exactly. The width bound is attained on most planar frames and on the worst Tangaroa and Cylinder frames but not uniformly on large trees; Wildfires at $\varepsilon > 0$ and one OLR frame at $\varepsilon = 10\%$ keep a worst-frame gap.

9 Conclusion

Merge tree maps can stay close to a spatial reference without giving up their hierarchy, and how close is computable. The order bound and its width and chain versions give the unavoidable displacement of every exact map; most of the displacement of existing maps lies above it, and our layouts remove it. A merge-level budget recovers

more position where the data allow, with the error certified, reported and marked on the map. Each map therefore carries two numbers: how far it moves features and how far it changes the hierarchy.

References

[1] D. Archambault, H. Purchase, and B. Pinaud. Animation, small multiples, and the effect of mental map preservation in dynamic graphs. *IEEE Transactions on Visualization and Computer Graphics*, 17(4):539–552, 2011. doi: 10.1109/TVCG.2010.78 1

[2] B. Bach, P. Dragicevic, D. Archambault, C. Hurter, and S. Carpendale. A descriptive framework for temporal data visualizations based on generalized space-time cubes. *Computer Graphics Forum*, 36(6):36–61, 2017. doi: 10.1111/cgf.12804 2

[3] Z. Bar-Joseph, D. K. Gifford, and T. S. Jaakkola. Fast optimal leaf ordering for hierarchical clustering. *Bioinformatics*, 17(Suppl. 1):S22–S29, June 2001. doi: 10.1093/bioinformatics/17.suppl_1.s22 2

[4] K. Beketayev, G. H. Weber, D. Morozov, A. Abzhanov, and B. Hamann. Geometry-preserving topological landscapes. In *Proc. SIGGRAPH Asia Workshop on Apps (WASA)*, pp. 155–160. ACM, New York, NY, USA, Nov. 2012. doi: 10.1145/2425296.2425324 2

[5] T. Beurskens et al. ParkView: Visualizing monotone interleavings. In *Proc. PacificVis*, pp. 118–127. IEEE, Los Alamitos, CA, USA, Apr. 2025. doi: 10.1109/pacificvis64226.2025.00018 2

[6] T. Beurskens, T. Ophelders, B. Speckmann, and K. Verbeek. Relating interleaving and Fréchet distances via ordered merge trees. In *Proc. ACM-SIAM Symposium on Discrete Algorithms (SODA)*, pp. 5027–5050, 2025. doi: 10.1137/1.9781611978322.170 2

[7] J. Buchmüller, D. Jäckle, E. Cakmak, U. Brandes, and D. A. Keim. MotionRugs: Visualizing collective trends in space and time. *IEEE Transactions on Visualization and Computer Graphics*, 25(1):76–86, Jan. 2019. doi: 10.1109/tvcg.2018.2865049 2

[8] L. Bulteau, P. Gambette, and O. Seminck. Reordering a tree according to an order on its leaves. In *Proc. CPM*, vol. 223 of *LIPIcs*, pp. 24:1–24:15. Schloss Dagstuhl–Leibniz-Zentrum für Informatik, Dagstuhl, Germany, June 2022. doi: 10.4230/LIPIcs.CPM.2022.24 2

[9] S. Camarri, M.-V. Salvetti, M. Buffoni, and A. Iollo. Simulation of the three-dimensional flow around a square cylinder between parallel walls at moderate Reynolds numbers. In *XVII Congresso di Meccanica Teorica ed Applicata*, 2005. 6

[10] R. Dafner, D. Cohen-Or, and Y. Matias. Context-based space filling curves. *Computer Graphics Forum*, 19(3):209–218, 2000. doi: 10.1111/1467-8659.00413 2

[11] M. Diaz, J. Heredia, N. Ferreira, and J. Poco. Spatiotemporal merge tree maps: A topology and geometry aware visualization for temporal scalar data, 2026. Preprint, SSRN 6604235. doi: 10.2139/ssrn.6604235 1, 2, 4, 6

[12] A. Dobler, T. Hegemann, M. Nöllenburg, and A. Wolff. Optimizing wiggle in storylines. In *Proc. Int. Symposium on Graph Drawing and Network Visualization (GD)*, vol. 357 of *LIPIcs*, 2025. doi: 10.4230/LIPIcs.GD.2025.39 2

[13] A. Dobler and M. Nöllenburg. Block crossings in one-sided tanglegrams. *Algorithmica*, 88(2), 2026. doi: 10.1007/s00453-025-01363-3 2

[14] Y. Dong, L. Wang, G. Shan, and J. Liu. An Integrated Dataset of PM2.5, Elevation, and Meteorological Variables over China at a 10-km Resolution (2000–2023), 2026. Version V2; year-2000 regional subset used for the annual experiment. doi: 10.57760/sciencedb.35623 6

[15] H. Edelsbrunner, D. Letscher, and A. Zomorodian. Topological persistence and simplification. *Discrete & Computational Geometry*, 28(4):511–533, Nov. 2002. doi: 10.1007/s00454-002-2885-2 8

[16] M. B. Eisen, P. T. Spellman, P. O. Brown, and D. Botstein. Cluster analysis and display of genome-wide expression patterns. *Proceedings of the National Academy of Sciences*, 95(25):14863–14868, Dec. 1998. doi: 10.1073/pnas.95.25.14863 2

[17] M. Farach, S. Kannan, and T. Warnow. A robust model for finding optimal evolutionary trees. *Algorithmica*, 13(1-2):155–179, Feb. 1995. doi: 10.1007/bf01188585 2, 6

[18] H. Fernau, M. Kaufmann, and M. Poths. Comparing trees via crossing minimization. *Journal of Computer and System Sciences*, 76(7):593–608, 2010. doi: 10.1016/j.jcss.2009.10.014 2

[19] M. Franke, H. Martin, S. Koch, and K. Kurzhals. Visual analysis of spatio-temporal phenomena with 1D projections. *Computer Graphics Forum*, 40(3):335–347, June 2021. doi: 10.1111/cgf.14311 2, 6

[20] E. Gasparovic, E. Munch, S. Oudot, K. Turner, B. Wang, and Y. Wang. Intrinsic interleaving distance for merge trees. *La Matematica*, 4(1):40–65, 2025. doi: 10.1007/s44007-024-00143-9 2

[21] D. Guo and M. Gahegan. Spatial ordering and encoding for geographic data mining and visualization. *Journal of Intelligent Information Systems*, 27(3):243–266, 2006. doi: 10.1007/s10844-006-9952-8 2

[22] C. Heine et al. A survey of topology-based methods in visualization. *Computer Graphics Forum*, 35(3):643–667, 2016. doi: 10.1111/cgf.12933 2

[23] C. Heine, D. Schneider, H. Carr, and G. Scheuermann. Drawing contour trees in the plane. *IEEE Transactions on Visualization and Computer Graphics*, 17(11):1599–1611, 2011. doi: 10.1109/TVCG.2010.270 2

[24] M. Herick, V. Molchanov, and L. Linsen. Temporally coherent topological landscapes for time-varying scalar fields. In *Proc. 15th Int. Joint Conf. on Computer Vision, Imaging and Computer Graphics Theory and Applications (IVAPP)*, pp. 54–61, 2020. doi: 10.5220/0008956300540061 2

[25] H. Hersbach et al. 6

[26] E. Hovmöller. The trough-and-ridge diagram. *Tellus*, 1(2):62–66, May 1949. doi: 10.1111/j.2153-3490.1949.tb01260.x 1, 2

[27] D. H. Huson. Displacement-optimized tanglegrams for trees and networks. *Molecular Biology and Evolution*, 43(3):msag066, Mar. 2026. doi: 10.1093/molbev/msag066 2

[28] A. Kamakshidasan and V. Natarajan. Mergemaps: Treemaps for scientific data. In *Topological Methods in Data Analysis and Visualization VI*, Mathematics and Visualization, pp. 19–38. Springer, 2021. doi: 10.1007/978-3-030-83500-2_2 2, 8

[29] J. Klawitter, F. Klesen, J. Y. Scholl, T. C. van Dijk, and A. Zaft. Visualizing geophylogenies – internal and external labeling with phylogenetic tree constraints. *Journal of Graph Algorithms and Applications*, 29(1):29–61, Mar. 2025. doi: 10.7155/jgaa.v29i1.2975 2

[30] W. Köpp and T. Weinkauf. Temporal treemaps: Static visualization of evolving trees. *IEEE Transactions on Visualization and Computer Graphics*, 25(1):534–543, Jan. 2019. doi: 10.1109/tvcg.2018.2865265 2

[31] W. Köpp and T. Weinkauf. Temporal merge tree maps: A topology-based static visualization for temporal scalar data. *IEEE Transactions on Visualization and Computer Graphics*, 29(1):1157–1167, Jan. 2023. doi: 10.1109/tvcg.2022.3209387 1, 2, 4, 6

[32] H.-T. Lee. NOAA Climate Data Record of Daily Outgoing Longwave Radiation, Version 1.2, 2011. Tropical Indo-Pacific subset, 1 June–30 July 2024; accessed 12 October 2026. doi: 10.7289/V5SJ1HH2 6

[33] S. Liu, Y. Wu, E. Wei, M. Liu, and Y. Liu. StoryFlow: Tracking the evolution of stories. *IEEE Transactions on Visualization and Computer Graphics*, 19(12):2436–2445, Dec. 2013. doi: 10.1109/tvcg.2013.196 2

[34] J. Lukasczyk, C. Garth, G. H. Weber, T. Biedert, R. Maciejewski, and H. Leitte. Dynamic nested tracking graphs. *IEEE Transactions on Visualization and Computer Graphics*, 26(1):249–258, 2020. doi: 10.1109/TVCG.2019.2934368 2

[35] J. Lukasczyk, G. Weber, R. Maciejewski, C. Garth, and H. Leitte. Nested tracking graphs. *Computer Graphics Forum*, 36(3):12–22, June 2017. doi: 10.1111/cgf.13164 2

[36] A. McNutt, G. Kindlmann, and M. Correll. Surfacing visualization mirages. In *Proc. CHI*, pp. 1–16. ACM, New York, NY, USA, Apr. 2020. doi: 10.1145/3313831.3376420 8

[37] D. Morozov, K. Beketayev, and G. H. Weber. Interleaving distance between merge trees. https://mrzv.org/publications/interleaving-distance-merge-trees/, 2013. Manuscript presented at TopoInVis. 2

[38] E. Munch and A. Stefanou. The ℓ^∞-cophenetic metric for phylogenetic trees as an interleaving distance. In *Research in Data Science*, pp. 109–127. Springer, Cham, Switzerland, 2019. doi: 10.1007/978-3-030-11566-1_5 2

[39] P. Oesterling, C. Heine, G. H. Weber, D. Morozov, and G. Scheuermann. Computing and visualizing time-varying merge trees for high-

dimensional data. In H. Carr, C. Garth, and T. Weinkauf, eds., *Topological Methods in Data Analysis and Visualization IV*, pp. 87–101. Springer, 2017. doi: 10.1007/978-3-319-44684-4_5 2

[40] P. Oesterling, C. Heine, G. H. Weber, and G. Scheuermann. Visualizing nD point clouds as topological landscape profiles to guide local data analysis. *IEEE Transactions on Visualization and Computer Graphics*, 19(3):514–526, 2013. doi: 10.1109/TVCG.2012.120 2

[41] M. Pont, J. Vidal, J. Delon, and J. Tierny. Wasserstein distances, geodesics and barycenters of merge trees. *IEEE Transactions on Visualization and Computer Graphics*, 28(1):291–301, Jan. 2022. doi: 10.1109/tvcg.2021.3114839 2

[42] S. Popinet, M. Smith, and C. Stevens. Experimental and numerical study of the turbulence characteristics of airflow around a research vessel. *Journal of Atmospheric and Oceanic Technology*, 21(10):1575–1589, 2004. doi: 10.1175/1520-0426(2004)021<1575:EANSOT>2.0.CO;2 6

[43] G. Robertson, R. Fernandez, D. Fisher, B. Lee, and J. Stasko. Effectiveness of animation in trend visualization. *IEEE Transactions on Visualization and Computer Graphics*, 14(6):1325–1332, 2008. doi: 10.1109/tvcg.2008.125 1

[44] M. Stolk, J. Wulms, and K. Verbeek. GroupRugs: Visual summaries for groups in collective movement data. In *Proc. PacificVis*, pp. 128–137. IEEE, Los Alamitos, CA, USA, Apr. 2025. doi: 10.1109/pacificvis64226.2025.00019 2

[45] Y. Tanahashi and K.-L. Ma. Design considerations for optimizing storyline visualizations. *IEEE Transactions on Visualization and Computer Graphics*, 18(12):2679–2688, 2012. doi: 10.1109/TVCG.2012.212 2

[46] J. Tierny and V. Pascucci. Generalized topological simplification of scalar fields on surfaces. *IEEE Transactions on Visualization and Computer Graphics*, 18(12):2005–2013, Dec. 2012. doi: 10.1109/tvcg.2012.228 8

[47] B. Tversky, J. B. Morrison, and M. Bétrancourt. Animation: Can it facilitate? *International Journal of Human-Computer Studies*, 57(4):247–262, 2002. doi: 10.1006/ijhc.2002.1017 1

[48] G. Valdrighi, N. Ferreira, and J. Poco. MoReVis: A visual summary for spatiotemporal moving regions. *IEEE Transactions on Visualization and Computer Graphics*, 30(4):1927–1941, Apr. 2024. doi: 10.1109/tvcg.2023.3250166 2

[49] G. H. Weber, P.-T. Bremer, and V. Pascucci. Topological landscapes: A terrain metaphor for scientific data. *IEEE Transactions on Visualization and Computer Graphics*, 13(6):1416–1423, Nov. 2007. doi: 10.1109/tvcg.2007.70601 2

[50] T. Weinkauf. 3D flow around a confined square cylinder. Public uniformly resampled simulation dataset. Accessed 22 October 2026. 6

[51] J. Weißenböck, B. Fröhler, E. Gröller, J. Kastner, and C. Heinzl. Dynamic volume lines: Visual comparison of 3D volumes through space-filling curves. *IEEE Transactions on Visualization and Computer Graphics*, 25(1):1040–1049, 2019. doi: 10.1109/tvcg.2018.2864510 2

[52] W. Widanagamaachchi, C. Christensen, P.-T. Bremer, and V. Pascucci. Interactive exploration of large-scale time-varying data using dynamic tracking graphs. In *IEEE Symposium on Large Data Analysis and Visualization (LDAV)*, pp. 9–17. IEEE, 2012. doi: 10.1109/ldav.2012.6378962 2

[53] J. Wulms, J. Buchmüller, W. Meulemans, K. Verbeek, and B. Speckmann. Stable visual summaries for trajectory collections. In *Proc. PacificVis*, pp. 61–70. IEEE, Los Alamitos, CA, USA, Apr. 2021. doi: 10.1109/pacificvis52677.2021.00016 2

[54] L. Yan et al. Scalar field comparison with topological descriptors: Properties and applications for scientific visualization. *Computer Graphics Forum*, 40(3):599–633, 2021. doi: 10.1111/cgf.14331 2

[55] L. Yan, T. B. Masood, F. Rasheed, I. Hotz, and B. Wang. Geometry-aware merge tree comparisons for time-varying data with interleaving distances. *IEEE Transactions on Visualization and Computer Graphics*, 29(8):3489–3506, Aug. 2023. doi: 10.1109/tvcg.2022.3163349 2

[56] L. Zhou, C. R. Johnson, and D. Weiskopf. Data-driven space-filling curves. *IEEE Transactions on Visualization and Computer Graphics*, 27(2):1591–1600, Feb. 2021. doi: 10.1109/tvcg.2020.3030473 2