

## A NOTE ON THE WORST CASE OF HEAPSORT

by Clyde P. Kruskal and Elia Weixelbaum

Courant Institute of Mathematical Sciences  
New York University

February 1981

It is interesting to compare various sorting algorithms based on numbers of comparisons and exchanges. This point is emphasized in Knuth [Kn, sec. 5.3.1]: "... a theoretical study of this subject [counting comparisons] gives us a good deal of useful insight into the nature of sorting processes ..."

The most commonly known  $O(n \log n)$  comparison-exchange sorting algorithm not needing external storage is heapsort (sometimes referred to as treesort) [Fl], [Wi]. It is relatively easy to calculate the maximum number of exchanges required by heapsort; this note discusses the maximum number of (key) comparisons required.

The version of heapsort considered (Knuth's Algorithm H [Kn]) appears in Appendix A. We obtain in [KW] the worst-case number of comparisons for heapsort, assuming  $n$  is one less than a power of two:

$$2n \log(n+1) - 2n - 3 \log(n+1) + 3 \quad \text{if } n \leq 7,$$

$$2n \log(n+1) - 2n - 4 \log(n+1) + 6 \quad \text{otherwise.}$$

An algorithm producing input yielding this maximum appears in Appendix B.

APPENDIX A

PROCEDURE HEAPSORT (A,N);

BEGIN

PROCEDURE SIFT (S,BOUND);

COMMENT this procedure sifts the item in position S to no lower  
than position BOUND;

BEGIN

I := S; J := 2 \* I; X := A[I];

WHILE J < BOUND DO

BEGIN

IF J < BOUND THEN IF A[J] < A[J+1] THEN J := J + 1;

IF X > A[J] THEN GOTO DONESIFT;

A[I] := A[J]; I := J J := 2 \* I

END;

DONESIFT:

A[I] := X

END SIFT;

PROCEDURE CREATE\_HEAP;

FOR P := (N DIV 2) TO 1 STEP -1 DO SIFT (P,N);

PROCEDURE SELECT;

FOR K := N TO 2 STEP -1 DO

BEGIN

HOLD := A[1]; A[1] := A[K]; A[K] := HOLD;

SIFT (1,K-1)

END;

CREATE\_HEAP;

SELECT

END

APPENDIX B

PROCEDURE WORST\_CASE\_OF\_HEAPSORT (A,N);

COMMENT this algorithm produces an array, A, that yields the worst case number of comparisons for heapsort, assuming that N is 1 less than a power of 2.

BEGIN

PROCEDURE UNSIFT (S,BOUND);

COMMENT this procedure unsifts the item in position S up to position BOUND;

BEGIN

I := S; J := I DIV 2; X := A[I];

WHILE J > BOUND DO

BEGIN A[I] := A[J]; I := J; J := I DIV 2 END;

A[I] := X

END;

PROCEDURE REVERSE\_SELECT;

IF N = 1 THEN A[1] := 1

ELSE IF N = 3 THEN

BEGIN A[1] := 3; A[2] := 2; A[3] := 1 END

ELSE

BEGIN

A[1] := 7; A[2] := 6; A[3] := 3; A[4] := 5;

A[5] := 4; A[6] := 1; A[7] := 2;

FOR L := 4 TO LOG(N+1) DO

FOR K := 2 \*\* (L-1) TO (2 \*\* L) - 2 STEP 2 DO

BEGIN

UNSIFT (index of node containing the 1, 1);

A[1] := K; A[K] := 1

UNSIFT (index of node containing the 2, 1);

A[1] := K+1; A[K+1] := 2

END

END

PROCEDURE CREATE\_REVERSE\_HEAP;

FOR P := 1 TO (N DIV 2) DO UNSIFT(index of node containing smallest element in tree rooted by P, P);

REVERSE\_SELECT;

CREATE\_REVERSE\_HEAP

END

REFERENCES

- [Fl] Floyd, R.W., "Treesort 3: Algorithm 245," Communications of the ACM, 7 12(Dec. 1964), 701.
- [Kn] Knuth, D.E., The Art of Computer Programming, Vol. 3: Sorting and Searching. Addison-Wesley, Reading, Mass., 1973.
- [KW] Kruskal, C.P. and Weixelbaum, E., "A Worst Case Analysis of Heapsort," Technical Report #18, Department of Computer Science, New York University, N.Y., Nov. 1979.
- [Wi] Williams, J.W.J., "Heapsort: Algorithm 232," Communications of the ACM, 7, 6(June 1964), 347-348.