## Tutorial #1 - oTree Objects - Web Technologies

Juan Cabral - jbc.develop@gmail.com

Jan, 2018

```
% phd.m
 author: Cecilia
                                                    FOREVER?
load THESIS_TOPIC
while (funding==true)
   data = run_experiment(THESIS_TOPIC);
   GOOD_ENOUGH = query(advisor);
   if (data > GOOD_ENOUGH)
       graduate();
       break
   else
       THESIS_TOPIC = new();
       years_in_gradschool += 1:
   end
end
                                                www.phdcomics.com
```

- Open your console (Powershell, terminal, or any flaored pyton console)
- Open an editor (PyCharm, SublimeText, Kate, Atom...)
- ► Follow Me!

This is a three player game where each player is initially endowed with 100 points. Each player individually makes a decision about how many of their points they want to contribute to the group. The combined contributions are multiplied by 2, and then divided evenly three ways and redistributed back to the players.

#### models.Constants

Open models.py. This file contains the game's data models (player, group, subsession) and constant parameters.

First, let's modify the Constants class to define our constants and parameters – things that are the same for all players in all games.

- ► There are 3 players per group. So, change players\_per\_group to 3. oTree will then automatically divide players into groups of 3.
- ► The endowment to each player is 100 points. So, let's define endowment and set it to c(100).
- Each contribution is multiplied by 2. So let's define multiplier and set it to 2.

#### models.Player

After the game is played, what data points will we need about each player? It's important to know how much each person contributed. So, we define a field **contribution**, which is a currency

#### models.Group

What data points are we interested in recording about each group? We might be interested in knowing the total contributions to the group, and the individual share returned to each player. So, we define those 2 fields.

Finally let's define our payoff function. The argument to the function should be a group whose payoffs should be calculated.

## views.py and Templates

Now we define our views, which contain the logic for how to display the HTML templates.

Since we have 2 templates, we need 2 Page classes in views.py

- First let's define Contribute. This page contains a form, so we need to define form\_model and form\_fields. Specifically, this form should let you set the contribution field on the player.
- 2. The template contains a brief explanation of the game, and a form field where the player can enter their contribution.

### views.py and Templates

- 3. Now we define Results. This page doesn't have a form so our class definition can be empty (with the pass keyword).
- 4. Now create the **Results.html** template

### views.py and Templates

#### Consideration

5. After a player makes a contribution, they cannot see the results page right away; they first need to wait for the other players to contribute. You therefore need to add a WaitPage. When a player arrives at a wait page, they must wait until all other players in the group have arrived. Then everyone can proceed to the next page.

## Finally

- ► Edit the views.page\_sequence
- Define the session in sessions.py
- Reset the database and run









www.phdcomics.com

### References

http://otree.readthedocs.io/en/latest/