

Sync Team Project

GeoAnalytics Planner Dashboard

Laboratory of advanced programming

Alessandro Savo, 2021372

Leonardo Santucci, 2282707

Academic Year 2025/2026



SAPIENZA
UNIVERSITÀ DI ROMA



Business Problem

- **Context:** The project helps a federation of three companies plan visits for their sales representatives.
- **Data:** We start from an Excel file containing customers, delivery points, sales agents, and revenue data.
- **The Challenge:** Sales representatives have limited time. The problem is deciding **which customers to visit**, in **which order**, and on **which days**.
- **The Goal:** Cover as much relevant revenue as possible within the available working time.
- **What-if Analysis:** The user can easily compare different scenarios by changing the number of available days and the duration of each visit.



Main User Stories (1/2)

- **Upload & Reuse**

"As a Business Analyst, I want to upload an Excel file, so that I can work with the latest data extracted from the ERP."

- **Company Selection**

"As a Sales Manager, I want to select a company, so that I can analyze only the customers and revenue related to that company."

- **Customer Map**

"As a Sales Manager, I want to see the customers of the selected company on a map, so that I can understand their geographic distribution."



Main User Stories (2/2)

- **Start Date & Working Days**

"As a Sales Manager, I want to choose the starting date of the visit campaign, so that I can plan visits for a specific commercial period."

- **Suggested Visit Sequence**

"As a Sales Manager, I want the system to create a suggested sequence of customer visits, so that I can organize the working day."

- **Recoverable Revenue**

"As a Sales Manager, I want to see the estimated recoverable revenue of the proposed plan, so that I can understand the economic value."

- **What-if Analysis**

"As a Sales Manager, I want to change the number of available days and run the analysis again, so that I can compare different scenarios."



Non-Functional Requirements

- **Usability**

The application should be easy to use and understandable without specific technical knowledge.

- **Reusability**

The application should be reusable with future ERP files having the same logical structure.

- **Portability**

The application should be deployable on another computer using Docker and Docker Compose.

- **Accuracy & Robustness**

Provide clear error messages for invalid files and use real geographic coordinates for customer locations.



From Requirements to Interface

These mockups were used to define the structure of the dashboard before implementation.

Mockup 1

Upload and Scenario Setup

Sales Visit Optimizer

ERP Excel File

Company
WINES ▼

Campaign Start Date


Available Working Days

Visit Duration in Hours

Run Analysis

Mockup 2

Results, Map and KPIs



Mockup 3

Suggested Visit Plan

Suggested Visit Plan


Selected Company
WINES

Visit Agenda

DATE	DAY	TIME	CUSTOMER	CITY	ADDRESS	ESTIMATED REVENUE
01/10/2023	Wednesday	09:00 - 11:00	Customer A	Rome	Via Salaria 56	€1,000
01/10/2023	Wednesday	11:30-13:30	Customer B	Rome	Via Bove 24	€7,500
02/10/2023	Thursday	14:30-16:30	Customer C	Guidonia	Via Roma 144	€3,000
03/10/2023	Friday	9:00-11:00	Customer D	Rome	Via Tiburtina 630	€4,100



Software Architecture





Docker Deployment

Docker

Packages the application and its dependencies.

Docker Compose

Orchestrates multi-container lifecycle.

Frontend: Port 8080 (Web UI)

Backend: Port 8000 (REST API)

`docker-compose.yml`

```
backend:
  build: ./backend
  ports: ["8000:8000"]

frontend:
  build: ./frontend
  ports: ["8080:80"]
  depends_on: [backend]
```

Separation of Concerns

Separate host ports **isolate** the end-user Web UI from direct Swagger/REST API debugging.



Data Processing & Deduplication

The same physical location often appears multiple times in the ERP dataset (e.g. multiple invoice or delivery rows).

ERP Deduplication Example (Selected Company: WINES)

Customer A – Via Roma 10 – Row 1 (WINES): EUR 600

Customer A – Via Roma 10 – Row 2 (WINES): EUR 400

↓ **GROUP BY PHYSICAL LOCATION** ↓

Customer A – Via Roma 10 – Total WINES: EUR 1,000 (*1 visit planned*)

1. **Flexible parser:** Handles arbitrary column order and discovers new companies.
2. **Deduplicate:** Groups duplicate ERP rows for the chosen company.
3. **Geocode:** Converts unique delivery addresses into coordinates.
4. **Travel matrix:** Computes driving times with OSRM and Haversine.



Optimization Problem

Finding the exact global optimum is **NP-hard** (Team Orienteering with Time Windows).
An exhaustive search is computationally intractable, requiring **heuristic optimization**.

INPUTS

- ERP Customers & Revenues
- Starting Depot location
- Available business days (N)
- Target visit duration (2h–4h)
- OSRM travel duration matrix


CONSTRAINTS

- **Calendar:** Mon–Fri (skip holidays)
- **Work budget:** max 8h/day (09–18)
- **Lunch slot:** flexible 1h window
- **Uniqueness:** at most 1 visit/client
- **Transfers:** multi-day trips for remote clients

Objective: Maximize total recovered revenue while guaranteeing feasibility.



How the Optimizer Works





Simplified Algorithm

Simplified logic — not the actual source code

```
best = initial_plan

for each iteration:
    partial = destroy(current_plan)
    candidate = repair(partial)

    if candidate is feasible:
        current_plan = candidate

        if candidate is better than best:
            best = candidate

return best
```

DESTROY

Remove some visits.

REPAIR

Try to insert them again in better positions.

FEASIBLE

All time and calendar constraints are respected.

BEST

Keep the best plan found so far.



Real Optimizer Code - Destroy

alns.py

```
num_remove = max(1, int(len(
    route.client_indices) *
    random.uniform(0.1, 0.2)))

indices_to_remove = random.sample(
    range(len(route.client_indices)),
    num_remove)

for idx in sorted(indices_to_remove,
                  reverse=True):
    client_idx = \
        route.client_indices.pop(idx)
```

1. Decide how many visits to remove.
2. Randomly choose the visits.
3. Remove them from the current route.

Why?

Removing visits gives the algorithm space to rebuild part of the route differently.



Real Optimizer Code - Repair

alns.py

```
for client_idx in candidates:
    # ... skips if already scheduled ...

    insertion = _find_best_insertion(...)

    if insertion:
        d_idx, pos, new_route, _ = insertion
        solution.day_routes[d_idx] = new_route
        solution.scheduled_client_ids.add(...)
```

Removed customer



Try possible positions

- Day 1 - Position 1
Not feasible
- Day 1 - Position 2
Feasible
- Day 2 - Position 1
Feasible and better



Choose the best feasible position

_find_best_insertion searches for the best valid day and position.



Testing & Automated Verification

Test Suite Execution (14 Unit Tests)

```
$ pytest -q
.....
14 passed in 8.24s
```

[100%]

Planner & Scheduling (6 tests)

- **Working time:** 8h/day limit and flexible lunch window.
- **Calendar:** Skips weekends and national holidays.
- **Transfers:** >120 min trip threshold and overnight stays.

Geocoding & Routing (8 tests)

- **Civic numbers:** Exact house number parsing and local caching.
- **Travel time:** OSRM matrix with Haversine fallback.
- **Feasibility:** Recheck all constraints on final schedule.

Automated tests guarantee algorithm correctness and dataset integrity.



Conclusions

WHAT WE LEARNED

- Real business data need cleaning before optimization.
- Geographic accuracy strongly affects route quality.
- Route planning must balance revenue, visit time and driving time.
- Heuristic methods can find useful solutions without testing every possible route.
- Docker makes the application easier to reproduce and deploy.



Live Demo

Now let's see the Demo in action!

Live Application:

<http://localhost:8080>