(0%	00-	38.8%	56.1%	71.9%	85.9%	94.3%	98.1%	99.8%	100.0%	100.0%	100.0%	100.0%
olic chargers (%)	90-	38.7%	55.8%	71.5%	85.2%	93.5%	97.6%	99.5%	100.0%	100.0%	100.0%	100.0%
	80-	38.5%	55.5%	70.9%	84.1%	92.5%	96.9%	99.1%	100.0%	100.0%	100.0%	100.0%
	70-	38.3%	55.1%	70.3%	83.1%	91.5%	96.0%	98.3%	99.9%	100.0%	100.0%	100.0%
		37.9%		69.3%		89.7%	94.4%	97.2%	99.1%	99.9%	100.0%	100.0%
of public	50-	37.6%	53.8%	68.1%	79.3%	87.6%	92.5%	95.5%	97.7%	99.2%	99.9%	100.0%
	40-	37.3%	53.2%	67.2%	77.8%	85.9%	91.2%	94.3%	96.6%	98.5%	99.6%	100.0%
lity	30-	37.0%	52.5%	66.4%	76.7%	84.6%	90.1%	93.1%	95.2%	96.7%	97.3%	97.3%
Avaibility	20-	36.1%	51.0%	64.1%	73.6%	81.2%	87.2%	90.0%	91.1%	91.2%	91.2%	91.2%
Av	10-	33.5%	47.2%	58.7%	67.0%	73.3%	78.0%	79.7%	79.8%	79.8%	79.8%	79.8%
		1.0x	1.5x	_		_	3.5x		4.5x	_	5.5x	
EV hosting capacity (in multiples of original)												