Start coding or generate with AI.

Final Project Third FFNN Architecture
Hidden Layers = 3
Neurons:
nn.Linear(28, 15)
nn.ReLU()
nn.Linear(15, 40)
nn.ReLU()
nn.Linear(40, 25)
nn.ReLU()
nn.Linear(25, 1)
nn.Sigmoid())

Epochs: 2000

Optimizer: Adam
lr: 1e-4

```
import pandas as pd
import numpy as np
from sklearn.model_selection import train_test_split
from sklearn.preprocessing import StandardScaler
from sklearn.preprocessing import OneHotEncoder
from sklearn.preprocessing import LabelEncoder
from sklearn.decomposition import PCA
import torch
import torch.nn as nn
import torch.optim as optim
import seaborn as sns
import matplotlib.pyplot as plt
import time
```

```
# capture start time
start_time = time.time()
```

```
data = pd.read_csv('../content/sample_data/project_data.csv')
```

```
# Reviewing data values in dataset
data.head()
```

	Booking_ID	no_of_adults	no_of_children	no_of_weekend_nights	no_of_week_nights	type_of_meal_plan	required_car_parking_space	room_type_reserved	lead_time	arrival_date	mark
0	INN00001	2	0	1	2	meal_plan_1	0	room_type1	224	2017-10-02	
1	INN00002	2	0	2	3	not_selected	0	room_type1	5	2018-11-06	
2	INN00003	1	0	2	1	meal_plan_1	0	room_type1	1	2018-02-28	
3	INN00004	2	0	0	2	meal_plan_1	0	room_type1	211	2018-05-20	
4	INN00005	2	0	1	1	not_selected	0	room_type1	48	2018-04-11	

Next steps: Generate code with data | View recommended plots | New interactive sheet

```
# Preprocess/convert arrival_date column to season:
data['arrival_date'] = pd.to_datetime(data['arrival_date'])
data['month_number'] = data['arrival_date'].dt.month

def month_to_season(month):
    if month in [12, 1, 2]:
        return 'Winter'
    elif month in [3, 4, 5]:
        return 'Spring'
    elif month in [6, 7, 8]:
        return 'Summer'
    elif month in [9, 10, 11]:
        return 'Autumn'
    else:
        return 'Invalid Month'

data['season'] = data['month_number'].apply(month_to_season)
data.head()
```

	Booking_ID	no_of_adults	no_of_children	no_of_weekend_nights	no_of_week_nights	type_of_meal_plan	required_car_parking_space	room_type_reserved	lead_time	arrival_date	mark
0	INN00001	2	0	1	2	meal_plan_1	0	room_type1	224	2017-10-02	
1	INN00002	2	0	2	3	not_selected	0	room_type1	5	2018-11-06	
2	INN00003	1	0	2	1	meal_plan_1	0	room_type1	1	2018-02-28	
3	INN00004	2	0	0	2	meal_plan_1	0	room_type1	211	2018-05-20	
4	INN00005	2	0	1	1	not_selected	0	room_type1	48	2018-04-11	

Next steps: Generate code with data | View recommended plots | New interactive sheet

```
# Remove unneeded columns
data = data.drop(['Booking_ID', 'month_number', 'arrival_date'], axis=1)


# Change order of columns, putting numeric 1st
data = data.iloc[:, [0, 1, 2, 3, 7, 10, 11, 12, 13, 4, 5, 6, 8, 9, 14, 15]]


# Reviewing data values in dataset
data.head()
```

	no_of_adults	no_of_children	no_of_weekend_nights	no_of_week_nights	lead_time	no_of_previous_cancellations	no_of_previous_bookings_not_canceled	avg_price_per_room	no_of_spe
0	2	0	1	2	224	0	0	65.00	
1	2	0	2	3	5	0	0	106.68	
2	1	0	2	1	1	0	0	60.00	
3	2	0	0	2	211	0	0	100.00	
4	2	0	1	1	48	0	0	94.50	

Next steps: Generate code with data | View recommended plots | New interactive sheet

```
# Remove existing column where target will be; identify target column
X = data.drop('booking_status', axis=1)
target_label = data['booking_status']

# Encode target with LabelEncoder
label_encoder = LabelEncoder()
y = label_encoder.fit_transform(target_label)

# Split dataset into training and test sets (75:25 ratio)
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size = 0.25, random_state=123)  # split into train and test sets


# One Hot Encode using scikit-learn OneHotEncoder on the training set
encoder = OneHotEncoder(handle_unknown='error')
encoder.fit(X_train[['type_of_meal_plan', 'room_type_reserved', 'market_segment_type', 'season']])  # columns to fit

encoded_df = pd.DataFrame(encoder.transform(X_train[['type_of_meal_plan', 'room_type_reserved', 'market_segment_type', 'season']]).toarray(),
                          columns=encoder.get_feature_names_out(['type_of_meal_plan', 'room_type_reserved', 'market_segment_type', 'season']))

X_train = pd.concat([X_train.drop(['type_of_meal_plan', 'room_type_reserved', 'market_segment_type', 'season'], axis=1).reset_index(drop=True), encoded_df], axis=1)



# Perform scaling using scikit-learn StandardScaler
scaler = StandardScaler()
scaler.fit(X_train)
X_train_scaled = scaler.transform(X_train)
X_train_scaled = pd.DataFrame(X_train_scaled, columns=X_train.columns)


# One Hot Encode using scikit-learn OneHotEncoder on the test set
encoded_df = pd.DataFrame(encoder.transform(X_test[['type_of_meal_plan', 'room_type_reserved', 'market_segment_type', 'season']]).toarray(),
                          columns=encoder.get_feature_names_out(['type_of_meal_plan', 'room_type_reserved', 'market_segment_type', 'season']))
X_test = pd.concat([X_test.drop(['type_of_meal_plan', 'room_type_reserved', 'market_segment_type', 'season'], axis=1).reset_index(drop=True), encoded_df], axis=1)

# Perform scaling using same scaler identified in the training set scaling process
X_test_scaled = scaler.transform(X_test)
X_test_scaled = pd.DataFrame(X_test_scaled, columns=X_test.columns)
X_test.columns
```

```
Index(['no_of_adults', 'no_of_children', 'no_of_weekend_nights',
       'no_of_week_nights', 'lead_time', 'no_of_previous_cancellations',
       'no_of_previous_bookings_not_canceled', 'avg_price_per_room',
       'no_of_special_requests', 'required_car_parking_space',
       'repeated_guest', 'type_of_meal_plan_meal_plan_1',
       'type_of_meal_plan_meal_plan_2', 'type_of_meal_plan_meal_plan_3',
       'type_of_meal_plan_not_selected', 'room_type_reserved_room_type1',
       'room_type_reserved_room_type2', 'room_type_reserved_room_type3',
       'room_type_reserved_room_type4', 'room_type_reserved_room_type5',
       'room_type_reserved_room_type6', 'room_type_reserved_room_type7',
       'market_segment_type_aviation', 'market_segment_type_complementary',
       'market_segment_type_corporate', 'market_segment_type_offline',
       'market_segment_type_online', 'season_Autumn', 'season_Spring',
       'season_Summer', 'season_Winter'],
      dtype='object')
```

```
# Add PCA here
principal = PCA()
principal.fit(X_train_scaled.iloc[:, 0:9])
```

```
PCA
PCA()
```

```
principal.explained_variance_
```

```
array([1.73259582, 1.44418539, 1.27323741, 0.99439451, 0.96601343,
       0.80637495, 0.76452241, 0.51703961, 0.50196762])
```

```
principal.explained_variance_ratio_
```

```
array([0.19250356, 0.16045914, 0.14146562, 0.11048421, 0.10733088,
       0.08959392, 0.08494381, 0.05744673, 0.05577213])
```

```
plt.plot(principal.explained_variance_)
plt.title('Scree Plot')
plt.xlabel('Component #')
plt.ylabel('Explained Variance')
```

```
Text(0, 0.5, 'Explained Variance')
```




```
# cumulative explained variance
cumulative_variance = np.cumsum(principal.explained_variance_ratio_)
plt.plot(cumulative_variance)
plt.title('Cumulative Explained Variance')
plt.xlabel('Number of Components')
plt.ylabel('Cumulative Explained Variance')
plt.axhline(y=0.8, color='r', linestyle='--')
plt.axvline(x=5, color='grey', linestyle='dotted')
plt.show()

print("Explained variance ratio for each component")
print(principal.explained_variance_ratio_)
```




```
Explained variance ratio for each component
[0.19250356 0.16045914 0.14146562 0.11048421 0.10733088 0.08959392
 0.08494381 0.05744673 0.05577213]
```

```
# start with original set of numeric columns
# project observations onto PCs
latent_features = pd.DataFrame(principal.transform(X_train_scaled.iloc[:, 0:9]))


# take first 6 col from latent_features
X_train_PCA = pd.concat([latent_features.iloc[:, 0:6].reset_index(drop=True), X_train_scaled.iloc[:, 9:].reset_index(drop=True)], axis=1)


# repeat on test set
latent_features = pd.DataFrame(principal.transform(X_test_scaled.iloc[:, 0:9]))
X_test_PCA = pd.concat([latent_features.iloc[:, 0:6].reset_index(drop=True), X_test_scaled.iloc[:, 9:].reset_index(drop=True)], axis=1)


# create tensors from PCA values
X_train_tensor = torch.tensor(X_train_PCA.values, dtype=torch.float32)
y_train_tensor = torch.as_tensor(y_train, dtype=torch.float32)
X_test_tensor = torch.tensor(X_test_PCA.values, dtype=torch.float32)
y_test_tensor = torch.as_tensor(y_test, dtype=torch.float32)


# Divide training set into smaller training & validation datasets (80:20 ratio)
n_samples = X_train_tensor.shape[0]
n_val = int(0.2 * n_samples)
shuffled_indices = torch.randperm(n_samples)
train_indices = shuffled_indices[:-n_val]
```

```
val_indices = shuffled_indices[-n_val:]
train_indices, val_indices

# Assign values to tensor from indices
X_tr = X_train_tensor[train_indices]
y_tr = y_train_tensor[train_indices]
X_val = X_train_tensor[val_indices]
y_val = y_train_tensor[val_indices]


# Define feedforward neural network #1
# Note 3 hidden layers, 3 activation functions
# Sigmoid function used for output layer

seq_model = nn.Sequential(
    nn.Linear(28, 15),
    nn.ReLU(),
    nn.Linear(15, 40),
    nn.ReLU(),
    nn.Linear(40, 25),
    nn.ReLU(),
    nn.Linear(25, 1),
    nn.Sigmoid())
seq_model
```

```
Sequential(
  (0): Linear(in_features=28, out_features=15, bias=True)
  (1): ReLU()
  (2): Linear(in_features=15, out_features=40, bias=True)
  (3): ReLU()
  (4): Linear(in_features=40, out_features=25, bias=True)
  (5): ReLU()
  (6): Linear(in_features=25, out_features=1, bias=True)
  (7): Sigmoid()
)
```

```
# Establish empty arrays to capture losses for plotting later
train_losses = []
validation_losses = []


# Define the training loop
def training_loop(n_epochs, optimizer, model, loss_fn, X_tr, X_val, y_tr, y_val):
    for epoch in range(1, n_epochs + 1):
        X_tr_p = model(X_tr)
        loss_train = loss_fn(X_tr_p, y_tr.unsqueeze(1))
        train_losses.append(loss_train.item())  # for plotting purposes

        X_val_p = model(X_val)
        loss_val = loss_fn(X_val_p, y_val.unsqueeze(1))
        validation_losses.append(loss_val.item())  # for plotting purposes

        optimizer.zero_grad()
        loss_train.backward()
        optimizer.step()

        if epoch == 1 or epoch % 250 == 0:
            print(f"Epoch {epoch}, Training loss {loss_train.item():.4f},"f" Validation loss {loss_val.item():.4f}")


# Ran the training loop for 2000 epochs and used the Adam optimizer, learn rate 4.
optimizer = optim.Adam(seq_model.parameters(), lr=1e-4)
training_loop(
    n_epochs = 2000,
    optimizer = optimizer,
    model = seq_model,
    loss_fn = nn.BCELoss(),
    X_tr = X_tr,
    X_val = X_val,
    y_tr = y_tr,
    y_val = y_val)
```

```
Epoch 1, Training loss 0.6709, Validation loss 0.6701
Epoch 250, Training loss 0.6116, Validation loss 0.6106
Epoch 500, Training loss 0.5056, Validation loss 0.5061
Epoch 750, Training loss 0.4400, Validation loss 0.4424
Epoch 1000, Training loss 0.4181, Validation loss 0.4218
Epoch 1250, Training loss 0.4057, Validation loss 0.4115
Epoch 1500, Training loss 0.3953, Validation loss 0.4032
Epoch 1750, Training loss 0.3872, Validation loss 0.3960
Epoch 2000, Training loss 0.3801, Validation loss 0.3895
```

```
# Plot training and validation loss lines
epochs = range(1, len(train_losses) + 1)
plt.grid()
plt.plot(epochs, train_losses, 'b-', label='Training Loss')
plt.plot(epochs, validation_losses, 'r-', label='Validation Loss')
plt.title('Training and Validation Loss\nModel 3')
plt.xlabel('Epochs')
plt.ylabel('Loss')
plt.legend()
plt.show()
```




```
# Calculate the fitted model predictions for the test set
seq_model(X_test_tensor).detach().numpy()
```

```
array([[0.992761  ],
       [0.9582349 ],
       [0.7493851 ],
       ...,
       [0.9581422 ],
       [0.07055273],
       [0.46920562]], dtype=float32)
```

Create a data frame that combines the actual label values and the predicted probabilities of positive class membership.

```
# Create dataframe that combines actual label vaues vs predicted
# possibilities of a customer cancelling a reserved booking
p_1_actual = pd.DataFrame({'p_1': seq_model(X_test_tensor).detach().numpy().reshape(-1), 'actual': y_test})
p_1_actual.head()
```

	p_1	actual
0	0.992761	1
1	0.958235	1
2	0.749385	1
3	0.294603	1
4	0.221772	1

Next steps: Generate code with p_1_actual | View recommended plots | New interactive sheet

```
# calculate accuracy
from sklearn.metrics import accuracy_score

# Convert probabilities to class predictions using a threshold (e.g., 0.5)
y_pred = (seq_model(X_test_tensor).detach().numpy().reshape(-1) >= 0.5).astype(int)

accuracy = accuracy_score(y_test, y_pred)
print(f"Accuracy: {accuracy}")
```

```
Accuracy: 0.8221854304635762
```

```
# Compute Confusion Matrix
import pandas as pd
# Convert probabilities to class predictions using a 0.5 threshold
y_pred = (seq_model(X_test_tensor).detach().numpy().reshape(-1) >= 0.5).astype(int)

df_confusion = pd.crosstab(y_test, y_pred, rownames=['Actual'], colnames=['Predicted'])
df_confusion
```

Predicted	0	1
Actual		
0	1974	955
1	656	5475

Next steps: Generate code with df_confusion | View recommended plots | New interactive sheet

Calculate the information needed for the ROC curve.

```
# Calculation of data to produce an ROC curve
roc_data = pd.DataFrame({'threshold': np.arange(1, -0.01, -0.01), 'fpr': 0.0, 'tpr': 0.0})
for i in np.arange(1, -0.01, -0.01):

    over_threshold = p_1_actual[p_1_actual['p_1'] >= i]
```

```
    fp = len(over_threshold[over_threshold['actual']==0])
    actuals_0 = len(p_1_actual[p_1_actual['actual']==0])
    fpr = fp/actuals_0

    roc_data.loc[roc_data['threshold'] == i, 'fpr'] = fpr

    tp = len(over_threshold[over_threshold['actual']==1])
    actuals_1 = len(p_1_actual[p_1_actual['actual']==1])
    tpr = tp/actuals_1

    roc_data.loc[roc_data['threshold'] == i, 'tpr'] = tpr
```

```
roc_data
```

	threshold	fpr	tpr
0	1.000000e+00	0.000000	0.002120
1	9.900000e-01	0.002048	0.120372
2	9.800000e-01	0.004780	0.180558
3	9.700000e-01	0.005804	0.236014
4	9.600000e-01	0.008877	0.290654
...	...	...	...
96	4.000000e-02	0.918402	0.999348
97	3.000000e-02	0.938887	0.999511
98	2.000000e-02	0.972687	0.999837
99	1.000000e-02	0.994196	1.000000
100	-8.881784e-16	1.000000	1.000000

101 rows × 3 columns

Next steps: Generate code with `roc_data` | View recommended plots | New interactive sheet

```
# Plot the ROC curve
# Expecting a curve that approaches top-left corner of graph and then
# curves out to the right
roc = sns.lineplot(x='fpr', y='tpr', data=roc_data)
plt.xlim(-0.05, 1.05)

xlims = roc.get_xlim()
ylims = roc.get_ylim()

min_val = min(xlims[0], ylims[0])
max_val = max(xlims[1], ylims[1])

roc.plot([min_val, max_val], [min_val, max_val], linestyle='--', color='blue')

roc.set_xlim(xlims)
roc.set_ylim(ylims)
plt.title('ROC\nModel 3')
plt.xlabel('False Positive Rate')
plt.ylabel('True Positive Rate')

plt.show()
```




```
# Plot jitter plot to visualize predicted probabilities of cancelled bookings
# Expecting a balanced class membership
p_1_actual['actual'] = p_1_actual['actual'].astype(str)

# Create a jitter plot using stripplot
sns.stripplot(x='p_1', y='actual', data=p_1_actual, jitter=0.3)

# Customize the plot (optional)
plt.title('Jitter Plot of Actuals vs Predicted Probability\nModel 3')
plt.xlabel('Predicted Probability of Cancelling Booking')
plt.axvline(x=0.80, color='red', linestyle='--')
```

```
plt.ylabel('Actuals')

# Display the plot
plt.show()
```




```
# Calculate the information needed for the Calibration curve.

calibration_data = pd.DataFrame({'bin_midpoint': np.arange(0.05, 0.96, 0.1),
                                 'observed_event_percentage': 0.0})
for i in np.arange(0.05, 0.96, 0.1):

    in_interval = p_1_actual[(p_1_actual['p_1'] >= (i-0.05)) & (p_1_actual['p_1'] <= (i+0.05))].copy()
    in_interval['actual'] = in_interval['actual'].astype(int)
    num_positive_in_interval = len(in_interval.loc[in_interval['actual'] == 1])
    num_in_interval = len(in_interval)

    oep = num_positive_in_interval/num_in_interval

    calibration_data.loc[calibration_data['bin_midpoint'] == i, 'observed_event_percentage'] = oep

calibration_data
```

	bin_midpoint	observed_event_percentage
0	0.05	0.047386
1	0.15	0.132007
2	0.25	0.314480
3	0.35	0.365571
4	0.45	0.446640
5	0.55	0.560420
6	0.65	0.700910
7	0.75	0.746550
8	0.85	0.860353
9	0.95	0.967837

Next steps: Generate code with calibration_data | View recommended plots | New interactive sheet

```
# Plot the Calibration curve.

roc = sns.lineplot(x='bin_midpoint', y='observed_event_percentage'
        , data=calibration_data)
plt.xlim(-0.05, 1.05)
plt.ylim(-0.05, 1.05)

xlims = roc.get_xlim()
ylims = roc.get_ylim()

min_val = min(xlims[0], ylims[0])
max_val = max(xlims[1], ylims[1])

roc.plot([min_val, max_val], [min_val, max_val], linestyle='--', color='blue')

roc.set_xlim(xlims)
roc.set_ylim(ylims)
plt.title('Calibration Curve\nModel 3')
plt.xlabel('Bin Midpoint')
plt.ylabel('Observed Event Percentage')

plt.show()
```




```
# capture end time
end_time = time.time()

# calculate processing time
elapsed_time = end_time - start_time
print(f"Processing time: {elapsed_time:.4f} seconds")
```

```
Processing time: 49.2068 seconds
```

the end