


SIMD-accelerated data processing

Daniel Lemire, professor
Université du Québec (TÉLUQ)
Montréal 🇨🇦

blog: <https://lemire.me>


X: [@lemire](#)

GitHub: <https://github.com/lemire/>




Doubles every 3 years

Specification	year	one channel
PCIe 1.x	2003	500 MB/s
PCIe 2.x	2007	1 GB/s
PCIe 3.x	2010	2 GB/s
PCIe 4.x	2017	4 GB/s
PCIe 5.x	2019	8 GB/s
PCIe 6.x	2022	16 GB/s
PCIe 7.x	2025	32 GB/s




Disk at gigabytes per second

- Sony PlayStation 5 (2020):
5 GB/s
- Sony PlayStation 6 (2027):
15 GB/s (?)




High Bandwidth Memory

- Xeon Max processors contain 64 GB of HBM
- Bandwidth 800 GB/s




Some numbers

- Processors: 4 GHz
- One byte per cycle: 4 GB/s
- **Easily CPU bound**



- openbenchmarking.org
- 14 GB/s, less than 5.7 GHz
- Parsing JSON at better than 2.5 bytes per cycle



SIMD (Single Instruction, multiple data)

- Allows us to process 16 (or more) bytes or more with one instruction
- Supported on all modern CPUs (phone, laptop)
- Data-parallel types (SIMD) (recently added to C++26)

processor	year	arithmetic logic units	SIMD units
Pentium 4	2000	2	2×128
AMD Zen 2	2019	4	2×256
AMD Zen 5	2024	6	4×512

simdjson: Design

- First scan identifies the structural characters, start of all strings at about 10 GB/s using SIMD instructions.
- Validates Unicode at 30 GB/s.
- Rest of parsing relies on the generated index.
- Allows fast skipping. (Only parse what we need)
- Can minify JSON at 10 to 20 GB/s

```
{  
  "nom": "Marie Dubois",  
  "age": 28,  
  "ville": "Paris",  
  "loisirs": ["lecture", "voyage", "yoga"],  
  "contact": {  
    "email": "marie.dubois@example.com",  
    "phone": "+33123456789"  
  }  
}
```


Usage

You are probably using simdjson:


- Node.js, Electron,...
- ClickHouse
- WatermelonDB, Apache Doris, Meta Velox, Milvus, QuestDB, StarRocks



C++26 (compile-time reflection)



Serialization (Apple Silicon)



Optimization #1: Consteval

The Power of Compile-Time

The Insight: JSON field names are known at compile time!

Traditional (Runtime):

```
// Every serialization call:  
write_string("\"username\""); // Quote & escape at runtime  
write_string("\"level\"");    // Quote & escape again!
```

With Consteval (Compile-Time):

```
constexpr auto username_key = "\"username\""; // Pre-computed!  
b.append_literal(username_key); // Just memcpy!
```


Optimization #2: SIMD String Escaping

The Problem: JSON requires escaping `"`, `\`, and control chars


Traditional (1 byte at a time):

```
for (char c : str) {  
    if (c == '"' || c == '\\ ' || c < 0x20)  
        return true;  
}
```

SIMD (16 bytes at once):

```
auto chunk = load_16_bytes(str);  
auto needs_escape = check_all_conditions_parallel(chunk);  
if (!needs_escape)  
    return false; // Fast path!
```

Deserialization (Apple Silicon)



Example 2. Classifying characters

- comma (0x2c) ,
- colon (0x3a) :
- brackets (0x5b, 0x5d, 0x7b, 0x7d): [,], {, }
- white-space (0x09, 0x0a, 0x0d, 0x20)
- others

Vectorized classification

- Most SIMD ISAs support 'vectorized lookup tables' (at least 16-element)
- Find two tables `H1` and `H2` such as the bitwise AND of the look classify the characters: `H1(low(& 0xf) & H2(c >> 4))`

```
low_nibble_mask = {16, 0, 0, 0, 0, 0, 0, 0, 0, 8, 12, 1, 2, 9, 0, 0};  
high_nibble_mask = {8, 0, 18, 4, 0, 1, 0, 1, 0, 0, 0, 3, 2, 1, 0, 0};
```

Five instructions:

```
nib_lo = input & 0xf;  
nib_hi = input >> 4;  
shuf_lo = lookup(low_nibble_mask, nib_lo);  
shuf_hi = lookup(high_nibble_mask, nib_hi);  
return shuf_lo & shuf_hi;
```

- comma (0x2c): 1
- colon (0x3a): 2
- brackets (0x5b,0x5d, 0x7b, 0x7d): 4
- most white-space (0x09, 0x0a, 0x0d): 8
- white space (0x20): 16
- others: 0

- Part of Safari, Chrome, and most browsers
- Process Unicode and Base64 formats at gigabytes per second
- Support LoongArch, x64, ARM, POWER, RISC-V



simdutf

Unicode (UTF-16)

- Code points from U+0000 to U+FFFF, a single 16-bit value.
- Beyond: a surrogate pair [U+D800 to U+DBFF] followed by U+DC00 to U+DFFF

Validate

- Check whether we have a lone code unit ($x \leq 0xD7FF \vee x \geq 0xDBFF$), if so ok
- Check whether we have the first part of the surrogate ($0xD800 \leq x \leq 0xDBFF$) and if so check that we have the second part of a surrogate

Validate


```
PROCEDURE validate_utf16(code_units)
  i ← 0
  WHILE i < |code_units|
    unit ← code_units[i]
    IF unit ≤ 0xD7FF OR unit ≥ 0xE000 THEN
      INCREMENT i
      CONTINUE
    IF unit ≥ 0xD800 AND unit ≤ 0xDBFF THEN
      IF i + 1 ≥ |code_units| THEN
        RETURN false
      next_unit ← code_units[i + 1]
      IF next_unit < 0xDC00 OR next_unit > 0xDFFF THEN
        RETURN false
      i ← i + 2 // Valid surrogate pair
      CONTINUE
    RETURN false
  RETURN true
```

UTF-16

- Write SIMD correction function (not just validation)
- Actually deployed in v8 (Google Chrome, Microsoft Edge)

UTF-16 correction, Apple M4

	scalar	ARM NEON
GB/s	2.2	18.9
ins/byte	12.0	0.9



Base64

- Encodes binary data to text using 64 characters (A-Z, a-z, 0-9, +, /)
- 3 bytes input → 4 characters output (33% overhead)
- Used in data URLs, email, web APIs

New JavaScript functions

```
const b64 = Uint8Array.toBase64(bytes);      // string  
const recovered = Uint8Array.fromBase64(b64); // Uint8Array, matches original 'bytes'
```

- SIMD accelerates encoding/decoding to gigabytes per second
- Part of simdutf: fast, portable implementations

Result in the browser (Safari, Apple M4)

```
Uint8Array.fromBase64()           0.00292 ms (±0.88%) → 10716.22 MiB/s
Uint8Array.fromBase64() (line breaks) 0.00499 ms (±41.96%) → 6266.53 MiB/s
Uint8Array.toBase64()             0.00154 ms (±1.19%) → 20247.26 MiB/s
```

Test in your browser at <https://simdutf.github.io/browserbase64/>

Interested? Check these projects

- simdjson: The fastest JSON parser in the world <https://simdjson.org>
 - Node.js, Electron,...
 - ClickHouse, WatermelonDB, Apache Doris, Meta Velox, Milvus, QuestDB, StarRocks
- simdutf: Unicode routines (UTF8, UTF16, UTF32) and Base64 <https://github.com/simdutf/simdutf>
 - Node.js, Bun, WebKit (Safari), Chromium (Chrome, Edge)

Credit

- simdjson reflection work with Francisco Geiman Thiesen (Microsoft)
- simdutf UTF-16 correction is joint work with Robert Clausecker
- simdjson and simdutf are community efforts (Geoff Langdale, John Keiser, Paul Dreik, Yagiz Nizipli and others)


Measurements

- We often assume that measurements (timings) are normally distributed.
- It is often an incorrect assumption.


Measurements

- If your measurements are normally distributed, the 'error' falls off as $1/\sqrt{N}$


Original normal distribution



Sum of 10 i.i.d. normals / 10





Sigma events



- 1-sigma is 32%
- 2-sigma is 5%
- 3-sigma is 0.3% (once every 300 trials)
- 4-sigma is 0.00669% (once every 15000 trials)
- 5-sigma is 5.9e-05% (once every 1,700,000 trials)
- 6-sigma is 2e-07% (once every 500,000,000)
- $e^{-n^2/2} / (n * \sqrt{\pi/2}) \times 100$ for $n > 3$

What if we dealt with log-normal distributions?



Real-world measurements

- You cannot assume normality
- Measurements are **not independent**.
- Reality: the absolute minimum is often a *reliable metric*
- Margin: difference between mean and minimum

Conclusion

- Processors are getting much better! Wider!
- 'hot spot' engineering can fail, better to reduce overall instruction count.
- Branchy code can do well in synthetic benchmarks, but be careful.