Interface First, Then Teach, Then Consolidate: Self-Evolution of a 4B Local Computer-Use Agent on a Four-Dollar Teacher Budget

Wenbo Yan

October 2026

Draft v0.3, 2026-10-26 (§7 daily use rewritten: WeChat, decision-model routing, latency; references added). Every number is taken from a file under `evidence/` (cited in brackets). Concurrent work (Terminal-RSI, Harness²) is discussed in §7. Statistical tests are two-sided Fisher exact tests over task runs unless stated; small samples are marked as directional.

Abstract

We study how far a 4-billion-parameter local model (Agents-A1-4B, 4-bit, llama.cpp) can improve itself at computer-use tasks — file editing, web forms and native macOS applications — when a cloud teacher is available but capped at US$4 for the whole project (US$1.83 spent). Four findings come from controlled same-session comparisons on frozen benchmarks with programmatic checkers; a fifth from putting the agent in daily use:

1. **Learning from demonstrations works in context, on file tasks.** Trajectory memory or verified skills raise in-family success from 14/48 to 39–42/48 after a 60-task stream; skills are not better than plain memory.
2. **On web and desktop tasks, small students retrieve guidance but do not follow it.** Correct teacher guidance is present in the prompt, yet the student's actions do not change. Before calling this a capability gap, we found that several "capability" failures were *interface* failures: making one observation field explicit takes a settings task from 1/18 to 17/18 ($p < 1e\text{-}5$); replacing free-text editing with line-based tools takes desktop TextEdit tasks from 4/18 to 17/18 ($p = 2e\text{-}5$).
3. **Teacher lessons are adopted only when the student must ground them in the current task.** On unseen desktop tasks, lessons in the system prompt change nothing (3/15 vs 3/15); asking the student to first write how each lesson applies to this task gives 10/15 ($p = 0.025$), and a plan-only control separates the two effects.
4. **Consolidating guided successes into LoRA weights removes the need for guidance in-family (30/72 → 65/72) but erodes held-out code-writing (15/36 → 1/36).** Across five ablations, gain and forgetting come from the *same* training samples; replay (random or gradient-selected) protects only capabilities its data covers, and the trained student stops verifying its own output (48/72 → 0).
5. **In daily use, the 4B model should not be the one making choices.** A hosted decision model answering one multiple-choice question per request routes it to a program handler: 30/30 on two held-out phrasing sets where hand-written patterns get 15/30 and 16/30. Measured per stage, the model's latency is prompt reading and long retelling, not reasoning: routing a weather question away from web search takes it from 36 s to 0.8 s, and a knowledge question from 16 s (and a wrong answer) to 2.3 s.

With the resulting interface and grounded lessons, the student solves 41/45 native macOS tasks through the Accessibility API (baseline 19/30 on the training tasks, 3/15 on unseen variants). We argue that a self-improving small agent should, in order: rule out interface causes, teach procedures in a form the student adopts, and only then consolidate — while monitoring held-out behaviour, not just in-family scores.

1. Introduction

Small local models are private, cheap and always available, but weak. A useful personal agent built on one should improve with use: notice failures, get help at bounded cost, keep what it learns, and not apply it where it does not belong. Recent self-improvement work either changes the *harness* around a strong model (prompts, skills, memory; Harness², Meta-Harness) or changes the *weights* of a mid-size model with large compute (Terminal-RSI, 27B). Both implicitly assume the model follows the guidance it is given.

We test that assumption at the other end of the scale: a 4B model on consumer hardware (Kaggle T4, an Apple M4 laptop), a teacher (DeepSeek) behind a global US$4 ledger, and three task domains with hidden checkers. Our contribution is less a new method than a set of controlled findings about *where* a small self-improving agent fails and what fixes each failure:

- an **adoption gap**: retrieval is reliable, adoption is not (§4);
- **interface artefacts** that masquerade as capability gaps, found with one-field ablations (§5);
- **grounded lessons**: a cheap prompting change that makes teacher rules effective on unseen tasks (§5.3);
- **consolidation trade-offs**: a five-version ablation that localises forgetting to the samples that carry the gain (§6);
- **choices to a decision model, actions to the program** in daily use, with the failure modes that motivated it (invented tool results, look-alike requests) and a per-stage latency analysis (§7).

All code, frozen benchmarks, raw runs and per-experiment reports are public; negative results are reported.

2. System

Student and loop. Agents-A1-4B (Q4_K_M) served by llama.cpp; an agentic loop with at most 5–8 steps and 6–10 model calls per task; tools depend on the domain (workspace file tools; browser observe/act on DOM snapshots; macOS Accessibility press/fill/menu). The checker never reaches the agent.

Learning loop. After a failure the teacher solves the task from a clean state (cached per task instance); a verified demonstration becomes trajectory memory and/or a parameterised, sandbox-verified skill. A TF-IDF relevance gate shows learned items only for tasks close to where they were verified; when nothing passes, the request is byte-identical to the raw student's.

Lessons. After a failure the teacher compares the student's actions with the checker's finding and writes one or two general imperative rules without task-specific values; rules are gated like memory.

Consolidation loop (R). Following RSR-style re-execution: the student re-attempts practice variants *with* guidance (demonstration + rules), only verified successes are kept, the guidance is removed, and the student is fine-tuned with LoRA (rank 16 on attention-output and MLP projections, response-only loss) and evaluated without guidance.

Decision model. For choices rather than text, a hosted decision model (Cloudflare Clef, 27B) answers typed questions — yes/no or one of named options — with calibrated probabilities in about 0.3 s. It never writes text or acts. It extracts per-item goals for a web checker (§5.1) and routes daily requests (§7.2).

Budget. Every cloud call reserves against a global ledger before it is sent (US$4 total; US$1.83 spent over all experiments, including void runs; decision-model calls are booked at list price, US$0.10 in total, although they ran inside the provider's free allocation) [ledger, `core/evolution/teacher_budget.py`].

3. Benchmarks

- **Kage-Stream (files)**: 4 learned families, 2 held-out families (text normalisation, config migration) and 3 read-only negative families; procedurally generated, frozen by hash, calibrated so the raw student passes 10–50% [`eval/stream_v1`].
- **Kage-Web**: local fixtures for invoices (hidden rows), notification settings, hotel catalogue (ratings behind "Details"), a two-step profile form (held-out) and read-only lookups [`eval/stream_web_v1`].
- **Desktop-v1 (macOS)**: Calculator (4 + 2 unseen chain variants), TextEdit (3 + 3 unseen variants, dedicated files) and read-only System Settings (3), driven only through the Accessibility API — no keyboard events, no coordinates; checkers read the app or the disk themselves [`eval/desktop_v1`].

Evaluation discipline. GPU inference is not bit-reproducible even at temperature 0: four identical raw-student evaluations gave 7–13/24 in-family [`docs/report/kage-tech-report.md` §5.4]. We therefore compare arms in the same session with ≥ 3 runs and treat differences inside that range as noise.

4. Learning in context, and the adoption gap

Files (E-1). After a 60-task stream, trajectory memory reaches 42/48 and a skill library 39/48 in-family against 14/48 for the raw student and 12/48 for a budget-matched retry baseline (skills vs raw: $p = 6e\text{-}8$; skills vs memory: 5 vs 8 discordant pairs, $p = 0.58$) for US$0.07–0.20 per arm. Learned knowledge distracted the student on held-out families until the relevance gate restored them to the raw student's range with zero misuse [tech report §5].

Web (C2, C3). The same memory barely helps on web tasks (learned arms 20/72 vs raw 12/54, p = 0.54). Per-task inspection shows retrieval is not the problem: every evaluation prompt contained the relevant demonstration, yet the student followed it in 1–2 of 6 invoice tasks [`evidence/reports/c2`]. Teacher-written rules fix a *missing-step* failure (invoices: 0/24 → 14/24 with rules) [`evidence/reports/c3`]; guided re-execution also helps only where a step or idiom is missing (guided 71/112 vs unguided 34/112, p = 1e-6, but settings 6 vs 6 and hotels 7 vs 8) [`evidence/reports/r2`].

5. Interface first

That the interface between agent and computer matters is not new: SWE-agent designed an agent-computer interface (file viewer, editor with linting, search commands) and showed large gains for software-engineering agents built on strong models (Yang et al., 2024). Our contribution here is narrower and diagnostic: with a 4B student we isolate *single* interface factors — one observation field, one tool family — in controlled ablations, and show that failures we had attributed to missing capability, and that demonstrations, rules and consolidation did not fix, disappear when that one factor changes.

5.1 Web: one field (C4)

Settings tasks resisted demonstrations, rules and consolidation, and we had cited them as "knows but cannot do". Our compact observation omitted `checked: false` for unchecked boxes. With the raw student and no guidance [`evidence/reports/c4/analysis.md`]:

Interface	Settings (/18)	Total (/90)	Max input tokens
v1 (unchecked boxes have no `checked` key)	1	29	7,545
v2 (explicit `checked: true/false`)	14	41	7,406
v2 + context packing + state table	17	39	3,946

A second round [`evidence/reports/c4/round2.md`] re-baselined the benchmark on v2 (41/90, settings 18/18). A pre-save checker — Clef extracts per-item goals (48/48 correct), a program compares them with the page — never fired (0 of 59 checks): once the interface was fixed there was nothing left for it to catch. Hotel failures, which we first attributed to context packing, are procedural: the student never opens "Details" to compare ratings, with or without packing (7 vs 4/18, p = 0.47).

5.2 Desktop: line-based editing (G0)

Driving TextEdit through the Accessibility API with a `fill(text)` tool, the student fails 14 of 18 edits, all on line breaks: it drops the final newline or writes a literal `\n`. Teacher rules plus planning do not help (4/12) — the student *states* that each line ends with a newline and still emits the wrong JSON string. Tools that remove the need to encode control characters solve it [`evidence/reports/g0/analysis.md` §5]:

TextEdit tools	Fix typo (/6)	Append line (/6)	Write lines (/6)	Total
`fill` (whole text)	0	3	1	4/18
+ `replace_text`, `append_text`	6	2	0	8/18
`replace_text` + `append_lines` / `set_lines`	6	5	6	**17/18**

Two smaller interface slips on the desktop (the student passed a control's id or the whole observation line as its reference) were fixed by accepting both.

5.3 Grounded lessons (G0)

Calculator chain tasks fail on operator precedence: the student presses `15 + 27 × 3 =` and gets 96. The teacher wrote one rule from the failure ("when an expression mixes addition and multiplication, press Equals after the addition…", cost US$0.0005 for all four rules). On five unseen variants (three runs each):

Arm	Calculator chains (/6)	TextEdit (/9)	Total (/15)
no lessons	1	2	3
lessons in the system prompt	1	2	**3**
"write a plan first", no lessons	4	2	6
lessons next to the task + "say how each lesson applies, then act"	5	5	**10** (p = 0.025)

In the system prompt the rules are ignored: the student still presses `9 + 6 × 4 =`. Requiring it to ground each rule in the current task (an exact button order) makes it adopt them, and it generalises the addition rule to a subtraction/division variant ("press Equals to get 36, then divide"). The plan-only control shows that planning alone explains most of the Calculator gain, while the TextEdit gain needs the rule content.

Final desktop configuration (line-based tools, interface fixes, grounded lessons; 15 tasks × 3 runs): **41/45** — training tasks 29/30 (baseline 19/30, p = 0.003), unseen variants 12/15 (3/15, p = 0.003); Calculator 17/18, TextEdit 15/18, System Settings (read-only) 9/9 [`evidence/reports/g0/analysis.md` §6].

6. Consolidation: gain and forgetting come from the same samples

R2 collected 1,900 guided successes (guidance stripped); R3 trains a LoRA adapter and evaluates without guidance (file sets: 24 in-family + 12 held-out per run, 3 runs; web: 18 learned per run) [`evidence/reports/r3*`]:

Version	Training change	Files in-family (/72)	Held-out (/36)	Web learned (/54)
raw student	—	30	15 (pooled 27/60)	10
R3	guided successes	64 (p = 2.6e-9)	**1**	21
R3b	drop reasoning-free targets + random replay	34	**15**	31
R3c	drop + gradient-selected (LESS) replay	34	2	22
R3d	teacher rationales for reasoning-free targets + LESS replay	62	6	20
R3e	rationales + random replay	**65**	**1**	22

General-ability check (30 questions): 27–28/30 for every version. Under the round-2 web interface, R3e solves 7/18 invoices where the raw student solves 0/54 (p = 2e-5): consolidated knowledge survives an interface change.

LoRA is known to forget less than full fine-tuning, and also to learn less (Biderman et al., 2024). Even so, a rank-16 adapter trained on about 1,900 samples erased held-out code writing here; what the ablation adds is *which* samples do it. What the five versions show:

- **Gain and forgetting move together.** Held-out success collapses exactly when the ~300 file-solution steps (`write_file` targets, mostly without reasoning in the raw data) are trained (R3, R3d, R3e) and is preserved only when they are removed (R3b) — which also removes the in-family gain. Replay type and the presence of reasoning do not change this.
- **Replay protects only what it covers.** Our replay data (desktop-action text from AgentNet, MCP tool calls from Toucan) contains no code writing; neither random nor gradient-selected replay protected held-out *code* tasks. Gradient-influence selection (LESS) picks data aligned with the target — the opposite of what anti-forgetting replay needs.

- **The mechanism is code quality plus a lost habit.** On held-out tasks the trained student writes plausible but wrong code (e.g. `encode("ascii")` that raises on non-ASCII input) and no longer reads its output back: read-back verification after writing drops from 48/72 runs (raw) to 0 for every trained version, because training trajectories end as soon as the checker passes. "Not writing reasoning", our first explanation, was a symptom: R3d/R3e reason before every call and still forget.

Implications we did not test (compute ended with this study): self-distilled replay of the raw student's own correct code on other tasks, keeping write-then-verify steps in training trajectories, and gating the adapter by task family at deployment.

7. From benchmark to daily use

7.1 The program supplies information and acts

We then put the student behind the user's own requests on their Mac (calendar, mail, open documents, apps, websites, WeChat) and logged every turn. The benchmark pattern held in a sharper form: the model is reliable when the program hands it the information and the narrow tool surface the request needs, and unreliable otherwise [`evidence/reports/d0–d5`, `d4`].

Request type	Model chooses among ~25 tools	Program supplies information / acts directly
Edit an open document	invents paths (`/Users/yourname/⋯`), ≈2/10	server attaches the real path (read from the window's accessibility attribute), doc tools only: **11/11**
Open an app ("微信", "vscode")	5 of 9 replies claim "opened" with no tool call	resolver over localized app names + server fast path: **20/20**
Today's schedule	—	small helper app with its own permission text (Python is denied silently; AppleScript does not expand recurring events): **5/5** test events, one brief per day
Unread mail / summarize message *N*	—	Mail scripting (read-only) + local summary: **10/10** summaries without factual errors
Website content	old video/search heuristics answer instead	one read-only OpenCLI tool and the site's commands: Bilibili 3/3, Zhihu 3/3 (after login)
WeChat unread	—	the app exposes six accessibility nodes; window screenshot + on-device OCR: names 10/10, times 10/10, unread markers 4/4
WeChat send	—	search → click the exact-name entry → read the chat title back → paste → check the new bubble: 7/7 delivered

Every step of the WeChat sender is followed by a check, because GUI effects are not predictable: in the first live send, Return in the search box opened a web search instead of the contact, and the title check stopped the send before anything was typed. An unknown or misspelt recipient is looked up first ("wenbo yen" → "Wenbo yan?", sent only after confirmation); a name that is not in the contacts is never sent to.

Two near-misses. (i) Asked to edit a file that did not exist, the server fell back to listing every open document; the model then ran three replacements on the user's real source file in another editor (each replaced a line with itself, so the content was unchanged). The fix is least privilege rather than instructions: each turn may write only the files the request names and that exist, never a substitute, and no-op edits are rejected (re-test 11/11, the real file untouched). (ii) A bare "确认" (confirm) with no message pending reached the model, which replied "sent to Wenbo yan" — nothing had been sent. Confirmations are now answered by the program, and the per-turn usage log marks "claimed done without any tool call" (including "已发给", *sent*) as its own status; this status is also how the false "opened" replies were caught.

7.2 Choices to a decision model

Which handler a request needs was first decided by hand-written patterns. They are fast but know only the phrasings written into them and misfire on look-alikes. We replaced them with one decision-model question per turn ("which of these twelve kinds of request is this?", plus the day for schedule questions and read-or-summarize for mail), sent at the start of the turn so it overlaps the server's other checks. Below 0.8 confidence the request goes to the general local-model loop; if the decision model is unavailable, the patterns decide. Handlers still cut out text parameters themselves (recipient, message number, app name); when a WeChat request has no explicit boundary between recipient and message, the local model extracts them and the recipient must occur verbatim in the request [`evidence/reports/d7`, `eval/intent_v1`]:

Phrasing set	Classes	Patterns	Decision model	With threshold (unsure → local model)
held-out 1 (30, run once)	10	15/30	**30/30**	30/30
held-out 2 (30, run once)	12	16/30	**30/30**	28/30 (two correct answers below 0.8)

Pattern errors include "明天会下雨吗" (will it rain tomorrow) → schedule, "B 站是哪一年成立的" (when was Bilibili founded) → website, and "打开第一封看看" (open the first one, i.e. e-mail) → open an app; most new phrasings were simply not recognised. The same split serves website requests: the decision model picks the site command, row count and search term (from candidates the program cuts out of the request), and whether the user only wants the list. On ten held-out phrasings it chose the command correctly 10/10; a regex shortcut tried first got 2 of 7 wrong [`evidence/reports/d5/clef-routing`]. Asking about a concrete item ("does the request ask to summarise, compare, pick the highest or filter?") worked better than asking for a judgement ("is a plain list enough?"): the list-only decision was wrong on 2 of 12 development phrasings with confidences of 0.6–0.8, and on 1 of 12 with confidences mostly above 0.83 — the same pattern as in our decision-model benchmark, where whole-state judgements scored 0.64 and per-item extraction 1.00 [`evidence/reports/decision-thx01/report.md`].

Latency. On the M4 laptop the 4B model reads about 300 prompt tokens/s and writes about 26 tokens/s, so a reply's cost is set by prompt length and answer length. Per-stage timings in the usage log located the slow paths:

Request	Before	After	Cause
明天会下雨吗 (rain tomorrow?)	36.5 s, web search	0.8 s	weather path required the word "天气"; now routed
B 站是哪一年成立的 (knowledge)	16 s, "cannot find"	2.3 s, "2009"	tool loop with a 2,200–3,600-token prompt → short fixed chat prompt
知乎热榜前三 (top three on Zhihu)	14 s	4.5 s; 0.4 s repeated	model choosing the command (4.2 s) and retelling the list (5.7 s) → decision model + program listing; 5-minute cache for public lists
知乎上大家在聊什么 (what is Zhihu discussing)	27 s	4.8 s	model re-chose the command and retold ten rows (353 tokens) → run the decision model's first choice, model answers in three sentences

The routing call costs about US$0.00013 at list price; 248 calls in this study stayed within the free allocation. A live demonstration recorded on the user's Mac is in `docs/assets/demo/kage-live-demo.mp4`.

8. Related and concurrent work

Learning from experience in context. Skill libraries (Voyager; Wang et al., 2023), experience memory and extracted insights (ExpeL; Zhao et al., 2024; Agent Workflow Memory; Wang et al., 2025), evolving playbooks (ACE; Zhang et al., 2025) and skills co-trained with RL (SkillRL; Xia et al., 2026). These mostly use strong models; we find that a 4B student retrieves such guidance reliably but often does not act on it (§4) unless asked to ground it (§5.3).

Self-improvement of the harness or the weights. Harness search (ADAS; Hu et al., 2024; Meta-Harness; Lee et al., 2026; Harness², concurrent, Google, 2026) changes prompts, tools and memory around a model; weight-level methods include STaR (Zelikman et al., 2022), context distillation (Snell et al., 2022), expert iteration (Anthony et al., 2017) and, concurrently, Terminal-RSI (Yang et al., 2026), whose recursive self-rewrite (RSR) re-executes tasks with runbooks before SFT and RL at 27B. Our consolidation loop borrows RSR's guided re-execution explicitly; the in-context learning and adoption findings predate our reading of it (worklog timestamps). Gradient-based data selection (LESS; Xia et al., 2024) is the replay selector we found counter-productive for forgetting (§6); replay data came from AgentNet (OpenCUA; Wang et al., 2025) and Toucan (Xu et al., 2025).

Interfaces and routing. SWE-agent (Yang et al., 2024) is the closest work on agent-computer interfaces (§5); the ARTEMIS Android automation project prompted our interface ablation. Routing a request to a handler with a classifier is classic intent detection; LLM routers such as RouteLLM (Ong et al., 2025) route between *models* for cost, and semantic routers match embeddings against example utterances. Our router asks a calibrated choice model one question per turn and keeps a confidence fallback to the general loop (§7.2). A longer survey is in `docs/report/related-work.md`.

9. Limitations

Small samples (18–90 runs per arm; several p-values are directional); one student model; procedurally generated tasks with templated instructions (the TF-IDF gate relies on this); desktop tasks are few and partly read-only for safety; the pre-save checker's goals were extracted once and cached; consolidation used a single LoRA configuration and no RL. Desktop runs were on one Mac with one llama-server; GPU and CPU non-determinism means single-run comparisons are unreliable, which is why every comparison here is same-session and replicated. The daily-use results (§7) come from one user on one Mac with tens of requests per type; the phrasing sets were written by the authors, not collected from users. Routing sends each request's text to a hosted model; mail and WeChat content, documents and screenshots stay on the machine, but a privacy-strict setting would need a local router (the cached decision-model labels are a natural distillation set).

10. Conclusion

For a small local agent, "it retrieved the right guidance and still failed" is common, and the cause is often not capability. In order: make the observation and tools state what the student needs without inference or escaping (one field, one tool), make it ground teacher rules in the current task before acting, and only then consolidate — measuring held-out behaviour, because the samples that teach a family are the ones that overwrite general skills. On a US$4 budget this took a 4B model to 41/45 on real macOS applications. In daily use the same lesson goes one step further: let a decision model make the choices and the program take the actions, and keep the small model for reading and writing what only it can.

References

- Anthony, T., Tian, Z., Barber, D. (2017). Thinking Fast and Slow with Deep Learning and Tree Search. NeurIPS. arXiv:1705.08439.
- Biderman, D., Portes, J., et al. (2024). LoRA Learns Less and Forgets Less. TMLR. arXiv:2405.09673.
- Google (2026). Harness² (concurrent work). arXiv:2610.14224.
- Google. ARTEMIS: Android automation. github.com/google/artemis.
- Hu, S., Lu, C., Clune, J. (2024). Automated Design of Agentic Systems. arXiv:2408.08435.
- Lee, Nair, Zhang, Lee, Khattab, Finn (2026). Meta-Harness. arXiv:2603.28052.
- Ong, I., et al. (2025). RouteLLM: Learning to Route LLMs from Preference Data. ICLR. arXiv:2406.18665.
- Snell, C., Klein, D., Zhong, R. (2022). Learning by Distilling Context. arXiv:2209.15189.
- Wang, G., et al. (2023). Voyager: An Open-Ended Embodied Agent with Large Language Models. arXiv:2305.16291.
- Wang, X., et al. (2025). OpenCUA: Open Foundations for Computer-Use Agents (AgentNet). NeurIPS. arXiv:2508.09123.
- Wang, Z. Z., Mao, J., Fried, D., Neubig, G. (2025). Agent Workflow Memory. ICML. arXiv:2409.07429.

- Xia, M., Malladi, S., Gururangan, S., Arora, S., Chen, D. (2024). LESS: Selecting Influential Data for Targeted Instruction Tuning. ICML. arXiv:2402.04333.
- Xia, P., Yao, H., et al. (2026). SkillRL: Evolving Agents via Recursive Skill-Augmented Reinforcement Learning. arXiv:2602.08234.
- Xu, Z., et al. (2025). TOUCAN: Synthesizing 1.5M Tool-Agentic Data from Real-World MCP Environments. arXiv:2510.01179.
- Yang, J., Jimenez, C. E., Wettig, A., Lieret, K., Yao, S., Narasimhan, K., Press, O. (2024). SWE-agent: Agent-Computer Interfaces Enable Automated Software Engineering. NeurIPS. arXiv:2405.15793.
- Yang et al. (2026). Terminal-RSI: Recursive Self-Improving Terminal Agents via Recursive Self-Rewrite and Policy-Refine. arXiv:2610.22192.
- Zelikman, E., Wu, Y., Mu, J., Goodman, N. (2022). STaR: Bootstrapping Reasoning With Reasoning. NeurIPS. arXiv:2203.14465.
- Zhang, Q., et al. (2025). Agentic Context Engineering: Evolving Contexts for Self-Improving Language Models. arXiv:2510.04618.
- Zhao, A., et al. (2024). ExpeL: LLM Agents Are Experiential Learners. AAAI. arXiv:2308.10144.

Evidence index: E-1/E-2 `evidence/reports/e1*`, `e2*`; C2 `c2/`; C3 `c3/`; R2 `r2/`; R3–R3e `r3/`, `r3b/`–`r3e/`; C4 `c4/analysis.md`, `c4/round2.md`; G0 `g0/analysis.md`; daily use D0–D7 `d0/`–`d7/` (decision routing `d5/clef-routing/`, `d7/`); raw Kaggle runs `evidence/kaggle/v*-results.tar.gz`.