Interface First, Then Teach, Then Consolidate: Self-Evolution of a 4B Local Computer-Use Agent on a Four-Dollar Teacher Budget

Wenbo Yan

October 2026

Draft v0.2, 2026-10-25 (§6.5 added). Every number is taken from a file under `evidence/` (cited in brackets). Concurrent work (Terminal-RSI, Harness²) is discussed in §7. Statistical tests are two-sided Fisher exact tests over task runs unless stated; small samples are marked as directional.

Abstract

We study how far a 4-billion-parameter local model (Agents-A1-4B, 4-bit, llama.cpp) can improve itself at computer-use tasks — file editing, web forms and native macOS applications — when a cloud teacher is available but capped at US$4 for the whole project (US$1.78 spent). Four findings, each from controlled same-session comparisons on frozen benchmarks with programmatic checkers:

1. **Learning from demonstrations works in context, on file tasks.** Trajectory memory or verified skills raise in-family success from 14/48 to 39–42/48 after a 60-task stream; skills are not better than plain memory.
2. **On web and desktop tasks, small students retrieve guidance but do not follow it.** Correct teacher guidance is present in the prompt, yet the student's actions do not change. Before calling this a capability gap, we found that several "capability" failures were *interface* failures: making one observation field explicit takes a settings task from 1/18 to 17/18 ($p < 1e\text{-}5$); replacing free-text editing with line-based tools takes desktop TextEdit tasks from 4/18 to 17/18 ($p = 2e\text{-}5$).
3. **Teacher lessons are adopted only when the student must ground them in the current task.** On unseen desktop tasks, lessons in the system prompt change nothing (3/15 vs 3/15); asking the student to first write how each lesson applies to this task gives 10/15 ($p = 0.025$), and a plan-only control separates the two effects.
4. **Consolidating guided successes into LoRA weights removes the need for guidance in-family (30/72 → 65/72) but erodes held-out code-writing (15/36 → 1/36).** Across five ablations, gain and forgetting come from the *same* training samples; replay (random or gradient-selected) protects only capabilities its data covers, and the trained student stops verifying its own output (48/72 → 0).

With the resulting interface and grounded lessons, the student solves 41/45 native macOS tasks through the Accessibility API (baseline 19/30 on the training tasks, 3/15 on unseen variants). We argue that a self-improving small agent should, in order: rule out interface causes, teach procedures in a form the student adopts, and only then consolidate — while monitoring held-out behaviour, not just in-family scores.

1. Introduction

Small local models are private, cheap and always available, but weak. A useful personal agent built on one should improve with use: notice failures, get help at bounded cost, keep what it learns, and not apply it where it does not belong. Recent self-improvement work either changes the *harness* around a strong model (prompts, skills, memory; Harness², Meta-Harness) or changes the *weights* of a mid-size model with large compute (Terminal-RSI, 27B). Both implicitly assume the model follows the guidance it is given.

We test that assumption at the other end of the scale: a 4B model on consumer hardware (Kaggle T4, an Apple M4 laptop), a teacher (DeepSeek) behind a global US$4 ledger, and three task domains with hidden checkers. Our contribution is less a new method than a set of controlled findings about *where* a small self-improving agent fails and what fixes each failure:

- an **adoption gap**: retrieval is reliable, adoption is not (§4);

- **interface artefacts** that masquerade as capability gaps, found with one-field ablations (§5);
- **grounded lessons**: a cheap prompting change that makes teacher rules effective on unseen tasks (§5.3);
- **consolidation trade-offs**: a five-version ablation that localises forgetting to the samples that carry the gain (§6).

All code, frozen benchmarks, raw runs and per-experiment reports are public; negative results are reported.

2. System

Student and loop. Agents-A1-4B (Q4_K_M) served by llama.cpp; an agentic loop with at most 5–8 steps and 6–10 model calls per task; tools depend on the domain (workspace file tools; browser observe/act on DOM snapshots; macOS Accessibility press/fill/menu). The checker never reaches the agent.

Learning loop. After a failure the teacher solves the task from a clean state (cached per task instance); a verified demonstration becomes trajectory memory and/or a parameterised, sandbox-verified skill. A TF-IDF relevance gate shows learned items only for tasks close to where they were verified; when nothing passes, the request is byte-identical to the raw student's.

Lessons. After a failure the teacher compares the student's actions with the checker's finding and writes one or two general imperative rules without task-specific values; rules are gated like memory.

Consolidation loop (R). Following RSR-style re-execution: the student re-attempts practice variants *with* guidance (demonstration + rules), only verified successes are kept, the guidance is removed, and the student is fine-tuned with LoRA (rank 16 on attention-output and MLP projections, response-only loss) and evaluated without guidance.

Budget. Every cloud call reserves against a global ledger before it is sent (US$4 total; US$1.78 spent over all experiments, including void runs) [ledger, `core/evolution/teacher_budget.py`].

3. Benchmarks

- **Kage-Stream (files)**: 4 learned families, 2 held-out families (text normalisation, config migration) and 3 read-only negative families; procedurally generated, frozen by hash, calibrated so the raw student passes 10–50% [`eval/stream_v1`].
- **Kage-Web**: local fixtures for invoices (hidden rows), notification settings, hotel catalogue (ratings behind "Details"), a two-step profile form (held-out) and read-only lookups [`eval/stream_web_v1`].
- **Desktop-v1 (macOS)**: Calculator (4 + 2 unseen chain variants), TextEdit (3 + 3 unseen variants, dedicated files) and read-only System Settings (3), driven only through the Accessibility API — no keyboard events, no coordinates; checkers read the app or the disk themselves [`eval/desktop_v1`].

Evaluation discipline. GPU inference is not bit-reproducible even at temperature 0: four identical raw-student evaluations gave 7–13/24 in-family [`docs/report/kage-tech-report.md` §5.4]. We therefore compare arms in the same session with ≥ 3 runs and treat differences inside that range as noise.

4. Learning in context, and the adoption gap

Files (E-1). After a 60-task stream, trajectory memory reaches 42/48 and a skill library 39/48 in-family against 14/48 for the raw student and 12/48 for a budget-matched retry baseline (skills vs raw: $p = 6e\text{-}8$; skills vs memory: 5 vs 8 discordant pairs, $p = 0.58$) for US$0.07–0.20 per arm. Learned knowledge distracted the student on held-out families until the relevance gate restored them to the raw student's range with zero misuse [tech report §5].

Web (C2, C3). The same memory barely helps on web tasks (learned arms 20/72 vs raw 12/54, $p = 0.54$). Per-task inspection shows retrieval is not the problem: every evaluation prompt contained the relevant demonstration, yet the student followed it in 1–2 of 6 invoice tasks [`evidence/reports/c2`]. Teacher-written rules fix a *missing-step* failure (invoices: 0/24 → 14/24 with rules) [`evidence/reports/c3`]; guided re-execution also helps only where a step or idiom is missing (guided 71/112 vs unguided 34/112, $p = 1e\text{-}6$, but settings 6 vs 6 and hotels 7 vs 8) [`evidence/reports/r2`].

5. Interface first

5.1 Web: one field (C4)

Settings tasks resisted demonstrations, rules and consolidation, and we had cited them as "knows but cannot do". Our compact observation omitted `checked: false` for unchecked boxes. With the raw student and no guidance

[evidence/reports/c4/analysis.md]:

Interface	Settings (/18)	Total (/90)	Max input tokens
v1 (unchecked boxes have no `checked` key)	1	29	7,545
v2 (explicit `checked: true/false`)	14	41	7,406
v2 + context packing + state table	17	39	3,946

A second round [evidence/reports/c4/round2.md] re-baselined the benchmark on v2 (41/90, settings 18/18). A pre-save checker — Clef extracts per-item goals (48/48 correct), a program compares them with the page — never fired (0 of 59 checks): once the interface was fixed there was nothing left for it to catch. Hotel failures, which we first attributed to context packing, are procedural: the student never opens "Details" to compare ratings, with or without packing (7 vs 4/18, p = 0.47).

5.2 Desktop: line-based editing (G0)

Driving TextEdit through the Accessibility API with a `fill(text)` tool, the student fails 14 of 18 edits, all on line breaks: it drops the final newline or writes a literal `\n`. Teacher rules plus planning do not help (4/12) — the student *states* that each line ends with a newline and still emits the wrong JSON string. Tools that remove the need to encode control characters solve it [evidence/reports/g0/analysis.md §5]:

TextEdit tools	Fix typo (/6)	Append line (/6)	Write lines (/6)	Total
`fill` (whole text)	0	3	1	4/18
+ `replace_text`, `append_text`	6	2	0	8/18
`replace_text` + `append_lines` / `set_lines`	6	5	6	**17/18**

Two smaller interface slips on the desktop (the student passed a control's id or the whole observation line as its reference) were fixed by accepting both.

5.3 Grounded lessons (G0)

Calculator chain tasks fail on operator precedence: the student presses `15 + 27 × 3 =` and gets 96. The teacher wrote one rule from the failure ("when an expression mixes addition and multiplication, press Equals after the addition…", cost US$0.0005 for all four rules). On five unseen variants (three runs each):

Arm	Calculator chains (/6)	TextEdit (/9)	Total (/15)
no lessons	1	2	3
lessons in the system prompt	1	2	**3**
"write a plan first", no lessons	4	2	6
lessons next to the task + "say how each lesson applies, then act"	5	5	**10** (p = 0.025)

In the system prompt the rules are ignored: the student still presses `9 + 6 × 4 =`. Requiring it to ground each rule in the current task (an exact button order) makes it adopt them, and it generalises the addition rule to a subtraction/division variant ("press Equals to get 36, then divide"). The plan-only control shows that planning alone explains most of the Calculator gain, while the TextEdit gain needs the rule content.

Final desktop configuration (line-based tools, interface fixes, grounded lessons; 15 tasks × 3 runs): **41/45** — training tasks 29/30 (baseline 19/30, p = 0.003), unseen variants 12/15 (3/15, p = 0.003); Calculator 17/18, TextEdit 15/18, System Settings (read-only) 9/9 [`evidence/reports/g0/analysis.md` §6].

6. Consolidation: gain and forgetting come from the same samples

R2 collected 1,900 guided successes (guidance stripped); R3 trains a LoRA adapter and evaluates without guidance (file sets: 24 in-family + 12 held-out per run, 3 runs; web: 18 learned per run) [`evidence/reports/r3*`]:

Version	Training change	Files in-family (/72)	Held-out (/36)	Web learned (/54)
raw student	—	30	15 (pooled 27/60)	10
R3	guided successes	64 (p = 2.6e-9)	**1**	21
R3b	drop reasoning-free targets + random replay	34	**15**	31
R3c	drop + gradient-selected (LESS) replay	34	2	22
R3d	teacher rationales for reasoning-free targets + LESS replay	62	6	20
R3e	rationales + random replay	**65**	**1**	22

General-ability check (30 questions): 27–28/30 for every version. Under the round-2 web interface, R3e solves 7/18 invoices where the raw student solves 0/54 (p = 2e-5): consolidated knowledge survives an interface change.

What the five versions show:

- **Gain and forgetting move together.** Held-out success collapses exactly when the ~300 file-solution steps (`write_file` targets, mostly without reasoning in the raw data) are trained (R3, R3d, R3e) and is preserved only when they are removed (R3b) — which also removes the in-family gain. Replay type and the presence of reasoning do not change this.
- **Replay protects only what it covers.** Our replay data (desktop-action text from AgentNet, MCP tool calls from Toucan) contains no code writing; neither random nor gradient-selected replay protected held-out *code* tasks. Gradient-influence selection (LESS) picks data aligned with the target — the opposite of what anti-forgetting replay needs.
- **The mechanism is code quality plus a lost habit.** On held-out tasks the trained student writes plausible but wrong code (e.g. `encode("ascii")` that raises on non-ASCII input) and no longer reads its output back: read-back verification after writing drops from 48/72 runs (raw) to 0 for every trained version, because training trajectories end as soon as the checker passes. "Not writing reasoning", our first explanation, was a symptom: R3d/R3e reason before every call and still forget.

Implications we did not test (compute ended with this study): self-distilled replay of the raw student's own correct code on other tasks, keeping write-then-verify steps in training trajectories, and gating the adapter by task family at deployment.

6.5 From benchmark to daily use

We then put the student behind the user's own requests on their Mac (calendar, mail, open documents, apps, websites) and logged every turn. The same pattern held, in a sharper form: the model is reliable when the program hands it the information and the narrow tool surface the request needs, and unreliable otherwise [`evidence/reports/d0–d5`].

Request type	Model chooses among ~25 tools	Program supplies information / acts directly
Edit an open document	invents paths (`/Users/yourname/⋯`), ≈2/10	server attaches the real path (read from the window's accessibility attribute), doc tools only: **11/11**
Open an app ("微信", "vscode")	5 of 9 replies claim "opened" with no tool call	resolver over localized app names + server fast path: **20/20**
Today's schedule	—	small helper app with its own permission text (Python is denied silently; AppleScript does not expand recurring events): **5/5** test events, one brief per day
Unread mail / summarize message *N*	—	Mail scripting (read-only) + local summary: **10/10** summaries without factual errors
Website content	old video/search heuristics answer instead	dedicated loop with one read-only OpenCLI tool and the site's commands: **3/3** on Bilibili

A near-miss. Asked to edit a file that did not exist, the server fell back to listing every open document; the model then ran three replacements on the user's real source file in another editor (each replaced a line with itself, so the content was unchanged). The fix is least privilege rather than instructions: each turn may write only the files the request names and that exist, never a substitute, and no-op edits are rejected (re-test 11/11, the real file untouched). A per-turn usage log marks "claimed done without any tool call" as its own status, which is how the false "opened" replies were caught.

7. Related and concurrent work

Skill libraries (Voyager), experience memory and rule extraction (ACE, SkillRL), harness self-improvement (Meta-Harness; Harness², concurrent), weight-level self-improvement (STaR, context distillation, expert iteration; Terminal-RSI, concurrent: runbook-guided re-execution, SFT and RL at 27B). Our consolidation loop borrows RSR's guided re-execution explicitly; the in-context learning and adoption findings predate our reading of it (worklog timestamps). ARTEMIS (Android automation) prompted the interface ablation. See `docs/report/related-work.md`.

8. Limitations

Small samples (18–90 runs per arm; several p-values are directional); one student model; procedurally generated tasks with templated instructions (the TF-IDF gate relies on this); desktop tasks are few and partly read-only for safety; the pre-save checker's goals were extracted once and cached; consolidation used a single LoRA configuration and no RL. Desktop runs were on one Mac with one llama-server; GPU and CPU non-determinism means single-run comparisons are unreliable, which is why every comparison here is same-session and replicated.

9. Conclusion

For a small local agent, "it retrieved the right guidance and still failed" is common, and the cause is often not capability. In order: make the observation and tools state what the student needs without inference or escaping (one field, one tool), make it ground teacher rules in the current task before acting, and only then consolidate — measuring held-out behaviour, because the samples that teach a family are the ones that overwrite general skills. On a US$4 budget this took a 4B model to 41/45 on real macOS applications.

Evidence index: E-1/E-2 `evidence/reports/e1*`, `e2*`; C2 `c2/`; C3 `c3/`; R2 `r2/`; R3–R3e `r3/`, `r3b/`–`r3e/`; C4 `c4/analysis.md`, `c4/round2.md`; G0 `g0/analysis.md`; raw Kaggle runs `evidence/kaggle/v*-results.tar.gz`.