



API Document v16.0

(updated May 27, 2026)



Table of Contents

1. Authentication.....	3
LOGIN	3
2. Shipment	5
Get ESTIMATE Single Shipment (India Rate Calculator)	5
Get ESTIMATE Multi-Box Shipment (India Rate Calculator).....	8
Get ESTIMATE (India to Foreign Country Rate Calculator).....	12
Book SINGLE Shipment.....	14
Book MULTI-BOX Shipment.....	19
Book Shipment - INTERNATIONAL.....	21
CANCEL Shipment.....	25
REVERSE Shipment	26
TRACK a Shipment.....	27
SYNC Shipment STATUS.....	33
Webhook / POST Call Back on change in Shipment STATUS.....	35
Webhook / POST Call Back for NDR events.....	36
Webhook / POST Call Back for Weight Dispute events.....	38
SYNC Shipment CHARGES.....	39
PRINT Shipment Label	40
3. Pincode	41
Check SERVICEABILITY by PINCODE	41
4. Pickup Address	42
ADD a new PICKUP POINT for your shipments	42
UPDATE an existing PICKUP ADDRESS.....	45
DELETE an existing PICKUP ADDRESS	48
5. Appendix	49
State Codes.....	49



1. Authentication

LOGIN

Before any other operation, Login is needed to establish an authenticated session with iCarry.in server. Authentication requests sent to the iCarry.in API URL:

Must be made via SSL encrypted connection

Must use HTTP POST

Must contain **username** and **key** for the user account that will be submitting API requests

Login requests that meet these criteria will be granted an **api_token id**. This will be used as a URL parameter during subsequent API requests.

Request URL : https://www.icarry.in/api_login

Method: POST

Request Body Parameters

Parameter	Required	Description
username	Yes	The API username Example: ela10
Key	Yes	The API key generated for the API user Example: sELj4wHd45xTE5CwWgvt2G25xoVgGXYhnNZdIxhA73Q01d265VjoZCBF0f6AST3Gi GkY56rLROjBiDt5BCvTbcaD70hDV5CYqOVU5Ld4gqCyEQPikv0FdS1dqjOo2u44mK Lb5y8jfBkwSHpG2co7WRLRB46ijkfyCm3IMdbGfNlyVqeIzRexkmFc1mNJmNqHBeITV WHIsTCP6P22fxA5I3O7gHpdApIM0eLPMFUANMDZ4qUuyT4qp8ANHjGfxu6V

Sample Successful Response

```
{
  "success": "Success: API session successfully started!", "api_token": "42b1731751593218bd256cbf01"
}
```



Sample Error Response

```
{
  "error": {
    "ip": "Warning: Your IP 172.68.46.114 is not allowed to access this API!", "key": "Warning: Incorrect API Key!"
  }
}
```

Note: BOTH USERNAME AND API KEY ARE UNIQUE TO INDIVIDUAL USERS. API TOKEN ID ARE VALID FOR 60 MINUTES. IN CONTRAST, USER KEYS ARE VALID INDEFINITELY WHICH YOU CAN REGENERATE AS NEEDED.



2. Shipment

Get ESTIMATE Single Shipment (India Rate Calculator)

You can get estimated cost of a shipment by providing certain shipment details. In the response you will get the list of couriers which can provide you service along with associated cost. This is just an estimate and actual costs deducted will be dependent on the actual shipment data and any other services availed during delivery.

Request URL :

https://www.icarry.in/api_get_estimate&api_token=<api_token>

Method: POST

Request Body Parameters

Parameter	Required	Description
length	Yes	Data type: integer Notes: Length in centimeters of the parcel being shipped Example: \$shipment['length'] = 10;
breadth	Yes	Data type: integer Notes: Breadth in centimeters of the parcel being shipped Example: \$shipment['breadth'] = 10;
height	Yes	Data type: integer Notes: Height in centimeters of the parcel being shipped Example: \$shipment['height'] = 25;
weight	Yes	Data type: integer Notes: Weight in grams of the parcel being shipped Example: \$shipment['weight'] = 520;



Parameter	Required	Description
destination_pincode	Yes	Data type: integer Notes: Postal code of recipient Example: \$shipment['destination_pincode'] = '560068';
origin_pincode	Yes	Data type: integer Notes: Postal code of pickup (sender) Example: \$shipment['origin_pincode'] = '400081';
destination_country_code	Yes	Data type: 2 characters Notes: Country Code of Destination address Example: \$shipment['destination_country_code'] = 'IN'; (only IN is supported)
origin_country_code	Yes	Data type: 2 characters Notes: Country Code of Pickup address Example: \$shipment['origin_country_code'] = 'IN'; (only IN is supported)
shipment_mode	Yes	Data type: 1 character enum (E P H) Notes: E – Express / Air, S – Surface, H – Hyperlocal (Same Day) Example: \$shipment['shipment_mode'] = 'E';
shipment_type	Yes	Data type: 1 character enum (C P) Notes: C – COD, P - Prepaid Example: \$shipment['shipment_type'] = 'P';
shipment_value	Yes	Data type: float Notes: Declared value of shipment. In case of COD shipment the amount mentioned here will be collected from the shipment recipient at time of delivery Example: \$shipment['shipment_value'] = '1000';



Parameter	Required	Description
sender_address	Yes (only for mode 'H')	Data type: alphanumeric characters Notes: Detailed and Complete address of the sender Example: \$shipment['sender_address'] = 'B-307 Ravi Sagar Apartment, Sunder Nager locality';
sender_city	Yes (only for mode 'H')	Data type: alphanumeric characters Notes: Sender city name Example: \$shipment['sender_city'] = 'Mumbai';
consignee_address	Yes (only for mode 'H')	Data type: alphanumeric characters Notes: Detailed and Complete address of the sender Example: \$shipment['consignee_address'] = 'B-307 Ravi Sagar Apartment, Sunder Nager locality';
consignee_city	Yes (only for mode 'H')	Data type: alphanumeric characters Notes: Detailed and Complete address of the sender Example: \$shipment['consignee_city'] = 'Mumbai';

Successful Response

```
{
  "success": 1,
  "error": "",
  "estimate": [
    {
      "courier_id": "29",
      "courier_name": "Xpressbees Surface",
      "courier_group_name": "Xpressbees",
      "courier_cost": "26.52"
    },
    {
      "courier_id": "33",
      "courier_name": "",
      "courier_group_name": "Bluedart",
      "courier_cost": "41.31"
    }
  ]
}
```



Get ESTIMATE Multi-Box Shipment (India Rate Calculator)

You can get estimated cost of a shipment by providing certain shipment details. In the response you will get the list of couriers which can provide you service along with associated cost. This is just an estimate and actual costs deducted will be dependent on the actual shipment data and any other services availed during delivery.

Request URL :

https://www.icarry.in/api_get_estimate_b2b&api_token=<api_token>

Method: POST

Request Body Parameters

Parameter	Required	Description
destination_pincode	Yes	Data type: alphanumeric characters Notes: Postal code of recipient Example: \$shipment['destination_pincode'] = '560068';
origin_pincode	Yes	Data type: alphanumeric characters Notes: Postal code of pickup (sender) Example: \$shipment['origin_pincode'] = '400081';
destination_country_code	Yes	Data type: 2 characters Notes: Country Code of Destination address Example: \$shipment['destination_country_code'] = 'IN'; (only IN is supported)
origin_country_code	Yes	Data type: 2 characters Notes: Country Code of Pickup address Example: \$shipment['origin_country_code'] = 'IN'; (only IN is supported)
shipment_mode	Yes	Data type: 1 character enum (E P) Notes: E – Express / Air, S - Surface Example: \$shipment['shipment_mode'] = 'E';
shipment_type	Yes	Data type: 1 character enum (C P)



Parameter	Required	Description																								
		Notes: C – COD, P - Prepaid Example: <code>\$shipment['shipment_type'] = 'P';</code>																								
shipment_value	Yes	Data type: float Notes: Declared value of shipment. In case of COD shipment the amount mentioned here will be collected from the shipment recipient at time of delivery Example: <code>\$shipment['shipment_value'] = '1000';</code>																								
boxes	Yes	Data Type: Array <table border="1"> <thead> <tr> <th>Parameter</th><th>Required</th><th>Description</th></tr> </thead> <tbody> <tr> <td>quantity</td><td>Yes</td><td>Positive integer</td></tr> <tr> <td>length</td><td>Yes</td><td>Positive decimal</td></tr> <tr> <td>breadth</td><td>Yes</td><td>Positive decimal</td></tr> <tr> <td>height</td><td>Yes</td><td>Positive decimal</td></tr> <tr> <td>dimension_unit</td><td>Yes</td><td>Can be 'cm' only</td></tr> <tr> <td>weight</td><td>Yes</td><td>Positive decimal</td></tr> <tr> <td>weight_unit</td><td>Yes</td><td>Can be 'gm' or 'kg'</td></tr> </tbody> </table> <code>\$box_type_1 = array('quantity' => '2' 'length' => '10', 'breadth' => '4', 'height' => '20', 'dimension_unit' => 'cm', 'weight' => '20000', 'weight_unit' => 'gm');</code> <code>\$box_type_2 = array('quantity' => '3' 'length' => '10', 'breadth' => '4', 'height' => '20', 'dimension_unit' => 'cm', 'weight' => '30000', 'weight_unit' => 'gm');</code> <code>\$boxes = array(); \$boxes[] = \$box_type_1; \$boxes[] = \$box_type_2;</code>	Parameter	Required	Description	quantity	Yes	Positive integer	length	Yes	Positive decimal	breadth	Yes	Positive decimal	height	Yes	Positive decimal	dimension_unit	Yes	Can be 'cm' only	weight	Yes	Positive decimal	weight_unit	Yes	Can be 'gm' or 'kg'
Parameter	Required	Description																								
quantity	Yes	Positive integer																								
length	Yes	Positive decimal																								
breadth	Yes	Positive decimal																								
height	Yes	Positive decimal																								
dimension_unit	Yes	Can be 'cm' only																								
weight	Yes	Positive decimal																								
weight_unit	Yes	Can be 'gm' or 'kg'																								



```
$shipment['parcel']['boxes'] = $boxes;
```

Above means there are 2 boxes of 20 Kg each and 3 boxes of 30 Kg each. Total weight is $2 \times 20 + 3 \times 30 = 40 + 90 = 130$ Kg

Postman Screenshot of Request Sample

http://localhost:8081/api_get_estimate_b2b&api_token=01f88c0cc481a79e7...

Save

POST

http://localhost:8081/api_get_estimate_b2b&api_token=01f88c0cc481a79e735...

Send

Params

Auth

Headers (9)

Body

Pre-req.

Tests

Settings

Cookies

form-data

☒	origin_pincode	560068
☒	destination_country_code	IN
☒	origin_country_code	IN
☒	shipment_type	P
☒	shipment_value	10000
☒	shipment_mode	S
☒	boxes[0][quantity]	2
☒	boxes[0][length]	10
☒	boxes[0][breadth]	10
☒	boxes[0][height]	2
☒	boxes[0][weight]	20
☒	boxes[0][weight_unit]	kg

</> Code snippet

cURL

```
1 curl --location --request POST 'http://
  localhost:8081/api_get_estimate_b2b&
  api_token=01f88c0cc481a79e7390c4f8c7'
2 --header 'Cookie:
  OCSESSID=687b641bc3d6cd6a28bcb27e0' \
3 --form 'destination_pincode="110001"' \
4 --form 'origin_pincode="560068"' \
5 --form 'destination_country_code="IN"' \
6 --form 'origin_country_code="IN"' \
7 --form 'shipment_type="P"' \
8 --form 'shipment_value="10000"' \
9 --form 'shipment_mode="S"' \
10 --form 'boxes[0][quantity]="2"' \
11 --form 'boxes[0][length]="10"' \
12 --form 'boxes[0][breadth]="10"' \
13 --form 'boxes[0][height]="2"' \
14 --form 'boxes[0][weight]="20"' \
15 --form 'boxes[0][weight_unit]="kg"' \
16 --form 'boxes[0][dimension_unit]="cm"' \
17 --form 'boxes[1][weight]="30"' \
18 --form 'boxes[1][quantity]="3''
```

Successful Response

```
{
  "error": "",
  "success": 1,
  "estimate": {
    "Ekart LTL": {
      "courier_group_name": "Ekart LTL",
      "courier_cost": 2050.84,
      "freight_cost": 2050.84,
      "cod_cost": 0,
      "courier_group_id": 25
    },
    "Wheelex Kargo": {
      "courier_group_name": "Wheelex Kargo",
```



```
    "courier_cost": 2347.76,
    "freight_cost": 2347.76,
    "cod_cost": 0,
    "courier_group_id": 22
  },
  "Delhivery LTL Dense": {
    "courier_group_name": "Delhivery LTL Dense",
    "courier_cost": 1960.85,
    "freight_cost": 1960.85,
    "cod_cost": 0,
    "courier_group_id": 21
  },
  "Aerex Kargo": {
    "courier_group_name": "Aerex Kargo",
    "courier_cost": 12505.58,
    "freight_cost": 12505.58,
    "cod_cost": 0,
    "courier_group_id": 23
  },
  "Delhivery LTL": {
    "courier_group_name": "Delhivery LTL",
    "courier_cost": 2410.65,
    "freight_cost": 2410.65,
    "cod_cost": 0,
    "courier_group_id": 17
  }
}
```



Get ESTIMATE (India to Foreign Country Rate Calculator)

You can get estimated cost of a shipment by providing certain shipment details. This is just an estimate and actual costs deducted will be dependent on the actual shipment data and any other services availed during delivery.

Request URL :

https://www.icarry.in/api_get_estimate_international&api_token=<api_token>

Method: POST

Request Body Parameters

Parameter	Required	Description
weight	Yes	Data type: integer Weight in grams is provided as input Notes: Weight in grams of the parcel being shipped Example: \$shipment['weight'] = 520;
length	Yes	Data type: integer Notes: Length in centimeters of the parcel being shipped Example: \$shipment['length'] = 10;
breadth	Yes	Data type: integer Notes: Breadth in centimeters of the parcel being shipped Example: \$shipment['breadth'] = 10;
height	Yes	Data type: integer Notes: Height in centimeters of the parcel being shipped Example: \$shipment['height'] = 25;
origin_pincode	Yes	Data type: alphanumeric characters Notes: Postal code of pickup (sender) Example: \$shipment['origin_pincode'] = '400081';



destination_country_code	Yes	Data type: 2 characters Notes: ISO2 Country Code of Destination address Example: <code>\$shipment['destination_country_code'] = 'US';</code>
--------------------------	-----	--

Successful Response

```
{
  "success": 1,
  "estimates": [
    {
      "courier_name": "Aramex International",
      "courier_id": "17-34",
      "total": 2156.7,
      "shipping": 1827.71,
      "tax": 328.99,
      "surcharge": 0,
      "fsc": 0
    }
  ]
}
```



Book SINGLE Shipment

Create a new shipment by choosing your courier while booking. On successful creation a shipment_id is returned along with the pickup request id.

Request

Request URL for Surface or Hyperlocal Shipment:

https://www.icarry.in/api_add_shipment_surface&api_token=<api_token>

Request URL for Air Shipment:

https://www.icarry.in/api_add_shipment_air&api_token=<api_token obtained on successful Login>

Method: POST

Request Body Parameters

Parameter	Required	Description
pickup_address_id	Yes	Data_type: integer Notes: Address id can be found in your list of My Account -> My Addresses -> Pick up address Example: \$shipment['pickup_address_id'] = 10;
return_address_id	No	Data_type: integer Notes: If this is empty then the FROM address on shipment label is same as pickup address. If you need the from address to be a different one then choose the appropriate address id from list of addresses in My Account -> My Addresses -> Registered Address Example: \$shipment['return_address_id'] = ''; /* this means that the From Address printed on shipment label is the same as pickup address */
rto_address_id	No	Data_type: integer Notes: If this is empty then the RTO address is same as pickup address. If you need the RTO address to be a different one then choose the appropriate address id from list of addresses in My Account -> My Addresses -> RTO Address Example: \$shipment['rto_address_id'] = ''; /* this means that the RTO will be done to an address different from default pickup address */



client_order_id	No	Data_type: string Notes: This is order id in client system and can be used for co-relating with shipment_id on the iCarry end. Example: <pre>\$shipment['client_order_id'] = '146255';</pre>																											
save_only	No	Datatype: integer Notes: If this parameter is set then the order details are saved and courier is not assigned. Use this parameter if you want to save orders but not book them. If you want bookings then this parameter should NOT be sent in the payload. Any value in this parameters is considered as indication to save the order only and not book it.																											
courier_id	No	Data_type: integer Notes: This is the value of one of the courier options returned via the get_estimate_by_courier API end point. If this is not provided then a courier option is auto chosen during booking. Example: <pre>\$shipment['courier_id'] = 7;</pre>																											
shipment_mode	Yes (only for Hyperlocal shipment)	Only valid value is 'H' for hyperlocal or 'S' for surface. If not present it is defaulted to 'S'																											
consignee	Yes	Data Type: Array <table border="1"> <thead> <tr> <th>Parameter name</th><th>Required</th><th>Description</th></tr> </thead> <tbody> <tr> <td>name</td><td>Yes</td><td>First name and Last name of the consignee</td></tr> <tr> <td>mobile</td><td>Yes</td><td>10 digit mobile number of consignee without 0 or +91 prefix</td></tr> <tr> <td>alt_mobile</td><td>No</td><td>10 digit mobile number of consignee without 0 or +91 prefix</td></tr> <tr> <td>address</td><td>Yes</td><td>Address of the consignee including house or flat number, street name or number, locality and landmark</td></tr> <tr> <td>city</td><td>Yes</td><td>Name of city</td></tr> <tr> <td>pincode</td><td>Yes</td><td>Postal code</td></tr> <tr> <td>state</td><td>Yes</td><td>State code. The code should be the 2 character code from the supported list of states in Appendix.</td></tr> <tr> <td>country_code</td><td>Yes</td><td>'IN' (only supported country at this time)</td></tr> </tbody> </table>	Parameter name	Required	Description	name	Yes	First name and Last name of the consignee	mobile	Yes	10 digit mobile number of consignee without 0 or +91 prefix	alt_mobile	No	10 digit mobile number of consignee without 0 or +91 prefix	address	Yes	Address of the consignee including house or flat number, street name or number, locality and landmark	city	Yes	Name of city	pincode	Yes	Postal code	state	Yes	State code. The code should be the 2 character code from the supported list of states in Appendix.	country_code	Yes	'IN' (only supported country at this time)
Parameter name	Required	Description																											
name	Yes	First name and Last name of the consignee																											
mobile	Yes	10 digit mobile number of consignee without 0 or +91 prefix																											
alt_mobile	No	10 digit mobile number of consignee without 0 or +91 prefix																											
address	Yes	Address of the consignee including house or flat number, street name or number, locality and landmark																											
city	Yes	Name of city																											
pincode	Yes	Postal code																											
state	Yes	State code. The code should be the 2 character code from the supported list of states in Appendix.																											
country_code	Yes	'IN' (only supported country at this time)																											



PHP Example :

```
$shipment['consignee'] = array(
    'name' => 'Uma Shankar', 'mobile' => '6362182960',
    'address' => 'No 10 Charconil street, Laxmi nagar, next to Nandini Milk Parlor',
    'city' => 'Mumbai',
    'pincode' => '400081', 'state' => 'MA',
    'country_code' => 'IN' );
```

parcel

Yes

Data Type: Array

Parameter	Required	Description															
type	Yes	Prepaid / COD (parcel type can have one of two values 'Prepaid' or 'COD')															
value	Yes	Positive decimal (value of shipment. In case of COD type this is the amount to be collected from consignee)															
currency	No	'INR' (only INR is supported and is default)															
contents	Yes	string with max length 255 (brief description of contents)															
items	No	Data Type: Array Optional parameter array providing the details of the contents <table border="1"> <thead> <tr> <th>Parameter</th><th>Required</th><th>Description</th></tr> </thead> <tbody> <tr> <td>name</td><td>Yes</td><td>Product name max 50 chars</td></tr> <tr> <td>pid</td><td>Yes</td><td>Unique product identifier</td></tr> <tr> <td>price</td><td>Yes</td><td>Product price</td></tr> <tr> <td>quantity</td><td>Yes</td><td>Number of units in parcel</td></tr> </tbody> </table>	Parameter	Required	Description	name	Yes	Product name max 50 chars	pid	Yes	Unique product identifier	price	Yes	Product price	quantity	Yes	Number of units in parcel
Parameter	Required	Description															
name	Yes	Product name max 50 chars															
pid	Yes	Unique product identifier															
price	Yes	Product price															
quantity	Yes	Number of units in parcel															
dimensions	Yes	Data Type: Array <table border="1"> <thead> <tr> <th>Parameter</th><th>Required</th><th>Description</th></tr> </thead> <tbody> <tr> <td>length</td><td>Yes</td><td>Positive decimal</td></tr> <tr> <td>breadth</td><td>Yes</td><td>Positive decimal</td></tr> <tr> <td>height</td><td>Yes</td><td>Positive decimal</td></tr> <tr> <td>unit</td><td>Yes</td><td>'cm' (only)</td></tr> </tbody> </table>	Parameter	Required	Description	length	Yes	Positive decimal	breadth	Yes	Positive decimal	height	Yes	Positive decimal	unit	Yes	'cm' (only)
Parameter	Required	Description															
length	Yes	Positive decimal															
breadth	Yes	Positive decimal															
height	Yes	Positive decimal															
unit	Yes	'cm' (only)															



weight

Yes

Data Type: Array

Parameter	Required	Description
weight	Yes	Positive decimal
unit	Yes	'gm (only)

PHP Example 1 :

Only minimum required parameters used for this example

```
$shipment['parcel'] = array(
    'type' => 'Prepaid', 'currency' => 'INR', 'value' => '1200',
    'contents' => 'Fashion Jewellery');
```

PHP Example 2 :

All parameters including optional parameters are used for this example.

```
$dims = array(
    'length' => '10',
    'breadth' => '4',
    'height' => '20',
    'unit' => 'cm'
);
```

```
$shipment['parcel'] = array(
    'type' => 'Prepaid', 'currency' => 'INR', 'value' => '1200',
    'contents' => 'Fashion Jewellery', 'dimensions' => $dims,
    'weight' => $wt
);
```

Example JSON

```
{
  "pickup_address_id":"55",
  "consignee[name]":"Osama",
  "consignee[mobile]":"7794845315",
  "consignee[address]":"XYZ123 benson Street",
  "consignee[city]":"Delhi",
  "consignee[pincode]":"110001",
  "consignee[state]":"DL",
  "consignee[country_code]":"IN",
  "parcel[type]":"C",
```



```
"parcel[value]":"1500",
"parcel[currency]":"INR",
"parcel[contents]":"1 x Ayurvedic Chaay",
"parcel[weight][weight]":"500",
"parcel[weight][unit]":"gm",
"parcel[dimensions][length]":"10",
"parcel[dimensions][breadth]":"10",
"parcel[dimensions][height]":"10",
"parcel[dimensions][unit]":"cm",
"courier_id":1
}
```

Successful Response

```
{
"error": "",
"success": "Success: You have added a new shipment with id 352. | Successfully created Pickup Id 13784202 | Shipments Expected : 1 | Pick up scheduled for : 2019-06-14 16:00:00 | Pickup center : Bengaluru_Bomsndra_PC",
"shipment_id": 352,
"pickup_id": 13784202,
"courier_id": 7,
"courier_name": "Shadowfax",
"awb": 345642367564,
"cost_estimate": 41.3,
"tracking_url": "https://www.icarry.in/track-shipment?shipment_id=352&awb=345642367564&courier_id=7"
}
```

Sample Error Response 1

```
{
"error": "Pickup Address is mandatory. Consignee array is mandatory. Parcel array is mandatory. "
}
```

Sample Error Response 2

```
{
"error": "Consignee name is mandatory. Consignee address is mandatory. Consignee city is mandatory. Consignee country is mandatory. Consignee pincode is mandatory. Consignee mobile is mandatory. Consignee state is mandatory. Parcel type is mandatory. Parcel value is mandatory. Parcel contents is mandatory. "
}
```

Sample Error Response 3

```
{
"error": "Telephone must be 10 digits without any spaces or other characters and excluding starting 0 or starting +91 country code.
}
```



Book MULTI-BOX Shipment

Create a new MPS (Multi Box Shipment) shipment by choosing your courier while booking. On successful creation a shipment_id is returned along with the pickup request id.

Request URL for Multi-Box Shipment:

https://www.icarry.in/api_add_multibox_shipment&api_token=<api_token obtained on successful Login>

Method: POST

Request Body Parameters

The same parameters used for booking Single box shipment can be used with following change.

Parameter	Required	Description																														
mode	Yes	Data type: 1 character enum (E P) Notes: E – Air, S - Surface Example: \$shipment['mode'] = 'S';																														
parcel	Yes	Data Type: Array <table border="1"> <thead> <tr> <th>Parameter</th><th>Required</th><th>Description</th></tr> </thead> <tbody> <tr> <td>boxes</td><td>Yes</td><td> Data Type: Array <table border="1"> <thead> <tr> <th>Parameter</th><th>Required</th><th>Description</th></tr> </thead> <tbody> <tr> <td>quantity</td><td>Yes</td><td>Positive integer</td></tr> <tr> <td>length</td><td>Yes</td><td>Positive decimal</td></tr> <tr> <td>breadth</td><td>Yes</td><td>Positive decimal</td></tr> <tr> <td>height</td><td>Yes</td><td>Positive decimal</td></tr> <tr> <td>dimension_unit</td><td>Yes</td><td>Can be 'cm' only</td></tr> <tr> <td>weight</td><td>Yes</td><td>Positive decimal</td></tr> <tr> <td>weight_unit</td><td>Yes</td><td>Can be 'gm' or 'kg'</td></tr> </tbody> </table> </td></tr> </tbody> </table>	Parameter	Required	Description	boxes	Yes	Data Type: Array <table border="1"> <thead> <tr> <th>Parameter</th><th>Required</th><th>Description</th></tr> </thead> <tbody> <tr> <td>quantity</td><td>Yes</td><td>Positive integer</td></tr> <tr> <td>length</td><td>Yes</td><td>Positive decimal</td></tr> <tr> <td>breadth</td><td>Yes</td><td>Positive decimal</td></tr> <tr> <td>height</td><td>Yes</td><td>Positive decimal</td></tr> <tr> <td>dimension_unit</td><td>Yes</td><td>Can be 'cm' only</td></tr> <tr> <td>weight</td><td>Yes</td><td>Positive decimal</td></tr> <tr> <td>weight_unit</td><td>Yes</td><td>Can be 'gm' or 'kg'</td></tr> </tbody> </table>	Parameter	Required	Description	quantity	Yes	Positive integer	length	Yes	Positive decimal	breadth	Yes	Positive decimal	height	Yes	Positive decimal	dimension_unit	Yes	Can be 'cm' only	weight	Yes	Positive decimal	weight_unit	Yes	Can be 'gm' or 'kg'
Parameter	Required	Description																														
boxes	Yes	Data Type: Array <table border="1"> <thead> <tr> <th>Parameter</th><th>Required</th><th>Description</th></tr> </thead> <tbody> <tr> <td>quantity</td><td>Yes</td><td>Positive integer</td></tr> <tr> <td>length</td><td>Yes</td><td>Positive decimal</td></tr> <tr> <td>breadth</td><td>Yes</td><td>Positive decimal</td></tr> <tr> <td>height</td><td>Yes</td><td>Positive decimal</td></tr> <tr> <td>dimension_unit</td><td>Yes</td><td>Can be 'cm' only</td></tr> <tr> <td>weight</td><td>Yes</td><td>Positive decimal</td></tr> <tr> <td>weight_unit</td><td>Yes</td><td>Can be 'gm' or 'kg'</td></tr> </tbody> </table>	Parameter	Required	Description	quantity	Yes	Positive integer	length	Yes	Positive decimal	breadth	Yes	Positive decimal	height	Yes	Positive decimal	dimension_unit	Yes	Can be 'cm' only	weight	Yes	Positive decimal	weight_unit	Yes	Can be 'gm' or 'kg'						
Parameter	Required	Description																														
quantity	Yes	Positive integer																														
length	Yes	Positive decimal																														
breadth	Yes	Positive decimal																														
height	Yes	Positive decimal																														
dimension_unit	Yes	Can be 'cm' only																														
weight	Yes	Positive decimal																														
weight_unit	Yes	Can be 'gm' or 'kg'																														



		<pre>'weight_unit' => 'gm ');</pre> <pre>\$boxes = array(); \$boxes[] = \$box_type_1; \$boxes[] = \$box_type_2;</pre> <pre>\$shipment['parcel']['boxes'] = \$boxes;</pre> Above means there are 2 boxes of 20 Kg each and 3 boxes of 30 Kg each. Total weight is $2 \times 20 + 3 \times 30 = 40 + 90 = 130$ Kg
type	Yes	Prepaid / COD (parcel type can have one of two values 'Prepaid' or 'COD')
value	Yes	Positive decimal (value of shipment. In case of COD type this is the amount to be collected from consignee)
currency	No	'INR' (only INR is supported and is default)
contents	Yes	string with max length 255 (brief description of contents)
ewbn	No	Eway bill number
eway_file_name	No	Url link for Eway bill pdf
invoice_file_name	No	Url link for invoice pdf



Book Shipment - INTERNATIONAL

Create a new **International** shipment (India to foreign country). This API is available only for GOLD and PLATINUM plan members. Prior to calling this API you need to check whether service to the destination foreign country is available from your India pincode. If available then you can call this API with the courier_id of the chosen courier partner.

Request

https://www.icarry.in/api_add_shipment_international&api_token=<api_token>

Method: POST

Request Body Parameters

Parameter	Required	Description
pickup_address_id	Yes	Data_type: integer Notes: Address id can be found in your list of My Account -> Pick up address Example: \$shipment['pickup_address_id'] = 10;
courier_id	Yes	Data_type: string Notes: courier_id is the chosen string which is obtained from the International Shipment Estimate and Serviceability API Example: \$shipment['courier_id'] = '12';
return_address_id	No	Data_type: integer Notes: If this is empty then the from address is same as pickup address. If you need the from address to be a different one then choose the appropriate address id from list of addresses in My Account -> Registered Address Example: \$shipment['return_address_id'] = ''; /* this means that the From Address printed on shipment label is the same as pickup address */



rto_address_id	No	Data_type: integer Notes: If this is empty then the RTO address is same as pickup address. If you need the RTO address to be a different one then choose the appropriate address id from list of addresses in My Account -> My Addresses -> RTO Address Example: <pre>\$shipment['rto_address_id'] = ''; /* this means that the RTO will be done to an address different from default pickup address */</pre>																																													
client_order_id	No	Data_type: string Notes: This is order id in client system and can be used for co-relating with shipment_id on the iCarry end. Example: <pre>\$shipment['client_order_id'] = '146255';</pre>																																													
parcel	Yes	Data Type: Array <table border="1"> <thead> <tr> <th>Parameter</th><th>Required</th><th>Description</th></tr> </thead> <tbody> <tr> <td>type</td><td>Yes</td><td>Prepaid (parcel type can have only one value i.e. 'Prepaid')</td></tr> <tr> <td>value</td><td>Yes</td><td>Positive decimal (value of shipment)</td></tr> <tr> <td>currency</td><td>No</td><td>'INR' (only INR is supported and is default)</td></tr> <tr> <td>contents</td><td>Yes</td><td>string with max length 255 (brief description of contents)</td></tr> <tr> <td>dimensions</td><td>Yes</td><td> Data Type: Array <table border="1"> <thead> <tr> <th>Parameter</th><th>Required</th><th>Description</th></tr> </thead> <tbody> <tr> <td>length</td><td>Yes</td><td>Positive decimal</td></tr> <tr> <td>breadth</td><td>Yes</td><td>Positive decimal</td></tr> <tr> <td>height</td><td>Yes</td><td>Positive decimal</td></tr> <tr> <td>unit</td><td>Yes</td><td>'cm' (only)</td></tr> </tbody> </table> </td></tr> <tr> <td>weight</td><td>Yes</td><td> Data Type: Array <table border="1"> <thead> <tr> <th>Parameter</th><th>Required</th><th>Description</th></tr> </thead> <tbody> <tr> <td>weight</td><td>Yes</td><td>Positive decimal</td></tr> <tr> <td>unit</td><td>Yes</td><td>'gm' (only)</td></tr> </tbody> </table> </td></tr> </tbody> </table>	Parameter	Required	Description	type	Yes	Prepaid (parcel type can have only one value i.e. 'Prepaid')	value	Yes	Positive decimal (value of shipment)	currency	No	'INR' (only INR is supported and is default)	contents	Yes	string with max length 255 (brief description of contents)	dimensions	Yes	Data Type: Array <table border="1"> <thead> <tr> <th>Parameter</th><th>Required</th><th>Description</th></tr> </thead> <tbody> <tr> <td>length</td><td>Yes</td><td>Positive decimal</td></tr> <tr> <td>breadth</td><td>Yes</td><td>Positive decimal</td></tr> <tr> <td>height</td><td>Yes</td><td>Positive decimal</td></tr> <tr> <td>unit</td><td>Yes</td><td>'cm' (only)</td></tr> </tbody> </table>	Parameter	Required	Description	length	Yes	Positive decimal	breadth	Yes	Positive decimal	height	Yes	Positive decimal	unit	Yes	'cm' (only)	weight	Yes	Data Type: Array <table border="1"> <thead> <tr> <th>Parameter</th><th>Required</th><th>Description</th></tr> </thead> <tbody> <tr> <td>weight</td><td>Yes</td><td>Positive decimal</td></tr> <tr> <td>unit</td><td>Yes</td><td>'gm' (only)</td></tr> </tbody> </table>	Parameter	Required	Description	weight	Yes	Positive decimal	unit	Yes	'gm' (only)
Parameter	Required	Description																																													
type	Yes	Prepaid (parcel type can have only one value i.e. 'Prepaid')																																													
value	Yes	Positive decimal (value of shipment)																																													
currency	No	'INR' (only INR is supported and is default)																																													
contents	Yes	string with max length 255 (brief description of contents)																																													
dimensions	Yes	Data Type: Array <table border="1"> <thead> <tr> <th>Parameter</th><th>Required</th><th>Description</th></tr> </thead> <tbody> <tr> <td>length</td><td>Yes</td><td>Positive decimal</td></tr> <tr> <td>breadth</td><td>Yes</td><td>Positive decimal</td></tr> <tr> <td>height</td><td>Yes</td><td>Positive decimal</td></tr> <tr> <td>unit</td><td>Yes</td><td>'cm' (only)</td></tr> </tbody> </table>	Parameter	Required	Description	length	Yes	Positive decimal	breadth	Yes	Positive decimal	height	Yes	Positive decimal	unit	Yes	'cm' (only)																														
Parameter	Required	Description																																													
length	Yes	Positive decimal																																													
breadth	Yes	Positive decimal																																													
height	Yes	Positive decimal																																													
unit	Yes	'cm' (only)																																													
weight	Yes	Data Type: Array <table border="1"> <thead> <tr> <th>Parameter</th><th>Required</th><th>Description</th></tr> </thead> <tbody> <tr> <td>weight</td><td>Yes</td><td>Positive decimal</td></tr> <tr> <td>unit</td><td>Yes</td><td>'gm' (only)</td></tr> </tbody> </table>	Parameter	Required	Description	weight	Yes	Positive decimal	unit	Yes	'gm' (only)																																				
Parameter	Required	Description																																													
weight	Yes	Positive decimal																																													
unit	Yes	'gm' (only)																																													
		PHP Example 1 : Only minimum required parameters used for this example																																													



		<pre>\$shipment['parcel'] = array('type' => 'Prepaid', 'currency' => 'INR', 'value' => '1200', 'contents' => 'Fashion Jewellery');</pre> PHP Example 2 : All parameters including optional parameters are used for this example. <pre>\$dims = array('length' => '10', 'breadth' => '4', 'height' => '20', 'unit' => 'cm'); \$wt = array('weight' => '1250', 'unit' => 'gm'); \$shipment['parcel'] = array('type' => 'Prepaid', 'currency' => 'INR', 'value' => '1200', 'contents' => 'Fashion Jewellery', 'dimensions' => \$dims, 'weight' => \$wt);</pre>																									
consignee	Yes	Data Type: Array <table><tr><th>Parameter</th><th>Required</th><th>Description</th></tr><tr><td>name</td><td>Yes</td><td>First name and Last name of the consignee</td></tr><tr><td>mobile</td><td>Yes</td><td>Mobile number or Telephone number of the recipient</td></tr><tr><td>address</td><td>Yes</td><td>Address of the consignee including house or flat number, street name or number, locality and landmark</td></tr><tr><td>city</td><td>Yes</td><td>Name of city</td></tr><tr><td>pincode</td><td>Yes</td><td>Postal code</td></tr><tr><td>state</td><td>Yes</td><td>State / Region / Province name in the destination country. Example: California or New York etc.</td></tr><tr><td>country_code</td><td>Yes</td><td>2 character standardized ISO2 country code Example - US</td></tr></table>	Parameter	Required	Description	name	Yes	First name and Last name of the consignee	mobile	Yes	Mobile number or Telephone number of the recipient	address	Yes	Address of the consignee including house or flat number, street name or number, locality and landmark	city	Yes	Name of city	pincode	Yes	Postal code	state	Yes	State / Region / Province name in the destination country. Example: California or New York etc.	country_code	Yes	2 character standardized ISO2 country code Example - US	
Parameter	Required	Description																									
name	Yes	First name and Last name of the consignee																									
mobile	Yes	Mobile number or Telephone number of the recipient																									
address	Yes	Address of the consignee including house or flat number, street name or number, locality and landmark																									
city	Yes	Name of city																									
pincode	Yes	Postal code																									
state	Yes	State / Region / Province name in the destination country. Example: California or New York etc.																									
country_code	Yes	2 character standardized ISO2 country code Example - US																									

**PHP Example :**

```
$shipment['consignee'] = array(
'name' => 'Uma Shankar', 'mobile' => '4082307380',
'address' => 'No 10 Charconil street, Next to Golf Center',
'city' => 'Fremont',
'pincode' => '94536', 'state' => 'California',
'country_code' => 'US' );
```

Successful Response

```
{
"error": "",
"success": "Success: You have added a new shipment with id 352. | Successfully created Pickup Id 13784202 | Shipments Expected : 1 | Pick up scheduled for : 2019-06-14 16:00:00 | Pickup center : Bengaluru_Bomsndra_PC",
"shipment_id": 352,
"pickup_id": 13784202,
"courier_id": 7,
"courier_name": "Shadowfax",
"awb": 345642367564,
"tracking_url": "https://www.icarry.in/track-shipment?shipment_id=352&awb=345642367564&courier_id=7"
}
```

Sample Error Response 1

```
{
"error": "Pickup Address is mandatory. Consignee array is mandatory. Parcel array is mandatory. "
}
```

Sample Error Response 2

```
{
"error": "Consignee name is mandatory. Consignee address is mandatory. Consignee city is mandatory. Consignee country is mandatory. Consignee pincode is mandatory. Consignee mobile is mandatory. Consignee state is mandatory. Parcel type is mandatory. Parcel value is mandatory. Parcel contents is mandatory. "
}
```



CANCEL Shipment

You can cancel an existing shipment. In case this is already picked up then it will be returned back and RTO charges will apply. If the parcel was not shipped then no charges apply. If a cancelled parcel is accidentally shipped then it will be returned back and RTO charges may apply.

Request

Request URL : https://www.icarry.in/api_cancel_shipment&api_token=<api_token>

Method: POST

Request Body Parameters

Parameter	Required	Description
shipment_id	Yes	Data type: integer Notes: Shipment id can be found in your list of My Account -> My Shipments Example: \$shipment['shipment_id'] = 10;

Successful Response

```
{  
  "success": "Cancelled iCarry Shipment Id 252",  
  "shipment_id": "252",  
}
```

Sample Error Response 1

```
{  
  "error": "Shipment id not found. "  
}
```



REVERSE Shipment

You can reverse pickup an existing shipment that has been delivered.

Request URL : https://www.icarry.in/api_add_reverse_shipment&api_token=<api_token>

Method: POST

Request Body Parameters

Parameter	Required	Description
shipment_id	Yes	Data type: integer Notes: Shipment id can be found in your list of My Account -> My Shipments Example: \$shipment['shipment_id'] = 10;

Successful Response

```
{
  "success": "Successfully generated reverse pickup shipment for iCarry Shipment Id 252",
  "shipment_id": "252",
  "courier_id": "7",
  "courier_name": "Delhivery",
  "awb": "25234543425",
  "tracking_url": " https://www.icarry.in/track- shipment?shipment_id=252&awb=25234543425&courier_id=7",
  "pickup_id": "2345252",
}
```

Sample Error Response 1

```
{
  "error": "Shipment id not found. "
}
```



TRACK a Shipment

You can track an existing shipment using shipment_id returned by Create Shipment api call.

Request URL : https://www.icarry.in/api_track_shipment&api_token=<api_token>

Method: POST

Request Body Parameters

Parameter	Required	Description
shipment_id	Yes	Data type: integer Notes: Shipment id can be found in your list of My Account -> My Shipments Example: \$shipment['shipment_id'] = 10;

On success returns an array.

Sample Successful Response for Delivered shipment

```
{
  "courier_name": "DELHIVERY SURFACE",
  "success": 1,
  "eta_datetime": "",
  "picked_datetime": "",
  "delivered_datetime": "",
  "receiver": "",
  "status": "Delivered",
  "location": "Bengaluru_South_D_20 (Karnataka)",
  "datetime": "2019-08-16T16:02:52.002000",
  "details": [
    {
      "datetime": "2019-08-12T13:36:10.268000",
      "location": "Bengaluru_Bomsndra_PC (Karnataka)",
      "notes": "Consignment Manifested"
    },
    {
      "datetime": "2019-08-13T21:19:36",
      "location": "Bengaluru_Nelmngla_P (Karnataka)",

```



```
"notes": "Shipment Picked Up from Client Location"
},
{
  "datetime": "2019-08-13T22:27:52",
  "location": "Bengaluru_Nelmngla_P (Karnataka)", "notes": "Vehicle Reached at Origin Center"
},
{
  "datetime": "2019-08-14T06:33:26.037000",
  "location": "Bengaluru_Nelmngla_P (Karnataka)", "notes": "Shipment Recieved at Origin Center"
},
{
  "datetime": "2019-08-14T06:56:22.827000",
  "location": "Bangalore_Nelmngla_H (Karnataka)", "notes": "Received At Delhivery Hub"
},
{
  "datetime": "2019-08-14T08:16:31.933000",
  "location": "Bangalore_Nelmngla_H (Karnataka)", "notes": "Connected to destination"
},
{
  "datetime": "2019-08-14T10:45:46.187000",
  "location": "BLR_HSR_Layout_PC (Karnataka)", "notes": "Received At Delhivery Hub"
},
{
  "datetime": "2019-08-14T10:49:17.957000",
  "location": "BLR_HSR_Layout_PC (Karnataka)", "notes": "Received At Delhivery Hub"
},
{
  "datetime": "2019-08-14T11:07:57.030000",
  "location": "BLR_HSR_Layout_PC (Karnataka)", "notes": "Received At Delhivery Hub"
},
{
  "datetime": "2019-08-14T12:20:22.684000",
  "location": "BLR_HSR_Layout_PC (Karnataka)", "notes": "Connected to destination"
},
{
  "datetime": "2019-08-14T13:16:47.131000",
  "location": "Bengaluru_Agrahara_DC (Karnataka)", "notes": "Received At Delhivery Hub"
},
{
  "datetime": "2019-08-14T13:19:54.102000",
  "location": "Bengaluru_Agrahara_DC (Karnataka)", "notes": "Received At Delhivery Hub"
},
},
```



```
{
  "datetime": "2019-08-14T13:32:36.583000",
  "location": "Bengaluru_Agrahara_DC (Karnataka)", "notes": "Received at destination city"
},
{
  "datetime": "2019-08-14T14:40:55.427000",
  "location": "Bengaluru_Agrahara_DC (Karnataka)", "notes": "Misrouted"
},
{
  "datetime": "2019-08-14T15:28:05.042000",
  "location": "Bengaluru_Agrahara_DC (Karnataka)", "notes": "Connected to destination"
},
{
  "datetime": "2019-08-14T16:24:37.613000",
  "location": "BLR_HSR_Layout_PC (Karnataka)", "notes": "Received At Delhivery Hub"
},
{
  "datetime": "2019-08-14T16:25:24.906000",
  "location": "BLR_HSR_Layout_PC (Karnataka)", "notes": "Received At Delhivery Hub"
},
{
  "datetime": "2019-08-14T17:17:52.108000",
  "location": "BLR_HSR_Layout_PC (Karnataka)", "notes": "Connected to destination"
},
{
  "datetime": "2019-08-14T17:44:09.009000",
  "location": "Bengaluru_South_D_20 (Karnataka)", "notes": "Received At Delhivery Hub"
},
{
  "datetime": "2019-08-14T17:45:39.692000",
  "location": "Bengaluru_South_D_20 (Karnataka)", "notes": "Received At Delhivery Hub"
},
{
  "datetime": "2019-08-16T06:35:46.240000",
  "location": "Bengaluru_South_D_20 (Karnataka)", "notes": "Received at destination city"
},
{
  "datetime": "2019-08-16T07:35:12.841000",
  "location": "Bengaluru_South_D_20 (Karnataka)", "notes": "Out for delivery"
},
{
  "datetime": "2019-08-16T16:02:04.002000",
```



```
    "location": "Bengaluru_South_D_20 (Karnataka)",
    "notes": "Customer call placed"
  },
  {
    "datetime": "2019-08-16T16:02:52.002000",
    "location": "Bengaluru_South_D_20 (Karnataka)",
    "notes": "Delivered to consignee"
  }
]
}
```

Another sample :

```
{
  "courier_name": "FEDEX PRIORITY",
  "success": 1,
  "details": [
    {
      "datetime": "2019-08-27T13:00:00+05:30",
      "location": "DELIVERY_LOCATION",
      "notes": "Delivered"
    },
    {
      "datetime": "2019-08-27T12:47:00+05:30",
      "location": "VEHICLE",
      "notes": "On FedEx vehicle for delivery"
    },
    {
      "datetime": "2019-08-27T12:17:00+05:30",
      "location": "DESTINATION_FEDEX_FACILITY",
      "notes": "At local FedEx facility"
    },
    {
      "datetime": "2019-08-27T10:59:00+05:30",
      "location": "FEDEX_FACILITY",
      "notes": "In transit"
    },
    {
      "datetime": "2019-08-27T10:58:00+05:30",
      "location": "FEDEX_FACILITY",
      "notes": "Departed FedEx location"
    },
    {
      "datetime": "2019-08-27T09:54:00+05:30",
      "location": "FEDEX_FACILITY",
      "notes": "In transit"
    },
    {
      "datetime": "2019-08-27T01:49:00+05:30",
      "location": "FEDEX_FACILITY",
      "notes": "In transit"
    },
    {
      "datetime": "2019-08-27T01:48:00+05:30",
      "location": "FEDEX_FACILITY",
      "notes": "In transit"
    }
  ],
}
```



```
{
  "datetime": "2019-08-26T23:26:00+05:30",
  "location": "FEDEX_FACILITY",
  "notes": "Arrived at FedEx location"
},
{
  "datetime": "2019-08-26T22:31:00+05:30",
  "location": "ORIGIN_FEDEX_FACILITY",
  "notes": "Left FedEx origin facility"
},
{
  "datetime": "2019-08-26T16:20:00+05:30",
  "location": "PICKUP_LOCATION",
  "notes": "Picked up"
},
{
  "datetime": "2019-08-25T21:47:18-05:00",
  "location": "CUSTOMER",
  "notes": "Shipment information sent to FedEx"
}
],
"datetime": "",
"eta_datetime": "",
"picked_datetime": "2019-08-26T16:20:00+05:30",
"delivered_datetime": "2019-08-27T13:00:00+05:30",
"location": "Hyderabad, TS, India",
"receiver": "SIGN",
"status": "Delivered"
}
```

Sample Successful Response for Manifested shipment which has not been picked up yet

```
{
"success": 1,
"status": "Manifested",
"location": "Bengaluru_Bomsndra_PC (Karnataka)", "datetime": "2019-06-14T14:21:37.852000",
"details": [
{
"datetime": "2019-06-14T14:21:37.852000",
"location": "Bengaluru_Bomsndra_PC (Karnataka)", "notes": "Consignment Manifested"
}
]
}
```

Sample Successful Response for shipment that was cancelled

```
{
"success": 1,
"status": "Manifested",
"location": "Bengaluru_Bomsndra_PC (Karnataka)", "datetime": "2019-06-11T09:37:20.094000",
"details": [
```



```
{
  "datetime": "2019-06-11T09:16:14.967000",
  "location": "Bengaluru_Bomsndra_PC (Karnataka)", "notes": "Consignment Manifested"
},
{
  "datetime": "2019-06-11T09:37:20.094000",
  "location": "Bengaluru_Bomsndra_PC (Karnataka)", "notes": "Seller cancelled the order"
}
]
```



SYNC Shipment STATUS

You can sync the shipment status, pickup and delivery dates of multiple shipments with the iCarry.in server using shipment_id returned by Create Shipment api call.

Request URL :

https://www.icarry.in/api_shipment_status_sync&api_token=<api_token>

Method: POST

Request Body Parameters

Parameter	Required	Description
shipment_ids	Yes	Data type: Array Notes: Shipment id can be found in your list of My Account -> My Shipments Example: <pre>\$shipment_ids = array (10, 11, 45);</pre> <pre>/* 10, 11, 45 are the shipment_id in iCarry */</pre>

On success returns an array. In response below, 10 is Shipped but not Delivered yet. 11 is picked and delivered. 45 is still pending pickup.

Sample Successful Response for Sync'ed shipments

```
{
  "success": "Shipment statuses synced successfully", "msg": [
    {
      "shipment_id": "10",
      "status": "3", "date_delivered": "",
      "date_picked": "2019-06-06T21:15:31.780000"
    },
    {
      "shipment_id": "11",
      "status": "21",
      "date_delivered": "2019-06-09T21:15:31.780000", "date_picked": "2019-06-06T21:15:31.780000"
    },
  ],
}
```



```
{  
  "shipment_id": "45",  
  "status": "1", "date_delivered": "", "date_picked ": "" },  
}
```

List of **Shipment status** returned in the 'status' field are below:

Status	Name
1	Pending Pickup
2	Processing
3	Shipped
7	Canceled
12	Damaged
14	Lost
16	Voided
21	Delivered
22	In Transit
23	Returned to Origin
24	Manifested
25	Pickup Scheduled
26	Out For Delivery
27	Pending Return



Webhook / POST Call Back on change in Shipment STATUS

You can save a callback url to be called when there is change in shipment status. The webhook url is saved in Account Menu > Integrations > API Credentials

Method: POST

Post Body Parameters

Parameter	Description
client_name	icarry
callback_type	sync_status
awb	The AWB / Tracking number of the shipment. Example: 14100040123332
status	Integer indicating the shipment status as per the Status codes table in Sync STATUS api. (previous page) Example: 3 This indicates shipment has now moved to 'Shipped'.
token	This is the API key setup with us via My Account Menu > Integrations > API Credentials. It is expected that the call back code will verify this token to ensure that the callback is being made by trusted partner icarry and not someone else.



Webhook / POST Call Back for NDR events

You can save a callback url to be called when there is change in shipment status. The webhook url is saved in Account Menu > Integrations > API Credentials

Once a day all the NDR events will be consolidated and sent for NDR detected on that day as well as previous day (in case this was missed). The list of NDR event types is mentioned below:

NDR Event	Description
REATTEMPT-CONTACT	Consignee address incomplete / wrong or not reachable on given mobile. Delivery executive is facing difficult contacting the consignee or location the delivery address
REATTEMPT	Delivery attempt failed
MISROUTE	Shipment is in wrong delivery pincode - either courier error or wrong pincode given during booking
DC-ADDRESS	Delivery address is ODA - either due to remote location or due to incorrect nearby pincode given by consignee during booking. Shipment has to be self collected by consignee.
URGENT-DELIVERY	Delivery is detected as beyond EDD
REATTEMPT-COD-NOT-READY	Consignee did not have COD amount ready or asked to come later
RTO-MISSING	Shipment is missing while in return
OPEN-DELIVERY	Consignee asked for Open Delivery before accepting parcel
CONSIGNEE-OPENED-REFUSED	Consignee opened the parcel and refused to accept delivery
RTO-REATTEMPT	Return shipment delivery attempt failed
REATTEMPT-NEW-DATE	Consignee has asked for a future delivery date
REATTEMPT-RESTRICTED-ENTRY	Consignee address entry is restricted and delivery executive unable to deliver
RTO-PACKING	Return shipment could not be completed due to improper packaging
REATTEMPT-CUST-REFUSED	Consignee has refused to accept shipment. Reattempt requested
REATTEMPT-OTP	Consignee did not have OTP to accept delivery
MANUAL-VERIFY	Unknown NDR event. Manual verification of shipment needed
RTO-SECURITY	Shipment has been returned by courier due to security reason such as X-Ray mismatch or banned substance etc.
FINANCE-EMBARGO	Shipment has been held by courier due to payment issue



EWAY-SEND	Shipment is held pending receipt of E-Way bill information
REATTEMPT-DAMAGE	Shipment is damaged
REATTEMPT-RTO-REFUSED	Return shipment has been refused by the shipper
REATTEMPT-OUTOFSTN	Shipment could not be delivered as consignee is not at the delivery address

Method: POST

Post Body Parameters (this is sent as a JSON)

Parameter	Description
client_name	icarry
callback_type	ndr_status
ndr_data	Array containing list of AWB and NDR events along with the date when event was detected. Example: 2025-01-24 8:04:55 - webhook_test data = Array <pre>([client_name] => icarry [callback_type] => ndr_status [ndr_data] => Array ([0] => Array ([shipment_id] => 249772 [awb] => 162419608174 [type] => REATTEMPT-CONTACT [date_added] => 23/01/2025) [1] => Array ([shipment_id] => 252546 [awb] => 17883091940 [type] => REATTEMPT-CONTACT [date_added] => 23/01/2025)))</pre>



Webhook / POST Call Back for Weight Dispute events

You can save a callback url to be notified when a weight discrepancy is detected for one of your shipments. The webhook url is saved in Account Menu > Integrations > API Credentials

Weight discrepancy events are sent within a few hours of detection. Each shipment is notified only once.

Method: POST

Post Body Parameters

Parameter	Description
client_name	icarry
callback_type	new_weight_discrepancy
awb	The AWB / Tracking number of the shipment. Example: 14100040123332
shipment_id	The iCarry shipment ID.
status	1 (new weight discrepancy detected)
old_weight	Original billed weight in grams as booked.
old_dimensions	Original dimensions (LxBxH cm) as booked.
new_weight	Revised weight in grams as measured by courier.
new_dimensions	Revised dimensions (LxBxH cm) as measured by courier and if provided.
courier_products	Product description
token	API key from My Account > Integrations > API Credentials. Verify this token to confirm the callback is from iCarry.



SYNC Shipment CHARGES

You can sync the shipment charges of multiple shipments with the iCarry.in server using shipment_id returned by Create Shipment api call.

Request URL :

https://www.icarry.in/api_shipment_billing_sync&api_token=<api_token>

Method: POST

Request Body Parameters

Parameter	Required	Description
shipment_ids	Yes	Data type: Array Notes: Shipment id can be found in your list of My Account -> My Shipments Example: <pre>\$shipment_ids = array (10, 11);</pre> /* 10, 11 are the shipment_id in iCarry */

On success returns an array. Shipment id 10 has been charged Rs.45.5 and shipment id 11 has been charged Rs. 100.24. If a query is made before shipment has been billed then the shipment charge returned will be zero.

Sample Successful Response for Sync'ed shipments

```
{
  "success": "Shipment billing synced successfully", "msg": [
    {
      "shipment_id": "10",
      "awb": "7734222323423",
      "date": "2019-06-09T21:15:31.780000",
      "miles": "45.5",
      "mode": "S",
      "zone": "A",
      "weight": "300"
    },
    {
      "shipment_id": "11",
      "awb": "773469023423",
      "date": "2019-06-09T21:15:31.780000", "miles": "100.24",
      "mode": "E",
      "zone": "C",
      "weight": "1300"
    }
  ]
}
```



PRINT Shipment Label

You can print shipping label of existing shipment using shipment_id returned by Create Shipment api call.

Request URL :

https://www.icarry.in/api_print_shipment_label&api_token=<api_token>

Method: POST

Request Body Parameters

Parameter	Required	Description
shipment_id	Yes	Data type: integer Notes: Shipment id can be found in your list of My Account -> My Shipments Example: \$shipment['shipment_id'] = 10;

On success returns an array containing the return address, consignee address, courier name, courier tracking number awb, barcode url and barcode data.

Enough data will be provided to create your own label. If you want ready made label you can find it in the shipment_label array in response fields. There may be more than one labels for B2B and International shipments. The type will be png or pdf.

```
{
  "success": 1,
  "awb": "ICYP0006518415",
  "parcel_type": "Prepaid",
  "parcel_value": "₹ 1,000.00",
  "courier_name": "EKART",
  "courier_id": "80",
  "sort_code": "",
  "barcode_img": "https://www.icarry.in/image/shadowfax-awbs/ICYP0006518415.jpg",
  "return_address": "123 Telangana Street, Near Shobha Cinnamon, Bengaluru 560001,India",
  "consignee_address": "Manoj, 1235 Sansad Apartments, Mulund East, Mumbai 400001, Maharashtra,IN",
  "consignee_mobile": "9665322763",
  "shipment_label": [
    {
      "url": "https://www.icarry.in/image/srk-awbs/609-A4-6518415.pdf",
      "type": "pdf"
    },
    {
      "url": "https://ekart.apptmyz.com/flipkart/cron/displayPDF?image=2026/5/27/Docket_TqjYnQS.pdf",
      "type": "pdf"
    }
  ]
}
```



3. Pincode

Check SERVICEABILITY by PINCODE

You can print check serviceability of a pincode before booking a shipment.

Request

Request URL : https://www.icarry.in/api_check_pincode&api_token=<api_token>

Method: POST

Request Body Parameters

Parameter	Required	Description
pincode	Yes	Data_type: string

On success returns an array containing the pincode and which services are available. Y-Yes, N-No, U- Unknown

```
{
  "success": 1,
  "msg" : {
    [0] = array ( "prepaid": "Y",
    "cod": "Y",
    "pickup": "Y" "pickup": "standard"
    ),
    [1] = array ( "prepaid": "Y",
    "cod": "Y",
    "pickup": "Y" "pickup": "express"
    )
  }
}
```

Return empty array if pincode is invalid or if there is an error or if pincode is not covered at all with "success = 0".



4. Pickup Address

ADD a new PICKUP POINT for your shipments

You can add a new pickup address from where to pick your shipments.

Request URL : https://www.icarry.in/api_add_pickup_address&api_token=<api_token>

Method: POST

Request Body Parameters

Parameter	Required	Description
nickname	Yes	Data_type: string User Identifier for this pickup location. Alphabets and no spaces allowed.
name	Yes	Data_type: string Contact person name
email	Yes	Data_type: string Contact person email
phone	Yes	Data_type: string 10 digit mobile number of contact person without 0 or +91 prefix
alt_phone	No	Data_type: string Alternative mobile number. 10 digit mobile number of contact person without 0 or +91 prefix
street1	Yes	Data_type: string Address details such as House No or Apartment No, Building name, Street name etc
street2	No	Data_type: string
locality	No	Data_type: string
city	Yes	Data_type: string Name of city. Example - Hyderabad
pincode	Yes	Data_type: string Postal code. Example - 400071



Parameter	Required	Description																																																																																																									
zone_id	Yes	Data_type: integer																																																																																																									
		Integer zone_id for state																																																																																																									
		<table><tr><th>zone_id</th><th>name</th><th>code</th></tr><tr><td>1475</td><td>Andaman and Nicobar Islands</td><td>AN</td></tr><tr><td>1476</td><td>Andhra Pradesh</td><td>AP</td></tr><tr><td>1477</td><td>Arunachal Pradesh</td><td>AR</td></tr><tr><td>1478</td><td>Assam</td><td>AS</td></tr><tr><td>1479</td><td>Bihar</td><td>BI</td></tr><tr><td>1480</td><td>Chandigarh</td><td>CH</td></tr><tr><td>1481</td><td>Dadra and Nagar Haveli</td><td>DA</td></tr><tr><td>1482</td><td>Daman and Diu</td><td>DM</td></tr><tr><td>1483</td><td>Delhi</td><td>DE</td></tr><tr><td>1484</td><td>Goa</td><td>GO</td></tr><tr><td>1485</td><td>Gujarat</td><td>GU</td></tr><tr><td>1486</td><td>Haryana</td><td>HA</td></tr><tr><td>1487</td><td>Himachal Pradesh</td><td>HP</td></tr><tr><td>1488</td><td>Jammu and Kashmir</td><td>JA</td></tr><tr><td>1489</td><td>Karnataka</td><td>KA</td></tr><tr><td>1490</td><td>Kerala</td><td>KE</td></tr><tr><td>1491</td><td>Lakshadweep Islands</td><td>LI</td></tr><tr><td>1492</td><td>Madhya Pradesh</td><td>MP</td></tr><tr><td>1493</td><td>Maharashtra</td><td>MA</td></tr><tr><td>1494</td><td>Manipur</td><td>MN</td></tr><tr><td>1495</td><td>Meghalaya</td><td>ME</td></tr><tr><td>1496</td><td>Mizoram</td><td>MI</td></tr><tr><td>1497</td><td>Nagaland</td><td>NA</td></tr><tr><td>1498</td><td>Odisha</td><td>OD</td></tr><tr><td>1499</td><td>Puducherry</td><td>PO</td></tr><tr><td>1500</td><td>Punjab</td><td>PU</td></tr><tr><td>1501</td><td>Rajasthan</td><td>RA</td></tr><tr><td>1502</td><td>Sikkim</td><td>SI</td></tr><tr><td>1503</td><td>Tamil Nadu</td><td>TN</td></tr><tr><td>1504</td><td>Tripura</td><td>TR</td></tr><tr><td>1505</td><td>Uttar Pradesh</td><td>UP</td></tr><tr><td>1506</td><td>West Bengal</td><td>WB</td></tr><tr><td>4231</td><td>Telangana</td><td>TS</td></tr><tr><td>4239</td><td>Jharkhand</td><td>JH</td></tr></table>	zone_id	name	code	1475	Andaman and Nicobar Islands	AN	1476	Andhra Pradesh	AP	1477	Arunachal Pradesh	AR	1478	Assam	AS	1479	Bihar	BI	1480	Chandigarh	CH	1481	Dadra and Nagar Haveli	DA	1482	Daman and Diu	DM	1483	Delhi	DE	1484	Goa	GO	1485	Gujarat	GU	1486	Haryana	HA	1487	Himachal Pradesh	HP	1488	Jammu and Kashmir	JA	1489	Karnataka	KA	1490	Kerala	KE	1491	Lakshadweep Islands	LI	1492	Madhya Pradesh	MP	1493	Maharashtra	MA	1494	Manipur	MN	1495	Meghalaya	ME	1496	Mizoram	MI	1497	Nagaland	NA	1498	Odisha	OD	1499	Puducherry	PO	1500	Punjab	PU	1501	Rajasthan	RA	1502	Sikkim	SI	1503	Tamil Nadu	TN	1504	Tripura	TR	1505	Uttar Pradesh	UP	1506	West Bengal	WB	4231	Telangana	TS	4239	Jharkhand	JH
		zone_id	name	code																																																																																																							
		1475	Andaman and Nicobar Islands	AN																																																																																																							
		1476	Andhra Pradesh	AP																																																																																																							
		1477	Arunachal Pradesh	AR																																																																																																							
		1478	Assam	AS																																																																																																							
		1479	Bihar	BI																																																																																																							
		1480	Chandigarh	CH																																																																																																							
		1481	Dadra and Nagar Haveli	DA																																																																																																							
		1482	Daman and Diu	DM																																																																																																							
		1483	Delhi	DE																																																																																																							
		1484	Goa	GO																																																																																																							
		1485	Gujarat	GU																																																																																																							
		1486	Haryana	HA																																																																																																							
		1487	Himachal Pradesh	HP																																																																																																							
		1488	Jammu and Kashmir	JA																																																																																																							
		1489	Karnataka	KA																																																																																																							
		1490	Kerala	KE																																																																																																							
		1491	Lakshadweep Islands	LI																																																																																																							
		1492	Madhya Pradesh	MP																																																																																																							
		1493	Maharashtra	MA																																																																																																							
		1494	Manipur	MN																																																																																																							
		1495	Meghalaya	ME																																																																																																							
		1496	Mizoram	MI																																																																																																							
		1497	Nagaland	NA																																																																																																							
		1498	Odisha	OD																																																																																																							
		1499	Puducherry	PO																																																																																																							
		1500	Punjab	PU																																																																																																							
		1501	Rajasthan	RA																																																																																																							
		1502	Sikkim	SI																																																																																																							
		1503	Tamil Nadu	TN																																																																																																							
		1504	Tripura	TR																																																																																																							
		1505	Uttar Pradesh	UP																																																																																																							
1506	West Bengal	WB																																																																																																									
4231	Telangana	TS																																																																																																									
4239	Jharkhand	JH																																																																																																									



Parameter	Required	Description			
		4240	Uttarakhand	UK	
		4241	Chattisgarh	CG	
		4242	Ladakh	LA	
country_id	Yes	Data_type: string Only '99' allowed (for India)			

On success returns an array showing the identifier to be used for the newly created pickup address. This warehouse_id should be stored as it will be required in case you want to update the pickup address later.

```
{  
  "success": 1,  
  "warehouse_id" : 456  
}
```



UPDATE an existing PICKUP ADDRESS

You can edit an existing pickup address

Request URL : https://www.icarry.in/api_edit_pickup_address&api_token=<api_token>

Method: POST

Request Body Parameters

Parameter	Required	Description
warehouse_id	Yes	Data_type: string warehouse_id obtained on successful addition of a pickup address. From previous API example - 456
name	Yes	Data_type: string Contact person name
email	Yes	Data_type: string Contact person email
phone	Yes	Data_type: string 10 digit mobile number of contact person without 0 or +91 prefix
alt_phone	No	Data_type: string Alternative mobile number. 10 digit mobile number of contact person without 0 or +91 prefix
street1	Yes	Data_type: string Address details such as House No or Apartment No, Building name, Street name etc
street2	No	Data_type: string
locality	No	Data_type: string
city	Yes	Data_type: string Name of city. Example - Hyderabad
pincode	Yes	Data_type: string



Parameter	Required	Description																																																																																																			
		Postal code. Example - 400071																																																																																																			
zone_id	Yes	Data_type: integer Integer zone_id for state <table border="1"> <thead> <tr> <th>zone_id</th><th>name</th><th>code</th></tr> </thead> <tbody> <tr><td>1475</td><td>Andaman and Nicobar Islands</td><td>AN</td></tr> <tr><td>1476</td><td>Andhra Pradesh</td><td>AP</td></tr> <tr><td>1477</td><td>Arunachal Pradesh</td><td>AR</td></tr> <tr><td>1478</td><td>Assam</td><td>AS</td></tr> <tr><td>1479</td><td>Bihar</td><td>BI</td></tr> <tr><td>1480</td><td>Chandigarh</td><td>CH</td></tr> <tr><td>1481</td><td>Dadra and Nagar Haveli</td><td>DA</td></tr> <tr><td>1482</td><td>Daman and Diu</td><td>DM</td></tr> <tr><td>1483</td><td>Delhi</td><td>DE</td></tr> <tr><td>1484</td><td>Goa</td><td>GO</td></tr> <tr><td>1485</td><td>Gujarat</td><td>GU</td></tr> <tr><td>1486</td><td>Haryana</td><td>HA</td></tr> <tr><td>1487</td><td>Himachal Pradesh</td><td>HP</td></tr> <tr><td>1488</td><td>Jammu and Kashmir</td><td>JA</td></tr> <tr><td>1489</td><td>Karnataka</td><td>KA</td></tr> <tr><td>1490</td><td>Kerala</td><td>KE</td></tr> <tr><td>1491</td><td>Lakshadweep Islands</td><td>LI</td></tr> <tr><td>1492</td><td>Madhya Pradesh</td><td>MP</td></tr> <tr><td>1493</td><td>Maharashtra</td><td>MA</td></tr> <tr><td>1494</td><td>Manipur</td><td>MN</td></tr> <tr><td>1495</td><td>Meghalaya</td><td>ME</td></tr> <tr><td>1496</td><td>Mizoram</td><td>MI</td></tr> <tr><td>1497</td><td>Nagaland</td><td>NA</td></tr> <tr><td>1498</td><td>Odisha</td><td>OD</td></tr> <tr><td>1499</td><td>Puducherry</td><td>PO</td></tr> <tr><td>1500</td><td>Punjab</td><td>PU</td></tr> <tr><td>1501</td><td>Rajasthan</td><td>RA</td></tr> <tr><td>1502</td><td>Sikkim</td><td>SI</td></tr> <tr><td>1503</td><td>Tamil Nadu</td><td>TN</td></tr> <tr><td>1504</td><td>Tripura</td><td>TR</td></tr> <tr><td>1505</td><td>Uttar Pradesh</td><td>UP</td></tr> <tr><td>1506</td><td>West Bengal</td><td>WB</td></tr> </tbody> </table>	zone_id	name	code	1475	Andaman and Nicobar Islands	AN	1476	Andhra Pradesh	AP	1477	Arunachal Pradesh	AR	1478	Assam	AS	1479	Bihar	BI	1480	Chandigarh	CH	1481	Dadra and Nagar Haveli	DA	1482	Daman and Diu	DM	1483	Delhi	DE	1484	Goa	GO	1485	Gujarat	GU	1486	Haryana	HA	1487	Himachal Pradesh	HP	1488	Jammu and Kashmir	JA	1489	Karnataka	KA	1490	Kerala	KE	1491	Lakshadweep Islands	LI	1492	Madhya Pradesh	MP	1493	Maharashtra	MA	1494	Manipur	MN	1495	Meghalaya	ME	1496	Mizoram	MI	1497	Nagaland	NA	1498	Odisha	OD	1499	Puducherry	PO	1500	Punjab	PU	1501	Rajasthan	RA	1502	Sikkim	SI	1503	Tamil Nadu	TN	1504	Tripura	TR	1505	Uttar Pradesh	UP	1506	West Bengal	WB
zone_id	name	code																																																																																																			
1475	Andaman and Nicobar Islands	AN																																																																																																			
1476	Andhra Pradesh	AP																																																																																																			
1477	Arunachal Pradesh	AR																																																																																																			
1478	Assam	AS																																																																																																			
1479	Bihar	BI																																																																																																			
1480	Chandigarh	CH																																																																																																			
1481	Dadra and Nagar Haveli	DA																																																																																																			
1482	Daman and Diu	DM																																																																																																			
1483	Delhi	DE																																																																																																			
1484	Goa	GO																																																																																																			
1485	Gujarat	GU																																																																																																			
1486	Haryana	HA																																																																																																			
1487	Himachal Pradesh	HP																																																																																																			
1488	Jammu and Kashmir	JA																																																																																																			
1489	Karnataka	KA																																																																																																			
1490	Kerala	KE																																																																																																			
1491	Lakshadweep Islands	LI																																																																																																			
1492	Madhya Pradesh	MP																																																																																																			
1493	Maharashtra	MA																																																																																																			
1494	Manipur	MN																																																																																																			
1495	Meghalaya	ME																																																																																																			
1496	Mizoram	MI																																																																																																			
1497	Nagaland	NA																																																																																																			
1498	Odisha	OD																																																																																																			
1499	Puducherry	PO																																																																																																			
1500	Punjab	PU																																																																																																			
1501	Rajasthan	RA																																																																																																			
1502	Sikkim	SI																																																																																																			
1503	Tamil Nadu	TN																																																																																																			
1504	Tripura	TR																																																																																																			
1505	Uttar Pradesh	UP																																																																																																			
1506	West Bengal	WB																																																																																																			



Parameter	Required	Description			
		4231	Telangana	TS	
		4239	Jharkhand	JH	
		4240	Uttarakhand	UK	
		4241	Chattisgarh	CG	
		4242	Ladakh	LA	
country_id	Yes	Data_type: string Only '99' allowed (for India)			

On success returns an array showing the success and same warehouse_id that was passed as input.

```
{
  "success": 1,
  "warehouse_id" : 456
}
```

Error message will be passed in error field in response.

```
{
  "error": "Cannot delete Pickup Address while there are shipments from this address that are yet to be picked. Please cancel the Pending shipments and then delete address again."
}
```



DELETE an existing PICKUP ADDRESS

You can soft delete an existing pickup address. Deleted pickup addresses will still be counted in your plan limits.

Request URL : https://www.icarry.in/api_delete_pickup_address&api_token=<api_token>

Method: POST

Request Body Parameters

Parameter	Required	Description
warehouse_id	Yes	Data_type: string warehouse_id obtained on successful addition of a pickup address. From previous API example – 456

On success returns an array showing the success and same warehouse_id that was passed as input.

```
{  
  "success": 1,  
  "warehouse_id" : 456  
}
```

Error message will be passed in error field in response.

```
{  
  "error": "Cannot delete Pickup Address while there are shipments from this address that are yet to be picked. Please cancel the Pending shipments and then delete address again."  
}
```

5. Appendix

State Codes

State Name	Code
Andaman and Nicobar Islands	AN
Andhra Pradesh	AP
Arunachal Pradesh	AR
Assam	AS
Bihar	BI
Chandigarh	CH
Dadra and Nagar Haveli	DA
Daman and Diu	DM
Delhi	DE
Goa	GO
Gujarat	GU
Haryana	HA
Himachal Pradesh	HP
Jammu and Kashmir	JA
Karnataka	KA
Kerala	KE
Lakshadweep Islands	LI
Madhya Pradesh	MP
Maharashtra	MA
Manipur	MN
Meghalaya	ME
Mizoram	MI
Nagaland	NA
Odisha	OD
Puducherry	PO
Punjab	PU
Rajasthan	RA
Sikkim	SI
Tamil Nadu	TN
Tripura	TR
Uttar Pradesh	UP
West Bengal	WB
Telangana	TS
Jharkhand	JH
Uttarakhand	UK
Chattisgarh	CG
Ladakh	LA