

## Contents

0 Basic	1
0A .vimrc	1
0B PBDS	1
0C pragma	1
0D Default Code	1
0E LambdaCompare	1
1 Graph	1
1A 2SAT/SCC	1
1B BCC Vertex	2
1C BCC Edge	2
1D VirtualTree	2
1E MinimumMeanCycle	2
1F MaximumCliqueDyn	3
1G MinimumSteinerTree	3
1H DominatorTree	3
1I DMST(slow)	4
1J DMST	4
1K VizingTheorem	5
1L MinimumCliqueCover	5
1M CountMaximalClique	5
1N Theorems	5
2 Flow-Matching	6
2A HopcroftKarp	6
2B KM	6
2C MCMF	6
2D GeneralGraphMatching	7
2E MaxWeightMatching	7
2F GlobalMinCut	8
2G BoundedFlow(Dinic)	9
2H GomoryHuTree	9
2I MinCostCirculation	9
2J FlowModelsBuilding	10
3 Data Structure	10
3A LichaoTree	10
3B Treap	11
3C LinkCutTree	11
3D CentroidDecomposition	11
3E HeavyLightDecomposition	12
4 String	12
4A KMP	12
4B Z	12
4C Manacher	12
4D SuffixArray	13
4E SAIS	13
4F ACAutomaton	13
4G MinRotation	14
4H ExtSAM	14
4I PalindromeTree	14
5 Number Theory	15
5A Primes	15
5B ExtGCD	15
5C FloorCeil	15
5D FloorSum	15
5E MillerRabin	15
5F PollardRho	15
5G Fraction	15
5H ChineseRemainder	16
5I FactorialMod $p^k$	16
5J QuadraticResidue	16

5K MeisselLehmer	16
5L DiscreteLog	16
5M Theorems	16
5N Estimation	17
5O Numbers	17
5P GeneratingFunctions	17
6 Linear Algebra	17
6A GaussianElimination	17
6B BerlekampMassey	17
6C Simplex	18
7 Polynomials	18
7A NTT (FFT)	18
7B FHT	19
7C PolynomialOperations	19
7D NewtonMethod+MiscGF	19
8 Geometry	20
8A Basic	20
8B ConvexHull	20
8C SortByAngle	20
8D Formulas	20
8E TriangleHearts	20
8F PointSegmentDist	21
8G PointInCircle	21
8H PointInConvex	21
8I PointTangentConvex	21
8J CircTangentCirc	21
8K LineCircleIntersect	21
8L LineConvexIntersect	21
8M CircIntersectCirc	22
8N PolyIntersectCirc	22
8O PolyUnion	22
8P MinkowskiSum	22
8Q MinMaxEnclosingRect	22
8R MinEnclosingCircle	22
8S CircleCover	23
8T LineCmp	23
8U Trapezoidalization	23
8V HalfPlaneIntersect	24
8W RotatingSweepLine	24
8X DelaunayTriangulation	24
8Y VoronoiDiagram	25
9 Misc	25
9A MoAlgoWithModify	25
9B MoAlgoOnTree	25
9C MoAlgoAdvanced	25
9D HilbertCurve	26
9E ManhattanMST	26
9F SternBrocotTree	26
9G ALLCS	26
9H MatroidIntersection	26
9I SimulatedAnnealing	26
9J SMAWK	26
9K Python	27
9L LineContainer	27

```
// order_of_key(n): # of elements <= n
// find_by_order(n): 0-indexed

#include <ext/pb_ds/assoc_container.hpp>
#include <ext/pb_ds/priority_queue.hpp>
__gnu_pbds::priority_queue
    <int, greater<int>, thin_heap_tag> pq;
```

## 0C pragma

```
#pragma GCC optimize("Ofast,unroll-loops")
#pragma GCC target("avx,avx2,sse,sse2
    ,sse3,ssse3,sse4,popcnt,abm,mmx,fma,tune=native")
// chrono
::steady_clock::now().time_since_epoch().count()
```

## 0D Default Code

```
using namespace std;

#define F first
#define S second
#define all(x) x.begin(), x.end()
#define pii pair<int, int>
#define pll pair<ll, ll>
#define pdd pair<double, double>
#define ll long long
#define ld long double
#define i128 __int128

#ifdef LOCAL
#define px(
    args...) LKJ("\033[1;32m(" #args "):\033[0m", args)
template<class I> void LKJ(I&&x){ cerr << x << '\n'; }
template<class I, class...T> void
    LKJ(I&&x, T&&...t){ cerr << x << ' ', LKJ(t...); }
template<class I> void OI(I a, I b){ while
    (a < b) cerr << *a << " \n"[next(a) == b], ++a; }
#define pv(v) cerr
    << "\033[1;31m[" << #v << "]: \033[0m"; OI(all(v))
#else
#define px(...)
#define OI(...)
#define pv(v)
#endif

template<class A, class
    B> ostream& operator<<(ostream &os, pair<A, B> p)
    { return os << '(' << p.F << ", " << p.S << ')'; }

void solve() {}

int main() {
    cin.tie(0)->sync_with_stdio(0);
    int T = 1;

    // cin >> T;
    while (T--) solve();
}
```

## 0E LambdaCompare

```
auto cmp = [](int x, int y) { return x < y; };
std::set<int, decltype(cmp)> st(cmp);
```

## 1 Graph

### 1A 2SAT/SCC

```
struct SAT { // 0-base
    int low[N], dfn[N], bln[N], n, Time, nScc;
    bool instack[N], istrue[N];
    stack<int> st;
    vector<int> G[N], SCC[N];
    void init(int _n) {
        n = _n; // assert(n * 2 <= N);
        for (int i = 0; i < n + n; ++i) G[i].clear();
    }
    void add_edge(int a, int b) { G[a].emplace_back(b); }
    int rv(int a) {
```

## 0 Basic

### 0A .vimrc

```
sy on
set ru nu cin cul sc so=3 ts=4 sw=4 bs=2 ls=2 mouse=a
ino {<CR> {<CR>}<C-o>0
ino jj <esc>
ino jk <esc>
map <F7> :w<CR>:!g++ "%*" -std
    =c++17 -DLOCAL -Wall -Wextra -Wshadow -Wconversion
    -fsanitize=address,undefined -g && ./a.out<CR>
ca Hash w !cpp -dD -P -fpreprocessed
    \|| tr -d "[space:]" \|| md5sum \|| cut -c-6
```

### 0B PBDS

```
// Tree and fast PQ
#include <bits/extc++.h>
using namespace __gnu_pbds;

#include <ext/pb_ds/assoc_container.hpp>
#include <ext/pb_ds/tree_policy.hpp>
tree<int, null_type, less<int>, rb_tree_tag
    , tree_order_statistics_node_update> bst;
```

```

    if (a >= n) return a - n;
    return a + n;
}
void add_clause(int a, int b) {
    add_edge(rv(a), b), add_edge(rv(b), a);
}
void dfs(int u) {
    dfn[u] = low[u] = ++Time;
    instack[u] = 1, st.push(u);
    for (int i : G[u])
        if (!dfn[i])
            dfs(i), low[u] = min(low[i], low[u]);
        else if (instack[i] && dfn[i] < dfn[u])
            low[u] = min(low[u], dfn[i]);
    if (low[u] == dfn[u]) {
        int tmp;
        do {
            tmp = st.top(), st.pop();
            instack[tmp] = 0, bln[tmp] = nScc;
        } while (tmp != u);
        ++nScc;
    }
}
bool solve() {
    Time = nScc = 0;
    for (int i = 0; i < n + n; ++i)
        SCC[i].clear(), low[i] = dfn[i] = bln[i] = 0;
    for (int i = 0; i < n + n; ++i)
        if (!dfn[i]) dfs(i);
    for (int i = 0; i < n + n; ++i) SCC[bln[i]].emplace_back(i);
    for (int i = 0; i < n; ++i) {
        if (bln[i] == bln[i + n]) return false;
        istrue[i] = bln[i] < bln[i + n];
        istrue[i + n] = !istrue[i];
    }
    return true;
}
};

```

## 1B BCC Vertex

```

int n, m, dfn[N], low[N], is_cut[N], nbcc = 0, t = 0;
vector<int> g[N], bcc[N], G[2 * N];
stack<int> st;
void tarjan(int p, int lp) {
    dfn[p] = low[p] = ++t;
    st.push(p);
    for (auto i : g[p]) {
        if (!dfn[i]) {
            tarjan(i, p);
            low[p] = min(low[p], low[i]);
            if (dfn[p] <= low[i]) {
                nbcc++;
                is_cut[p] = 1;
                for (int x = 0; x != i; st.pop()) {
                    x = st.top();
                    bcc[nbcc].push_back(x);
                }
                bcc[nbcc].push_back(p);
            }
        } else low[p] = min(low[p], dfn[i]);
    }
}
void build() { // [n+1, n+nbcc] cycle, [1, n] vertex
    for (int i = 1; i <= nbcc; i++) {
        for (auto j : bcc[i]) {
            G[i + n].push_back(j);
            G[j].push_back(i + n);
        }
    }
}
}

```

## 1C BCC Edge

```

namespace bridge_cc {
    vector<int> tim, low;

```

```

stack<int, vector<int>> st;
int t, bcc_id;
void dfs(int u, int p, const vector<
    vector<pair<int, int>>> &edge, vector<int> &pa) {
    tim[u] = low[u] = t++;
    st.push(u);
    for (const auto &[v, id] : edge[u]) {
        if (id == p)
            continue;
        if (tim[v])
            low[u] = min(low[u], tim[v]);
        else {
            dfs(v, id, edge, pa);
            if (low[v] > tim[u]) {
                int x;
                do {
                    pa[x = st.top()] = bcc_id;
                    st.pop();
                } while (x != v);
                bcc_id++;
            }
            else
                low[u] = min(low[u], low[v]);
        }
    }
}
vector<int> solve(const vector<
    <vector<pair<int, int>>> &edge) { // (to, id)
    int n = edge.size();
    tim.resize(n);
    low.resize(n);
    t = bcc_id = 1;
    vector<int> pa(n);

    for (int i = 0; i < n; i++) {
        if (!tim[i]) {
            dfs(i, -1, edge, pa);
            while (!st.empty()) {
                pa[st.top()] = bcc_id;
                st.pop();
            }
            bcc_id++;
        }
    }
    return pa;
} // return bcc id(start from 1)
};

```

## 1D VirtualTree

```

// requires DFS io, lca, is_child
vector<int> tre[N];
bool cmp(int a, int b){ return in[a] < in[b]; }
void add_edge(int a, int b){
    tre[a].emplace_back(b);
    tre[b].emplace_back(a);
}
void virtual_tree(vector<int> arr, int k){
    vector<int> sta;
    sort(arr.begin(), arr.end(), cmp);
    for (int i = 1; i < k; i++)
        arr.emplace_back(lca(arr[i], arr[i - 1]));
    sort(arr.begin(), arr.end(), cmp);
    arr.resize(
        (unique(arr.begin(), arr.end()) - arr.begin()));
    for (auto i : arr){
        while (!sta.empty()
            () && !is_child(sta.back(), i)) sta.pop_back();
        if (!sta.empty()) add_edge(sta.back(), i);
        sta.push_back(i);
    }
}

```

## 1E MinimumMeanCycle

```

/* O(V^3)
let dp[i][j] = min length from 1 to j exactly i edges
ans = min (dp[n + 1][u] - dp[i][u]) / (n + 1 - i) */

```

## 1F MaximumCliqueDyn

```

struct MaxClique { // fast when N <= 100
    bitset<N> G[N], cs[N];
    int ans, sol[N], q, cur[N], d[N], n;
    void init(int _n) {
        n = _n;
        for (int i = 0; i < n; ++i) G[i].reset();
    }
    void add_edge(int u, int v) {
        G[u][v] = G[v][u] = 1;
    }
    void pre_dfs(vector<int> &r, int l, bitset<N> mask) {
        if (l < 4) {
            for (int i : r) d[i] = (G[i] & mask).count();
            sort(all(r), [&](int x, int y) { return d[x] > d[y]; });
        }
        vector<int> c(r.size());
        int lft = max(ans - q + 1, 1), rgt = 1, tp = 0;
        cs[1].reset(), cs[2].reset();
        for (int p : r) {
            int k = 1;
            while ((cs[k] & G[p]).any()) ++k;
            if (k > rgt) cs[++rgt + 1].reset();
            cs[k][p] = 1;
            if (k < lft) r[tp++] = p;
        }
        for (int k = lft; k <= rgt; ++k)
            for (int p = cs[k]._Find_first(); p < N; p = cs[k]._Find_next(p))
                r[tp] = p, c[tp] = k, ++tp;
        dfs(r, c, l + 1, mask);
    }
    void dfs(vector<int> &r, vector<int> &c, int l, bitset<N> mask) {
        while (!r.empty()) {
            int p = r.back();
            r.pop_back(), mask[p] = 0;
            if (q + c.back() <= ans) return;
            cur[q++] = p;
            vector<int> nr;
            for (int i : r) if (G[p][i]) nr.emplace_back(i);
            if (!nr.empty()) pre_dfs(nr, l, mask & G[p]);
            else if (q > ans) ans = q, copy_n(cur, q, sol);
            c.pop_back(), --q;
        }
    }
    int solve() {
        vector<int> r(n);
        ans = q = 0, iota(all(r), 0);
        pre_dfs(r, 0, bitset<N>(string(n, '1')));
        return ans;
    }
};

```

## 1G MinimumSteinerTree

```

struct SteinerTree { // 0-base
    int n, dst[N][N], dp[1 << T][N], tdst[N];
    int vcst[N]; // the cost of vertexs
    void init(int _n) {
        n = _n;
        for (int i = 0; i < n; ++i) {
            fill_n(dst[i], n, INF);
            dst[i][i] = vcst[i] = 0;
        }
    }
    void chmin(int &x, int val) {
        x = min(x, val);
    }
    void add_edge(int ui, int vi, int wi) {
        chmin(dst[ui][vi], wi);
    }
    void shortest_path() {
        for (int k = 0; k < n; ++k)

```

```

            for (int i = 0; i < n; ++i)
                for (int j = 0; j < n; ++j)
                    chmin(dst[i][j], dst[i][k] + dst[k][j]);
    }
    int solve(const vector<int> &ter) {
        shortest_path();
        int t = ter.size(), full = (1 << t) - 1;
        for (int i = 0; i <= full; ++i)
            fill_n(dp[i], n, INF);
        copy_n(vcst, n, dp[0]);
        for (int msk = 1; msk <= full; ++msk) {
            if (!(msk & (msk - 1))) {
                int who = __lg(msk);
                for (int i = 0; i < n; ++i)
                    dp[msk][i] = vcst[ter[who]] + dst[ter[who]][i];
            }
            for (int i = 0; i < n; ++i)
                for (int sub = (msk - 1) & msk; sub; sub = (sub - 1) & msk)
                    chmin(dp[msk][i], dp[sub][i] + dp[msk ^ sub][i] - vcst[i]);
            for (int i = 0; i < n; ++i) {
                tdst[i] = INF;
                for (int j = 0; j < n; ++j)
                    chmin(tdst[i], dp[msk][j] + dst[j][i]);
            }
            copy_n(tdst, n, dp[msk]);
        }
        return *min_element(dp[full], dp[full] + n);
    }
}; // O(V 3^T + V^2 2^T)

```

## 1H DominatorTree

```

struct DominatorTree { // 1-base
    vector<int> G[N], rG[N];
    int n, pa[N], dfn[N], id[N], Time;
    int semi[N], idom[N], best[N];
    vector<int> tree[N]; // dominator_tree
    void init(int _n) {
        n = _n;
        for (int i = 1; i <= n; ++i)
            G[i].clear(), rG[i].clear();
    }
    void add_edge(int u, int v) {
        G[u].emplace_back(v), rG[v].emplace_back(u);
    }
    void dfs(int u) {
        id[dfn[u] = ++Time] = u;
        for (auto v : G[u])
            if (!dfn[v]) dfs(v), pa[dfn[v]] = dfn[u];
    }
    int find(int y, int x) {
        if (y <= x) return y;
        int tmp = find(pa[y], x);
        if (semi[best[y]] > semi[best[pa[y]]])
            best[y] = best[pa[y]];
        return pa[y] = tmp;
    }
    void tarjan(int root) {
        Time = 0;
        for (int i = 1; i <= n; ++i) {
            dfn[i] = idom[i] = 0;
            tree[i].clear();
            best[i] = semi[i] = i;
        }
        dfs(root);
        for (int i = Time; i > 1; --i) {
            int u = id[i];
            for (auto v : rG[u])
                if (v = dfn[v]) {
                    find(v, i);
                    semi[i] = min(semi[i], semi[best[v]]);
                }
            tree[semi[i]].emplace_back(i);
        }
    }

```

```

    for (auto v : tree[pa[i]]) {
        find(v, pa[i]);
        idom[v] =
            semi[best[v]] == pa[i] ? pa[i] : best[v];
    }
    tree[pa[i]].clear();
}
for (int i = 2; i <= Time; ++i) {
    if (idom[i] != semi[i]) idom[i] = idom[idom[i]];
    tree[id[idom[i]]].emplace_back(id[i]);
}
}
};

```

## 1I DMST(slow)

```

struct DMST { // O(VE)
    struct edge {
        int u, v;
        ll w;
    };
    vector<edge> E; // 0-base
    int pe[N], id[N], vis[N];
    ll in[N];
    void init() { E.clear(); }
    void add_edge(int u, int v, ll w) {
        if (u != v) E.emplace_back(edge{u, v, w});
    }
    ll build(int root, int n) {
        ll ans = 0;
        for (;;) {
            fill_n(in, n, INF);
            for (int i = 0; i < (int)E.size(); ++i)
                if (E[i].u != E[i].v && E[i].w < in[E[i].v])
                    pe[E[i].v] = i, in[E[i].v] = E[i].w;
            for (int u = 0; u < n; ++u) // no solution
                if (u != root && in[u] == INF) return -INF;
            int cntnode = 0;
            fill_n(id, n, -1), fill_n(vis, n, -1);
            for (int u = 0; u < n; ++u) {
                if (u != root) ans += in[u];
                int v = u;
                while (vis[v] != u && !~id[v] && v != root)
                    vis[v] = u, v = E[pe[v]].u;
                if (v != root && !~id[v]) {
                    for (int x = E[pe[v]].u; x != v;
                        x = E[pe[x]].u)
                        id[x] = cntnode;
                    id[v] = cntnode++;
                }
            }
            if (!cntnode) break; // no cycle
            for (int u = 0; u < n; ++u)
                if (!~id[u]) id[u] = cntnode++;
            for (int i = 0; i < (int)E.size(); ++i) {
                int v = E[i].v;
                E[i].u = id[E[i].u], E[i].v = id[E[i].v];
                if (E[i].u != E[i].v) E[i].w -= in[v];
            }
            n = cntnode, root = id[root];
        }
        return ans;
    }
};

```

## 1J DMST

```

#define rep(i, a, b) for (int i = a; i < (b); ++i)
#define sz(x) (int)(x).size()
typedef vector<int> vi;
struct RollbackUF {
    vi e;
    vector<pii> st;
    RollbackUF(int n) : e(n, -1) {}
    int size(int x) { return -e[find(x)]; }
    int find(int x) { return e[x] < 0 ? x : find(e[x]); }
    int time() { return sz(st); }
};

```

```

void rollback(int t) {
    for (int i = time(); i-- > t;)
        e[st[i].first] = st[i].second;
    st.resize(t);
}
bool join(int a, int b) {
    a = find(a), b = find(b);
    if (a == b) return false;
    if (e[a] > e[b]) swap(a, b);
    st.push_back({a, e[a]});
    st.push_back({b, e[b]});
    e[a] += e[b];
    e[b] = a;
    return true;
}
};
struct Edge {
    int a, b;
    ll w;
};
struct Node { // lazy skew heap node
    Edge key;
    Node *l, *r;
    ll delta;
    void prop() {
        key.w += delta;
        if (l) l->delta += delta;
        if (r) r->delta += delta;
        delta = 0;
    }
    Edge top() {
        prop();
        return key;
    }
};
Node *merge(Node *a, Node *b) {
    if (!a || !b) return a ? b : a;
    a->prop(), b->prop();
    if (a->key.w > b->key.w) swap(a, b);
    swap(a->l, (a->r = merge(b, a->r)));
    return a;
}
void pop(Node *a) {
    a->prop();
    a = merge(a->l, a->r);
}
pair<ll, vi> dmst(int n, int r, vector<Edge> &g) {
    RollbackUF uf(n);
    vector<Node*> heap(n);
    for (Edge e : g)
        heap[e.b] = merge(heap[e.b], new Node{e});
    ll res = 0;
    vi seen(n, -1), path(n, par(n));
    seen[r] = r;
    vector<Edge> Q(n), in(n, {-1, -1}), comp;
    deque<tuple<int, int, vector<Edge>>> cys;
    rep(s, 0, n) {
        int u = s, qi = 0, w;
        while (seen[u] < 0) {
            if (!heap[u]) return {-1, {}};
            Edge e = heap[u]->top();
            heap[u]->delta -= e.w, pop(heap[u]);
            Q[qi] = e, path[qi++] = u, seen[u] = s;
            res += e.w, u = uf.find(e.a);
            if (seen[u] == s) { // found cycle, contract
                Node *cyc = 0;
                int end = qi, time = uf.time();
                do cyc = merge(cyc, heap[w = path[--qi]]);
                while (uf.join(u, w));
                u = uf.find(u), heap[u] = cyc, seen[u] = -1;
                cys.push_front({u, time, {&Q[qi], &Q[end]}});
            }
        }
        rep(i, 0, qi) in[uf.find(Q[i].b)] = Q[i];
    }
}

```

```

for (auto &[u, t, cmp] : cyes) {
    // restore sol (optional)
    uf.rollback(t);
    Edge inEdge = in[u];
    for (auto &e : cmp) in[uf.find(e.b)] = e;
    in[uf.find(inEdge.b)] = inEdge;
}
rep(i, 0, n) par[i] = in[i].a;
return {res, par};
}

```

## 1K VizingTheorem

```

namespace Vizing { // Edge coloring
    // G: coloring adjM
int C[N][N], G[N][N];
void clear(int n) {
    for (int i = 0; i <= n; i++) {
        for (int j = 0; j <= n; j++) C[i][j] = G[i][j] = 0;
    }
}
void solve(vector<pii> &E, int n) {
    int X[n] = {}, a;
    auto update = [&](int u) {
        for (X[u] = 1; C[u][X[u]]; X[u]++);
    };
    auto color = [&](int u, int v, int c) {
        int p = G[u][v];
        G[u][v] = G[v][u] = c;
        C[u][c] = v;
        C[v][c] = u;
        C[u][p] = C[v][p] = 0;
        if (p) X[u] = X[v] = p;
        else update(u), update(v);
        return p;
    };
    auto flip = [&](int u, int c1, int c2) {
        int p = C[u][c1];
        swap(C[u][c1], C[u][c2]);
        if (p) G[u][p] = G[p][u] = c2;
        if (!C[u][c1]) X[u] = c1;
        if (!C[u][c2]) X[u] = c2;
        return p;
    };
    for (int i = 1; i <= n; i++) X[i] = 1;
    for (int t = 0; t < (int)E.size(); t++) {
        int u = E[t].first, v0 = E[t].second, v = v0,
            c0 = X[u], c = c0, d;
        vector<pii> L;
        int vst[n] = {};
        while (!G[u][v0]) {
            L.emplace_back(v, d = X[v]);
            if (!C[v][c])
                for (a = (int)L.size() - 1; a >= 0; a--)
                    c = color(u, L[a].first, c);
            else if (!C[u][d])
                for (a = (int)L.size() - 1; a >= 0; a--)
                    color(u, L[a].first, L[a].second);
            else if (vst[d]) break;
            else vst[d] = 1, v = C[u][d];
        }
        if (!G[u][v0]) {
            for (; v; v = flip(v, c, d), swap(c, d));
            if (C[u][c0]) {
                for (a = (int)L.size() - 2;
                    a >= 0 && L[a].second != c; a--);
                ;
                for (; a >= 0; a--)
                    color(u, L[a].first, L[a].second);
            } else t--;
        }
    }
}
} // namespace Vizing

```

## 1L MinimumCliqueCover

```

struct CliqueCover { // 0-base, O(n2^n)
    int co[1 << N], n, E[N];
    int dp[1 << N];
    void init(int _n) {
        n = _n, fill_n(dp, 1 << n, 0);
        fill_n(E, n, 0), fill_n(co, 1 << n, 0);
    }
    void add_edge(int u, int v) {
        E[u] |= 1 << v, E[v] |= 1 << u;
    }
    int solve() {
        for (int i = 0; i < n; ++i)
            co[1 << i] = E[i] | (1 << i);
        co[0] = (1 << n) - 1;
        dp[0] = (n & 1) * 2 - 1;
        for (int i = 1; i < (1 << n); ++i) {
            int t = i & -i;
            dp[i] = -dp[i ^ t];
            co[i] = co[i ^ t] & co[t];
        }
        for (int i = 0; i < (1 << n); ++i)
            co[i] = (co[i] & i) == i;
        fwt(co, 1 << n, 1); // needs FWHT
        for (int ans = 1; ans < n; ++ans) {
            int sum = 0; // probabilistic
            for (int i = 0; i < (1 << n); ++i)
                sum += (dp[i] * co[i]);
            if (sum) return ans;
        }
        return n;
    }
};

```

## 1M CountMaximalClique

```

struct BronKerbosch { // 1-base
    int n, a[N], g[N][N];
    int S, all[N][N], some[N][N], none[N][N];
    void init(int _n) {
        n = _n;
        for (int i = 1; i <= n; ++i)
            for (int j = 1; j <= n; ++j) g[i][j] = 0;
    }
    void add_edge(int u, int v) {
        g[u][v] = g[v][u] = 1;
    }
    void dfs(int d, int an, int sn, int nn) {
        if (S > 1000) return; // pruning
        if (sn == 0 && nn == 0) ++S;
        int u = some[d][0];
        for (int i = 0; i < sn; ++i) {
            int v = some[d][i];
            if (g[u][v]) continue;
            int tsu = 0, tnn = 0;
            copy_n(all[d], an, all[d + 1]);
            all[d + 1][an] = v;
            for (int j = 0; j < sn; ++j)
                if (g[v][some[d][j]])
                    some[d + 1][tsu++] = some[d][j];
            for (int j = 0; j < nn; ++j)
                if (g[v][none[d][j]])
                    none[d + 1][tnn++] = none[d][j];
            dfs(d + 1, an + 1, tsu, tnn);
            some[d][i] = 0, none[d][nn++] = v;
        }
    }
    int solve() {
        iota(some[0], some[0] + n, 1);
        S = 0, dfs(0, 0, n, 0);
        return S;
    }
};

```

## 1N Theorems

$|\text{max independent edge set}| = |V| - |\text{min edge cover}|$   
 $|\text{max independent set}| = |V| - |\text{min vertex cover}|$

## 2 Flow-Matching

### 2A HopcroftKarp

```
struct HopcroftKarp
{
    // 0-based, return btoa to get matching
    bool dfs(int a, int L, vector<vector<int>> &g,
        vector<int> &btoa, vector<int> &A,
        vector<int> &B) {
        if (A[a] != L) return 0;
        A[a] = -1;
        for (int b : g[a])
            if (B[b] == L + 1) {
                B[b] = 0;
                if (btoa[b] == -1 ||
                    dfs(btoa[b], L + 1, g, btoa, A, B))
                    return btoa[b] = a, 1;
            }
        return 0;
    }
    int solve(vector<vector<int>> &g, int m) {
        int res = 0;
        vector<int> btoa(m, -1), A(g.size()),
            B(btoa.size()), cur, next;
        for (;;) {
            fill(all(A), 0), fill(all(B), 0);
            cur.clear();
            for (int a : btoa)
                if (a != -1) A[a] = -1;
            for (int a = 0; a < (int)g.size(); a++)
                if (A[a] == 0) cur.push_back(a);
            for (int lay = 1;; lay++) {
                bool islast = 0;
                next.clear();
                for (int a : cur)
                    for (int b : g[a]) {
                        if (btoa[b] == -1) {
                            B[b] = lay;
                            islast = 1;
                        } else if (btoa[b] != a && !B[b]) {
                            B[b] = lay;
                            next.push_back(btoa[b]);
                        }
                    }
                if (islast) break;
                if (next.empty()) return res;
                for (int a : next) A[a] = lay;
                cur.swap(next);
            }
            res += dfs(a, 0, g, btoa, A, B);
        }
    }
};
```

### 2B KM

```
struct KM { // 0-base, maximum matching
    ll w[N][N], hl[N], hr[N], slk[N];
    int fl[N], fr[N], pre[N], qu[N], ql, qr, n;
    bool vl[N], vr[N];
    void init(int _n) {
        n = _n;
        for (int i = 0; i < n; ++i)
            fill_n(w[i], n, -INF);
    }
    void add_edge(int a, int b, ll wei) {
        w[a][b] = wei;
    }
    bool Check(int x) {
        if (vl[x] = 1, ~fl[x])
            return vr[qu[qr++] = fl[x]] = 1;
        while (~x) swap(x, fr[fl[x] = pre[x]]);
        return 0;
    }
    void bfs(int s) {
        fill_n(slk,
            n, INF), fill_n(vl, n, 0), fill_n(vr, n, 0);
```

```
        ql = qr = 0, qu[qr++] = s, vr[s] = 1;
        for (ll d;;) {
            while (ql < qr)
                for (int x = 0, y = qu[ql++]; x < n; ++x)
                    if (!vl[x] && slk
                        [x] >= (d = hl[x] + hr[y] - w[x][y])) {
                        if (pre[x] = y, d) slk[x] = d;
                        else if (!Check(x)) return;
                    }
            d = INF;
            for (int x = 0; x < n; ++x)
                if (!vl[x] && d > slk[x]) d = slk[x];
            for (int x = 0; x < n; ++x) {
                if (vl[x]) hl[x] += d;
                else slk[x] -= d;
                if (vr[x]) hr[x] -= d;
            }
            for (int x = 0; x < n; ++x)
                if (!vl[x] && !slk[x] && !Check(x)) return;
        }
    }
    ll solve() {
        fill_n(fl,
            n, -1), fill_n(fr, n, -1), fill_n(hr, n, 0);
        for (int i = 0; i < n; ++i)
            hl[i] = *max_element(w[i], w[i] + n);
        for (int i = 0; i < n; ++i) bfs(i);
        ll res = 0;
        for (int i = 0; i < n; ++i) res += w[i][fl[i]];
        return res;
    }
};
```

### 2C MCMF

```
struct MinCostMaxFlow { // 0-base
    struct Edge {
        ll from, to, cap, flow, cost, rev;
    } *past[N];
    vector<Edge> G[N];
    int inq[N], n, s, t;
    ll dis[N], up[N], pot[N];
    bool BellmanFord() {
        fill_n(dis, n, INF), fill_n(inq, n, 0);
        queue<int> q;
        auto relax = [&](int u, ll d, ll cap, Edge *e) {
            if (cap > 0 && dis[u] > d) {
                dis[u] = d, up[u] = cap, past[u] = e;
                if (!inq[u]) inq[u] = 1, q.push(u);
            }
        };
        relax(s, 0, INF, 0);
        while (!q.empty()) {
            int u = q.front();
            q.pop(), inq[u] = 0;
            for (auto &e : G[u]) {
                ll d2 = dis[u] + e.cost + pot[u] - pot[e.to];
                relax(
                    e.to, d2, min(up[u], e.cap - e.flow), &e);
            }
        }
        return dis[t] != INF;
    }
    bool Dijkstra() {
        fill_n(dis, n, INF);
        priority_queue<pll, vector<pll>, greater<pll>> pq;
        auto relax = [&](int u, ll d, ll cap, Edge *e) {
            if (cap > 0 && dis[u] > d) {
                dis[u] = d, up[u] = cap, past[u] = e;
                pq.push(pll(d, u));
            }
        };
        relax(s, 0, INF, 0);
        while (!pq.empty()) {
            auto [d, u] = pq.top();
            pq.pop();
```



```

    if (dis[u] != d) continue;
    for (auto &e : G[u]) {
        ll d2 = dis[u] + e.cost + pot[u] - pot[e.to];
        relax(
            e.to, d2, min(up[u], e.cap - e.flow), &e);
    }
}
return dis[t] != INF;
}

void solve(int _s, int _t, ll &flow, ll &cost,
    bool neg = true) {
    s = _s, t = _t, flow = 0, cost = 0;
    if (neg) BellmanFord(), copy_n(dis, n, pot);
    // do BellmanFord() if time isn't tight
    for (; Dijkstra(); copy_n(dis, n, pot)) {
        for (int i = 0; i < n; ++i)
            dis[i] += pot[i] - pot[s];
        flow += up[t], cost += up[t] * dis[t];
        for (int i = t; past[i]; i = past[i]->from) {
            auto &e = *past[i];
            e.flow += up[t], G[e.to][e.rev].flow -= up[t];
        }
    }
}

void init(int _n) {
    n = _n, fill_n(pot, n, 0);
    for (int i = 0; i < n; ++i) G[i].clear();
}

void add_edge(ll a, ll b, ll cap, ll cost) {
    G[a].emplace_back(
        Edge{a, b, cap, 0, cost, (int)G[b].size()});
    G[b].emplace_back(
        Edge{b, a, 0, 0, -cost, (int)G[a].size() - 1});
}
};

```

## 2D GeneralGraphMatching

```

struct Matching { // 0-base
    queue<int> q; int n;
    vector<int> fa, s, vis, pre, match;
    vector<vector<int>> G;
    int Find(int u)
    { return u == fa[u] ? u : fa[u] = Find(fa[u]); }
    int LCA(int x, int y) {
        static int tk = 0; tk++; x = Find(x); y = Find(y);
        for (; swap(x, y)) if (x != n) {
            if (vis[x] == tk) return x;
            vis[x] = tk;
            x = Find(pre[match[x]]);
        }
    }
    void Blossom(int x, int y, int l) {
        for (; Find(x) != l; x = pre[y]) {
            pre[x] = y, y = match[x];
            if (s[y] == 1) q.push(y), s[y] = 0;
            for (int z: {x, y}) if (fa[z] == z) fa[z] = l;
        }
    }
    bool Bfs(int r) {
        iota(all(fa), 0); fill(all(s), -1);
        q = queue<int>(); q.push(r); s[r] = 0;
        for (; !q.empty(); q.pop()) {
            for (int x = q.front(); int u : G[x])
                if (s[u] == -1) {
                    if (pre[u] = x, s[u] = 1, match[u] == n) {
                        for (int a = u, b = x, last;
                            b != n; a = last, b = pre[a])
                            last = match[b], match[b] = a, match[a] = b;
                        return true;
                    }
                    q.push(match[u]); s[match[u]] = 0;
                }
            else if (!s[u] && Find(u) != Find(x)) {
                int l = LCA(u, x);
                Blossom(x, u, l); Blossom(u, x, l);
            }
        }
    }
};

```

```

    }
}
return false;
}

Matching(int _n) : n(_n), fa(n + 1), s(n + 1), vis(
    n + 1), pre(n + 1, n), match(n + 1, n), G(n) {}

void add_edge(int u, int v)
{ G[u].emplace_back(v), G[v].emplace_back(u); }

int solve() {
    int ans = 0;
    for (int x = 0; x < n; ++x)
        if (match[x] == n) ans += Bfs(x);
    return ans;
} // match[x] == n means not matched
};

```

## 2E MaxWeightMaching

```

#define rep(i, l, r) for (int i = (l); i <= (r); ++i)
struct WeightGraph { // 1-based, note int!
    struct edge {
        int u, v, w;
    };
    int n, nx;
    vector<int> lab;
    vector<vector<edge>> g;
    vector<int> slack, match, st, pa, S, vis;
    vector<vector<int>> flo, flo_from;
    queue<int> q;
    WeightGraph(int n_)
        : n(n_), nx(n * 2), lab(nx + 1),
          g(nx + 1, vector<edge>(nx + 1)), slack(nx + 1),
          flo(nx + 1), flo_from(nx + 1, vector(n + 1, 0)) {
        match = st = pa = S = vis = slack;
        rep(u, 1, n) rep(v, 1, n) g[u][v] = {u, v, 0};
    }
    int ED(edge e) {
        return lab[e.u] + lab[e.v] - g[e.u][e.v].w * 2;
    }
    void update_slack(int u, int x, int &s) {
        if (!s || ED(g[u][x]) < ED(g[s][x])) s = u;
    }
    void set_slack(int x) {
        slack[x] = 0;
        for (int u = 1; u <= n; ++u)
            if (g[u][x].w > 0 && st[u] != x && S[st[u]] == 0)
                update_slack(u, x, slack[x]);
    }
    void q_push(int x) {
        if (x <= n) q.push(x);
        else
            for (int y : flo[x]) q.push(y);
    }
    void set_st(int x, int b) {
        st[x] = b;
        if (x > n)
            for (int y : flo[x]) set_st(y, b);
    }
    vector<int> split_flo(auto &f, int xr) {
        auto it = find(all(f), xr);
        if (auto pr = it - f.begin(); pr % 2 == 1)
            reverse(1 + all(f), it = f.end() - pr);
        auto res = vector(f.begin(), it);
        return f.erase(f.begin(), it), res;
    }
    void set_match(int u, int v) {
        match[u] = g[u][v].v;
        if (u <= n) return;
        int xr = flo_from[u][g[u][v].u];
        auto &f = flo[u], z = split_flo(f, xr);
        rep(i, 0, (int)z.size() - 1)
            set_match(z[i], z[i ^ 1]);
        set_match(xr, v);
        f.insert(f.end(), all(z));
    }
    void augment(int u, int v) {
        for (;;) {

```

```

    int xnv = st[match[u]];
    set_match(u, v);
    if (!xnv) return;
    set_match(xnv, st[pa[xnv]]);
    u = st[pa[xnv]], v = xnv;
}
}
int lca(int u, int v) {
    static int t = 0;
    ++t;
    for (++t; u || v; swap(u, v))
        if (u) {
            if (vis[u] == t) return u;
            vis[u] = t;
            u = st[match[u]];
            if (u) u = st[pa[u]];
        }
    return 0;
}
void add_blossom(int u, int o, int v) {
    int b = find(n + 1 + all(st), 0) - begin(st);
    lab[b] = 0, S[b] = 0;
    match[b] = match[o];
    vector<int> f = {o};
    for (int x = u, y; x != o; x = st[pa[y]])
        f.emplace_back(x),
        f.emplace_back(y = st[match[x]]), q_push(y);
    reverse(1 + all(f));
    for (int x = v, y; x != o; x = st[pa[y]])
        f.emplace_back(x),
        f.emplace_back(y = st[match[x]]), q_push(y);
    flo[b] = f;
    set_st(b, b);
    for (int x = 1; x <= nx; ++x)
        g[b][x].w = g[x][b].w = 0;
    fill(all(flo_from[b]), 0);
    for (int xs : flo[b]) {
        for (int x = 1; x <= nx; ++x)
            if (g[b][x].w == 0 ||
                ED(g[xs][x]) < ED(g[b][x]))
                g[b][x] = g[xs][x], g[x][b] = g[x][xs];
        for (int x = 1; x <= n; ++x)
            if (flo_from[xs][x]) flo_from[b][x] = xs;
    }
    set_slack(b);
}
void expand_blossom(int b) {
    for (int x : flo[b]) set_st(x, x);
    int xr = flo_from[b][g[b][pa[b]].u], xs = -1;
    for (int x : split_flo(flo[b], xr)) {
        if (xs == -1) {
            xs = x;
            continue;
        }
        pa[xs] = g[x][xs].u;
        S[xs] = 1, S[x] = 0;
        slack[xs] = 0;
        set_slack(x);
        q_push(x);
        xs = -1;
    }
    for (int x : flo[b])
        if (x == xr) S[x] = 1, pa[x] = pa[b];
        else S[x] = -1, set_slack(x);
    st[b] = 0;
}
bool on_found_edge(const edge &e) {
    if (int u = st[e.u], v = st[e.v]; S[v] == -1) {
        int nu = st[match[v]];
        pa[v] = e.u;
        S[v] = 1;
        slack[v] = slack[nu] = 0;
        S[nu] = 0;
        q_push(nu);
    } else if (S[v] == 0) {

```

```

        if (int o = lca(u, v)) add_blossom(u, o, v);
        else return augment(u, v), augment(v, u), true;
    }
    return false;
}
bool matching() {
    fill(all(S), -1), fill(all(slack), 0);
    q = queue<int>();
    for (int x = 1; x <= nx; ++x)
        if (st[x] == x && !match[x])
            pa[x] = 0, S[x] = 0, q.push(x);
    if (q.empty()) return false;
    for (;;) {
        while (q.size()) {
            int u = q.front();
            q.pop();
            if (S[st[u]] == 1) continue;
            for (int v = 1; v <= n; ++v)
                if (g[u][v].w > 0 && st[u] != st[v]) {
                    if (ED(g[u][v]) != 0)
                        update_slack(u, st[v], slack[st[v]]);
                    else if (on_found_edge(g[u][v]))
                        return true;
                }
        }
        int d = INF;
        for (int b = n + 1; b <= nx; ++b)
            if (st[b] == b && S[b] == 1)
                d = min(d, lab[b] / 2);
        for (int x = 1; x <= nx; ++x)
            if (int s = slack[x];
                st[x] == x && s && S[x] <= 0)
                d = min(d, ED(g[s][x]) / (S[x] + 2));
        for (int u = 1; u <= n; ++u)
            if (S[st[u]] == 1) lab[u] += d;
            else if (S[st[u]] == 0) {
                if (lab[u] <= d) return false;
                lab[u] -= d;
            }
        rep(b, n + 1, nx) if (st[b] == b && S[b] >= 0)
            lab[b] += d * (2 - 4 * S[b]);
        for (int x = 1; x <= nx; ++x)
            if (int s = slack[x]; st[x] == x && s &&
                st[s] != x && ED(g[s][x]) == 0)
                if (on_found_edge(g[s][x])) return true;
        for (int b = n + 1; b <= nx; ++b)
            if (st[b] == b && S[b] == 1 && lab[b] == 0)
                expand_blossom(b);
    }
    return false;
}
pair<ll, int> solve() {
    fill(all(match), 0);
    rep(u, 0, n) st[u] = u, flo[u].clear();
    int w_max = 0;
    rep(u, 1, n) rep(v, 1, n) {
        flo_from[u][v] = (u == v ? u : 0);
        w_max = max(w_max, g[u][v].w);
    }
    fill(all(lab), w_max);
    int n_matches = 0;
    ll tot_weight = 0;
    while (matching()) ++n_matches;
    rep(u, 1, n) if (match[u] && match[u] < u)
        tot_weight += g[u][match[u]].w;
    return make_pair(tot_weight, n_matches);
}
void add_edge(int u, int v, int w) {
    g[u][v].w = g[v][u].w = w;
}
};

```

## 2F GlobalMinCut

```

struct StoerWagner { //  $O(V^3)$ , is it  $O(VE + V \log V)$ ?
    int vst[N], edge[N][N], wei[N];

```



```

void init(int n) {
    for (int i = 0; i < n; ++i) fill_n(edge[i], n, 0);
}
void addEdge(int u, int v, int w) {
    edge[u][v] += w;
    edge[v][u] += w;
}
int search(int &s, int &t, int n) {
    fill_n(vst, n, 0), fill_n(wei, n, 0);
    s = t = -1;
    int mx, cur;
    for (int j = 0; j < n; ++j) {
        mx = -1, cur = 0;
        for (int i = 0; i < n; ++i)
            if (wei[i] > mx) cur = i, mx = wei[i];
        vst[cur] = 1, wei[cur] = -1;
        s = t;
        t = cur;
        for (int i = 0; i < n; ++i)
            if (!vst[i]) wei[i] += edge[cur][i];
    }
    return mx;
}
int solve(int n) {
    int res = INF;
    for (int x, y; n > 1; n--) {
        res = min(res, search(x, y, n));
        for (int i = 0; i < n; ++i)
            edge[i][x] = (edge[x][i] += edge[y][i]);
        for (int i = 0; i < n; ++i) {
            edge[y][i] = edge[n - 1][i];
            edge[i][y] = edge[i][n - 1];
        } // edge[y][y] = 0;
    }
    return res;
}
} sw;

```

## 2G BoundedFlow(Dinic)

```

struct BoundedFlow { // 0-base
    struct edge { // note int!
        int to, cap, flow, rev;
    };
    vector<edge> G[N];
    int n, s, t, dis[N], cur[N], cnt[N];
    void init(int _n) {
        n = _n;
        for (int i = 0; i < n + 2; ++i)
            G[i].clear(), cnt[i] = 0;
    }
    void add_edge(int u, int v, int lcap, int rcap) {
        cnt[u] -= lcap, cnt[v] += lcap;
        G[u].emplace_back(
            edge{v, rcap, lcap, (int)G[v].size()});
        G[v].emplace_back(
            edge{u, 0, 0, (int)G[u].size() - 1});
    }
    void add_edge(int u, int v, int cap) {
        G[u].emplace_back(
            edge{v, cap, 0, (int)G[v].size()});
        G[v].emplace_back(
            edge{u, 0, 0, (int)G[u].size() - 1});
    }
    int dfs(int u, int cap) {
        if (u == t || !cap) return cap;
        for (int &i = cur[u]; i < (int)G[u].size(); ++i) {
            edge &e = G[u][i];
            if (dis[e.to] == dis[u] + 1 && e.cap != e.flow) {
                int df = dfs(e.to, min(e.cap - e.flow, cap));
                if (df) {
                    e.flow += df, G[e.to][e.rev].flow -= df;
                    return df;
                }
            }
        }
    }
    dis[u] = -1;
}

```

```

return 0;
}
bool bfs() {
    fill_n(dis, n + 3, -1);
    queue<int> q;
    q.push(s), dis[s] = 0;
    while (!q.empty()) {
        int u = q.front();
        q.pop();
        for (edge &e : G[u])
            if (!dis[e.to] && e.flow != e.cap)
                q.push(e.to), dis[e.to] = dis[u] + 1;
    }
    return dis[t] != -1;
}
int maxflow(int _s, int _t) {
    s = _s, t = _t;
    int flow = 0, df;
    while (bfs()) {
        fill_n(cur, n + 3, 0);
        while ((df = dfs(s, INF))) flow += df;
    }
    return flow;
}
bool solve() {
    int sum = 0;
    for (int i = 0; i < n; ++i)
        if (cnt[i] > 0)
            add_edge(n + 1, i, cnt[i]), sum += cnt[i];
        else if (cnt[i] < 0) add_edge(i, n + 2, -cnt[i]);
    if (sum != maxflow(n + 1, n + 2)) sum = -1;
    for (int i = 0; i < n; ++i)
        if (cnt[i] > 0)
            G[n + 1].pop_back(), G[i].pop_back();
        else if (cnt[i] < 0)
            G[i].pop_back(), G[n + 2].pop_back();
    return sum != -1;
}
int solve(int _s, int _t) {
    add_edge(_t, _s, INF);
    if (!solve()) return -1; // invalid flow
    int x = G[_t].back().flow;
    return G[_t].pop_back(), G[_s].pop_back(), x;
}
};

```

## 2H GomoryHuTree

```

BoundedFlow Dinic;
int g[N];
void add_edge(int u, int v, int w); // TODO
void GomoryHu(int n) { // 0-base
    fill_n(g, n, 0);
    for (int i = 1; i < n; ++i) {
        Dinic.init(n);
        // build the graph
        add_edge(i, g[i], Dinic.maxflow(i, g[i]));
        for (int j = i + 1; j <= n; ++j)
            if (g[j] == g[i] && ~Dinic.dis[j])
                g[j] = i;
    }
}

```

## 2I MinCostCirculation

```

struct MinCostCirculation { // 0-base
    struct Edge {
        ll from, to, cap, fcap, flow, cost, rev;
    } *past[N];
    vector<Edge> G[N];
    ll dis[N], inq[N], n;
    void BellmanFord(int s) {
        fill_n(dis, n, INF), fill_n(inq, n, 0);
        queue<int> q;
        auto relax = [&](int u, ll d, Edge *e) {
            if (dis[u] > d) {
                dis[u] = d, past[u] = e;
            }
        };
    }
}

```

```

    if (!inq[u]) inq[u] = 1, q.push(u);
}
};
relax(s, 0, 0);
while (!q.empty()) {
    int u = q.front();
    q.pop(), inq[u] = 0;
    for (auto &e : G[u])
        if (e.cap > e.flow)
            relax(e.to, dis[u] + e.cost, &e);
}
}
void try_edge(Edge &cur) {
    if (cur.cap > cur.flow) return ++cur.cap, void();
    BellmanFord(cur.to);
    if (dis[cur.from] + cur.cost < 0) {
        ++cur.flow, --G[cur.to][cur.rev].flow;
        for (int
            i = cur.from; past[i]; i = past[i]->from) {
            auto &e = *past[i];
            ++e.flow, --G[e.to][e.rev].flow;
        }
    }
    ++cur.cap;
}
}
void solve(int mxlg) {
    for (int b = mxlg; b >= 0; --b) {
        for (int i = 0; i < n; ++i)
            for (auto &e : G[i])
                e.cap *= 2, e.flow *= 2;
        for (int i = 0; i < n; ++i)
            for (auto &e : G[i])
                if (e.fcap >> b & 1)
                    try_edge(e);
    }
}
void init(int _n) { n = _n;
    for (int i = 0; i < n; ++i) G[i].clear();
}
void add_edge(ll a, ll b, ll cap, ll cost) {
    G[a].emplace_back(Edge{a, b,
        0, cap, 0, cost, (ll)G[b].size() + (a == b)});
    G[b].emplace_back(Edge
        {b, a, 0, 0, 0, -cost, (ll)G[a].size() - 1});
}
} mcmf; // O(VE * ElogC)

```

## 2J FlowModelsBuilding

- Maximum/Minimum flow with lower bound / Circulation problem
  - Construct super source  $S$  and sink  $T$ .
  - For each edge  $(x,y,l,u)$ , connect  $x \rightarrow y$  with capacity  $u-l$ .
  - For each vertex  $v$ , denote by  $in(v)$  the difference between the sum of incoming lower bounds and the sum of outgoing lower bounds.
  - If  $in(v) > 0$ , connect  $S \rightarrow v$  with capacity  $in(v)$ , otherwise, connect  $v \rightarrow T$  with capacity  $-in(v)$ .
    - To maximize, connect  $t \rightarrow s$  with capacity  $\infty$  (skip this in circulation problem), and let  $f$  be the maximum flow from  $S$  to  $T$ . If  $f \neq \sum_{v \in V, in(v) > 0} in(v)$ , there's no solution. Otherwise, the maximum flow from  $s$  to  $t$  is the answer.
    - To minimize, let  $f$  be the maximum flow from  $S$  to  $T$ . Connect  $t \rightarrow s$  with capacity  $\infty$  and let the flow from  $S$  to  $T$  be  $f'$ . If  $f + f' \neq \sum_{v \in V, in(v) > 0} in(v)$ , there's no solution. Otherwise,  $f'$  is the answer.
  - The solution of each edge  $e$  is  $l_e + f_e$ , where  $f_e$  corresponds to the flow of edge  $e$  on the graph.
- Construct minimum vertex cover from maximum matching  $M$  on bipartite graph  $(X,Y)$ 
  - Redirect every edge:  $y \rightarrow x$  if  $(x,y) \in M$ ,  $x \rightarrow y$  otherwise.
  - DFS from unmatched vertices in  $X$ .
  - $x \in X$  is chosen iff  $x$  is unvisited.
  - $y \in Y$  is chosen iff  $y$  is visited.
- Minimum cost cyclic flow
  - Construct super source  $S$  and sink  $T$
  - For each edge  $(x,y,c)$ , connect  $x \rightarrow y$  with  $(cost, cap) = (c, 1)$  if  $c > 0$ , otherwise connect  $y \rightarrow x$  with  $(cost, cap) = (-c, 1)$

- For each edge with  $c < 0$ , sum these cost as  $K$ , then increase  $d(y)$  by 1, decrease  $d(x)$  by 1
- For each vertex  $v$  with  $d(v) > 0$ , connect  $S \rightarrow v$  with  $(cost, cap) = (0, d(v))$
- For each vertex  $v$  with  $d(v) < 0$ , connect  $v \rightarrow T$  with  $(cost, cap) = (0, -d(v))$
- Flow from  $S$  to  $T$ , the answer is the cost of the flow  $C + K$

### • Maximum density induced subgraph

- Binary search on answer, suppose we're checking answer  $T$
- Construct a max flow model, let  $K$  be the sum of all weights
- Connect source  $s \rightarrow v$ ,  $v \in G$  with capacity  $K$
- For each edge  $(u,v,w)$  in  $G$ , connect  $u \rightarrow v$  and  $v \rightarrow u$  with capacity  $w$
- For  $v \in G$ , connect it with sink  $v \rightarrow t$  with capacity  $K + 2T - (\sum_{e \in E(v)} w(e)) - 2w(v)$
- $T$  is a valid answer if the maximum flow  $f < K|V|$

### • Minimum weight edge cover

- For each  $v \in V$  create a copy  $v'$ , and connect  $u' \rightarrow v'$  with weight  $w(u,v)$ .
- Connect  $v \rightarrow v'$  with weight  $2\mu(v)$ , where  $\mu(v)$  is the cost of the cheapest edge incident to  $v$ .
- Find the minimum weight perfect matching on  $G'$ .

### • Project selection problem

- If  $p_v > 0$ , create edge  $(s,v)$  with capacity  $p_v$ ; otherwise, create edge  $(v,t)$  with capacity  $-p_v$ .
- Create edge  $(u,v)$  with capacity  $w$  with  $w$  being the cost of choosing  $u$  without choosing  $v$ .
- The mincut is equivalent to the maximum profit of a subset of projects.

### • Dual of minimum cost maximum flow

- Capacity  $c_{uv}$ , Flow  $f_{uv}$ , Cost  $w_{uv}$ , Required Flow difference for vertex  $b_u$ .
- If all  $w_{uv}$  are integers, then optimal solution can happen when all  $p_u$  are integers.

$$\begin{aligned}
 \min \sum_{uv} w_{uv} f_{uv} & \quad \min \sum_u b_u p_u + \sum_{uv} c_{uv} \max(0, p_v - p_u - w_{uv}) \\
 -f_{uv} & \geq -c_{uv} \Leftrightarrow & p_u \geq 0 \\
 \sum_v f_{vu} - \sum_v f_{uv} & = -b_u
 \end{aligned}$$

## 3 Data Struture

### 3A LichaoTree

```

struct lichao { // maxn: range
    struct line {
        ll a, b;
        line() : a(0), b(0) {} // or b(LINF) if min
        line(ll a, ll b) : a(a), b(b) {}
        ll operator()(ll x) { return a * x + b; }
        // v[x] if after discretization
    } arr[maxn << 2];
    void insert(int l, int r, int id, line x) {
        int m = (l + r) >> 1;
        if (arr[id](m) < x(m)) swap(arr[id], x);
        if (l == r - 1) return;
        if (arr[id].a < x.a) insert(m, r, id << 1 | 1, x);
        else insert(l, m, id << 1, x);
    } // change to > if query min
    // maxn -> v.size() after li san hua
    void insert(ll a, ll b) {
        insert(0, maxn, 1, line(a, b));
    }
    ll que(int l, int r, int id, int p) {
        if (l == r - 1) return arr[id](p);
        int m = (l + r) >> 1;
        if (p < m)
            return max(arr[id](p), que(l, m, id << 1, p));
        return max(arr[id](p), que(m, r, id << 1 | 1, p));
    } // chnage to min if query min
    // maxn -> v.size() after li san hua
    ll que(int p) { return que(0, maxn, 1, p); }
} tree;

```

### 3B Treap

```
mt19937 rd(1);
#define sz(t) ((t) == 0 ? 0 : (t)->size)
struct Treap {
    int pri, size;
    Treap *l, *r;
    Treap(ll val = 0)
        : pri(rd()), size(1), l(0), r(0) {};
    void push();
    void pull() { size = 1 + sz(l) + sz(r); }
};
void spilt(int k, Treap *rt, Treap *&a, Treap *&b) {
    if (!rt) return a = b = 0, void();
    rt->push();
    int lsz = 1 + sz(rt->l);
    if (k >= lsz)
        a = rt, spilt(k - lsz, a->r, a->r, b), a->pull();
    else b = rt, spilt(k, b->l, a, b->l), b->pull();
}
Treap *merge(Treap *l, Treap *r) {
    if (!l) return r;
    if (!r) return l;
    if (l->pri < r->pri) {
        l->push(), l->r = merge(l->r, r), l->pull();
        return l;
    } else {
        r->push(), r->l = merge(l, r->l), r->pull();
        return r;
    }
}
```

### 3C LinkCutTree

```
#define ls(x) Tree[x].son[0]
#define rs(x) Tree[x].son[1]
#define fa(x) Tree[x].fa
struct node {
    int son[2], Min, id, fa, lazy;
} Tree[N];
int n, m, q, w[N], Min;
struct Node {
    int u, v, w;
} a[N];
inline bool IsRoot(int x) {
    return (ls(fa(x)) == x || rs(fa(x)) == x) ? false : true;
}
inline void PushUp(int x) {
    Tree[x].Min = w[x], Tree[x].id = x;
    if (ls(x) && Tree[ls(x)].Min < Tree[x].Min) {
        Tree[x].Min = Tree[ls(x)].Min;
        Tree[x].id = Tree[ls(x)].id;
    }
    if (rs(x) && Tree[rs(x)].Min < Tree[x].Min) {
        Tree[x].Min = Tree[rs(x)].Min;
        Tree[x].id = Tree[rs(x)].id;
    }
}
inline void Update(int x) {
    Tree[x].lazy ^= 1;
    swap(ls(x), rs(x));
}
inline void PushDown(int x) {
    if (!Tree[x].lazy) return;
    if (ls(x)) Update(ls(x));
    if (rs(x)) Update(rs(x));
    Tree[x].lazy = 0;
}
inline void Rotate(int x) {
    int y = fa(x), z = fa(y), k = rs(y) == x,
        w = Tree[x].son[!k];
    if (!IsRoot(y)) Tree[z].son[rs(z) == y] = x;
    fa(x) = z, fa(y) = x;
    if (w) fa(w) = y;
    Tree[x].son[!k] = y, Tree[y].son[k] = w;
    PushUp(y);
}
```

```
}
inline void Splay(int x) {
    stack<int> Stack;
    int y = x, z;
    Stack.push(y);
    while (!IsRoot(y)) Stack.push(y = fa(y));
    while (!Stack.empty())
        PushDown(Stack.top()), Stack.pop();
    while (!IsRoot(x)) {
        y = fa(x), z = fa(y);
        if (!IsRoot(y))
            Rotate((ls(y) == x) ^ (ls(z) == y) ? x : y);
        Rotate(x);
    }
    PushUp(x);
}
inline void Access(int root) {
    for (int x = 0; root; x = root, root = fa(root))
        Splay(root), rs(root) = x, PushUp(root);
}
inline void MakeRoot(int x) {
    Access(x), Splay(x), Update(x);
}
inline int FindRoot(int x) {
    Access(x), Splay(x);
    while (ls(x)) x = ls(x);
    return Splay(x), x;
}
inline void Link(int u, int v) {
    MakeRoot(u);
    if (FindRoot(v) != u) fa(u) = v;
}
inline void Cut(int u, int v) {
    MakeRoot(u);
    if (FindRoot(v) != u || fa(v) != u || ls(v)) return;
    fa(v) = rs(u) = 0;
}
inline void Split(int u, int v) {
    MakeRoot(u), Access(v), Splay(v);
}
inline bool Check(int u, int v) {
    return MakeRoot(u), FindRoot(v) == u;
}
inline int LCA(int root, int u, int v) {
    MakeRoot(root), Access(u), Access(v), Splay(u);
    if (!fa(u)) {
        Access(u), Splay(v);
        return fa(v);
    }
    return fa(u);
}
/* ETT
每次進入節點和走邊都放入一次共 3n - 2
node(u) 表示進入節點 u 放入 treap 的位置
edge(u, v) 表示 u -> v 的邊放入 treap 的位置 (push v)
Makeroor u :
    L1 = [begin, node(u) - 1], L2 = [node(u), end]
    -> L2 + L1
Insert u, v :
    Tu -> L1 = [begin, node(u) - 1], L2 = [node(u), end]
    Tv -> L3 = [begin, node(v) - 1], L4 = [node(v), end]
    -> L2 + L1 + edge(u, v) + L4 + L3 + edge(v, u)
Delete u, v :
    maybe need swap u, v
    T -> L1 + edge(u, v) + L2 + edge(v, u) + L3
    -> L1 + L3, L2
*/
```

### 3D CentroidDecomposition

```
struct Cent_Dec { // 1-base
    vector<pll> G[N];
    pll info[N]; // store info. of itself
    pll upinfo[N]; // store info. of climbing up
    int n, pa[N], layer[N], sz[N], done[N];
};
```

```

ll dis[__lg(N) + 1][N];
void init(int _n) {
    n = _n, layer[0] = -1;
    fill_n(pa + 1, n, 0), fill_n(done + 1, n, 0);
    for (int i = 1; i <= n; ++i) G[i].clear();
}
void add_edge(int a, int b, int w) {
    G[a].pb(pll(b, w)), G[b].pb(pll(a, w));
}
void get_cent(
    int u, int f, int &mx, int &c, int num) {
    int mxsz = 0;
    sz[u] = 1;
    for (pll e : G[u])
        if (!done[e.X] && e.X != f) {
            get_cent(e.X, u, mx, c, num);
            sz[u] += sz[e.X], mxsz = max(mxsz, sz[e.X]);
        }
    if (mx > max(mxsz, num - sz[u]))
        mx = max(mxsz, num - sz[u]), c = u;
}
void dfs(int u, int f, ll d, int org) {
    // if required, add self info or climbing info
    dis[layer[org]][u] = d;
    for (pll e : G[u])
        if (!done[e.X] && e.X != f)
            dfs(e.X, u, d + e.Y, org);
}
int cut(int u, int f, int num) {
    int mx = 1e9, c = 0, lc;
    get_cent(u, f, mx, c, num);
    done[c] = 1, pa[c] = f, layer[c] = layer[f] + 1;
    for (pll e : G[c])
        if (!done[e.X]) {
            if (sz[e.X] > sz[c])
                lc = cut(e.X, c, num - sz[c]);
            else lc = cut(e.X, c, sz[e.X]);
            upinfo[lc] = pll(), dfs(e.X, c, e.Y, c);
        }
    return done[c] = 0, c;
}
void build() { cut(1, 0, n); }
void modify(int u) {
    for (int a = u, ly = layer[a]; a;
        a = pa[a], --ly) {
        info[a].X += dis[ly][u], ++info[a].Y;
        if (pa[a])
            upinfo[a].X += dis[ly - 1][u], ++upinfo[a].Y;
    }
}
ll query(int u) {
    ll rt = 0;
    for (int a = u, ly = layer[a]; a;
        a = pa[a], --ly) {
        rt += info[a].X + info[a].Y * dis[ly][u];
        if (pa[a])
            rt -=
                upinfo[a].X + upinfo[a].Y * dis[ly - 1][u];
    }
    return rt;
}
};

```

### 3E HeavyLightDecomposition

```

struct Heavy_Light_Decomposition { // 1-base
    int n, ulink[N], deep[N], mxson[N], w[N], pa[N];
    int t, pl[N], data[N], dt[N], bln[N], edge[N], et;
    vector<pii> G[N];
    void init(int _n) {
        n = _n, t = 0, et = 1;
        for (int i = 1; i <= n; ++i)
            G[i].clear(), mxson[i] = 0;
    }
    void add_edge(int a, int b, int w) {
        G[a].pb(pii(b, et));
        G[b].pb(pii(a, et));
        edge[et++] = w;
    }
    void dfs(int u, int f, int d) {
        w[u] = 1, pa[u] = f, deep[u] = d++;
        for (auto &i : G[u])
            if (i.X != f) {
                dfs(i.X, u, d), w[u] += w[i.X];
                if (w[mxson[u]] < w[i.X]) mxson[u] = i.X;
            } else bln[i.Y] = u, dt[u] = edge[i.Y];
    }
    void cut(int u, int link) {
        data[pl[u] = t++] = dt[u], ulink[u] = link;
        if (!mxson[u]) return;
        cut(mxson[u], link);
        for (auto i : G[u])
            if (i.X != pa[u] && i.X != mxson[u])
                cut(i.X, i.X);
    }
    void build() { dfs(1, 1, 1), cut(1, 1), /*build*/; }
    int query(int a, int b) {
        int ta = ulink[a], tb = ulink[b], re = 0;
        while (ta != tb)
            if (deep[ta] < deep[tb])
                /*query*/, tb = ulink[tb = pa[tb]];
            else /*query*/, ta = ulink[ta = pa[ta]];
        if (a == b) return re;
        if (pl[a] > pl[b]) swap(a, b);
        /*query*/
        return re;
    }
};

```

```

G[b].pb(pii(a, et));
edge[et++] = w;
}
void dfs(int u, int f, int d) {
    w[u] = 1, pa[u] = f, deep[u] = d++;
    for (auto &i : G[u])
        if (i.X != f) {
            dfs(i.X, u, d), w[u] += w[i.X];
            if (w[mxson[u]] < w[i.X]) mxson[u] = i.X;
            } else bln[i.Y] = u, dt[u] = edge[i.Y];
    }
    void cut(int u, int link) {
        data[pl[u] = t++] = dt[u], ulink[u] = link;
        if (!mxson[u]) return;
        cut(mxson[u], link);
        for (auto i : G[u])
            if (i.X != pa[u] && i.X != mxson[u])
                cut(i.X, i.X);
    }
    void build() { dfs(1, 1, 1), cut(1, 1), /*build*/; }
    int query(int a, int b) {
        int ta = ulink[a], tb = ulink[b], re = 0;
        while (ta != tb)
            if (deep[ta] < deep[tb])
                /*query*/, tb = ulink[tb = pa[tb]];
            else /*query*/, ta = ulink[ta = pa[ta]];
        if (a == b) return re;
        if (pl[a] > pl[b]) swap(a, b);
        /*query*/
        return re;
    }
};

```

## 4 String

### 4A KMP

```

int KMP(string s, string t) {
    t = " "s + t; // consistency with Aca
    int ans = 0;
    vector<int> f(t.size(), 0);
    f[0] = -1;
    for (int i = 1, j = -1; i < (int)t.size(); i++) {
        while (j >= 0 && t[j + 1] != t[i]) j = f[j];
        f[i] = ++j;
    }
    for (int i = 0, j = 0; i < (int)s.size(); i++) {
        while (j >= 0 && t[j + 1] != s[i]) j = f[j];
        if (++j + 1 == (int)t.size()) ans++, j = f[j];
    }
    return ans;
}

```

### 4B Z

```

int Z[N];
void z(string s) {
    for (int i = 1, mx = 0; i < (int)s.size(); i++) {
        if (i < Z[mx] + mx)
            Z[i] = min(Z[mx] - i + mx, Z[i - mx]);
        while (
            Z[i] +
                i < (int)s.size() && s[i + Z[i]] == s[Z[i]])
            Z[i]++;
        if (Z[i] + i > Z[mx] + mx) mx = i;
    }
}

```

### 4C Manacher

```

int man[N]; // len: man[i] - 1
void manacher(string s) { // uses 2/s+1
    string t;
    for (int i = 0; i < (int)s.size(); i++) {
        t.push_back('$');
        t.push_back(s[i]);
    }
}

```

```

t.push_back('$');
int mx = 1;
for (int i = 0; i < (int)t.size(); i++) {
    man[i] = 1;
    man[i] = min(man[mx] + mx - i, man[2 * mx - i]);
    while (man[i] + i < (int)t.size() && i >= man[i] &&
           t[i + man[i]] == t[i - man[i]])
        man[i]++;
    if (i + man[i] > mx + man[mx]) mx = i;
}
}

```

#### 4D SuffixArray

```

struct SuffixArray {
#define add(x, k) (x + k + n) % n
    vector<int> sa, cnt, rk, tmp, lcp;
    // sa: order, rk[i]: pos of s[i..],
    // lcp[i]: LCP of sa[i], sa[i-1]
    void SA(string s) { // remember to append '\1'
        int n = (int)s.size();
        sa.resize(n), cnt.resize(n);
        rk.resize(n), tmp.resize(n);
        iota(all(sa), 0);
        sort(all(sa),
             [&](int i, int j) { return s[i] < s[j]; });
        rk[0] = 0;
        for (int i = 1; i < n; i++)
            rk[sa[i]] =
                rk[sa[i - 1]] + (s[sa[i - 1]] != s[sa[i]]);
        for (int k = 1; k <= n; k <= 1) {
            fill(all(cnt), 0);
            for (int i = 0; i < n; i++)
                cnt[rk[add(sa[i], -k)]]++;
            for (int i = 1; i < n; i++) cnt[i] += cnt[i - 1];
            for (int i = n - 1; i >= 0; i--)
                tmp[--cnt[rk[add(sa[i], -k)]]] =
                    add(sa[i], -k);
            sa.swap(tmp);
            tmp[sa[0]] = 0;
            for (int i = 1; i < n; i++)
                tmp[sa[i]] = tmp[sa[i - 1]] +
                    (rk[sa[i - 1]] != rk[sa[i]] ||
                     rk[add(sa[i - 1], k)] !=
                     rk[add(sa[i], k)]);
            rk.swap(tmp);
        }
    }
    void LCP(string s) {
        int n = (int)s.size(), k = 0;
        lcp.resize(n);
        for (int i = 0; i < n; i++)
            if (rk[i] == 0) lcp[rk[i]] = 0;
            else {
                if (k) k--;
                int j = sa[rk[i] - 1];
                while (
                    max(i, j) + k < n && s[i + k] == s[j + k])
                    k++;
                lcp[rk[i]] = k;
            }
    }
};

```

#### 4E SAIS

```

auto sais(const auto &s) {
    const int n = (int)s.size(), z = ranges::max(s) + 1;
    if (n == 1) return vector{0};
    vector<int> c(z);
    for (int x : s) ++c[x];
    partial_sum(all(c), begin(c));
    vector<int> sa(n);
    auto I = views::iota(0, n);
    vector<bool> t(n, true);
    for (int i = n - 2; i >= 0; --i)

```

```

        t[i] =
            (s[i] == s[i + 1] ? t[i + 1] : s[i] < s[i + 1]);
    auto is_lms = views::filter(
        [&t](int x) { return x && t[x] && !t[x - 1]; });
    auto induce = [&] {
        for (auto x = c; int y : sa)
            if (y-- > 0)
                if (!t[y]) sa[x[s[y] - 1]++] = y;
        for (auto x = c; int y : sa | views::reverse)
            if (y-- > 0)
                if (t[y]) sa[--x[s[y]]] = y;
    };
    vector<int> lms, q(n);
    lms.reserve(n);
    for (auto x = c; int i : I | is_lms)
        q[i] = (int)lms.size(),
        lms.emplace_back(sa[--x[s[i]]] = i);
    induce();
    vector<int> ns((int)lms.size());
    for (int j = -1, nz = 0; int i : sa | is_lms) {
        if (j >= 0) {
            int len = min({n - i, n - j, lms[q[i] + 1] - i});
            ns[q[i]] = nz += lexicographical_compare(
                begin(s) + j, begin(s) + j + len, begin(s) + i,
                begin(s) + i + len);
        }
        j = i;
    }
    fill(all(sa), 0);
    auto nsa = sais(ns);
    for (auto x = c; int y : nsa | views::reverse)
        y = lms[y], sa[--x[s[y]]] = y;
    return induce(), sa;
}
// sa[i]: sa[i]-th suffix is the i-th lexicographically
// smallest suffix. hi[i]: LCP of suffix sa[i] and
// suffix sa[i - 1].
struct Suffix {
    int n;
    vector<int> sa, hi, ra;
    Suffix(const auto &s, int _n)
        : n(_n), hi(n), ra(n) {
        vector<int> s(n + 1); // s[n] = 0;
        copy_n(s, n, begin(s)); // _s shouldn't contain 0
        sa = sais(s);
        sa.erase(sa.begin());
        for (int i = 0; i < n; ++i) ra[sa[i]] = i;
        for (int i = 0, h = 0; i < n; ++i) {
            if (!ra[i]) {
                h = 0;
                continue;
            }
            for (int j = sa[ra[i] - 1];
                 max(i, j) + h < n && s[i + h] == s[j + h];)
                ++h;
            hi[ra[i]] = h ? h-- : 0;
        }
    }
};

```

#### 4F ACAutomaton

```

#define sigma 26
#define base 'a'
struct AhoCorasick { // N: sum of length
    int ch[N][sigma] = {{}}, f[N] = {-1}, tag[N],
        mv[N][sigma], jump[N], cnt[N];
    int idx = 0, t = -1;
    vector<int> E[N], q;
    pii o[N];
    int insert(string &s) {
        int j = 0;
        for (int i = 0; i < (int)s.size(); i++) {
            if (!ch[j][s[i] - base])
                ch[j][s[i] - base] = ++idx;
            j = ch[j][s[i] - base];
        }
    }
}

```

```

    tag[j] = 1;
    return j;
}
int next(int u, int c) {
    return u < 0 ? 0 : mv[u][c];
}
void dfs(int u) {
    o[u].F = ++t;
    for (auto v : E[u]) dfs(v);
    o[u].S = t;
}
void build() {
    int k = -1;
    q.emplace_back(0);
    while (++k < (int)q.size()) {
        int u = q[k];
        for (int v = 0; v < sigma; v++) {
            if (ch[u][v]) {
                f[ch[u][v]] = next(f[u], v);
                q.emplace_back(ch[u][v]);
            }
            mv[u][v] =
                (ch[u][v] ? ch[u][v] : next(f[u], v));
        }
        if (u) jump[u] = (tag[f[u]] ? f[u] : jump[f[u]]);
    }
    reverse(q.begin(), q.end());
    for (int i = 1; i <= idx; i++)
        E[f[i]].emplace_back(i);
    dfs(0);
}
void match(string &s) {
    fill(cnt, cnt + idx + 1, 0);
    for (int i = 0, j = 0; i < (int)s.size(); i++)
        cnt[j = next(j, s[i] - base)]++;
    for (int i : q)
        if (f[i] > 0) cnt[f[i]] += cnt[i];
}
} ac;

```

## 4G MinRotation

```

int mincyc(string s) {
    int n = (int)s.size();
    s = s + s;
    int i = 0, ans = 0;
    while (i < n) {
        ans = i;
        int j = i + 1, k = i;
        while (j < 2 * n && s[j] >= s[k]) {
            k = (s[j] > s[k] ? i : k + 1);
            ++j;
        }
        while (i <= k) i += j - k;
    }
    return ans;
}

```

## 4H ExtSAM

```

#define CNUM 26
struct exSAM {
    int len[N * 2], link[N * 2]; // maxlength, suflink
    int next[N * 2][CNUM], tot; // [0, tot), root = 0
    int lenSorted[N * 2]; // topo. order
    int cnt[N * 2]; // occurence
    int newnode() {
        fill_n(next[tot], CNUM, 0);
        len[tot] = cnt[tot] = link[tot] = 0;
        return tot++;
    }
    void init() { tot = 0, newnode(), link[0] = -1; }
    int insertSAM(int last, int c) {
        int cur = next[last][c];
        len[cur] = len[last] + 1;
        int p = link[last];
        while (p != -1 && !next[p][c])

```

```

            next[p][c] = cur, p = link[p];
        if (p == -1) return link[cur] = 0, cur;
        int q = next[p][c];
        if (len
            [p] + 1 == len[q]) return link[cur] = q, cur;
        int clone = newnode();
        for (int i = 0; i < CNUM; ++i)
            next[
                clone][i] = len[next[q][i]] ? next[q][i] : 0;
        len[clone] = len[p] + 1;
        while (p != -1 && next[p][c] == q)
            next[p][c] = clone, p = link[p];
        link[link[cur] = clone] = link[q];
        link[q] = clone;
        return cur;
    }
    void insert(const string &s) {
        int cur = 0;
        for (auto ch : s) {
            int &nxt = next[cur][(int)(ch - 'a')];
            if (!nxt) nxt = newnode();
            cnt[cur = nxt] += 1;
        }
    }
    void build() {
        queue<int> q;
        q.push(0);
        while (!q.empty()) {
            int cur = q.front();
            q.pop();
            for (int i = 0; i < CNUM; ++i)
                if (next[cur][i])
                    q.push(insertSAM(cur, i));
        }
        vector<int> lc(tot);
        for (int i = 1; i < tot; ++i) ++lc[len[i]];
        partial_sum(all(lc), lc.begin());
        for (int i
            = 1; i < tot; ++i) lenSorted[--lc[len[i]]] = i;
    }
    void solve() {
        for (int i = tot - 2; i >= 0; --i)
            cnt[link[lenSorted[i]]] += cnt[lenSorted[i]];
    }
};

```

## 4I PalindromeTree

```

struct PalindromicTree {
    struct node {
        int next[26], fail, len;
        int cnt, num; // cnt: appear times, num: number of
                        // pal. suf.
        node(int l = 0) : fail(0), len(l), cnt(0), num(0) {
            for (int i = 0; i < 26; ++i) next[i] = 0;
        }
    };
    vector<node> St;
    vector<char> s;
    int last, n;
    PalindromicTree() : St(2), last(1), n(0) {
        St[0].fail = 1, St[1].len = -1, s.emplace_back(-1);
    }
    inline void clear() {
        St.clear(), s.clear(), last = 1, n = 0;
        St.emplace_back(0), St.emplace_back(-1);
        St[0].fail = 1, s.emplace_back(-1);
    }
    inline int get_fail(int x) {
        while (s[n - St[x].len - 1] != s[n])
            x = St[x].fail;
        return x;
    }
    inline void add(int c) {
        s.push_back(c -= 'a'), ++n;
        int cur = get_fail(last);

```



```

if (!St[cur].next[c]) {
    int now = (int)St.size();
    St.emplace_back(St[cur].len + 2);
    St[now].fail =
        St[get_fail(St[cur].fail)].next[c];
    St[cur].next[c] = now;
    St[now].num = St[St[now].fail].num + 1;
}
last = St[cur].next[c], ++St[last].cnt;
}
inline void count() { // counting cnt
    auto i = St.rbegin();
    for (; i != St.rend(); ++i) {
        St[i->fail].cnt += i->cnt;
    }
}
inline int size() { // The number of diff. pal.
    return (int)St.size() - 2;
}
};

```

## 5 Number Theory

### 5A Primes

```

12721 13331 14341 75577 123457 222557 556679 999983
1097774749 1076767633 100102021 999997771 1001010013
1000512343 987654361 999991231 999888733 98789101
987777733 999991921 1010101333 1010102101 1000000000039
100000000000037 2305843009213693951 4611686018427387847
9223372036854775783 18446744073709551557

```

### 5B ExtGCD

```

// beware of negative numbers!
void extgcd(ll a, ll b, ll c, ll &x, ll &y) {
    if (b == 0) x = c / a, y = 0;
    else {
        extgcd(b, a % b, c, y, x);
        y -= x * (a / b);
    }
} // |x| <= b/2, |y| <= a/2

```

### 5C FloorCeil

```

int floor(int a, int b)
{ return a / b - (a % b && (a < 0) ^ (b < 0)); }
int ceil(int a, int b)
{ return a / b + (a % b && (a < 0) ^ (b > 0)); }

```

### 5D FloorSum

Computes

$$f(a,b,c,n) = \sum_{i=0}^n \left\lfloor \frac{a \cdot i + b}{m} \right\rfloor$$

Furthermore, Let  $m = \left\lfloor \frac{an+b}{c} \right\rfloor$ :

$$g(a,b,c,n) = \sum_{i=0}^n i \left\lfloor \frac{ai+b}{c} \right\rfloor$$

$$= \begin{cases} \left\lfloor \frac{a}{c} \right\rfloor \cdot \frac{n(n+1)(2n+1)}{6} + \left\lfloor \frac{b}{c} \right\rfloor \cdot \frac{n(n+1)}{2} \\ + g(a \bmod c, b \bmod c, n), & a \geq c \vee b \geq c \\ 0, & n < 0 \vee a = 0 \\ \frac{1}{2} \cdot (n(n+1)m - f(c, c-b-1, a, m-1)) \\ - h(c, c-b-1, a, m-1), & \text{otherwise} \end{cases}$$

$$h(a,b,c,n) = \sum_{i=0}^n \left\lfloor \frac{ai+b}{c} \right\rfloor^2$$

$$= \begin{cases} \left\lfloor \frac{a}{c} \right\rfloor^2 \cdot \frac{n(n+1)(2n+1)}{6} + \left\lfloor \frac{b}{c} \right\rfloor^2 \cdot (n+1) \\ + \left\lfloor \frac{a}{c} \right\rfloor \cdot \left\lfloor \frac{b}{c} \right\rfloor \cdot n(n+1) \\ + h(a \bmod c, b \bmod c, n) \\ + 2 \left\lfloor \frac{a}{c} \right\rfloor \cdot g(a \bmod c, b \bmod c, n) \\ + 2 \left\lfloor \frac{b}{c} \right\rfloor \cdot f(a \bmod c, b \bmod c, n), & a \geq c \vee b \geq c \\ 0, & n < 0 \vee a = 0 \\ nm(m+1) - 2g(c, c-b-1, a, m-1) \\ - 2f(c, c-b-1, a, m-1) - f(a, b, c, n), & \text{otherwise} \end{cases}$$

```

ll floorsum(ll A, ll B, ll C, ll N) {
    if (A == 0) return (N + 1) * (B / C);
    if (A > C || B > C)
        return (N + 1) * (B / C) +
            N * (N + 1) / 2 * (A / C) +
            floorsum(A % C, B % C, C, N);
    ll M = (A * N + B) / C;
    return N * M - floorsum(C, C - B - 1, A, M - 1);
}

```

### 5E MillerRabin

```

// n < 4,759,123,141      3 : 2, 7, 61
// n < 1,122,004,669,633  4 : 2, 13, 23, 1662803
// n < 3,474,749,660,383  6 : primes <= 13
// n < 2^64                7 :
// 2, 325, 9375, 28178, 450775, 9780504, 1795265022
ll mul(ll a, ll b, ll mod) {
    return (ll)(__int128(a) * b % mod);
}
bool Miller_Rabin(ll a, ll n) {
    if ((a = a % n) == 0) return 1;
    if (n % 2 == 0) return n == 2;
    ll tmp = (n - 1) / ((n - 1) & (1 - n));
    ll t = __lg(((n - 1) & (1 - n))), x = 1;
    for (; tmp; tmp >>= 1, a = mul(a, a, n))
        if (tmp & 1) x = mul(x, a, n);
    if (x == 1 || x == n - 1) return 1;
    while (--t)
        if ((x = mul(x, x, n)) == n - 1) return 1;
    return 0;
}

```

### 5F PollardRho

```

map<ll, int> cnt;
void PollardRho(ll n) {
    if (n == 1) return;
    if (prime(n)) return ++cnt[n], void();
    if (n % 2
        == 0) return PollardRho(n / 2), ++cnt[2], void();
    ll x = 2, y = 2, d = 1, p = 1;
    #define f(x, n, p) ((mul(x, x, n) + p) % n)
    while (true) {
        if (d != n && d != 1) {
            PollardRho(n / d);
            PollardRho(d);
            return;
        }
        if (d == n) ++p;
        x = f(x, n, p), y = f(f(y, n, p), n, p);
        d = gcd(abs(x - y), n);
    }
}

```

### 5G Fraction

```

struct fraction {
    ll n, d;
    fraction(const ll &n = 0, const ll &d = 1)
        : n(_n), d(_d) {
        ll t = __gcd(n, d);
        n /= t, d /= t;
        if (d < 0) n = -n, d = -d;
    }
    fraction operator-() const {
        return fraction(-n, d);
    }
    fraction operator+(const fraction &b) const {
        return fraction(n * b.d + b.n * d, d * b.d);
    }
    fraction operator-(const fraction &b) const {
        return fraction(n * b.d - b.n * d, d * b.d);
    }
    fraction operator*(const fraction &b) const {
        return fraction(n * b.n, d * b.d);
    }
}

```

```

fraction operator/(const fraction &b) const {
    return fraction(n * b.d, d * b.n);
}
void print() {
    cout << n;
    if (d != 1) cout << "/" << d;
}
};

```

## 5H ChineseRemainder

```

ll solve(ll x1, ll m1, ll x2, ll m2) {
    ll g = gcd(m1, m2);
    if ((x2 - x1) % g) return -1; // no sol
    m1 /= g; m2 /= g;
    ll x, y;
    extgcd(m1, m2, __gcd(m1, m2), x, y);
    ll lcm = m1 * m2 * g;
    ll res = x * (x2 - x1) * m1 + x1;
    // be careful with overflow
    return (res % lcm + lcm) % lcm;
}

```

## 5I FactorialMod $p^k$

```

//  $O(p^k + \log^2 n)$ ,  $pk = p^k$ 
ll prod[MAXP];
ll fac_no_p(ll n, ll p, ll pk) {
    prod[0] = 1;
    for (int i = 1; i <= pk; ++i)
        if (i % p) prod[i] = prod[i - 1] * i % pk;
        else prod[i] = prod[i - 1];
    ll rt = 1;
    for (; n; n /= p) {
        rt = rt * mpow(prod[pk], n / pk, pk) % pk;
        rt = rt * prod[n % pk] % pk;
    }
    return rt;
} // (n! without factor p) %  $p^k$ 

```

## 5J QuadraticResidue

```

// Berlekamp-Rabin,  $\log^2(p)$ 
ll trial(ll y, ll z, ll m) {
    ll a0 = 1, a1 = 0, b0 = z, b1 = 1, p = (m - 1) / 2;
    while (p) {
        if (p & 1)
            tie(a0, a1) =
                make_pair((a1 * b1 % m * y + a0 * b0) % m,
                    (a0 * b1 + a1 * b0) % m);
            tie(b0, b1) =
                make_pair((b1 * b1 % m * y + b0 * b0) % m,
                    (2 * b0 * b1) % m);
        p >>= 1;
    }
    if (a1) return inv(a1, m);
    return -1;
}
mt19937 rd(49);
ll psqrt(ll y, ll p) {
    if (fpow(y, (p - 1) / 2, p) != 1) return -1;
    for (int i = 0; i < 30; i++) {
        ll z = rd() % p;
        if (z * z % p == y) return z;
        ll x = trial(y, z, p);
        if (x == -1) continue;
        return x;
    }
    return -1;
}

```

## 5K MeisselLehmer

```

ll PrimeCount(ll n) { //  $n \sim 10^{13} \Rightarrow < 2s$ 
    if (n <= 1) return 0;
    int v = sqrt(n), s = (v + 1) / 2, pc = 0;
    vector<int> smalls(v + 1), skip(v + 1), roughs(s);
    vector<ll> larges(s);

```

```

    for (int i = 2; i <= v; ++i) smalls[i] = (i + 1) / 2;
    for (int i = 0; i < s; ++i) {
        roughs[i] = 2 * i + 1;
        larges[i] = (n / (2 * i + 1) + 1) / 2;
    }
    for (int p = 3; p <= v; ++p) {
        if (smalls[p] > smalls[p - 1]) {
            int q = p * p;
            ++pc;
            if (1LL * q * q > n) break;
            skip[p] = 1;
            for (int i = q; i <= v; i += 2 * p) skip[i] = 1;
            int ns = 0;
            for (int k = 0; k < s; ++k) {
                int i = roughs[k];
                if (skip[i]) continue;
                ll d = 1LL * i * p;
                larges[ns] = larges[k] - (d <= v ? larges[smalls[d] - pc] : smalls[n / d]) + pc;
                roughs[ns++] = i;
            }
            s = ns;
            for (int j = v / p; j >= p; --j) {
                int c =
                    smalls[j] - pc, e = min(j * p + p, v + 1);
                for (int i = j * p; i < e; ++i) smalls[i] -= c;
            }
        }
        for (int k = 1; k < s; ++k) {
            const ll m = n / roughs[k];
            ll t = larges[k] - (pc + k - 1);
            for (int l = 1; l < k; ++l) {
                int p = roughs[l];
                if (1LL * p * p > m) break;
                t -= smalls[m / p] - (pc + l - 1);
            }
            larges[0] -= t;
        }
        return larges[0];
    }
}

```

## 5L DiscreteLog

```

int DiscreteLog(int s, int x, int y, int m) {
    constexpr int kStep = 32000;
    unordered_map<int, int> p;
    int b = 1;
    for (int i = 0; i < kStep; ++i) {
        p[y] = i;
        y = 1LL * y * x % m;
        b = 1LL * b * x % m;
    }
    for (int i = 0; i < m + 10; i += kStep) {
        s = 1LL * s * b % m;
        if (p.find(s) != p.end()) return i + kStep - p[s];
    }
    return -1;
}
int DiscreteLog(int x, int y, int m) {
    if (m == 1) return 0;
    int s = 1;
    for (int i = 0; i < 100; ++i) {
        if (s == y) return i;
        s = 1LL * s * x % m;
    }
    if (s == y) return 100;
    int p = 100 + DiscreteLog(s, x, y, m);
    if (fpow(x, p, m) != y) return -1;
    return p;
}

```

## 5M Theorems

### • Cramer's Rule

$$\begin{aligned}
 ax + by &= e & x &= \frac{ed - bf}{ad - bc} \\
 cx + dy &= f & y &= \frac{af - ec}{ad - bc}
 \end{aligned}$$

### Vandermonde's Identity

$$C(n+m, k) = \sum_{i=0}^k C(n, i) C(m, k-i)$$

### Kirchhoff's Theorem

Denote  $L$  be a  $n \times n$  matrix as the Laplacian matrix of graph  $G$ , where  $L_{ii} = d(i)$ ,  $L_{ij} = -c$  where  $c$  is the number of edge  $(i, j)$  in  $G$ .

- The number of undirected spanning in  $G$  is  $|\det(\tilde{L}_{11})|$ .
- The number of directed spanning tree rooted at  $r$  in  $G$  is  $|\det(\tilde{L}_{rr})|$ .

### Tutte's Matrix

Let  $D$  be a  $n \times n$  matrix, where  $d_{ij} = x_{ij}$  ( $x_{ij}$  is chosen uniformly at random) if  $i < j$  and  $(i, j) \in E$ , otherwise  $d_{ij} = -d_{ji}$ .  $\frac{\text{rank}(D)}{2}$  is the maximum matching on  $G$ .

### Cayley's Formula

- Given a degree sequence  $d_1, d_2, \dots, d_n$  for each labeled vertices, there are  $\frac{(n-2)!}{(d_1-1)!(d_2-1)!\dots(d_n-1)!}$  spanning trees.
- Let  $T_{n,k}$  be the number of labeled forests on  $n$  vertices with  $k$  components, such that vertex  $1, 2, \dots, k$  belong to different components. Then  $T_{n,k} = kn^{n-k-1}$ .

### Erdős-Gallai Theorem

A sequence of nonnegative integers  $d_1 \geq \dots \geq d_n$  can be represented as the degree sequence of a finite simple graph on  $n$  vertices if and only if  $d_1 + \dots + d_n$  is even and

$$\sum_{i=1}^k d_i \leq k(k-1) + \sum_{i=k+1}^n \min(d_i, k) \text{ holds for every } 1 \leq k \leq n.$$

### Gale-Ryser Theorem

A pair of sequences of nonnegative integers  $a_1 \geq \dots \geq a_n$  and  $b_1, \dots, b_n$  is bigraphic (degree sequence of bipartite graph) if and only if  $\sum_{i=1}^n a_i = \sum_{i=1}^n b_i$  and  $\sum_{i=1}^k a_i \leq \sum_{i=1}^k \min(b_i, k)$

holds for every  $1 \leq k \leq n$ .

### Fulkerson-Chen-Anstee Theorem

A sequence  $(a_1, b_1), \dots, (a_n, b_n)$  of nonnegative integer pairs with  $a_1 \geq \dots \geq a_n$  is digraphic (in, out degree of a directed graph) if and only if  $\sum_{i=1}^n a_i = \sum_{i=1}^n b_i$  and  $\sum_{i=1}^k a_i \leq$

$$\sum_{i=1}^k \min(b_i, k-1) + \sum_{i=k+1}^n \min(b_i, k) \text{ holds for every } 1 \leq k \leq n.$$

### Möbius Inversion Formula

- $f(n) = \sum_{d|n} g(d) \Leftrightarrow g(n) = \sum_{d|n} \mu(d) f(\frac{n}{d})$
- $f(n) = \sum_{n|d} g(d) \Leftrightarrow g(n) = \sum_{n|d} \mu(\frac{d}{n}) f(d)$

### Lagrange Multiplier

- Optimize  $f(x_1, \dots, x_n)$  when  $k$  constraints  $g_i(x_1, \dots, x_n) = 0$ .
- Lagrangian function  $\mathcal{L}(x_1, \dots, x_n, \lambda_1, \dots, \lambda_k) = f(x_1, \dots, x_n) - \sum_{i=1}^k \lambda_i g_i(x_1, \dots, x_n)$ .
- The solution corresponding to the original constrained optimization is always a saddle point of the Lagrangian function.

## 5N Estimation

### Number of divisors

$n \leq$	100	10 <sup>3</sup>	10 <sup>6</sup>	10 <sup>9</sup>	10 <sup>12</sup>	10 <sup>15</sup>	10 <sup>18</sup>
$\max d(n)$	12	32	240	1344	6720	26880	103680

### Unordered integer partition

$n$	2	3	4	5	6	7	8	9	20	30	40	50	100
$p(n)$	2	3	5	7	11	15	22	30	627	5604	4·10 <sup>4</sup>	2·10 <sup>5</sup>	2·10 <sup>8</sup>

### Ways of partitions of $n$ distinct elements

$n$	2	3	4	5	6	7	8	9	10	11	12	13
$B_n$	2	5	15	52	203	877	4140	21147	115975	7·10 <sup>5</sup>	4·10 <sup>6</sup>	3·10 <sup>7</sup>

## 50 Numbers

### Bernoulli numbers

$$B_0 = 1, B_1^\pm = \pm \frac{1}{2}, B_2 = \frac{1}{6}, B_3 = 0$$

$$\sum_{j=0}^m \binom{m+1}{j} B_j = 0, \text{ EGF is } B(x) = \frac{x}{e^x - 1} = \sum_{n=0}^{\infty} B_n \frac{x^n}{n!}.$$

$$S_m(n) = \sum_{k=1}^n k^m = \frac{1}{m+1} \sum_{k=0}^m \binom{m+1}{k} B_k^+ n^{m+1-k}$$

### Stirling numbers of the second kind Partitions of $n$ distinct elements into exactly $k$ groups.

$$S(n, k) = S(n-1, k-1) + k S(n-1, k), S(n, 1) = S(n, n) = 1$$

$$S(n, k) = \frac{1}{k!} \sum_{i=0}^k (-1)^{k-i} \binom{k}{i} i^n$$

$$x^n = \sum_{i=0}^n S(n, i) (x)_i$$

### Pentagonal number theorem

$$\prod_{n=1}^{\infty} (1 - x^n) = 1 + \sum_{k=1}^{\infty} (-1)^k \left( x^{k(3k+1)/2} + x^{k(3k-1)/2} \right)$$

### Catalan numbers

$$C_n^{(k)} = \frac{1}{(k-1)n+1} \binom{kn}{n}$$

$$C^{(k)}(x) = 1 + x[C^{(k)}(x)]^k$$

### Eulerian numbers

Number of permutations  $\pi \in S_n$  in which exactly  $k$  elements are greater than the previous element.  $k$  j:s s.t.  $\pi(j) > \pi(j+1)$ ,  $k+1$  j:s s.t.  $\pi(j) \geq j$ ,  $k$  j:s s.t.  $\pi(j) > j$ .

$$E(n, k) = (n-k)E(n-1, k-1) + (k+1)E(n-1, k)$$

$$E(n, 0) = E(n, n-1) = 1$$

$$E(n, k) = \sum_{j=0}^k (-1)^j \binom{n+1}{j} (k+1-j)^n$$

## 5P Generating Functions

### Ordinary Generating Function $A(x) = \sum_{i \geq 0} a_i x^i$

- $A(rx) \Rightarrow r^n a_n$
- $A(x) + B(x) \Rightarrow a_n + b_n$
- $A(x)B(x) \Rightarrow \sum_{i=0}^n a_i b_{n-i}$
- $A(x)^k \Rightarrow \sum_{i_1+i_2+\dots+i_k=n} a_{i_1} a_{i_2} \dots a_{i_k}$
- $xA(x)' \Rightarrow na_n$
- $\frac{A(x)}{1-x} \Rightarrow \sum_{i=0}^n a_i$

### Exponential Generating Function $A(x) = \sum_{i \geq 0} \frac{a_i}{i!} x^i$

- $A(x) + B(x) \Rightarrow a_n + b_n$
- $A^{(k)}(x) \Rightarrow a_{n+k}$
- $A(x)B(x) \Rightarrow \sum_{i=0}^n \binom{n}{i} a_i b_{n-i}$
- $A(x)^k \Rightarrow \sum_{i_1+i_2+\dots+i_k=n} \binom{n}{i_1, i_2, \dots, i_k} a_{i_1} a_{i_2} \dots a_{i_k}$
- $xA(x) \Rightarrow na_n$

### Special Generating Function

- $(1+x)^n = \sum_{i \geq 0} \binom{n}{i} x^i$
- $\frac{1}{(1-x)^n} = \sum_{i \geq 0} \binom{n-1}{i} x^i$
- $S_k = \sum_{x=1}^n x^k$ :  $S = \sum_{p=0}^{\infty} x^p = \frac{e^x - e^{x(n+1)}}{1 - e^x}$

## 6 Linear Algebra

### 6A Gaussian Elimination

```
struct matrix { // m variables, n equations
    int n, m;
    fraction A[N][N+1], sol[N];
    int solve() { // -1: inconsistent, >= 0: rank
        for (int i = 0; i < n; ++i) {
            int piv = 0;
            while (piv < m && !A[i][piv].n) ++piv;
            if (piv == m) continue;
            for (int j = 0; j < n; ++j) {
                if (i == j) continue;
                fraction tmp = -A[j][piv] / A[i][piv];
                for (int k = 0; k <= m; ++k)
                    A[j][k] = tmp * A[i][k] + A[j][k];
            }
        }
        int rank = 0;
        for (int i = 0; i < n; ++i) {
            int piv = 0;
            while (piv < m && !A[i][piv].n) ++piv;
            if (piv == m && A[i][m].n) return -1;
            else if (piv < m)
                ++rank, sol[piv] = A[i][m] / A[i][piv];
        }
        return rank;
    }
};
```

### 6B BerlekampMassey

```
template <typename T>
vector<T> BerlekampMassey(const vector<T> &output) {
    vector<T> d(output.size() + 1), me, he;
    for (int f = 0, i = 1; i <= output.size(); ++i) {
        for (int j = 0; j < me.size(); ++j)
            d[i] += output[i - j - 2] * me[j];
        if ((d[i] -= output[i - 1]) == 0) continue;
        if (me.empty()) {
            me.resize(f = i);
            continue;
        }
        vector<T> o(i - f - 1);
        T k = -d[i] / d[f];
        o.emplace_back(-k);
```

```

    for (T x : he) o.emplace_back(x * k);
    o.resize(max(o.size(), me.size()));
    for (int j = 0; j < me.size(); ++j) o[j] += me[j];
    if (i - f + (int)
        )he.size() >= (int)me.size()) he = me, f = i;
    me = o;
}
return me;
}

```

## 6C Simplex

Standard form: maximize  $c^T x$  subject to  $Ax \leq b$  and  $x \geq 0$ .  
 Dual LP: minimize  $b^T y$  subject to  $A^T y \geq c$  and  $y \geq 0$ .  
 $\bar{x}$  and  $\bar{y}$  are optimal if and only if for all  $i \in [1, n]$ , either  $\bar{x}_i = 0$  or  $\sum_{j=1}^m A_{ji} \bar{y}_j = c_i$  holds and for all  $i \in [1, m]$  either  $\bar{y}_i = 0$  or  $\sum_{j=1}^n A_{ij} \bar{x}_j = b_j$  holds.

1. In case of minimization, let  $c'_i = -c_i$
2.  $\sum_{1 \leq i \leq n} A_{ji} x_i \geq b_j \rightarrow \sum_{1 \leq i \leq n} -A_{ji} x_i \leq -b_j$
3.  $\sum_{1 \leq i \leq n} A_{ji} x_i = b_j$ 
  - $\sum_{1 \leq i \leq n} A_{ji} x_i \leq b_j$
  - $\sum_{1 \leq i \leq n} A_{ji} x_i \geq b_j$
4. If  $x_i$  has no lower bound, replace  $x_i$  with  $x_i - x'_i$

```

// n variable, m constraints, M >= n + 2m
struct simplex {
    const double inf = 1 / .0, eps = 1e-9;
    int n, m, k, var[N], inv[N], art[N];
    double A[M][N], B[M], x[N];
    void init(int _n) { n = _n, m = 0; }
    void equation(vector<double> a, double b) {
        for (int i = 0; i < n; i++) A[m][i] = a[i];
        B[m] = b, var[m] = n + m, ++m;
    }
    void pivot(int r, int c, double bx) {
        for (int i = 0; i <= m + 1; i++)
            if (i != r && abs(A[i][c]) > eps) {
                x[var[i]] -= bx * A[i][c] / A[r][c];
                double f = A[i][c] / A[r][c];
                for (int j = 0; j <= n + m + k; j++)
                    A[i][j] -= A[r][j] * f;
                B[i] -= B[r] * f;
            }
    }
    double phase(int p) {
        while (true) {
            int in = (int)(min_element(A[m + p],
                A[m + p] + n + m + k + 1) - A[m + p]);
            if (A[m + p][in] >= -eps) break;
            double bx = inf;
            int piv = -1;
            for (int i = 0; i < m; i++)
                if (A[i][in] > eps && B[i] / A[i][in] <= bx)
                    piv = i, bx = B[i] / A[i][in];
            if (piv == -1) return inf;
            int out = var[piv];
            pivot(piv, in, bx);
            x[out] = 0, x[in] = bx, var[piv] = in;
        }
        return x[n + m];
    }
    double solve(vector<double> c) {
        auto invert = [&](int r) {
            for (int j = 0; j <= n + m; j++) A[r][j] *= -1;
            B[r] *= -1;
        };
        k = 1;
        for (int i = 0; i < n; i++) A[m][i] = -c[i];
        fill(A[m + 1], A[m + 1] + N, 0.0);
        for (int i = 0; i <= m + 1; i++)
            fill(A[i] + n, A[i] + n + m + 2, 0.0),
                var[i] = n + i, A[i][n + i] = 1;
        for (int i = 0; i < m; i++) {
            if (B[i] < 0) {
                ++k;
                for (int j = 0; j <= n + m; j++)

```

```

                A[m + 1][j] += A[i][j];
                invert(i);
                var[i] = n + m + k, A[i][var[i]] = 1,
                    art[var[i]] = n + i;
            }
            x[var[i]] = B[i];
        }

        phase(1);
        if (*max_element(
            x + (n + m + 2), x + (n + m + k + 1)) > eps)
            return .0 / .0;
        for (int i = 0; i <= m; i++)
            if (var[i] > n + m)
                var[i] = art[var[i]], invert(i);
        k = 0;
        return phase(0);
    }
} lp;

```

## 7 Polynomials

### 7A NTT (FFT)

	Mod	g	Form
	65 537	3	$2^{16} + 1$
	998 244 353	3	$119 \cdot 2^{23} + 1$
	1 315 962 881	3	$1255 \cdot 2^{20} + 1$
	1 711 276 033	29	$51 \cdot 2^{25} + 1$
	9 223 372 036 737 335 297	3	$549755813881 \cdot 2^{24} + 1$

```

#define base ll // complex<double>
// const double PI = acos(-1);
const ll mod = 998244353, g = 3;
base omega[4 * N], omega_[4 * N];
int rev[4 * N];

ll fpow(ll b, ll p);

ll inverse(ll a) { return fpow(a, mod - 2); }

void calcW(int n) {
    ll r = fpow(g, (mod - 1) / n), invr = inverse(r);
    omega[0] = omega_[0] = 1;
    for (int i = 1; i < n; i++) {
        omega[i] = omega[i - 1] * r % mod;
        omega_[i] = omega_[i - 1] * invr % mod;
    }
    // double arg = 2.0 * PI / n;
    // for (int i = 0; i < n; i++)
    // {
    //     omega[i] = base(cos(i * arg), sin(i * arg));
    //     omega_[i] = base(cos(-i * arg), sin(-i * arg));
    // }
}

void calcCrev(int n) {
    int k = __lg(n);
    for (int i = 0; i < n; i++) rev[i] = 0;
    for (int i = 0; i < n; i++)
        for (int j = 0; j < k; j++)
            if (i & (1 << j)) rev[i] ^= 1 << (k - j - 1);
}

vector<base> NTT(vector<base> poly, bool inv) {
    base *w = (inv ? omega_ : omega);
    int n = (int)poly.size();
    for (int i = 0; i < n; i++)
        if (rev[i] > i) swap(poly[i], poly[rev[i]]);

    for (int len = 1; len < n; len <= 1) {
        int arg = n / len / 2;
        for (int i = 0; i < n; i += 2 * len)
            for (int j = 0; j < len; j++) {
                base odd =
                    w[j * arg] * poly[i + j + len] % mod;
                poly[i + j + len] =
                    (poly[i + j] - odd + mod) % mod;

```

```

    poly[i + j] = (poly[i + j] + odd) % mod;
}
}
if (inv)
    for (auto &a : poly) a = a * inverse(n) % mod;
return poly;
}

vector<base> mul(vector<base> f, vector<base> g) {
    int sz = 1 << (lg(f.size() + g.size() - 1) + 1);
    f.resize(sz), g.resize(sz);
    calcrev(sz);
    calcW(sz);
    f = NTT(f, 0), g = NTT(g, 0);
    for (int i = 0; i < sz; i++)
        f[i] = f[i] * g[i] % mod;
    return NTT(f, 1);
}

```

## 7B FHWT

```

/* x: a[j], y: a[j + (L >> 1)]
or: (y += x * op), and: (x += y * op)
xor: (x, y = (x + y) * op, (x - y) * op)
op: 1, invop: or, and, xor = -1, -1, 1/2 */
void fwt(int *a, int n, int op) { // or
    for (int L = 2; L <= n; L <= 1)
        for (int i = 0; i < n; i += L)
            for (int j = i; j < i + (L >> 1); ++j)
                a[j + (L >> 1)] += a[j] * op;
}

const int P = 21; // power of max N
int f[P][1 << P], g[P][1 << P], h[P][1 << P],
    ct[1 << P];
void subset_convolution(
    int *a, int *b, int *c, int L) {
    // c_k = sum_{i+j=k, i&j=0} a_i * b_j
    int n = 1 << L;
    for (int i = 1; i < n; ++i)
        ct[i] = ct[i & (i - 1)] + 1;
    for (int i = 0; i < n; ++i)
        f[ct[i]][i] = a[i], g[ct[i]][i] = b[i];
    for (int i = 0; i <= L; ++i)
        fwt(f[i], n, 1), fwt(g[i], n, 1);
    for (int i = 0; i <= L; ++i)
        for (int j = 0; j <= i; ++j)
            for (int x = 0; x < n; ++x)
                h[i][x] += f[j][x] * g[i - j][x];
    for (int i = 0; i <= L; ++i) fwt(h[i], n, -1);
    for (int i = 0; i < n; ++i) c[i] = h[ct[i]][i];
}

```

## 7C PolynomialOperations

```

#define poly vector<ll>
poly inv(poly A) {
    A.resize(1 << (lg(A.size() - 1) + 1));
    poly B = {inverse(A[0])};
    for (int n = 1; n < (int)A.size(); n <= 1) {
        poly pA(A.begin(), A.begin() + 2 * n);
        calcrev(4 * n), calcW(4 * n);
        pA.resize(4 * n), B.resize(4 * n);
        pA = NTT(pA, 0);
        B = NTT(B, 0);
        for (int i = 0; i < 4 * n; i++)
            B[i] =
                ((B[i] * 2 - pA[i] * B[i] % mod * B[i]) % mod +
                 mod) %
                mod;
        B = NTT(B, 1);
        B.resize(2 * n);
    }
    return B;
}

pair<poly, poly> div(poly A, poly B) {
    if (A.size() < B.size()) return make_pair(poly(), A);
    int n = A.size(), m = B.size();

```

```

    poly revA = A, invrevB = B;
    reverse(all(revA)), reverse(all(invrevB));
    revA.resize(n - m + 1);
    invrevB.resize(n - m + 1);
    invrevB = inv(invrevB);
    poly Q = mul(revA, invrevB);
    Q.resize(n - m + 1);
    reverse(all(Q));
    poly R = mul(Q, B);
    R.resize(m - 1);
    for (int i = 0; i < m - 1; i++)
        R[i] = (A[i] - R[i] + mod) % mod;
    return make_pair(Q, R);
}

poly modulo(poly A, poly B) { return div(A, B).S; }
ll fast_kitamasala(ll k, poly A, poly C) {
    int n = A.size();
    C.emplace_back(mod - 1);
    poly Q, R = {0, 1}, F = {1};
    R = modulo(R, C);
    for (; k; k >= 1) {
        if (k & 1) F = modulo(mul(F, R), C);
        R = modulo(mul(R, R), C);
        k >= 1;
    }
    ll ans = 0;
    for (int i = 0; i < F.size(); i++)
        ans = (ans + A[i] * F[i]) % mod;
    return ans;
}

vector<ll> fpow(vector<ll> f, ll p, ll m) {
    int b = 0;
    while (b < f.size() && f[b] == 0) b++;
    f = vector<ll>(f.begin() + b, f.end());
    int n = f.size();
    f.emplace_back(0);
    vector<ll> q(min(m, b * p), 0);
    q.emplace_back(fpow(f[0], p));
    for (int k = 0; q.size() < m; k++) {
        ll res = 0;
        for (int i = 0; i < min(n, k + 1); i++)
            res = (res +
                    p * (i + 1) % mod * f[i + 1] % mod *
                    q[k - i + b * p]) %
                    mod;
        for (int i = 1; i < min(n, k + 1); i++)
            res = (res -
                    f[i] * (k - i + 1) % mod *
                    q[k - i + 1 + b * p]) %
                    mod;
        res = (res < 0 ? res + mod : res) *
            inv(f[0] * (k + 1) % mod) % mod;
        q.emplace_back(res);
    }
    return q;
}

```

## 7D NewtonMethod+MiscGF

Given  $F(x)$  where

$$F(x) = \sum_{i=0}^{\infty} \alpha_i (x - \beta)^i$$

for  $\beta$  being some constant. Polynomial  $P$  such that  $F(P) = 0$  can be found iteratively. Denote by  $Q_k$  the polynomial such that  $F(Q_k) \equiv 0 \pmod{x^{2^k}}$ , then

$$Q_{k+1} = Q_k - \frac{F(Q_k)}{F'(Q_k)} \pmod{x^{2^{k+1}}}$$

- $A^{-1}$ :  $B_{k+1} = B_k(2 - AB_k) \pmod{x^{2^{k+1}}}$
- $\ln A$ :  $(\ln A)' = \frac{A'}{A}$
- $\exp A$ :  $B_{k+1} = B_k(1 + A - \ln B_k) \pmod{x^{2^{k+1}}}$
- $\sqrt{A}$ :  $B_{k+1} = \frac{1}{2}(B_k + AB_k^{-1}) \pmod{x^{2^{k+1}}}$

## 8 Geometry

### 8A Basic

```
typedef pair<pdd, pdd> Line;
struct Cir{ pdd O; double R; };
const double pi = acos(-1);
const double eps = 1e-8;
pll operator+(pll a, pll b)
{ return pll(a.F + b.F, a.S + b.S); }
pll operator-(pll a, pll b)
{ return pll(a.F - b.F, a.S - b.S); }
pll operator*(pll a)
{ return pll(-a.F, -a.S); }
pll operator*(pll a, ll b)
{ return pll(a.F * b, a.S * b); }
pdd operator/(pll a, double b)
{ return pdd(a.F / b, a.S / b); }
ll dot(pll a, pll b)
{ return a.F * b.F + a.S * b.S; }
ll cross(pll a, pll b)
{ return a.F * b.S - a.S * b.F; }
ll abs2(pll a)
{ return dot(a, a); }
double abs(pll a)
{ return sqrt(dot(a, a)); }
int sign(ll a)
{ return fabs(a) < eps ? 0 : a > 0 ? 1 : -1; }
int ori(pll a, pll b, pll c)
{ return sign(cross(b - a, c - a)); }
bool collinearity(pll p1, pll p2, pll p3)
{ return sign(cross(p1 - p3, p2 - p3)) == 0; }
bool btw(pll a, pll b, pll c) {
    return collinearity
        (a, b, c) && sign(dot(a - c, b - c)) <= 0;
}
bool seg_strict_intersect
    (pdd p1, pdd p2, pdd p3, pdd p4) {
    int a123 = ori(p1, p2, p3);
    int a124 = ori(p1, p2, p4);
    int a341 = ori(p3, p4, p1);
    int a342 = ori(p3, p4, p2);
    return a123 * a124 < 0 && a341 * a342 < 0;
}
bool seg_intersect(pdd p1, pdd p2, pdd p3, pdd p4) {
    int a123 = ori(p1, p2, p3);
    int a124 = ori(p1, p2, p4);
    int a341 = ori(p3, p4, p1);
    int a342 = ori(p3, p4, p2);
    if (a123 == 0 && a124 == 0)
        return btw(p1, p2, p3) || btw(p1, p2, p4) ||
            btw(p3, p4, p1) || btw(p3, p4, p2);
    return a123 * a124 <= 0 && a341 * a342 <= 0;
}
pdd intersect(pdd p1, pdd p2, pdd p3, pdd p4) {
    double a123 = cross(p2 - p1, p3 - p1);
    double a124 = cross(p2 - p1, p4 - p1);
    return (p4
        * a123 - p3 * a124) / (a123 - a124); // C^3 / C^2
}
pdd orth(pdd p1)
{ return pdd(-p1.S, p1.F); }
pdd projection(pdd p1, pdd p2, pdd p3)
{ return p1 + (
    p2 - p1) * dot(p3 - p1, p2 - p1) / abs2(p2 - p1); }
pdd reflection(pdd p1, pdd p2, pdd p3)
{ return p3 + orth(p2 - p1
    ) * cross(p3 - p1, p2 - p1) / abs2(p2 - p1) * 2; }
pdd linearTransformation
    (pdd p0, pdd p1, pdd q0, pdd q1, pdd r) {
    pdd dp = p1 - p0
        , dq = q1 - q0, num(cross(dp, dq), dot(dp, dq));
    return q0 + pdd(
        cross(r - p0, num), dot(r - p0, num)) / abs2(dp);
} // from line p0--p1 to q0--q1, apply to r
```

### 8B ConvexHull

```
void hull(vector<pll> &dots) { // n=1 => ans = {}
    sort(dots.begin(), dots.end());
    vector<pll> ans(1, dots[0]);
    for (int ct = 0; ct < 2; ++ct, reverse(all(dots)))
        for (int i = 1, t = (int)ans.size();
            i < (int)dots.size();
            ans.emplace_back(dots[i++]))
            while ((int)ans.size() > t &&
                ori(ans.end()[-2], ans.back(), dots[i]) <= 0)
                ans.pop_back();
    ans.pop_back(), ans.swap(dots);
}
```

### 8C SortByAngle

```
bool down(pll k) {
    return sign(k.S) < 0 ||
        (sign(k.S) == 0 && sign(k.F) < 0);
}
int cmp(pll a, pll b, bool same = true) {
    int A = down(a), B = down(b);
    if (A != B) return A < B;
    if (sign(cross(a, b)) == 0)
        return same ? abs2(a) < abs2(b) : -1;
    return sign(cross(a, b)) > 0;
}
```

### 8D Formulas

#### • Rotation

$$M(\theta) = \begin{bmatrix} \cos\theta & -\sin\theta \\ \sin\theta & \cos\theta \end{bmatrix}$$

90 degree:  $(x, y) = (Y - y, x)$

#### • Pick's theorem

For simple integer-coordinate polygon,

$$A = B + \frac{I}{2} - 1$$

Where  $A$  is the area;  $B, I$  is #lattice points in the interior, on the boundary.

#### • Spherical Cap

- A portion of a sphere cut off by a plane.
- $r$ : sphere radius,  $a$ : radius of the base of the cap,  $h$ : height of the cap,  $\theta$ :  $\arcsin(a/r)$ .
- Volume =  $\pi h^2(3r - h)/3 = \pi h(3a^2 + h^2)/6 = \pi r^3(2 + \cos\theta)(1 - \cos\theta)^2/3$ .
- Area =  $2\pi rh = \pi(a^2 + h^2) = 2\pi r^2(1 - \cos\theta)$ .

#### • Nearest points of two skew lines

- Line 1:  $v_1 = p_1 + t_1 d_1$
- Line 2:  $v_2 = p_2 + t_2 d_2$
- $n = d_1 \times d_2$
- $n_1 = d_1 \times n$
- $n_2 = d_2 \times n$
- $c_1 = p_1 + \frac{(p_2 - p_1) \cdot n_2}{d_1 \cdot n_2} d_1$
- $c_2 = p_2 + \frac{(p_1 - p_2) \cdot n_1}{d_2 \cdot n_1} d_2$

### 8E TriangleHearts

```
pdd excenter(
    pdd p0, pdd p1, pdd p2) { // radius = abs(center)
    p1 = p1 - p0, p2 = p2 - p0;
    auto [x1, y1] = p1;
    auto [x2, y2] = p2;
    double m = 2. * cross(p1, p2);
    pdd center = pdd((x1 * x1 * y2 - x2 * x2 * y1 +
        y1 * y2 * (y1 - y2)),
        (x1 * x2 * (x2 - x1) - y1 * y1 * x2 +
        x1 * y2 * y2)) /
        m;
    return center + p0;
}
pdd incenter(
    pdd p1, pdd p2, pdd p3) { // radius = area / s * 2
    double a = abs(p2 - p3), b = abs(p1 - p3),
        c = abs(p1 - p2);
    double s = a + b + c;
    return (p1 * a + p2 * b + p3 * c) / s;
}
```



```

pdd masscenter(pdd p1, pdd p2, pdd p3) {
    return (p1 + p2 + p3) / 3;
}

pdd orthcenter(pdd p1, pdd p2, pdd p3) {
    return masscenter(p1, p2, p3) * 3 -
        excenter(p1, p2, p3) * 2;
}

```

## 8F PointSegmentDist

```

double PointSegDist(pdd q0, pdd q1, pdd p) {
    if (abs(q0 - q1) <= eps) return abs(q0 - p);
    if (dot(q1 - q0,
        p - q0) >= -eps && dot(q0 - q1, p - q1) >= -eps)
        return fabs(cross(q1 - q0, p - q0) / abs(q0 - q1));
    return min(abs(p - q0), abs(p - q1));
}

```

## 8G PointInCircle

```

// return q'
// s relation with circumcircle of tri(p[0],p[1],p[2])
bool in_cc(const array<pll, 3> p, pll q) {
    __int128 det = 0;
    for (int i = 0; i < 3; ++i)
        det += __int128(abs2(p[i]) - abs2(q)) *
            cross(p[(i + 1) % 3] - q, p[(i + 2) % 3] - q);
    return det > 0; // in: >0, on: =0, out: <0
}

```

## 8H PointInConvex

```

bool PointInConvex
    (const vector<pll> &C, pll p, bool strict = true) {
    int a = 1, b = (int)C.size() - 1, r = !strict;
    if ((int)C.size() == 0) return false;
    if ((int)
        C.size() < 3) return r && btw(C[0], C.back(), p);
    if (ori(C[0], C[a], C[b]) > 0) swap(a, b);
    if (ori
        (C[0], C[a], p) >= r || ori(C[0], C[b], p) <= -r)
        return false;
    while (abs(a - b) > 1) {
        int c = (a + b) / 2;
        (ori(C[0], C[c], p) > 0 ? b : a) = c;
    }
    return ori(C[a], C[b], p) < r;
}

```

## 8I PointTangentConvex

```

/* The point should be strictly out of hull
   return arbitrary point on the tangent line */
/* bool pred(int a, int b);
f(0) ~ f(n - 1) is a cyclic-shift U-function
return idx s.t. pred(x, idx) is false forall x*/
int cyc_tsearch(int n, auto pred) {
    if (n == 1) return 0;
    int l = 0, r = n; bool rv = pred(1, 0);
    while (r - l > 1) {
        int m = (l + r) / 2;
        if (pred(0, m) ? rv : pred(m, (m + 1) % n)) r = m;
        else l = m;
    }
    return pred(l, r % n) ? l : r % n;
}

pii get_tangent(vector<pll> &C, pll p) {
    auto gao = [&](int s) {
        return cyc_tsearch((int)C.size(), [&](int x, int y)
            { return ori(p, C[x], C[y]) == s; });
    };
    return pii(gao(1), gao(-1));
}
// return (a, b), ori(p, C[a], C[b]) >= 0

```

## 8J CircTangentCirc

```

vector<Line> go(Cir c1, Cir c2, int sign1) {
    // sign1 = 1 for outer tang, -1 for inter tang
    vector<Line> ret;
    double d_sq = abs2(c1.0 - c2.0);
    if (sign(d_sq) == 0) return ret;
    double d = sqrt(d_sq);
    pdd v = (c2.0 - c1.0) / d;
    double c = (c1.R - sign1 * c2.R) / d;
    if (c * c > 1) return ret;
    double h = sqrt(max(0.0, 1.0 - c * c));
    for (int sign2 = 1; sign2 >= -1; sign2 -= 2) {
        pdd n = pdd(v.F * c - sign2 * h * v.S,
            v.S * c + sign2 * h * v.F);
        pdd p1 = c1.0 + n * c1.R;
        pdd p2 = c2.0 + n * (c2.R * sign1);
        if (sign(p1.F - p2.F) == 0 and
            sign(p1.S - p2.S) == 0)
            p2 = p1 + perp(c2.0 - c1.0);
        ret.emplace_back(Line(p1, p2));
    }
    return ret;
}

```

## 8K LineCircleIntersect

```

vector<pdd> circleLine(pdd c, double r, pdd a, pdd b) {
    pdd p
        = a + (b - a) * dot(c - a, b - a) / abs2(b - a);
    double s = cross
        (b - a, c - a), h2 = r * r - s * s / abs2(b - a);
    if (h2 < 0) return {};
    if (h2 == 0) return {p};
    pdd h = (b - a) / abs(b - a) * sqrt(h2);
    return {p - h, p + h};
}

```

## 8L LineConvexIntersect

```

int cyc_tsearch(int n, auto pred); // ref: TanPointHull
int TangentDir(vector<pll> &C, pll dir) {
    return cyc_tsearch((int)C.size(), [&](int a, int b) {
        return cross(dir, C[a]) > cross(dir, C[b]);
    });
}

#define cmpL(i) sign(cross(C[i] - a, b - a))
pii lineHull(pll a, pll b, vector<pll> &C) {
    int A = TangentDir(C, a - b);
    int B = TangentDir(C, b - a);
    int n = (int)C.size();
    if (cmpL(A) < 0 || cmpL(B) > 0)
        return pii(-1, -1); // no collision
    auto gao = [&](int l, int r) {
        for (int t = l; (l + 1) % n != r; t = (l + 1) % n) {
            int m = ((l + r + (l < r ? 0 : n)) / 2) % n;
            (cmpL(m) == cmpL(t) ? l : r) = m;
        }
        return (l + !cmpL(r)) % n;
    };
    pii res = pii(gao(B, A), gao(A, B)); // (i, j)
    if (res.F == res.S) // touching the corner i
        return pii(res.F, -1);
    if (!cmpL(res.F) &&
        !cmpL(res.S)) // along side i, i+1
        switch ((res.F - res.S + n + 1) % n) {
            case 0: return pii(res.F, res.F);
            case 2: return pii(res.S, res.S);
        }
    /* crossing sides (i, i+1) and (j, j+1)
       crossing corner i is treated as side (i, i+1)
       returned in the same order as the line hits the
       convex */
    return res;
}
// convex cut: (r, l]

```

## 8M CircIntersectCirc

```
bool CCinter(Cir &a, Cir &b, pdd &p1, pdd &p2) {
    pdd o1 = a.O, o2 = b.O;
    double r1 =
        a.R, r2 = b.R, d2 = abs2(o1 - o2), d = sqrt(d2);
    if(d < max
        (r1, r2) - min(r1, r2) || d > r1 + r2) return 0;
    pdd u = (o1 + o2) * 0.5
        + (o1 - o2) * ((r2 * r2 - r1 * r1) / (2 * d2));
    double A = sqrt((r1 + r2 + d) *
        (r1 - r2 + d) * (r1 + r2 - d) * (-r1 + r2 + d));
    pdd v
        = pdd(o1.S - o2.S, -o1.F + o2.F) * A / (2 * d2);
    p1 = u + v, p2 = u - v;
    return 1;
}
```

## 8N PolyIntersectCirc

```
// Divides into multiple triangle, and sum up
const double PI = acos(-1);
double _area(pdd pa, pdd pb, double r) {
    if (abs(pa) < abs(pb)) swap(pa, pb);
    if (abs(pb) < eps) return 0;
    double S, h, theta;
    double a = abs(pb), b = abs(pa), c = abs(pb - pa);
    double cosB = dot(pb, pb - pa) / a / c,
        B = acos(cosB);
    double cosC = dot(pa, pb) / a / b, C = acos(cosC);
    if (a > r) {
        S = (C / 2) * r * r;
        h = a * b * sin(C) / c;
        if (h < r && B < PI / 2)
            S -= (acos(h / r) * r * r -
                h * sqrt(r * r - h * h));
    } else if (b > r) {
        theta = PI - B - asin(sin(B) / r * a);
        S = .5 * a * r * sin(theta) +
            (C - theta) / 2 * r * r;
    } else S = .5 * sin(C) * a * b;
    return S;
}
double area_poly_circle(const vector<pdd> poly,
    const pdd &O, const double r) {
    const pdd &O, const double r) {
    double S = 0;
    for (int i = 0; i < (int)poly.size(); ++i)
        S += _area(poly[i] - O,
            poly[(i + 1) % (int)poly.size()] - O, r) *
            ori(
                O, poly[i], poly[(i + 1) % (int)poly.size()]);
    return fabs(S);
}
```

## 8O PolyUnion

```
double rat(pll a, pll b) {
    return sign
        (b.F) ? ((double)a.F / b.F : ((double)a.S / b.S);
} // all poly. should be ccw
double polyUnion(vector<vector<pll>> &poly) {
    double res = 0;
    for (auto &p : poly)
        for (int a = 0; a < (int)p.size(); ++a) {
            pll A = p[a], B = p[(a + 1) % (int)p.size()];
            vector
                <pair<double, int>> segs = {{0, 0}, {1, 0}};
            for (auto &q : poly) {
                if (&p == &q) continue;
                for (int b = 0; b < (int)q.size(); ++b) {
                    pll C = q[b], D = q[(b + 1) % (int)q.size()];
                    int sc = ori(A, B, C), sd = ori(A, B, D);
                    if (sc != sd && min(sc, sd) < 0) {
                        double sa = cross(D
                            - C, A - C), sb = cross(D - C, B - C);
                        segs.emplace_back
                            (sa / (sa - sb), sign(sc - sd));
                    }
                }
            }
        }
    }
```

```
if (!sc && !sd &&
    &q < &p && sign(dot(B - A, D - C)) > 0) {
    segs.emplace_back(rat(C - A, B - A), 1);
    segs.emplace_back(rat(D - A, B - A), -1);
}
}
sort(all(segs));
for (auto &s : segs) s.F = clamp(s.F, 0.0, 1.0);
double sum = 0;
int cnt = segs[0].second;
for (int j = 1; j < (int)segs.size(); ++j) {
    if (!cnt) sum += segs[j].F - segs[j - 1].F;
    cnt += segs[j].S;
}
res += cross(A, B) * sum;
}
return res / 2;
}
```

## 8P MinkowskiSum

```
vector<pll> Minkowski
    (vector<pll> A, vector<pll> B) { // |A|,|B|>=3
    hull(A), hull(B);
    vector<pll> C(1, A[0] + B[0]), s1, s2;
    for (int i = 0; i < A.size(); ++i)
        s1.emplace_back(A[(i + 1) % A.size()] - A[i]);
    for (int i = 0; i < B.size(); ++i)
        s2.emplace_back(B[(i + 1) % B.size()] - B[i]);
    for (int i = 0, j = 0; i < A.size() || j < B.size(); ++i)
        if (j >= B.size()
            || (i < A.size() && cross(s1[i], s2[j]) >= 0))
            C.emplace_back(B[j % B.size()] + A[i++]);
        else
            C.emplace_back(A[i % A.size()] + B[j++]);
    return hull(C), C;
}
```

## 8Q MinMaxEnclosingRect

```
const double qi = acos(-1) / 2 * 3;
pdd solve(vector<pll> &dots) {
#define diff(u, v) (dots[u] - dots[v])
#define vec(v) (dots[v] - dots[0])
    hull(dots);
    double Max = 0, Min = INF, deg;
    int n = (int)dots.size();
    dots.emplace_back(dots[0]);
    for (int i = 0, u = 1, r = 1, l = 1; i < n; ++i) {
        pll nw = vec(i + 1);
        while (cross(nw, vec(u + 1)) > cross(nw, vec(u)))
            u = (u + 1) % n;
        while (dot(nw, vec(r + 1)) > dot(nw, vec(r)))
            r = (r + 1) % n;
        if (!i) l = (r + 1) % n;
        while (dot(nw, vec(l + 1)) < dot(nw, vec(l)))
            l = (l + 1) % n;
        Min = min(Min, (double)(dot(nw, vec(r)) - dot
            (nw, vec(l))) * cross(nw, vec(u)) / abs2(nw));
        deg = acos(dot(diff(r
            , l), vec(u)) / abs(diff(r, l)) / abs(vec(u)));
        deg = (qi - deg) / 2;
        Max = max(Max, abs(diff
            (r, l)) * abs(vec(u)) * sin(deg) * sin(deg));
    }
    return pdd(Min, Max);
}
```

## 8R MinEnclosingCircle

```
pdd Minimum_Enclosing_Circle
    (vector<pdd> dots, double &r) {
    pdd cent;
    random_shuffle(all(dots));
    cent = dots[0], r = 0;
    for (int i = 1; i < (int)dots.size(); ++i)
```

```

    if (abs(dots[i] - cent) > r) {
        cent = dots[i], r = 0;
        for (int j = 0; j < i; ++j)
            if (abs(dots[j] - cent) > r) {
                cent = (dots[i] + dots[j]) / 2;
                r = abs(dots[i] - cent);
                for (int k = 0; k < j; ++k)
                    if (abs(dots[k] - cent) > r)
                        cent =
                            excenter(dots[i], dots[j], dots[k]),
                            r = abs(cent - dots[i]);
            }
    }
    return cent;
}
}

```

## 8S CircleCover

```

// N ~ 1000
struct CircleCover {
    int C;
    Cir c[N];
    bool g[N][N], overlap[N][N];
    // Area[i] : area covered by at least i circles
    double Area[ N ];
    void init(int _c){ C = _c;}
    struct Teve {
        pdd p; double ang; int add;
        Teve() {}
        Teve(pdd _a
            , double _b, int _c):p(_a), ang(_b), add(_c){}
        bool operator<(const Teve &a)const
        {return ang < a.ang;}
    }eve[N * 2];
    // strict: x = 0, otherwise x = -1
    bool disjuct(Cir &a, Cir &b, int x)
    {return sign(abs(a.0 - b.0) - a.R - b.R) > x;}
    bool contain(Cir &a, Cir &b, int x)
    {return sign(a.R - b.R - abs(a.0 - b.0)) > x;}
    bool contain(int i, int j) {
        /* c[j] is non-strictly in c[i]. */
        return (sign
            (c[i].R - c[j].R) > 0 || (sign(c[i].R - c[j].
                R) == 0 && i < j)) && contain(c[i], c[j], -1);
    }
    void solve(){
        fill_n(Area, C + 2, 0);
        for (int i = 0; i < C; ++i)
            for (int j = 0; j < C; ++j)
                overlap[i][j] = contain(i, j);
        for (int i = 0; i < C; ++i)
            for (int j = 0; j < C; ++j)
                g[i][j] = !(overlap[i][j] || overlap[j][i] ||
                    disjuct(c[i], c[j], -1));
        for (int i = 0; i < C; ++i){
            int E = 0, cnt = 1;
            for (int j = 0; j < C; ++j)
                if (j != i && overlap[j][i])
                    ++cnt;
            for (int j = 0; j < C; ++j)
                if (i != j && g[i][j]) {
                    pdd aa, bb;
                    CCinter(c[i], c[j], aa, bb);
                    double A =
                        atan2(aa.S - c[i].0.S, aa.F - c[i].0.F);
                    double B =
                        atan2(bb.S - c[i].0.S, bb.F - c[i].0.F);
                    eve[E++] = Teve
                        (bb, B, 1), eve[E++] = Teve(aa, A, -1);
                    if (B > A) ++cnt;
                }
            if (E == 0) Area[cnt] += pi * c[i].R * c[i].R;
            else{
                sort(eve, eve + E);
                eve[E] = eve[0];
                for (int j = 0; j < E; ++j){
                    cnt += eve[j].add;

```

```

                Area[cnt
                    ] += cross(eve[j].p, eve[j + 1].p) * .5;
                double theta = eve[j + 1].ang - eve[j].ang;
                if (theta < 0) theta += 2. * pi;
                Area[cnt] += (theta
                    - sin(theta)) * c[i].R * c[i].R * .5;
            }
        }
    }
};

```

## 8T LineCmp

```

struct LineCmp { // coordinates should be even!
    bool operator()(Line l1, Line l2) const {
        int X =
            (max(l1.F.F, l2.F.F) + min(l1.S.F, l2.S.F)) / 2;
        ll p1 =
            (X - l1.F.F) * l1.S.S + (l1.S.F - X) * l1.F.S,
            p2 =
            (X - l2.F.F) * l2.S.S + (l2.S.F - X) * l2.F.S,
            q1 = (l1.S.F - l1.F.F), q2 = (l2.S.F - l2.F.F);
        if (q1 == 0) p1 = l1.F.S + l1.S.S, q1 = 2;
        if (q2 == 0) p2 = l2.F.S + l2.S.S, q2 = 2;
        // for query a point: ask make_pair(P, P)
        if (l1.F == l2.F || l2.F == l2.S) l1 = l2;
        return make_tuple((__int128)(p1 * q2), l1) <
            make_tuple((__int128)(p2 * q1), l2);
    }
};

```

## 8U Trapezoidalization

```

template<class T>
struct SweepLine {
    struct cmp {
        cmp(const SweepLine &swp): swp(_swp) {}
        bool operator()(int a, int b) const {
            if (abs(swp.get_y(a) - swp.get_y(b)) <= swp.eps)
                return swp.slope_cmp(a, b);
            return swp.get_y(a) + swp.eps < swp.get_y(b);
        }
    } _cmp;
    const SweepLine &swp;
    T curTime, eps, curQ;
    vector<Line> base;
    multiset<int, cmp> sweep;
    multiset<pair<T, int>> event;
    vector<typename multiset<int, cmp>::iterator> its;
    vector
        <typename multiset<pair<T, int>>::iterator> eits;
    bool slope_cmp(int a, int b) const {
        assert(a != -1);
        if (b == -1) return 0;
        return sign(cross(base
            [a].S - base[a].F, base[b].S - base[b].F)) < 0;
    }
    T get_y(int idx) const {
        if (idx == -1) return curQ;
        Line l = base[idx];
        if (l.F.F == l.S.F) return l.S.S;
        return ((curTime - l.F.F) * l.S.S
            + (l.S.F - curTime) * l.F.S) / (l.S.F - l.F.F);
    }
    void insert(int idx) {
        its[idx] = sweep.insert(idx);
        if (its[idx] != sweep.begin())
            update_event(*prev(its[idx]));
        update_event(idx);
        event.emplace
            (base[idx].S.F, idx + 2 * (int)base.size());
    }
    void erase(int idx) {
        assert(eits[idx] == event.end());
        auto p = sweep.erase(its[idx]);
        its[idx] = sweep.end();
        if (p != sweep.begin())

```

```

    update_event(*prev(p));
}
void update_event(int idx) {
    if (eits[idx] != event.end())
        event.erase(eits[idx]);
    eits[idx] = event.end();
    auto nxt = next(its[idx]);
    if (nxt ==
        sweep.end() || !slope_cmp(idx, *nxt)) return;
    auto t = intersect(base[idx].
        F, base[idx].S, base[*nxt].F, base[*nxt].S).F;
    if (t + eps < curTime || t
        >= min(base[idx].S.F, base[*nxt].S.F)) return;
    eits[idx]
        ] = event.emplace(t, idx + (int)base.size());
}
void swp(int idx) {
    assert(eits[idx] != event.end());
    eits[idx] = event.end();
    int nxt = *next(its[idx]);
    swap((int*)&its[idx], (int*)&its[nxt]);
    swap(its[idx], its[nxt]);
    if (its[nxt] != sweep.begin())
        update_event(*prev(its[nxt]));
    update_event(idx);
}
// only expected to call the functions below
SweepLine(T t, T e, vector<Line> vec): _cmp
    (*this), curTime(t), eps(e), curQ(), base(vec),
    sweep(_cmp), event(), its((int)vec.size(), sweep
        .end()), eits((int)vec.size(), event.end()) {
    for (int i = 0; i < (int)base.size(); ++i) {
        auto &p, q] = base[i];
        if (p > q) swap(p, q);
        if (p.F <= curTime && curTime <= q.F)
            insert(i);
        else if (curTime < p.F)
            event.emplace(p.F, i);
    }
}
void setTime(T t, bool ers = false) {
    assert(t >= curTime);
    while (!event.empty() && event.begin()->F <= t) {
        auto [et, idx] = *event.begin();
        int s = idx / (int)base.size();
        idx %= (int)base.size();
        if (abs(et - t) <= eps && s == 2 && !ers) break;
        curTime = et;
        event.erase(event.begin());
        if (s == 2) erase(idx);
        else if (s == 1) swp(idx);
        else insert(idx);
    }
    curTime = t;
}
T nextEvent() {
    if (event.empty()) return INF;
    return event.begin()->F;
}
int lower_bound(T y) {
    curQ = y;
    auto p = sweep.lower_bound(-1);
    if (p == sweep.end()) return -1;
    return *p;
}
};

```

## 8V HalfPlaneIntersect

```

pll area_pair(Line a, Line b)
{ return pll(cross(a.S
    - a.F, b.F - a.F), cross(a.S - a.F, b.S - a.F)); }
bool isin(Line l0, Line l1, Line l2) {
    // Check inter(l1, l2) strictly in l0
    auto [a02X, a02Y] = area_pair(l0, l2);
    auto [a12X, a12Y] = area_pair(l1, l2);

```

```

    if (a12X - a12Y < 0) a12X *= -1, a12Y *= -1;
    return (__int128)
        a02Y * a12X - (__int128) a02X * a12Y > 0; // C^4
}
/* Having solution, check size > 2 */
/* --^-- Line.X --^-- Line.Y --^-- */
vector<Line> halfPlaneInter(vector<Line> arr) {
    sort(all(arr), [&](Line a, Line b) -> int {
        if (cmp(a.S - a.F, b.S - b.F, 0) != -1)
            return cmp(a.S - a.F, b.S - b.F, 0);
        return ori(a.F, a.S, b.S) < 0;
    });
    deque<Line> dq(1, arr[0]);
    for (auto p : arr) {
        if (cmp(
            dq.back().S - dq.back().F, p.S - p.F, 0) == -1)
            continue;
        while ((int)dq.size() >= 2
            && !isin(p, dq[(int)dq.size() - 2], dq.back()))
            dq.pop_back();
        while
            ((int)dq.size() >= 2 && !isin(p, dq[0], dq[1]))
            dq.pop_front();
        dq.emplace_back(p);
    }
    while ((int)dq.size() >= 3 &&
        !isin(dq[0], dq[(int)dq.size() - 2], dq.back()))
        dq.pop_back();
    while ((int)
        dq.size() >= 3 && !isin(dq.back(), dq[0], dq[1]))
        dq.pop_front();
    return vector<Line>(all(dq));
}

```

## 8W RotatingSweepLine

```

void rotatingSweepLine(vector<pii> &ps) {
    int n = (int)ps.size(), m = 0;
    vector<int> id(n), pos(n);
    vector<pii> line(n * (n - 1));
    for (int i = 0; i < n; ++i)
        for (int j = 0; j < n; ++j)
            if (i != j) line[m++] = pii(i, j);
    sort(all(line), [&](pii a, pii b) {
        return cmp(ps[a.S] - ps[a.F], ps[b.S] - ps[b.F]);
    }); // cmp(): polar angle compare
    iota(all(id), 0);
    sort(all(id), [&](int a, int b) {
        if (ps[a].S != ps[b].S) return ps[a].S < ps[b].S;
        return ps[a] < ps[b];
    }); // initial order, since (1, 0) is the smallest
    for (int i = 0; i < n; ++i) pos[id[i]] = i;
    for (int i = 0; i < m; ++i) {
        auto l = line[i];
        // do something
        tie(pos[l.F], pos[l.S], id[pos[l.F]], id[pos[l.S]
            ]) = make_tuple(pos[l.S], pos[l.F], l.S, l.F);
    }
}

```

## 8X DelaunayTriangulation

*/\* Delaunay Triangulation:  
Given a sets of points on 2D plane, find a  
triangulation such that no points will strictly  
inside circumcircle of any triangle. \*/*

```

struct Edge {
    int id; // oidx[id]
    list<Edge>::iterator twin;
    Edge(int _id = 0) : id(_id) {}
};
struct Delaunay { // 0-base
    int n, oidx[N];
    list<Edge> head[N]; // result udir. graph
    pll p[N];
    void init(int _n, pll _p[]) {
        n = _n, iota(oidx, oidx + n, 0);
    }

```

```

    for (int i = 0; i < n; ++i) head[i].clear();
    sort(oidx, oidx + n,
        [&](int a, int b) { return _p[a] < _p[b]; });
    for (int i = 0; i < n; ++i) p[i] = _p[oidx[i]];
    divide(0, n - 1);
}

void addEdge(int u, int v) {
    head[u].push_front(Edge(v));
    head[v].push_front(Edge(u));
    head[u].begin()->twin = head[v].begin();
    head[v].begin()->twin = head[u].begin();
}

void divide(int l, int r) {
    if (l == r) return;
    if (l + 1 == r) return addEdge(l, l + 1);
    int mid = (l + r) >> 1, nw[2] = {l, r};
    divide(l, mid), divide(mid + 1, r);
    auto gao = [&](int t) {
        pll pt[2] = {p[nw[0]], p[nw[1]]};
        for (auto it : head[nw[t]]) {
            int v = ori(pt[1], pt[0], p[it.id]);
            if (v > 0 ||
                (v == 0 &&
                 abs2(pt[t ^ 1] - p[it.id]) <
                 abs2(pt[1] - pt[0])))
                return nw[t] = it.id, true;
        }
        return false;
    };
    while (gao(0) || gao(1));
    addEdge(nw[0], nw[1]); // add tangent
    while (true) {
        pll pt[2] = {p[nw[0]], p[nw[1]]};
        int ch = -1, sd = 0;
        for (int t = 0; t < 2; ++t)
            for (auto it : head[nw[t]])
                if (ori(pt[0], pt[1], p[it.id]) > 0 &&
                    (ch == -1 ||
                     in_cc({pt[0], pt[1], p[ch]}, p[it.id])))
                    ch = it.id, sd = t;
        if (ch == -1) break; // upper common tangent
        for (auto it = head[nw[sd]].begin();
             it != head[nw[sd]].end();)
            if (seg_strict_intersect(
                pt[sd], p[it->id], pt[sd ^ 1], p[ch]))
                head[it->id].erase(it->twin),
                head[nw[sd]].erase(it++);
            else ++it;
        nw[sd] = ch, addEdge(nw[0], nw[1]);
    }
}
} tool;

```

## 8Y VoronoiDiagram

```

// all coord. is even
// , you may want to call halfPlaneInter after then
vector<vector<Line>> vec;
void build_voronoi_line(int n, pll *arr) {
    tool.init(n, arr); // Delaunay
    vec.clear(), vec.resize(n);
    for (int i = 0; i < n; ++i)
        for (auto e : tool.head[i]) {
            int u = tool.oidx[i], v = tool.oidx[e.id];
            pll m = (arr[v]
                + arr[u]) / 2LL, d = perp(arr[v] - arr[u]);
            vec[u].emplace_back(Line(m, m + d));
        }
}

```

## 9 Misc

### 9A MoAlgoWithModify

```

// Mo's Algorithm With modification
// Block:  $N^{\frac{2}{3}}$ , Complexity:  $N^{\frac{5}{3}}$ 
struct Query {

```

```

    static const int blk = 2000;
    int L, R, LBid, RBid, T;
    Query(int l, int r, int t) {
        L(l), R(r), LBid(l / blk), RBid(r / blk), T(t) {}
    }
    bool operator<(const Query &q) const {
        if (LBid != q.LBid) return LBid < q.LBid;
        if (RBid != q.RBid) return RBid < q.RBid;
        return T < q.T;
    }
};

void solve(vector<Query> query) {
    sort(all(query));
    int L=0, R=0, T=-1;
    for (auto q : query) { // TODO: fill in
        // while (T < q.T) addTime(L, R, ++T);
        // while (T > q.T) subTime(L, R, T--);
        // while (R < q.R) add(arr[++R]);
        // while (L > q.L) add(arr[--L]);
        // while (R > q.R) sub(arr[R--]);
        // while (L < q.L) sub(arr[L++]);
        // answer query
    }
}

```

## 9B MoAlgoOnTree

```

/*
Mo's Algorithm On Tree
Preprocess:
1) LCA
2) dfs with in[u] = dft++, out[u] = dft++
3) ord[in[u]] = ord[out[u]] = u
4) bitset<MAXN> inset
*/
struct Query {
    int L, R, LBid, lca;
    Query(int u, int v) {
        int c = LCA(u, v);
        if (c == u || c == v)
            q.lca = -1, q.L = out[c ^ u ^ v], q.R = out[c];
        else if (out[u] < in[v])
            q.lca = c, q.L = out[u], q.R = in[v];
        else
            q.lca = c, q.L = out[v], q.R = in[u];
        q.Lid = q.L / blk;
    }
    bool operator<(const Query &q) const {
        if (LBid != q.LBid) return LBid < q.LBid;
        return R < q.R;
    }
};

void flip(int x) {
    if (inset[x]) sub(arr[x]); // TODO
    else add(arr[x]); // TODO
    inset[x] = ~inset[x];
}

void solve(vector<Query> query) {
    sort(ALL(query));
    int L = 0, R = 0;
    for (auto q : query) {
        while (R < q.R) flip(ord[++R]);
        while (L > q.L) flip(ord[--L]);
        while (R > q.R) flip(ord[R--]);
        while (L < q.L) flip(ord[L++]);
        if (~q.lca) add(arr[q.lca]);
        // answer query
        if (~q.lca) sub(arr[q.lca]);
    }
}

```

## 9C MoAlgoAdvanced

- Mo's Algorithm With Addition Only
  - Sort queries same as the normal Mo's algorithm.
  - For each query  $[l, r]$ :
    - If  $l/blk = r/blk$ , brute-force.
    - If  $l/blk \neq r/blk$ , initialize  $curL := (l/blk + 1) \cdot blk, curR := curL - 1$



- If  $r > curR$ , increase  $curR$
- decrease  $curL$  to fit  $l$ , and then undo after answering
- Mo's Algorithm With Offline Second Time
  - Require: Changing answer  $\equiv$  adding  $f([l, r], r+1)$ .
  - Require:  $f([l, r], r+1) = f([1, r], r+1) - f([1, l], r+1)$ .
  - Part1: Answer all  $f([1, r], r+1)$  first.
  - Part2: Store  $curR \rightarrow R$  for  $curL$  (reduce the space to  $O(N)$ ), and then answer them by the second offline algorithm.
  - Note: You must do the above symmetrically for the left boundaries.

## 9D HilbertCurve

```
ll hilbert(int n, int x, int y) {
    ll res = 0;
    for (int s = n / 2; s; s >>= 1) {
        int rx = (x & s) > 0;
        int ry = (y & s) > 0;
        res += s * 1ll * s * ((3 * rx) ^ ry);
        if (ry == 0) {
            if (rx == 1) x = s - 1 - x, y = s - 1 - y;
            swap(x, y);
        }
    }
    return res;
} // n = 2^k
```

## 9E ManhattanMST

```
#define p3i tuple<int, int, int>
struct DSU {
    vector<int> v;
    DSU(int n);
    int query(int u);
    void merge(int x, int y);
};
vector<p3i> manhattanMST(vector<p3i> ps) {
    vector<int> id(ps.size());
    iota(id.begin(), id.end(), 0);
    vector<p3i> edges;
    for (int k = 0; k < 4; ++k) {
        sort(id.begin(), id.end(), [&](int i, int j) {
            return (ps[i] - ps[j]).F < (ps[j] - ps[i]).S;
        });
        map<int, int> sweep;
        for (int i : id) {
            for (auto it = sweep.lower_bound(-ps[i].S);
                 it != sweep.end(); sweep.erase(it++)) {
                int j = it->second;
                p3i d = ps[i] - ps[j];
                if (d.S > d.F) break;
                edges.emplace_back(d.S + d.F, i, j);
            }
            sweep[-ps[i].S] = i;
        }
        for (auto &p : ps)
            if (k & 1) p.F = -p.F;
            else swap(p.F, p.S);
    }
    return edges;
}
vector<int> MST(int n, const vector<p3i> &e) {
    vector<int> idx(e.size());
    iota(idx.begin(), idx.end(), 0);
    sort(idx.begin(), idx.end(), [&](int i, int j) {
        return get<0>(e[i]) < get<0>(e[j]);
    });
    vector<int> r;
    DSU dsu(n);
    for (int o : idx) {
        const auto &[w, i, j] = e[o];
        if (dsu.query(i) == dsu.query(j)) continue;
        r.push_back(o);
        dsu.merge(i, j);
    }
    return r;
}
```

## 9F SternBrocotTree

- Construction: Root  $\frac{1}{1}$ , left/right neighbor  $\frac{0}{1}, \frac{1}{0}$ , each node is sum of last left/right neighbor:  $\frac{a}{b}, \frac{c}{d} \rightarrow \frac{a+c}{b+d}$
- Property: Adjacent (mid-order DFS)  $\frac{a}{b}, \frac{c}{d} \Rightarrow bc - ad = 1$ .
- Search known  $\frac{p}{q}$ : keep L-R alternative. Each step can be calculated in  $O(1) \Rightarrow$  total  $O(\log C)$ .
- Search unknown  $\frac{p}{q}$ : keep L-R alternative. Each step can be calculated in  $O(\log C)$  checks  $\Rightarrow$  total  $O(\log^2 C)$  checks.

## 9G ALLCS

```
void all_lcs(string s, string t) { // 0-base
    vector<int> h((int)t.size());
    iota(all(h), 0);
    for (int a = 0; a < (int)s.size(); ++a) {
        int v = -1;
        for (int c = 0; c < (int)t.size(); ++c)
            if (s[a] == t[c] || h[c] < v)
                swap(h[c], v);
        // LCS[s[0], a], t[b, c] =
        // c - b + 1 - sum([h[i] >= b] | i <= c)
        // h[i] might become -1 !!
    }
}
```

## 9H MatroidIntersection

- Start from  $S = \emptyset$ . In each iteration, let
- $Y_1 = \{x \notin S \mid S \cup \{x\} \in I_1\}$
  - $Y_2 = \{x \notin S \mid S \cup \{x\} \in I_2\}$
- If there exists  $x \in Y_1 \cap Y_2$ , insert  $x$  into  $S$ . Otherwise for each  $x \in S, y \notin S$ , create edges
- $x \rightarrow y$  if  $S - \{x\} \cup \{y\} \in I_1$ .
  - $y \rightarrow x$  if  $S - \{x\} \cup \{y\} \in I_2$ .
- Find a *shortest* path (with BFS) starting from a vertex in  $Y_1$  and ending at a vertex in  $Y_2$  which doesn't pass through any other vertices in  $Y_2$ , and alternate the path. The size of  $S$  will be incremented by 1 in each iteration. For the weighted case, assign weight  $w(x)$  to vertex  $x$  if  $x \in S$  and  $-w(x)$  if  $x \notin S$ . Find the path with the minimum number of edges among all minimum length paths and alternate it.

## 9I SimulatedAnnealing

```
double factor = 100000;
const int base = 1e9; // remember to run ~ 10 times
for (int it = 1; it <= 1000000; ++it) {
    // ans: answer, nw: current value
    if (exp(-(nw -
        ans) / factor) >= (double)(rd() % base) / base)
        ans = nw;
    factor *= 0.99995;
}
```

## 9J SMAWK

```
int opt[N];
ll A(int x, int y); // target func
void smawk(vector<int> &r, vector<int> &c);
void interpolate(vector<int> &r, vector<int> &c) {
    int n = (int)r.size();
    vector<int> er;
    for (int i = 1; i < n; i += 2) er.emplace_back(r[i]);
    smawk(er, c);
    for (int i = 0, j = 0; j < c.size(); j++) {
        if (A(r[i], c[j]) < A(r[i], opt[r[i]]))
            opt[r[i]] = c[j];
        if (i + 2 < n && c[j] == opt[r[i + 1]])
            j--, i += 2;
    }
}
void reduce(vector<int> &r, vector<int> &c) {
    int n = (int)r.size();
    vector<int> nc;
    for (int i : c) {
        int j = (int)nc.size();
        while (
            j && A(r[j - 1], nc[j - 1]) > A(r[j - 1], i))
            nc.pop_back(), j--;
        if (nc.size() < n) nc.emplace_back(i);
    }
}
```



```

    smawk(r, nc);
}
void smawk(vector<int> &r, vector<int> &c) {
    if (r.size() == 1 && c.size() == 1) opt[r[0]] = c[0];
    else if (r.size() >= c.size()) interpolate(r, c);
    else reduce(r, c);
}

```

## 9K Python

```

import math
math.isqrt(2) # integer sqrt

```

## 9L LineContainer

```

struct Line {
    mutable ll k, m, p;
    bool operator<(const Line &o) const {
        return k < o.k;
    }
    bool operator<(ll x) const { return p < x; }
};

struct LineContainer : multiset<Line, less<>> {
    // (for doubles, use inf = 1/.0, div(a,b) = a/b)
    static const ll inf = LLONG_MAX;
    ll div(ll a, ll b) { // floored division
        return a / b - ((a ^ b) < 0 && a % b);
    }
    bool isect(iterator x, iterator y) {
        if (y == end()) return x->p = inf, 0;
        if (x->k == y->k) x->p = x->m > y->m ? inf : -inf;
        else x->p = div(y->m - x->m, x->k - y->k);
        return x->p >= y->p;
    }
    void add(ll k, ll m) {
        auto z = insert({k, m, 0}), y = z++, x = y;
        while (isect(y, z)) z = erase(z);
        if (x != begin() && isect(--x, y))
            isect(x, y = erase(y));
        while ((y = x) != begin() && (--x)->p >= y->p)
            isect(x, erase(y));
    }
    ll query(ll x) {
        assert(!empty());
        auto l = *lower_bound(x);
        return l.k * x + l.m;
    }
};

```