



Online Judge
[Web Board](#)
[Home Page](#)
[F.A.Qs](#)
[Statistical Charts](#)

Problem Set
[Problems](#)
[Submit Problem](#)
[Online Status](#)
 Prob.ID:

Authors
[Register](#)
[Update your info](#)
[Authors ranklist](#)

Online Contests
[Current Contest](#)
[Past Contests](#)
[Scheduled Contests](#)
[Award Contest](#)

User
[lydliyudong](#) [Log Out](#)
 Mail:5(0)
[Login Log](#) [Archive](#)

SUBTRACT

Language: ▼

Time Limit: 1000MS

Memory Limit: 10000K

Total Submissions: 1796

Accepted: 797

Special Judge

Description

We are given a sequence of N positive integers $a = [a_1, a_2, \dots, a_N]$ on which we can perform contraction operations.

One contraction operation consists of replacing adjacent elements a_i and a_{i+1} by their difference $a_i - a_{i+1}$. For a sequence of N integers, we can perform exactly $N-1$ different contraction operations, each of which results in a new $(N-1)$ element sequence.

Precisely, let $\text{con}(a, i)$ denote the $(N-1)$ element sequence obtained from $[a_1, a_2, \dots, a_N]$ by replacing the elements a_i and a_{i+1} by a single integer $a_i - a_{i+1}$:

$\text{con}(a, i) = [a_1, \dots, a_{i-1}, a_i - a_{i+1}, a_{i+2}, \dots, a_N]$

Applying $N-1$ contractions to any given sequence of N integers obviously yields a single integer.

For example, applying contractions 2, 3, 2 and 1 in that order to the sequence $[12, 10, 4, 3, 5]$ yields 4, since :

$\text{con}([12, 10, 4, 3, 5], 2) = [12, 6, 3, 5]$

$\text{con}([12, 6, 3, 5], 3) = [12, 6, -2]$

$\text{con}([12, 6, -2], 2) = [12, 8]$

$\text{con}([12, 8], 1) = [4]$

Given a sequence a_1, a_2, \dots, a_N and a target number T , the problem is to find a sequence of $N-1$ contractions that applied to the original sequence yields T .

Input

The first line of the input contains two integers separated by blank character : the integer N , $1 \leq N \leq 100$, the number of integers in the original sequence, and the target integer T , $-10000 \leq T \leq 10000$.

The following N lines contain the starting sequence : for each i , $1 \leq i \leq N$, the $(i+1)^{\text{st}}$ line of the input file contains integer a_i , $1 \leq a_i \leq 100$.

Output

Output should contain $N-1$ lines, describing a sequence of contractions that transforms the original sequence into a single element sequence containing only number T . The i^{th} line of the output file should contain a single integer denoting the i^{th} contraction to be applied. You can assume that at least one such sequence of contractions will exist for a given input.

Sample Input

```
5 4
12
10
4
3
5
```

Sample Output

```
2
3
2
1
```

Source

[CEOI 1998](#)[\[Submit\]](#) [\[Go Back\]](#) [\[Status\]](#) [\[Discuss\]](#)[Home Page](#)[Go Back](#)[To top](#)

All Rights Reserved 2003-2013 Ying Fuchen,Xu Pengcheng,Xie Di
Any problem, Please [Contact Administrator](#)