public member function

# std::multiset::count

<set>

```
size_type count (const value_type& val) const;
```

**Count elements with a specific key**

Searches the container for elements equivalent to *val* and returns the number of matches.

Two elements of a multiset are considered equivalent if the container's comparison object returns `false` reflexively (i.e., no matter the order in which the elements are passed as arguments).

## Parameters

`val`
Value to search for.
Member type `value_type` is the type of the elements in the container, defined in multiset as an alias of its first template parameter (`T`).

## Return value

The number of elements in the container that are equivalent to *val*.

Member type `size_type` is an unsigned integral type.

## Example

```
// multiset::count
#include <iostream>
#include <set>

int main ()
{
  int myints[]={10,73,12,22,73,73,12};
  std::multiset<int> mymultiset (myints,myints+7);

  std::cout << "73 appears " << mymultiset.count(73) << " times in mymultiset.\n";

  return 0;
}
```

Output:

```
73 appears 3 times in mymultiset.
```

## Complexity

Logarithmic in size and linear in the number of matches.

## Iterator validity

No changes.

## Data races

The container is accessed.
Concurrently accessing the elements of a multiset is safe.

## Exception safety

**Strong guarantee:** if an exception is thrown, there are no changes in the container.

## See also

| | |
|---|---|
| **multiset::find** | Get iterator to element (public member function ) |
| **multiset::equal_range** | Get range of equal elements (public member function ) |
| **multiset::size** | Return container size (public member function ) |
| **multiset::lower_bound** | Return iterator to lower bound (public member function ) |
| **multiset::upper_bound** | Return iterator to upper bound (public member function ) |