

 <h1>杭州电子科技大学</h1>  <h2>HANGZHOU DIANZI UNIVERSITY Online Judge</h2> 				
Online Judge F.A.Q Hand In Hand Online Acmers Forum Discuss Statistical Charts	Online Exercise Problem Archive Realtime Judge Status Authors Ranklist <input type="text"/> <input type="button" value="Search"/>	Online Teaching C/C++/Java Exams ACM Steps Go to Job Contest LiveCast ICPC@China	Online Contests Best Coder <small>beta</small> VIP STD Contests Virtual Contests DIY Web-DIY <small>beta</small> Recent Contests	Exercise Author  用QQ帐号登录 Author ID: <input type="text" value="lydrainbowcat"/> Password: <input type="password" value="....."/> <input type="button" value="Sign In"/> <input type="button" value="Register new ID"/>

Estimation

Time Limit: 40000/15000 MS (Java/Others) Memory Limit: 131072/131072 K (Java/Others)
 Total Submission(s): 883 Accepted Submission(s): 332

Problem Description

“There are too many numbers here!” your boss bellows. “How am I supposed to make sense of all of this? Pare it down! Estimate!”

You are disappointed. It took a lot of work to generate those numbers. But, you’ll do what your boss asks.

You decide to estimate in the following way: You have an array **A** of numbers. You will partition it into **k** contiguous sections, which won’t necessarily be of the same size. Then, you’ll use a single number to estimate an entire section. In other words, for your array **A** of size **n**, you want to create another array **B** of size **n**, which has **k** contiguous sections. If **i** and **j** are in the same section, then **B[i]=B[j]**. You want to minimize the error, expressed as the sum of the absolute values of the differences ($\sum |A[i]-B[i]|$).

Input

There will be several test cases in the input. Each test case will begin with two integers on a line, **n** ($1 \leq n \leq 2,000$) and **k** ($1 \leq k \leq 25$, $k \leq n$), where **n** is the size of the array, and **k** is the number of contiguous sections to use in estimation. The array **A** will be on the next **n** lines, one integer per line. Each integer element of **A** will be in the range from -10,000 to 10,000, inclusive. The input will end with a line with two 0s.

Output

For each test case, output a single integer on its own line, which is the minimum error you can achieve. Output no extra spaces, and do not separate answers with blank lines. All possible inputs yield answers which will fit in a signed 64-bit integer.

Sample Input

```
7 2
6
5
4
3
2
1
7
0 0
```

Sample Output

```
9
```

Source

[The University of Chicago Invitational Programming Contest 2012](#)

Recommend

liuyiding

[Statistic](#) | [Submit](#) | [Discuss](#) | [Note](#)

[Home](#) | [Top](#)

Hangzhou Dianzi University Online Judge 3.0
Copyright © 2005-2017 [HDU ACM Team](#). All Rights Reserved.
[Designer & Developer](#) : Wang Rongtao LinLe GaoJie GanLu
Total 0.000000(s) query 1, Server time : 2017-09-26 17:22:43, Gzip enabled

[Administration](#)