

Line detection


This Jupyter Notebook show how we can detect a line using Hough Transformation

```
# Import libraries
import cv2
import numpy as np
import matplotlib.pyplot as plt
```

Load data


```
plt.figure(figsize=(15,6))

plt.subplot(1, 5, 1)
plt.imshow(cv2.imread('datas/ladrinho1.jpg'));
plt.subplot(1, 5, 2)
plt.imshow(cv2.imread('datas/ladrinho2_esquerda.jpg'));
plt.subplot(1, 5, 3)
plt.imshow(cv2.imread('datas/ladrinho3_reto.jpg'));
plt.subplot(1, 5, 4)
plt.imshow(cv2.imread('datas/ladrinho3_esquerda.jpg'));
plt.subplot(1, 5, 5)
plt.imshow(cv2.imread('datas/ladrinho3_direita.jpg'));
```




Detecting the line

```
img = cv2.imread('datas/ladrinho3_reto.jpg')
img_reserve = img.copy()
# Convert the image to grayscale
img_gray = cv2.cvtColor(img, cv2.COLOR_BGR2GRAY)
# find the edges in the image
edges = cv2.Canny(img_gray, 50, 200)
plt.imshow(edges);
```



```
# Detect points that form a line
lines = cv2.HoughLinesP(edges, 1, np.pi/180, 70, minLineLength=15,
maxLineGap=250)

# Draw lines on the image
for line in lines:
    x1, y1, x2, y2 = line[0]
    cv2.line(img, (x1, y1), (x2, y2), (255, 0, 0), 3)
# Show result
plt.imshow(img);
```



We got detect the line, but we need create a imagination line to make the measure of the car

```
# determine the size of the line
line_thickness = 32


# extract the img size
x, y, _ = img.shape

# determine the position of car flow line in relation of x label
car_flow_x = int((x - line_thickness) / 2)
start_point = (car_flow_x, 0)
end_point = (car_flow_x, y)

thickness = 3
color=(0, 255, 0)
# drawn the line 1
line_flow_1 = cv2.line(img, start_point, end_point, color, thickness)

start_point = (car_flow_x + line_thickness, 0)
end_point = (car_flow_x + line_thickness, y)
# drawn the line 2
line_flow_2 = cv2.line(img, start_point, end_point, color, thickness)

plt.imshow(img);
```



We got drawn the flow car line

now we've to measure the diff into the path correct(red) and the flow path(green)

```
# get the correct path
target_line1 = lines[0]
target_line2 = lines[1]

# extract the point x of target_line
start_point_target = target_line1[0][:2][0]
end_point_target = target_line2[0][:2][0]

start_point_target, end_point_target
(202, 234)

# extract the point x of flow_car
start_point_flow = car_flow_x
end_point_flow = start_point_flow + line_thickness

start_point_flow, end_point_flow
(201, 233)
```

```

# calculate the diff = error
error_left = np.abs(start_point_target - start_point_flow)
error_right = np.abs(end_point_target - end_point_flow)

error_left, error_right

(1, 1)

```

Wow, we got made the measure of target line and car flow. What's happen now?

- We need make a algoritm to adjust the motor speed to fix the carr in target line, but before let's try with another images.

Do you mind. I need do rewrite all code again. A: no, let's make a function!

```

def calculate_error(target_line):
    """
    Calculates the error between the target line position and the car
    flow line position.

    Args:
        target_line (list): List containing the coordinates of the
        detected target line.
        start_point_flow (int): X-axis starting position of the car
        flow line.

    Returns:
        int: erro in degrees.
    """
    #print(target_line)
    if isinstance(target_line, tuple):
        target_line = target_line[0]

    # Convert to numpy array e remove the extra dimensions
    contour = np.squeeze(np.array(target_line))

    # avoid erro if has few points
    if contour.shape[0] < 2:
        return None

    # get the extrames points
    x1, y1 = tuple(contour[np.argmin(contour[:, 1])]) # few value of
Y (top)
    x2, y2 = tuple(contour[np.argmax(contour[:, 1])]) # bigger value
of Y (base)

    # calculate angle em rad
    theta_rad = np.arctan2(y2 - y1, x2 - x1)

```

```

# convert to degree
theta_deg = np.degrees(theta_rad)

# to debug
#print(theta_deg)

# assure the degrees in [0, 180]
if theta_deg < 0:
    theta_deg += 180

# calculate the error
error = theta_deg - 90

# return the error in degree (for less use of memory)
return int(error)

def draw_line(img):
    """
    Draws two vertical lines on the image representing the car flow
    boundaries.

    Args:
        img (numpy.ndarray): The input image on which the lines will
        be drawn.

    Returns:
        tuple: A tuple (left, right) representing the X-coordinates of
        the left and right
        boundaries of the car flow line.
    """
    # determine the size of the line
    line_thickness = 32

    # extract the img size
    y, x, _ = img.shape

    # determine the position of car flow line in relation of x label
    car_flow_x = int((x - line_thickness) / 2)
    start_point1 = (car_flow_x, 0)
    end_point1 = (car_flow_x, y)

    thickness = 3
    color=(0, 255, 0)
    # drawn the line 1
    line_flow_1 = cv2.line(img, start_point1, end_point1, color,
thickness)

    start_point2 = (car_flow_x + line_thickness, 0)
    end_point2 = (car_flow_x + line_thickness, y)
    # drawn the line 2

```

```

    line_flow_2 = cv2.line(img, start_point2, end_point2, color,
thickness)

    # return the position in format (left, right)
    return (car_flow_x, car_flow_x+line_thickness)

def identify_colour(img):
    """
    Identifies the dominant color in an image based on predefined HSV
    ranges.

    This function converts the input image to the HSV color space and
    detects specific colors
    (red, green, and gray) using predefined hue, saturation, and value
    ranges. It then applies
    morphological operations to reduce noise, finds contours, and
    calculates the area covered
    by each detected color. The function returns the color with the
    largest detected area.

    Parameters:
    img (numpy.ndarray): The input image in BGR format.

    Returns:
    str or None: The detected color with the largest area ("red",
    "green", or "gray"), or None
    if no significant color region is foun
    """
    # convert image in HSV scale
    hsv_img = cv2.cvtColor(img, cv2.COLOR_BGR2HSV)

    # definy colour ranges
    color_ranges = {
        "red": [(np.array([0, 100, 100]), np.array([10, 255, 255])),
        (np.array([160, 100, 100]), np.array([180, 255,
255]))], # Red (Hue 0-10)
        "green": [(np.array([40, 40, 40]), np.array([90, 255, 255]))],
# Green (Hue 40-90)
        "gray": [(np.array([0, 0, 50]), np.array([130, 60, 220]))] #
Gray
    }

    kernel = np.ones((3, 3), np.uint8)
    # create a dict to storage the colours
    detected_areas = {}

    # find colours
    for color, ranges in color_ranges.items():
        # create mask colours
        mask = sum(cv2.inRange(hsv_img, lower, upper) for lower, upper

```

```

in ranges)
    # reduce the noisy
    mask = cv2.morphologyEx(mask, cv2.MORPH_OPEN, kernel)

    contours, _ = cv2.findContours(mask, cv2.RETR_EXTERNAL,
cv2.CHAIN_APPROX_SIMPLE)
    detected_areas[color] = sum(cv2.contourArea(c) for c in
contours)

    if contours:
        # draw the contours in black colour
        cv2.drawContours(img, contours, -1, (0,0,0), 2)

if max(detected_areas.values()) > 0:
    dominant_color = max(detected_areas, key=detected_areas.get)

    if dominant_color == 'green':
        # split the image in two sides
        mid = img.shape[1] // 2

        # create a green mask
        green_mask = sum(cv2.inRange(hsv_img, lower, upper) for
lower, upper in color_ranges['green'])

        # calculate moments of image
        moments = cv2.moments(green_mask)

        # find the center of object
        cX = int(moments["m10"] / moments["m00"])

        # find the side
        side = 'on left' if cX < mid else 'on right'
        dominant_color = f'{dominant_color} {side}'

        # return the colour with most area on the image
        return dominant_color
# return none if not has colour in the image
return None

def verify_curve(contours, img_width):
    """
    Checks if there is a curve in the image and identifies its
    direction.

    The function analyzes the detected contours and verifies the
    distribution
    of points relative to the center of the image. If most points are
    on the
    left side, the curve is classified as "Left"; if they are on the
    right side,

```

```

    it is classified as "Right". Otherwise, it returns "No curve".

    Additionally, if the number of points in the contour is too large
    (>= 8),
    it is assumed that the shape is not a sharp curve.

    Args:
        contours (list): List of detected contours in the image.
        img_width (int): Width of the image, used to determine the
        center.

    Returns:
        str: "Left" if the curve is on the left, "Right" if it is on
        the right,
        or "No curve" if no significant curve is detected.
        """

    for contour in contours:
        X = contour[:, 0, 0]

        # Divide a imagem ao meio
        mid = img_width // 2
        points_left = np.sum(X < mid)
        points_right = np.sum(X >= mid)

        # if contour > 8 probably it's not a curve 90
        if len(contour) < 8:
            if points_left > points_right:
                return 'Left'
            elif points_left < points_right:
                return 'Right'
        # return no curve
        return 'No curve'

def detect_line(img):
    """
    Detects lines in the given image using edge detection and Hough
    Transform,
    draws the detected lines, and calculates the error between the
    detected lines
    and a reference flow line.

    Args:
        img (numpy.ndarray): Input image, which should be in BGR
        format.

    Returns:
        float: The calculated error between the detected lines and the
        flow line.
        """

```

```

# verify if img exists
if img is not None:
    # Convert the image to grayscale
    img_gray = cv2.cvtColor(img, cv2.COLOR_BGR2GRAY)

    # Aplly a threshold to detect only darken colours
    _, binary = cv2.threshold(img_gray, 50, 255,
cv2.THRESH_BINARY_INV)

    # reduce the noise
    kernel = np.ones((3, 3), np.uint8)
    binary = cv2.morphologyEx(binary, cv2.MORPH_OPEN, kernel)
    binary = cv2.morphologyEx(binary, cv2.MORPH_CLOSE, kernel)

    # find the edges on the image
    edges = cv2.Canny(binary, 50, 200)

    # Detect points that form a line
    #lines = cv2.HoughLinesP(edges, 1, np.pi/180, 70,
minLineLength=20, maxLineGap=255)
    contours, _ = cv2.findContours(binary, cv2.RETR_EXTERNAL,
cv2.CHAIN_APPROX_SIMPLE)

    # verify if has a symbol on the img
    cor_detected = identify_colour(img)
    if cor_detected:
        print(f'Has the colour {cor_detected} on the image')

    # to debug
    #plt.imshow(binary, cmap='gray')
    #plt.show()

    if contours is not None:
        # drawn the line target
        cv2.drawContours(img, contours, -1, (255, 0, 0), 2)

        #draw the car flow line
        flow_line = draw_line(img)

        # send img_widht as img.shape[1]
        is_curve = verify_curve(contours, img.shape[1])

        # calculate the error
        erro = calculate_error(contours)

        # to avoid false-positive
        if (erro > 0 and erro <= 10) or (erro >= -10 and erro <
0):

```

```

        is_curve = 'No curve'


    print(is_curve)
    # to avoid false-positive
    if cor_detected or is_curve != 'No curve':
        erro = 0

    # return the erro
    return erro
return None

img = cv2.imread('datas/ladrinho3_reto.jpg')
erro = detect_line(img)
plt.imshow(img)
print('The error in degrees:', erro)

```

No curve
The error in degrees: 0




```

img = cv2.imread('datas/ladrinho3_esquerda.jpg')
erro = detect_line(img)
plt.imshow(img)
print('The error in degrees:', erro)


```

No curve
The error in degrees: -10




```
img = cv2.imread('datas/ladrinho3_direita.jpg')
erro = detect_line(img)
plt.imshow(img)
print('The error in degrees:', erro)
```

No curve
The error in degrees: 9




```
img = cv2.imread('datas/ladrinho1_esquerda.jpg')
erro = detect_line(img)
plt.imshow(img)
print('The error in degrees:', erro)
```

Left
The error in degrees: 0




```
img = cv2.imread('datas/ladrinho1_direita.jpg')
erro = detect_line(img)
plt.imshow(img)
print('The error in degrees:', erro)
```

Right
The error in degrees: 0




```
img = cv2.imread('datas/ladrinho5.jpg')
erro = detect_line(img)
plt.imshow(img)
print('The error in degrees:', erro)
```

No curve
The error in degrees: 0




```
img = cv2.imread('datas/ladrinho2_esquerda.jpg')
erro = detect_line(img)
plt.imshow(img);
print('The error in degrees:', erro)
```

No curve
The error in degrees: -40




```
img = cv2.imread('datas/ladrinho2_direita.jpg')
erro = detect_line(img)
plt.imshow(img);
print('The error in degrees:', erro)
```

No curve
The error in degrees: 44




```
img = cv2.imread('datas/ladrilho_verde.jpg')
erro = detect_line(img)
plt.imshow(img);
print('The error in degrees:', erro)
```

Has the colour green on right on the image
No curve
The error in degrees: 0



```
img = cv2.imread('datas/ladrilho_verde_esquerda.jpg')
erro = detect_line(img)
plt.imshow(img);
print('The error in degrees:', erro)
```

Has the colour green on left on the image
No curve
The error in degrees: 0




```
img = cv2.imread('datas/ladrilho_vermelho.jpg')
erro = detect_line(img)
plt.imshow(cv2.cvtColor(img, cv2.COLOR_BGR2RGB))
print('The error in degrees:', erro)
```

Has the colour red on the image

No curve

The error in degrees: 0



```
img = cv2.imread('datas/ladrilho_cinza.jpg')
erro = detect_line(img)
plt.imshow(img);
print('The error in degrees:', erro)
```

Has the colour gray on the image

No curve

The error in degrees: 0

