

Extension to the `kulemt` class*

Luc Van Eycken
`Luc.VanEycken@esat.kuleuven.be`

June 2, 2017

Abstract

The `kulemt` class provides a general L^AT_EX class to typeset a KU Leuven master's thesis. This document style adds some additional features. But none of these features are required by the guidelines of the Faculty of Engineering Science.

1 Using the `kulemtx` document style

The `kulemtx` document style provides currently only some commands to typeset a thesis with a look similar to the `kulemt` manual. The chapter style `kulemtman` and the heading style `kulemtman` are the styles used by the manual. Additionally a command `\kulemtmanToC` is defined to typeset the table of contents similar to the manual.

To enable the styles in your document, you have to use the following commands in your document preamble after loading `kulemtx`:

- To change headings of chapters, sections, . . . , use “`\headstyles{kulemtman}`”.
- To change only headings of chapters, use “`\chapterstyle{kulemtman}`”.
- To change the layout of the table of contents, use “`\kulemtmanToC`”.

In case you were wondering, the document preamble of the manual contains the following snippet:

```
\usepackage{kulemtx}  
\headstyles{kulemtman}  
\kulemtmanToC
```

You can also use the definitions of `kulemtx` as an inspiration for your own modifications. You can copy whatever you want from `kulemtx.sty` to your document preamble and modify it. Make sure you put a “`\makeatletter`” before it and a “`\makeatother`” after it. Of course, you get no support for these kind of modifications.

*This document corresponds to `kulemtx` v0.1, dated 2010/02/28.

2 Implementation of the kulemtx style

The namespace kulemtx is claimed, so all commands are prefixed with kulemtx@ to avoid name clashes. In case you notice that other packages use this prefix too, please contact the author of this class!

2.1 Chapter style kulemtman

This chapter style is based on the BlueBox chapter style.

```
1 \newsavebox\kulemtx@chpnumbox
2 \def\kulemtx@buildchpnum#1#2{\sbox\kulemtx@chpnumbox{%
3   \tabular[t]{@{}c@{}}%
4     \makebox[0pt][c]{\chapnamefont #1\strut}\[.5ex]%
5     \colorbox[gray]{.8}{\color{black}%
6       \rule[-7em]{0pt}{0pt}%
7       {\chapnumfont \hspace{.7ex}#2\hspace{.7ex}\strut}}}%
8   \endtabular}}
9 \makechapterstyle{kulemtman}{%
10   \def\chapnamefont{\sffamily\large}%
11   \def\chapnumfont{\sffamily\Huge}%
12   \def\chaptitelfont{\sffamily\raggedright\huge}%
13   \setlength\beforechapskip\z@skip
14   \setlength\midchapskip{29\p@}%
15   \setlength\afterchapskip{40\p@}%
16   \def\printchaptername{%
17     \def\chapternamenenum{}}%
18   \def\afterchapternum{%
19     \def\printchapternum{%
20       \kulemtx@buildchpnum\@chapapp\thechapter}%
21     \def\printchapternonum{%
22       \kulemtx@buildchpnum{\vphantom{\@chapapp}}{\hphantom{\thechapter}}}%
23     \def\printchaptertitle##1{%
24       \usebox\kulemtx@chpnumbox \hfill
25       \@tempdima\hsize \advance\@tempdima -1em%
26       \advance\@tempdima -\wd\kulemtx@chpnumbox
27       \parbox[t]{\@tempdima}{\vspace\midchapskip
28         \leavevmode \leaders\hrule\@height\p@ \hfill \kern\z@ \par
29         \chaptitelfont ##1\par}}}
```

2.2 Head style kulemtman

```
30 \makeheadstyles{kulemtman}{%
```

First define part title formatting.

```
31 \def\partnamefont{\normalfont\huge\sffamily}%
32 \def\partnumfont{\normalfont\huge\sffamily}%
33 \def\parttitlefont{\normalfont\Huge\sffamily}%
```

Chapters are typeset using the kulemtman style.

```
34 \chapterstyle{kulemtman}%
```

Changing the styling of sections.

```
35 \setsecheadstyle{\Large\sffamily\raggedright}%
36 \setsubsecheadstyle{\large\sffamily\raggedright}%
37 \setsubsubsecheadstyle{\large\sffamily\itshape\raggedright}%
```

Paragraph headings use the small caps shape instead of bold with a medium space before them.

```
38 \setparaheadstyle{\normalsize\scshape}%
39 \setbeforeparaskip{\medskipamount}}
```

2.3 ToC as in the kulemt manual

The table of contents formatting is based on that of the memoir manual.

```
\kulemtmanToC Use the command \kulemtmanToC to reinitialise the necessary parameters.
40 \newcommand*\kulemtmanToC{%
41   \let\cftchapterfont\sffamily
42   \let\cftchapterdotsep\cftdotsep
43   \def\cftchapterleader{\normalfont\cftdotfill{\cftchapterdotsep}}%
44   \def\cftchapterpagefont{}%
45   \setlength\cftbeforechapterskip{\medskipamount}%
46   \setlength\cftbeforesectionskip{\smallskipamount}%
47   \settocdepth{subsection}%
48   \addtodef\cftchapterbreak{\par}{}%
49   \let\cftsubsectionfont\itshape
50   \def\l@section##1##2{%
51     \leftskip\cftsubsectionindent \rightskip\@tocrmarg \parfillskip\fill
52     \ifhmode ,\quad \else\noindent\fi \ignorespaces
53     {\let\numberline\@gobble \cftsubsectionfont ##1}%
54     ~~{\cftsubsectionpagefont ##2}\ignorespaces}}
```