

Session 1: Introduction into fMRI analysis

Dr. Elena Galeano Weber

e.galeano-weber@dipf.de

Education and Human Development & Individualized Learning Laboratory, DIPF | Leibniz
Institute for Research and Information in Education

Who is this seminar for?

- This is a hands-on workshop on functional Magnetic Resonance Imaging (fMRI) analysis for the PsyMSc4 at the Goethe University.
- Very few assumptions are made about previous knowledge on the topic, so this workshop can be a very good entry point for complete beginners from any discipline. Also, the first introductory session could also be suited for non-scientists willing to get a broad idea into what MRI is.

What is this seminar for?

- The workshops will cover **which** are the necessary and common steps when conducting fMRI research and **how** to run them in MATLAB.
- The core Philosophy of the workshop is that one of the main skills that a cognitive neuroscientist should have is the ability to judge what **can** and what **cannot** be done with fMRI experiments from a conceptual level. In order to acquire such a skill, one needs to *understand* fMRI research , i.e., to know the basics of the technique itself and the logic behind the most common analysis.

How is this seminar structured?

The block seminar is structured in three days of ~8 hours each. There will be 2 sessions per day. Each session will be dedicated to a specific processing or analysis step.

Sessions 1 -4 (days 1-3) will start with **theory** and logic behind that day's step and will continue with a **hands-on exercise**. Students will select a particular dataset to use for the hands-on exercises.

Session 5 (day 3) will be dedicated to **students' presentations**. Each student will prepare a short presentation (~15 minutes / ~15 slides) describing the **motivation** of their own study, the **analysis** carried out, the **results** obtained and their **interpretation**.

At the end of the workshop, each student will submit an **individual brief report** (2 pages max) on the **results** obtained with their corresponding dataset and their **interpretation**.

Working in groups is allowed and even encouraged. However, the individual presentations and the reports need to be unique.



Agenda Day 1



Welcome (9:15-9:30)



Session 1: Introduction into fMRI analysis (9:30-10:30)



Coffee Break (10:30 -10:45)



Session 1: Hands-on exercise: Basics of fMRI preprocessing (10:45 – 12:15)



Lunch Break (12:15 – 13:00)



Session 2: Introduction into fMRI analysis (13:00 – 14:00)



Session 2: Hands-on exercise: GLM (14:00 – 15:30)

My Brain in Three Hashtags

Your task: Introduce yourself to the group in max. 1 minute:

Your name


Your academic background (1 sentence)



Three hashtags that describe you or how your brain works

Example hashtags:

#lovesdata #structureplease #boldbutintrovert #VLPFCfan #earlybird
#coffeeBeforeContrasts #notWithoutColorMaps 😊

Part I. Basics of MRI – How does functional MRI work?





Here are the basics of MR imaging -
Scanner

Here are the basics of MR imaging - Scanner



Scanner

Coil

Bed

Here are the basics of MR imaging – MR Safety

Scanner =
big magnet + radio frequency transmitter




big and **very**
strong!

CAUTION!!



loud and
annoying!

CAUTION!!





Here are the basics of MR imaging – MR Safety

Safety: Powerful MRI Magnet:

<https://www.youtube.com/watch?v=dxcr1-gmLQ>

<https://www.youtube.com/watch?v=2oICC8NVtAA>


Here are the basics of MR imaging



Source: <https://www.youtube.com/watch?v=4UOeBM5BwdY>

Here are the basics of MR imaging


Scanner =
big magnet + radio frequency transmitter



When you put something inside a magnetic field, its H protons align (their spin) to the magnetic field.


Here are the basics of MR imaging

Scanner =
big magnet + radio frequency transmitter



Here are the basics of MR
imaging

Scanner =
big magnet + radio frequency transmitter




When the RF pulse stops, the protons reorient to the field
emitting another RF signal.

The time taken is known as relaxation time.


Here are the basics of MR
imaging

Scanner =
big magnet + radio frequency transmitter



Different points in space have different relaxation times, and we can use those differences to reconstruct what is inside the scanner.


So... What are MR images?



If we zoom in, we can see that images are composed of pixels.

The size of each side of the pixel determines the image resolution (1 x 1 mm, in this example).

So... What are MR
images?





Each pixel contains one value (either 1 or 0, in this example).

0	1
---	---


The current color map assigns "black" to 0 and "white" to 1.
But remember that the color map is arbitrary!

So... What are MR images?



When we have a 3D image, we talk about voxels (1 x 1 x 1 mm, in this example).


So... What are MR images?



Most common 3D file formats:

- NifTi (.nii)
- Compressed NifTi (nii.gz)

So... What are MR images?



Voxel size determines our image resolution: smaller = better.

Resolution is (partly) dependent on the strength of the magnetic field.

The earth's magnetic field, at the equator, is approximately 0.00005 T

Common resolutions for different strengths:

1.5 Tesla ~ 3x3x3

3 Tesla ~ 2x2x2

7 Tesla ~ 0.8x0.8x0.8


Part I. Basics of MRI. Recap

- Scanner = magnet + RF transmitter
- MRI relies on the magnetic properties of the tissue.
- MR images are 3D “pictures” composed of voxels with one value per voxel.
- Most common 3D files: NifTi (.nii) and compressed NifTi (nii.gz).
- Spatial resolution depends on scanner strength.



Short break =)

Part II. Types of MR images



Types of MR images*

Anatomical
images


Functional
images

*For the purpose of this seminar only these two types will be covered since they are essential for standard fMRI analysis.

Types of MR images

Anatomical
images
(T1w)

Functional
images



Aim:
Structure
Feats:
Good spatial resolution.
Task free.
Slow acquisition
(~5 min full brain)

Differences in signal strength
caused by different tissue
types.

Types of MR images

Anatomical
images

Functional
images
(T2*)

Aim:
Activity
Feats:
“Good” time
resolution.
Measures blood flow.
Task sensitive.
Fast acquisition
(~2s full brain)




Differences in signal strength
caused by distortions in the
magnetic field.

Types of MR images

Anatomical
images

Functional
images




How to distinguish them?
Inverse contrast!

Types of MR images

Anatomic
images

Functional
images



How to distinguish them?
Inverse contrast!

T1w:

Grey matter – dark
White matter - bright


T2:

Grey matter – bright
White matter - dark

Types of MR images

Anatomic
al images


Functional
images



How to distinguish them?

Functional images have (usually) lower spatial resolution.


Gain in time resolution!



Types of MR images


Anatomic
images

Functional
images



How to distinguish them?

TR = time to sample the entire field (to collect one brain volume).



Types of MR images. Functional images

Functional runs. What are they?


Noise due to scanner drift accumulates over time so collecting images for too long will cause your images to look bad.

Solution: divide your task into shorter blocks, i.e., runs.

Aprox. run duration: ~10 minutes (adults) / ~6 minutes (children).

Max duration: 15 minutes (ideally shorter).


Run duration is often measured in volumes.



Part II. MR images types. Recap

Key ideas


- MR images can be roughly grouped into anatomical and functional images
- Anatomical images (usually one volume) have higher spatial resolution than functional images (usually several volumes)
- TR = time to collect one brain volume.
- Runs = blocks of recording time





Coffee Break
=)

Part III. Image preprocessing



Preprocessing.

Why?


- MR images as a reconstruction problem > This process is never perfect.
- Distortions in MR images can be grouped in two types: temporal and spatial.

Preprocessing.

Why?

MR images as a reconstruction problem > This process is never perfect.

Distortions in MR images can be grouped in two types: **temporal** and spatial.




Preprocessing.


Why?

MR images as a reconstruction problem > This process is never perfect.

Distortions in MR images can be grouped in two types: **temporal** and spatial.



Preprocessing.



Example:

- Before correction: Slice 1 captured at $t = 0s$, slice 20 at $t = 2s$ (for a $TR=2s$).
- After correction: All slices aligned to the midpoint ($t = 1s$) by interpolating intermediate data points.


Preprocessing.

Why?


MR images as a reconstruction problem > This process is never perfect.

Distortions in MR images can be grouped in two types: temporal and **spatial**.


Magnetic field inhomogeneities



“Magnetic field inhomogeneities, caused by susceptibility differences at tissue/air and tissue/bone interfaces, result in significant geometric and intensity distortions. The challenge of reducing these field inhomogeneity effects arises from their spatial dependence. Data from different spatial locations are corrupted to different degrees, with the amount of corruption determined by the local magnetic field environment.” (Gholipour, et al., 2011).



Right-Left



Anterior-Posterior


Preprocessing.

Why?

MR images as a reconstruction problem > This process is never perfect.

Distortions in MR images can be grouped in two types: temporal and **spatial**.


Magnetic field inhomogeneities




While some minor field inhomogeneity can be corrected by (automatic) shimming, much of it cannot...

Two main approaches to tackle the resulting distortions:

- **Field map**, i.e., acquiring a map of the magnetic field
- **Blip up – blip down**, i.e., acquiring an image in the inverted phase - encoding direction (Holland, Kuperman, & Dale, (2010).



Right-Left



Anterior-Posterior



Preprocessing.

Why?

MR images as a reconstruction problem > This process is never perfect.

Distortions in MR images can be grouped in two types: temporal and **spatial**.


Intensity inhomogeneities





Preprocessing.

Why?

Functional MR images are recorded over time > Participants move!




Volumes need to be re-aligned!



Preprocessing.

Why?

Anatomical and functional MR images are recorded at different time points and with different sequences > Volumes need to be registered to each other!



Preprocessing.

Why?

MR images are recorded for multiple individuals > Participants have different brain shapes!

We might want to have a common space for all of them.



Preprocessing.

Why?

MR images are recorded for multiple individuals > Participants have different brain shapes!

Common spaces:

- Native
- MNI
- Sample specific



Part III. Image preprocessing. Recap

Key steps.

- Slice-time correction
- Magnetic field distortions
- Intensity inhomogeneities
- Motion correction
- Registration
- Normalization

Part III. Image preprocessing. Recap

Key steps.

- Slice-time correction
- Magnetic field distortions
- Intensity inhomogeneities
- Motion correction
- Registration
- Normalization

How to do this?

- fMRIPrep (<https://fmriprep.org>)
- SPM
- FSL
- BrainVoyager
- ... and more

Let's get practical.

Software needed:

- MATLAB 2018 or later (<https://www.mathworks.com/>)
- SPM12 (<https://www.fil.ion.ucl.ac.uk/spm/software/spm12/>)
- ITK-Snap 3.8.0 (<http://www.itksnap.org/>)

Data needed:

Know my repository: <https://github.com/lenagaleano/fMRI-method>

All the steps involved in preprocessing take a while to complete (up to several hours sometimes!)

All the images have been already preprocessed with fMRIPrep. You can find them under here:

<https://cloud.educs-hosting.net/s/PE2gKNKqRPJLGgx>