pfi

Python for Fixed Income

COURSE 6 · NEURAL NETWORKS

Case Study: Class Weights on Bankruptcy

WEEK 2 · DAY 5

Created by **Jeff Lenamon**

This course is educational content created in a personal capacity. Nothing here is investment advice or a recommendation to buy or sell any security. All portfolio data is synthetic.

Two halves: the weights, then the case study

Hands-on, sections 10.1 and 10.2

balanced_class_weight: each class counts equally

What class_weight does inside fit

output_vs_rate: what the weights do to the output

Case study, sections 10.3 to 10.10

One setting at a time, by five folds

Class weights, none, or a lower threshold

Beside logistic regression and LightGBM

Paired intervals and a workbook

What it shows, and where it fails

326 of 4,680 training companies went bankrupt (6.97 percent). Do class weights help a network rank them? Promise nothing.

Class weights by hand

```
healthy weight  = n / (2 n0)        bankrupt weight = n / (2 n1)
netkit.balanced_class_weight(y_fit)  # equals compute_class_weight("balanced") within 1e-12
```

0.5375

healthy weight

7.1724

bankrupt weight


13.3448

times a healthy row

On the 3,744 fit rows the weights add up to 3,744.000000, the number of rows, and 0.500000 of the weight sits on bankrupt rows.

To the weighted loss the file looks half bankrupt: the weights pull every output up.

Rows and weight by class



Bankrupt rows: 261 of 3,744 fit rows, and 0.500000 of the weight. Inside a class every row counts the same.

What class_weight does inside fit


1. Each row gets its class's weight (class_weight_to_sample_weights)

2. A batch's loss: sum of weight x log loss, divided by the rows

Weights	Keras	By hand	Keras divides by
balanced	0.213971	0.213971 (weighted mean)	rows = sum of weights
1 and 5	0.283352	0.283352 (rows), 0.221568 (sum)	the number of rows

Source read for the course: Keras 3.15.1, data_adapter_utils.py and losses/loss.py ("sum_over_batch_size").

Loss by epoch, without and with weights



Keras weights the fit rows only: both stopping curves are the plain mean log loss, and the weighted network's sits higher.

What the weights do to the output

Stopping rows	Mean output	Bankrupt share	Ratio	Avg precision
no weights	0.0682	0.0694	0.9826	0.7331
balanced weights	0.1919	0.0694	2.7631	0.7480

The same network on 112 inputs (64 columns and 48 gap indicators), fitted twice on the 3,744 fit rows, stopped on the 936 stopping rows (65 bankrupt).

Allowed names

model probability of bankruptcy in this file

flagged at threshold t

the model's score (class-weighted)


Never called

a credit view on any company

a rating

an investment decision

Each class's outputs



The weights slide the healthy companies' outputs right: mean output 0.1919 against a bankrupt share of 0.0694.

The case study: context, objective, rows

Objective

1. Prepare as Course 4 did
2. One setting at a time, by five folds
3. Weights, none, or a lower threshold
4. Same folds for the earlier models
5. Paired intervals and a workbook
6. What it shows, and where it fails

Fold	Companies	Bankrupt
fold 1	936	65
fold 2	936	65
fold 3	936	65
fold 4	936	65
fold 5	936	66
test	closed	never scored

X1 net profit / total assets; X2 total liabilities / total assets (DATA.md). Attr1 is X1, Attr2 is X2, by position.


Model building by five folds

Kept only if the fold-mean average precision rises and the change is ahead on at least 4 of the 5 folds.

Model	Units	Dropout	Fold mean AP	Fold sd	Pooled AP
Model 1	(16, 8)	0	0.7284	0.0300	0.7206
Model 2	(16, 8)	0.2	0.6946	0.0604	0.6899

Model 2 ahead on 2 of 5 folds: not kept. Model 1 stands: 16 and 8 units, no dropout.

Fold by fold



Model 2 ahead on 2 of 5 folds by a hair, far behind on one. The rule counts folds as well as the mean.


Class weights against a lower threshold

Out of fold	Threshold	Recall	Precision	Flagged
network at 0.5	0.5000	0.5276	0.8557	201
network at recall 0.70	0.1741	0.7025	0.5797	395
weighted network at 0.5	0.5000	0.7454	0.4508	539
weighted network at recall 0.70	0.6073	0.7025	0.5078	451

Pooled average precision: 0.7206 without weights, 0.6732 with them. The weighted network's mean output is 0.1583: a score.

Decision: no class weights. A threshold chosen on out-of-fold outputs reaches recall 0.70 at a higher precision.

Four ways as confusion matrices



At recall 0.70, out of fold

Both catch the same bankrupt companies. Flagged in all: network 395, weighted network 451.


Fewer healthy companies flagged for the same catch: no class weights.

The comparison, by the same folds

Model	Pooled AP	Fold mean AP	Precision at 0.70	Flagged
network	0.7206	0.7284	0.5797	395
weighted network	0.6732	0.6826	0.5078	451
LightGBM	0.7759	0.7783	0.7003	327
logistic regression	0.6497	0.6624	0.4761	481


Fold means reproduce the earlier courses: LightGBM 0.7783, logistic regression 0.6624. Same rows, same folds.

Curves of every configuration



ROC AUC and average precision disagree below LightGBM; the case study reads average precision, set before scoring.


Intervals on the pooled average precision



Network minus	Difference	Lower	Upper
weighted network	0.0474	0.0248	0.0709
LightGBM	-0.0553	-0.0837	-0.0296
logistic regression	0.0709	0.0377	0.1075

Separately the network's interval (0.6739 to 0.7619) overlaps LightGBM's (0.7359 to 0.8129). Paired, LightGBM and the logistic regression are clear of zero; the weighted network is too.

Every model on every set of rows




Avg precision	Fitted	OOF
network	0.8341	0.7206
weighted network	0.8152	0.6732
LightGBM	1.0000	0.7759
logistic regression	0.7206	0.6497

A score on a model's own fitted rows measures fit; no choice today was made on one.


Out of fold the order is the case study's: LightGBM, the network, the weighted network, the logistic regression.

The network's confusion matrices



Recall: fit rows 81.6%, stopping rows 70.8%, out of fold 70.3%.

LightGBM and the logistic regression



Recall: training rows to out of fold

LightGBM 100.0% to 70.3%; logistic regression 76.4% to 70.3%.

Out of fold is the panel to compare.

What the model shows, and where it fails

At the network's threshold	Attr1 median	Attr2 median	Companies
bankrupt, missed	0.0203	0.5564	97
bankrupt, flagged	-0.1195	0.7634	229
healthy, flagged	-0.0588	0.7156	166
healthy, not flagged	0.0549	0.4295	4,188

Attr1: net profit / total assets. Attr2: total liabilities / total assets. Missed bankruptcies look sound on paper; flagged healthy companies show a loss.

63 of the 97 bankruptcies the network misses are missed by all three models. Outputs correlate 0.8759 with LightGBM's.

Excel side by side

Excel side by side (tested in Excel)

`=ROWS(A2:A3745)/(2*COUNTIF(A2:A3745,1))`	bankrupt weight: 7.1724
`=IF(A2=1,$F$2,$F$1)`	each row's weight, in C2, filled down
`=SUMPRODUCT(C2:C3745,D2:D3745)/SUM(C2:C3745)`	weighted mean log loss: 0.213971
`=SUM(C2:C3745)`	the number of rows: 3,744
`=SUMPRODUCT(C2:C3745,A2:A3745)/SUM(C2:C3745)`	share on bankrupt rows: 0.5000
`=COUNTIFS(A2:A4681,1,C2:C4681,1)`	bankrupt flagged: 229; precision 0.5797
`=PERCENTILE.INC(D2:D1001,0.025) and 0.975`	minus LightGBM -0.0837 to -0.0296

No network training, class weights in a fit, cross-validation, or seeded bootstrap in Excel. Every number equals Python's.

Save the week: week1 and week2

1. Week 1

netkit cut back; git tag week1

2. Week 2

today's netkit, byte for byte

3. Log

four cv rows; git tag week2

```
git diff --stat week1 week2
netkit.py      | 235 ++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++
results.csv    |   5 ++
test_netkit.py | 210 ++++++++++++++++++++++++++++++++++++++++++++++++++++++++++
3 files changed, 450 insertions(+)
```

43 tests pass. mlkit.py and ensemblekit.py are not in the list: week 2 never changed them.

The AI check

The docstring is the prompt. The code that comes back runs, and its number looks fine.

1

Docstring

Which rows fit, which rows stop, which rows report: what you asked for.

→

2

Code back

Written for the course in the style of an AI answer. Read it.

→

3

Test first

Assert what the docstring promises. Run it: it fails.

→

4

Fix

Find the rule it broke, fix it, run the test again.

Today: the keys are swapped, so the bankrupt rows carry 0.0056 of the weight instead of half.

Code that runs is not the same as code that is right.

What you can do now

- Work out balanced class weights, and why they add to n
- Say what class_weight does inside fit
- Show a weighted network's output is a score
- Weights against a lower threshold, out of fold
- Paired intervals; what it shows and where it fails

Week 3, Day 11 Windows and walk-forward on the yield curve