pfi

Python for Fixed Income

COURSE 1 · PYTHON FOUNDATIONS

pandas: Combining and Loading

WEEK 2 · DAY 3

Created by **Jeff Lenamon**

This course is educational content created in a personal capacity. Nothing here is investment advice or a recommendation to buy or sell any security. All portfolio data is synthetic.

By the end of today you can

Join tables on a shared column

The job VLOOKUP does, with the row count checked.

```
pd.merge(holdings, ratings, on='rating')
```

Summarize by group

Counts, totals, and averages. In Excel, a pivot table.

```
book.groupby('bucket')['oas'].mean()
```

Report a weighted average

Market-value-weighted OAS and duration.

```
book['oas'] * book['market_value']
```

Save results, work with dates

A CSV or an Excel workbook. Date text as real dates.

```
pd.to_datetime(book['maturity'])
```

Yesterday one table. Today, several.

Each file comes from a different system. A shared column, the key, links one to the next.

`positions.csv`

200 bonds

Six columns. A ticker, and nothing else about the issuer.

`ticker` →

`issuers.csv`

150 issuers

Name, sector, country, and rating. One row per ticker.

`rating` →

`ratings.csv`

18 ratings

A score, a bucket, and a grade for each rating.

`holdings.csv`

200 bonds

Yesterday's file. The same bonds, with all 19 columns.

`cusip` →

`benchmark.csv`

821 bonds

What the portfolio is measured against. Invented, too.

Two ways to combine

`merge`
side by side, adds columns

`concat`
stacked, adds rows

merge: a lookup across tables

```
named = pd.merge(positions, issuer_details, on='ticker')
```

on= names the column to match on: the key. It appears once in the result.

positions: three of its six columns

ticker	coupon	par_held
BEZE	7.000	5000000
BEZH	8.125	250000
BEZL	5.125	1500000

+

issuer_details: one row per ticker

ticker	issuer	sector	rating
BEZE	Bezane Finance	Financials	BBB-
BEZH	Bezamyth Machinery	Industrials	B
BEZL	Bezoquil Freight	Transportation	BB

Check the count

200 rows in, 200 rows out. Six columns became nine.

named: every position now carries its issuer, its sector, and its rating

ticker	coupon	par_held	issuer	sector	rating
BEZE	7.000	5000000	Bezane Finance	Financials	BBB-
BEZH	8.125	250000	Bezamyth Machinery	Industrials	B
BEZL	5.125	1500000	Bezoquil Freight	Transportation	BB

In Excel

```
=VLOOKUP(B2, issuers!A:C, 3, FALSE)
```

Filled down 200 rows, once for each column wanted.

how= decides which rows are kept

desk_small

ticker	face
QVNE	1500000
DNMR	500000
PLWK	750000
HLVF	250000

sector_small

ticker	sector
QVNE	Energy
DNMR	Transportation
PLWK	Materials
THAR	Materials

```
left_join = pd.merge(
    desk_small, sector_small,
    on='ticker', how='left')
  ticker     face          sector
0   QVNE  1500000          Energy
1   DNMR   500000  Transportation
2   PLWK   750000       Materials
3   HLVF   250000             NaN
```

how='inner'

Keys found in both tables. The default.

QVNE DNMR PLWK HLVF THAR

3 rows HLVF and THAR dropped

how='left'

Every row of the left table. Like a VLOOKUP.

QVNE DNMR PLWK HLVF THAR

4 rows HLVF kept, its sector is NaN

how='right'

Every row of the right table.

QVNE DNMR PLWK HLVF THAR

4 rows THAR kept, its face is NaN

how='outer'

Every key from either table.

QVNE DNMR PLWK HLVF THAR

5 rows Nothing dropped

A merge can add rows, and no error says so

desk_small: 4 rows

ticker	face
QVNE	1500000
DNMR	500000
PLWK	750000
HLVF	250000

+

sector_twice: QVNE is listed twice

ticker	sector
QVNE	Energy
QVNE	Energy
DNMR	Transportation
PLWK	Materials
HLVF	Consumer

→

doubled: 5 rows from a left merge

ticker	face	sector
QVNE	1500000	Energy
QVNE	1500000	Energy
DNMR	500000	Transportation
PLWK	750000	Materials
HLVF	250000	Consumer

Face before the merge

3,000,000

4 rows in the desk's table.

→

Face after the merge

4,500,000

5 rows. QVNE is counted twice.

The habit

Print the row count before and after every merge.

The cure: a lookup table with each key once. Check it with nunique().

Two guards written into the code

8.3 A repeated key: validate= stops the merge

```
pd.merge(desk_small, sector_twice,
         on='ticker', how='left',
         validate='many_to_one')
MergeError: Merge keys are not unique in
right dataset; not a many-to-one merge
```

many_to_one: many positions on the left, one row per key on the right. On the issuer details it passes: 200 rows in, 200 out.

In Excel VLOOKUP returns the first match and gives no sign of a second. The test: `=COUNTIF(A:A, A2)` on the lookup sheet, filtered for values above 1.

8.9 Identifiers are text: dtype={'cusip': str}

```
as_numbers = pd.read_csv(io.StringIO(typed_file))
0   9900123   1000000
as_text = pd.read_csv(io.StringIO(typed_file),
                      dtype={'cusip': str})
0  009900123   1000000
```

The file holds 009900123. Read as a number, the leading zero is gone, and a merge on that column would match nothing, with no error.

In Excel A double-click on the CSV shows 9900123 as well. Data, From Text/CSV, with that column set to Text, keeps the zero.

The portfolio against the benchmark, as counts

```
desk_face = holdings[['cusip', 'par_held']]
compared = pd.merge(benchmark, desk_face,
                    on='cusip', how='left')
print('Rows:', compared.shape[0])
Rows: 821
```

cusip	ticker	weight_pct	par_held
99001BAA4	QVNE	0.2076	2750000.0
99001BAB2	QVNE	0.1551	NaN
99001BAC0	QVNE	0.0245	NaN
99001BAD8	QVNE	0.2024	NaN

The benchmark's 821 bonds. Each box is as wide as its share of the benchmark's weight.

200 held
24.56 percent of the weight

621 not held
75.44 percent of the weight

`left_only`

621 In the benchmark alone

`both`

200 In both files

`right_only`

0 Held, and not in the benchmark

Two invented files. Counts and weights that describe the overlap. Not a view.

concat stacks tables and adds rows

Two tables with the same 22 columns

ig_book
128 rows

hy_book
72 rows

→

stacked
200 rows, 22 columns
Market value 490,819,215

```
stacked = pd.concat([ig_book, hy_book])
print('Stacked:', stacked.shape)
Stacked: (200, 22)
```

Row labels where the first table ends and the second begins

As stacked	198	199	**1**	**2**
`ignore_index=True`	126	127	128	129

merge

Side by side. Adds columns. Matches the rows on a key.

concat

Stacked. Adds rows. Lines the columns up by name.

In Excel


Paste one sheet under another, or =VSTACK(). Excel pastes by position.

groupby: split, apply, combine

```
book.groupby('sector')   ['market_value']   .sum()
```

How to split the rows | The column to use | The calculation

In Excel, a pivot table: sector in Rows, Sum of market_value in Values.



Seven more sectors follow. Ten totals, in alphabetical order. The index is the sector.

The same pattern	pandas
A mean, by rating bucket	`book.groupby('bucket')['oas'].mean()`
Several statistics at once	`book.groupby('grade')['oas'].agg(['count', 'mean', 'median', 'min', 'max'])`
A summary table, column by column	`book.groupby('sector').agg(bonds=('cusip', 'count'), ...)`

A typical bond, or a typical dollar

Simple average OAS 185.75

Every bond counts the same.

```
book['oas'].mean()
```

```
=AVERAGE(M2:M201)
```


Weighted average OAS 180.46

Each bond counts in proportion to its market value.

```
(book['oas'] * book['market_value']).sum()
    / book['market_value'].sum()
```

```
=SUMPRODUCT(M2:M201, S2:S201) / SUM(S2:S201)
```


Technology: 298.2 simple, 228.2 weighted. The three widest of its 12 bonds explain the gap.



ticker	rating	oas
FESR	CCC+	1551
FESR	CCC+	614
LORE	BB-	334

Neither figure is wrong. They answer different questions, about an invented portfolio.

Simple against weighted, by sector



Close in most sectors

The grey and green bars are within about 16 bp of each other

Technology is the exception

298 simple, 228 weighted: a gap of 70 bp

Why

The wide bonds are small positions, so dollars weight them less

Week 3 teaches charts. For now, read the picture and check it against the notebook.

A pivot table, a rule, and a file

```
pd.pivot_table(book, values='market_value',
               index='sector', columns='grade',
               aggfunc='sum', margins=True)
```

sector	High Yield	Investment Grade	All
Materials	38,747,115	32,954,502.5	71,701,617.5
Telecom	27,796,585	28,051,685	55,848,270
All	169,901,850	320,917,365	490,819,215

```
book['price_label'] = book['price'].apply(
    price_label)
Discount    113
Premium      87
```

apply runs a rule on every value

One price in, one label out. In Excel, a nested IF. np.where() gives the same labels on the whole column: prefer it.

Saving: to_csv() writes a table to a file, and read_csv() reads it back

`book.to_csv(file)`

25 columns saved, 26 read back. The row numbers return as a stray column.

`index=False`

25 saved, 25 read back. Row numbers carry no information, so leave them out.

`sector_summary.to_csv(file)`

A grouped table keeps its index. It holds the sector names.

Dates arrive as text

As loaded: text. It cannot be subtracted.

```
0    2032-06-18
1    2029-04-17
2    2030-06-03
Name: maturity, dtype: str
```

`pd.to_datetime()` →

Converted: real dates

```
0   2032-06-18
1   2029-04-17
2   2030-06-03
Name: maturity, dtype: datetime64[us]
```

The parts, with .dt

`year`	**2032**
`month`	**6**
`day_name()`	**Friday**

```
days_left = (book['maturity'] - as_of).dt.days
book['years_to_maturity'] = days_left / 365.25
```


Shortest	Longest	Average
1.0	**29.9**	**9.85**

Years to maturity as of 2026-09-30, by calendar days. An approximation, not the 30/360 count used to price these bonds.

pd.cut() sorts the years into buckets. Each box is as wide as its share of the 200 bonds.

0 to 3	3 to 7	7 to 15	15 and over
28 bonds	51 bonds	88 bonds	33 bonds
75,125,702.5	123,242,385	228,787,395	63,663,732.5

The maturity profile



7 to 15 years is the tallest

About 229 million of the 491 million

3 to 7 years follows

About 123 million

Built from three steps

to_datetime, years to maturity, then pd.cut and groupby

Week 3 teaches charts. For now, read the picture and check it against the notebook.

Excel workbooks: write, read back, two sheets

```
book.to_excel('desk_report.xlsx',
              sheet_name='book', index=False)
from_excel = pd.read_excel('desk_report.xlsx',
    sheet_name='book', dtype={'cusip': str})
Read back: (200, 30)
Market value read back: 490,819,215
```

What survived the trip: the type of three columns

column	saved	read back
cusip	str	str
maturity	datetime64[us]	datetime64[us]
maturity_bucket	category	str

A workbook stores a date as a date, where a CSV stores it as text. The bucket labels survive and their order does not. No formula makes the trip: pandas writes what Paste Special, Values would leave.

```
with pd.ExcelWriter('desk_report.xlsx') as writer:
    book.to_excel(writer, sheet_name='book', index=False)
    sector_summary.to_excel(writer, sheet_name='by_sector')
book: (200, 30)
by_sector: (10, 5)
```

pandas	Excel
to_excel()	File, Save As, Excel Workbook
read_excel()	File, Open, then the sheet's tab
pd.ExcelWriter	Two sheets, each with its own tab

The AI check

Every notebook ends with code written in the style of an AI assistant. It has one bug. Find it.

1

Read

Read the code before you run it.

→

2

Predict

Decide what it should produce.

→

3

Run

Run it and look at the output.

→

4

Check

Compare with a number you worked out yourself.

Code that runs is not the same as code that is right.

What you can do now

- Join tables, guard the merge with validate=, and compare with a benchmark by CUSIP
- Summarize by sector, rating bucket, or grade, and lay it out as a pivot table
- Report a market-value-weighted OAS or duration
- Save to a CSV file or an Excel workbook, and turn date text into dates
- Put tables side by side, join on the index, and style a comparison

Tomorrow Case study: three tables from three systems, and a first look at each