pfi

# Python for Fixed Income

COURSE 8 · IMPLEMENTING AGENTIC AI

# MCP: Connecting Data Sources

WEEK 2 · DAY 3

Created by **Jeff Lenamon**

This course is educational content created in a personal capacity. Nothing here is investment advice or a recommendation to buy or sell any security. All portfolio data is synthetic.

# Today: MCP, connecting data sources

### Day 6: tools in the notebook

| | |
|---|---|
| `tool_schema` | describes each function |
| `run_tools` | runs it in this process |
| `agent_loop` | holds it together |

### Today

1. What MCP is
2. course_server
3. The in-process client
4. mcp_tool_schemas
5. One question, local and through MCP
6. The same server over stdio
7. Version 2's names
8. What MCP adds, and not

**Every model response in the notebook is a saved response, replayed. A live run can differ.**

# The rules for agents

### What an agent produces: text, every number from a tool, wherever the tool runs

| Allowed names | Never called |
| --- | --- |
| the agent returned | the agent's opinion or view |
| the saved run | what the agent believes |
| the brief states | the agent's advice |

### On the Treasury curve: a level, a change, a slope from the file, never a view on rates

| Allowed names | Never called |
| --- | --- |
| the 10 Yr par yield in the file | a forecast or an outlook |
| the change in bp between two dates | a signal |
| the slope in bp | a view on rates |

# A server, a client, and a protocol

### Model

receives a tool list,

returns tool requests

### Client: your loop

lists the tools, sends

each request on

### Server

lists its tools, runs

them, returns results

**tool list and requests (JSON, as on day 2)**

**MCP: list_tools, call_tool (the model never sees it)**

## changes

where the tool runs

## unchanged

what the model is sent

## mcp 2.3.0

MCPServer, not FastMCP

**The agent loop stays on the client side, as on day 2: the model is sent a tool list and returns tool requests.**

# course_server: your own tools, served

```
market = agentkit.market_tools(curve, spreads)   # {name: function}, as run_tools takes
server = agentkit.course_server(market)
# server: course-data; class: MCPServer
```

## docstring

becomes the description

## type hints

become the input schema

## WARNING

so stderr stays empty

**The docstring is still the prompt. It now travels through a server.**

# The in-process client: list_tools and call_tool

```
treasury_yield     required ['tenor', 'as_of']
curve_on           required ['as_of']
curve_change_bp    required ['tenor', 'start', 'end']
slope_bp           required ['short', 'long', 'as_of']
synthetic_spread   required ['kind', 'as_of']
```

| | |
|---|---|
| **a date in the file: is_error False** | `{ "tenor": "10 Yr", "as_of": "2026-10-02", "yield_pct": 5.28 }` |
| **the date left out: is_error True** | `Error executing tool treasury_yield: 1 validation error for treasury_yieldA...` |
| **a date the file lacks: is_error False** | `{ "error": "no row for that date in the curve file: 2026-10-03 10 Yr" }` |

**Two kinds of error: arguments the schema refuses (the server's), an answer the data lacks (the tool's).**

# mcp_tool_schemas: the listing in the raw loop's format

**treasury_yield as MCP lists it**

```
{"type": "object", "properties": {"tenor": {"title": "Tenor", "type": "string"}, "as_of": {"title": "As
Of", "type": "string"}}, "required": ["tenor", "as_of"], "title": "treasury_yieldArguments"}
```

**the same tool, converted: titles gone, Args: descriptions added, required kept**

```
{"type": "object", "properties": {"tenor": {"type": "string", "description": "the tenor as the file labe
ls it: 1 Mo, 3 Mo, 6 Mo, 1 Yr, 2 Yr, 3 Yr, 5 Yr, 7 Yr, 10 Yr, 20 Yr, 30 Yr."}, "as_of": {"type": "string
", "description": "the date as YYYY-MM-DD, for example 2026-10-02."}}, "required": ["tenor", "as_of"], "
additionalProperties": false}
```

**Equal to tool_schema's for all five tools: the model can be sent the same list, byte for byte.**

# One question, local and through MCP

```
run_local = ask(QUESTIONS["change"], market)                    # agent_loop, tools in this process
run_mcp = await mcp_loop(session, QUESTIONS["change"])          # tools on the server: one await
```

### Request keys of the two saved runs (first 12 characters)

```
local  '2fa97943a81f', '2b8929ae57c8', '726ee6b407b9'

MCP    '2fa97943a81f', '2b8929ae57c8', '726ee6b407b9'
```

**same request keys: True  same answer: True  figures 2 of 2 passed**

Model gpt-4.1-mini-2025-04-14, temperature 0, seed 42; 3 requests, 3,432 prompt and 263 completion tokens; saved run recorded 2026-10-11; replayed (no key loaded).

**The model's side of the run cannot tell where the tools ran.**

# The same server over stdio: a separate process

**This notebook: the client**

```
stdio_client, ClientSession, mcp_loop
```

**course_server.py: its own process**

```
server.run("stdio")
```

stdin and stdout: the protocol  stderr: a log file

**2025-11-25**

protocol version

**True**

same request keys

**0 bytes**

the server's stderr

A tool that raised would write a traceback to stderr. The course's tools return an error result instead.

# Version 2's names: an import that now fails

```
from mcp.server.fastmcp import FastMCP      # the version 1 import most tutorials give
```

```
No module named 'mcp.server.fastmcp'
This is mcp 2.x, where FastMCP was renamed to MCPServer (from mcp.server.mcpserver import MCPServ...
see the migration guide at https://py.sdk.modelcontextprotocol.io/v2/migration/#fastmcp-renamed-t...
pin 'mcp<2' to keep running v1 code.
```

```
from mcp.server.mcpserver import MCPServer   # version 2: what the message says
```

**Read a migration message last part first. The course keeps version 2; it does not pin mcp<2.**

# What MCP adds, and what it does not

| | Day 6 | Through MCP |
|---|---|---|
| Tool list sent | tool_schema | mcp_tool_schemas: the same |
| Where a tool runs | this kernel | the server's process |
| Wrong argument shape | "wrong arguments" | is_error, pydantic's text |
| A date the file lacks | the tool's error | the same, passed through |
| Request bodies | agent_loop's | the same keys |
| A figure | check_figures, yours | check_figures, yours |

```
local  figures 2, passed 2; values [27.0, 45.0]
MCP    figures 2, passed 2; values [27.0, 45.0]
stdio  figures 2, passed 2; values [27.0, 45.0]
```

**MCP carries tools and checks their arguments' shape. It checks no number.**

# Excel and Git

### Excel side by side (tested in Excel)

| | |
|---|---|
| `=(INDEX(B2:O2941,MATCH(Q2,A2:A2941,0),12)-INDEX(B2:O2941,MATCH(Q1,A2:A2941,0),12))*100` | 27 |
| `=(INDEX(B2:O2941,MATCH(Q2,A2:A2941,0),12)-INDEX(B2:O2941,MATCH(Q2,A2:A2941,0),8))*100` | 45 |
| `=INDEX(B2:O2941,MATCH(Q3,A2:A2941,0),12)` | #N/A |

**Excel against the tools on the same file: 3 of 3 rows the same. Excel has no MCP client.**

```
agentkit.py | 79 ++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++
course_server.py | 19 +++++++++++++++
test_agentkit.py | 47 ++++++++++++++++++++++++++++++++++
```

**course_server.py committed with the day's code. 45 passed.**

# The AI check

The docstring is the prompt. The agent code that comes back runs and looks right.

1

## Docstring

Properties and the required list, exactly as the server lists them.

→

2

## Code back

Written for the course in the style of an AI answer. Read it.

→

3

## Test first

Every tool's required list must survive. Run it: it fails.

→

4

## Fix

Copy required with the properties. 5 of 5 kept.

**Today: the converter copies the properties and drops required, so every argument looks optional to the model.**

*Code that runs is not the same as code that is right.*

# What you can do now

- A server lists and runs tools; a client connects
- course_server from your own functions
- mcp_tool_schemas, required kept
- Through MCP: the same request keys
- stdio as its own process, stderr in a file; MCP checks no number

**Week 2, Day 4** The framework: the loop in the Agents SDK