pfi

Python for Fixed Income

COURSE 3 · MARKET DATA AND TIME SERIES

Rolling Windows and Volatility

WEEK 2 · DAY 2

Created by **Jeff Lenamon**

This course is educational content created in a personal capacity. Nothing here is investment advice or a recommendation to buy or sell any security. All portfolio data is synthetic.

Five choices behind one number

Choice	This course
Rows or calendar days?	Rows: 21, 63, 252 (about 1, 3, 12 months)
Which rows?	Trailing: the window ends on today
Window not full yet?	No value: NaN until it is full
Sample or population?	Sample: ddof=1, Excel STDEV.S
Per day or per year?	Per day, unless the name says _annual

The desk's question

How much has the 10-year yield been moving lately? One number answers it: a volatility.

Volatility describes how much a series moved over its window. It says nothing about what comes next.


A window in rows against a window in days

`rolling(21)`

The last 21 rows. Every full window holds 21 changes.


`rolling("30D")`

Every row in 30 calendar days: from 18 to 22 rows, by weekends and holidays.



This course counts windows in rows: 21, 63, and 252, called about one month, three months, one year. Conventions, not calendar months.

Trailing, right-aligned, and min_periods



A 3-row mean: each value is that row and the two before it. The partial column looks the same and is over fewer rows.

Excel: a relative range, filled down (tested)

`=AVERAGE(B2:B4)` in C4, filled down

C5 becomes =AVERAGE(B3:B5). C2 and C3 stay empty, like NaN.

`=AVERAGE(OFFSET(B4,-2,0,3,1))` in D4

Two rows up, three rows tall: the same window. Both columns: 2.00, 3.33, 3.67, 5.00.

Full windows only: min_periods equals the window. A blank is honest.

rolling_vol_bp: volatility of daily changes in bp

```
def rolling_vol_bp(changes_bp, window=63, annualise=False):
    """...sample standard deviation over a trailing window..."""
    _check_series(changes_bp, "changes_bp")
    vol = changes_bp.rolling(window, min_periods=window).std(ddof=1)
    if annualise:
        vol = vol * math.sqrt(TRADING_DAYS_PER_YEAR)
    return vol
```

5.29 bp

21-row volatility of the 10 Yr on the last date, per day

2.4e-14


bp: the largest gap from Excel's STDEV.S on 190 dates

```
=STDEV.S(F3:F23)  in G23, filled down
```

Always on daily changes, never on levels. The first change is NaN, so pass change_bp(...).dropna().

20 NaN, then the first full window. It describes how much the yield moved, nothing more.

The volatility, built from the changes



How to read it

Top: the daily changes in bp. Bottom: their standard deviation over the 21 rows ending on each date.

The line rises after a run of big bars and falls when the bars shrink.

Each point uses only the 21 rows up to its date.

Sample against population

	Divides by	pandas	NumPy	Excel
Sample	n - 1	`.std()`	`np.std(x, ddof=1)`	`STDEV.S`
Population	n	`.std(ddof=0)`	`np.std(x)`	`STDEV.P`

5.294651 bp

sample, last 21 changes

5.167051 bp

population, the same 21

1.024695


ratio: sqrt(21 / 20)

The trap

np.std() is population; pandas .std() is sample. Name ddof.

Excel: =STDEV.P(F3:F23) beside STDEV.S. STDEV.S of one value shows #DIV/0!.

Sample against population, drawn




Read the two panels

Left: sample is a little larger for the same 21 changes. Right: the gap shrinks as the window grows.

The choice matters most for short windows.

Annualising: the factor, labelled



5.29 bp

21-row volatility, per day

84.05 bp

the same, per year: x sqrt(252)

```
=G23*SQRT(252)  in I23, filled down
```

Never 252 in this file. Other desks use other factors.

252 is a convention. Per day by default; per year only with annualise=True and a name ending _annual.

Lookahead and assert_no_lookahead


Lookahead: a number for date t that uses data from after t. The test: the output up to t is the same whether the series stops at t or runs on.




```
shift(-1):  up to 2025-04-17, 7.8057 bp from the full series, nan from the cut one
```

From today every window function has a no-lookahead test. 29 tests pass.

shift(-1) lets a date see the next day




What the picture shows

The dashed line is the solid line moved one date to the left. On the cut date it already shows the next day's value.

A series cut at the date has no next day: the two runs disagree, and the test fails.

21, 63, and 252 rows on one chart



bp per day, over the file

21 rows

low 1.98, high 14.27

on 2026-10-02: 5.29

63 rows

low 2.57, high 9.43

on 2026-10-02: 4.63

252 rows

low 3.23, high 8.26

on 2026-10-02: 4.22

Excel side by side

Excel side by side (tested in Excel)

`=STDEV.S(F3:F23)  (G23)`	21-row volatility, sample
`=STDEV.P(F3:F23)  (H23)`	population, beside it
`=G23*SQRT(252)  (I23)`	per year, the factor in sight
`=STDEV.S(F3:F65)  (J65)`	63 rows
`=STDEV.S(F3:F254)  (K254)`	252 rows
`=AVERAGE(OFFSET(D64,-62,0,63,1))  (M64)`	63-row mean with OFFSET

Each written once in the first row with a full window, filled down over 2,940 rows, and compared with Python on every row: gaps below 1e-12 bp.

The window is the range. Where the first formula goes is min_periods.

Save the day: yesterday's file, and back

1. Morning

Commit the start-of-day files

2. Evening

Commit today's two files

3. Look back

restore --source=HEAD~1: 389 lines

4. Come back

restore: 417 lines again

```
git -C "{work}" restore --source=HEAD~1 marketdata.py   # yesterday's file in the folder
git -C "{work}" restore marketdata.py                   # back to the last commit
```

The commits never change; only the file in the folder does. Check git status before a plain restore.

The AI check

The docstring is the prompt. The code that comes back runs, and has one data bug.

1

Docstring

Units, conventions, and what it must never do: what you asked for.

→

2

Code back

Written for the course in the style of an AI answer. Read it.

→

3

Test first

Assert what the docstring promises. Run it: it fails.

→

4

Fix

Find the rule it broke, fix it, run the test again.

Today: trailing_vol_bp uses rolling(63, center=True): each value uses the 31 rows after its date.

Code that runs is not the same as code that is right.

What you can do now

- Count windows in rows, trailing, full windows only
- rolling_vol_bp: sample standard deviation of daily changes in bp
- Sample against population: STDEV.S, STDEV.P, and the NumPy default
- Annualise by sqrt(252) only when labelled: a convention
- Prove no future data with assert_no_lookahead

Week 2, Day 3 Z-scores and percentile ranks: where today sits in its own history