pfi

Python for Fixed Income

COURSE 5 · ADVANCED MACHINE LEARNING

Gradient Boosting From Residuals

WEEK 2 · DAY 2

Created by **Jeff Lenamon**

This course is educational content created in a personal capacity. Nothing here is investment advice or a recommendation to buy or sell any security. All portfolio data is synthetic.

Gradient boosting: three moves

1. Start from the mean

Every bond's fitted value is the average log spread.

2. Fit a tree to residuals

What the fit leaves over: target minus fit.

3. Add a fraction of it

Learning rate times the tree's output. Back to 2.

```
fitted = fitted + learning_rate * tree.fit(X, y - fitted).predict(X)
```

The benchmark: Course 4's 615 training bonds, target log_oas. Synthetic bonds; a fitted spread is never a fair value.

How gradient boosting works

1. Start at the mean

every bond's fit is the average log spread

2. Take the residuals

log spread minus the current fit

3. Fit a small tree

to those residuals, not to the spreads

4. Add a fraction

learning rate times the tree's output; repeat

You control

n_estimators, learning_rate, and the depth of the trees.

What comes out

A fitted GradientBoostingRegressor: predict is a fitted log spread, staged_predict the fit after every round.

Round 0: start from the mean

4.8776

mean log spread

131.3 bp

after exp: a geometric mean

354.1335

squared residuals to shrink

```
f0 = y.mean()
residual = y - f0
```

A residual is positive for a bond wider than the level and negative for a tighter one.

How a regression tree splits

1. Try every split

each threshold of every column

2. Two means

each side gets the mean of its residuals

3. Score it

the sum of squared residuals left over

4. Keep the lowest

a stump is that one split

You control

The depth and the columns offered.

What comes out

A question and two numbers, which round 1 scales by the learning rate and adds to the mean.

The first stump, by hand

The split that leaves the smallest squared residuals


```
score <= 9.5
```

The stump splits the rating scale between BBB and BBB-.

	Left (score <= 9.5)	Right
Bonds	327	288
Leaf value (mean residual, log)	-0.5401	0.6132
After round 1, learning rate 0.1	124.4 bp	139.6 bp

Round 0 had every bond at 131.3 bp. Round 1 moves each side a tenth of the way, in log units.

The stump, drawn: averages either side of the split



150.5
score

347.0
duration

347.3
years

Squared residuals left by each column's best split; 354.1335 before any split. Solid steps: the leaf values. Dashed: the tenth round 1 adds.

Each round of boosting is this picture again.

boost_by_hand: equal to the library within 1e-12


```
fitted = np.full(n, target.mean())
for _ in range(n_rounds):
    tree = DecisionTreeRegressor(...).fit(X, target - fitted)
    fitted = fitted + learning_rate * tree.predict(X)
```


Bond	oas (bp)	after 1	after 10	after 100
99130AAC6	49	118.4	75.6	53.8
99035JAB5	59	118.4	75.6	59.4
99143NAC3	22	118.4	61.2	33.7

100 rounds of depth-2 trees by hand equal GradientBoostingRegressor on all 615 bonds. 28 tests pass at the end of today.

Jerome H. Friedman, "Greedy function approximation: A gradient boosting machine.", The Annals of Statistics, vol. 29, issue 5, October 2001. Source, read 5 October 2026: the Crossref record (DOI 10.1214/aos/1013203451). Bibliographic facts only; the paper itself was not read for this course.


Round by round: the training error and three bonds





Measured on the bonds the model was fitted on: it describes the fit. Section 7.4 scores bonds the model did not see.

One round at a time: the fit above, the residuals below



The staircase gains a step wherever the residuals still lean to one side, and the residual cloud flattens toward zero: fit a tree to what is left over, drawn.

How the held-out curve works

1. Cut five folds

of the 615 training bonds

2. Fit on four

score the fifth: a fitted value from a model that never saw it

3. Stage the fit

staged_predict: every round from one fit

4. Score in bp

mean absolute error after exp


You control

The folds, the settings compared, and the metric.

What comes out

A curve of held-out error against rounds for each setting.

The learning rate against the number of rounds



Rate	Lowest	At round	At 300
0.30	33.6	86	35.6
0.10	34.9	923	36.6
0.05	35.8	973	38.2
0.01	39.0	1000	42.1

These curves describe; they do not choose. The comparison uses one setting fixed before looking: 300 rounds at 0.05.


Depth: one feature at a time, or two together


300 rounds, score and years	2 to 20 years, score 5	score 12	difference	trees on both
Stumps	0.2179	0.2179	0.0000	0
Depth 2	0.2126	0.2606	0.0481	160

Cross-validated MAE (bp), 300 rounds	Stumps	Depth 2
Score and years	39.9	40.7
Score, duration, and years	40.0	36.2

In logs the generator adds a rating term and a maturity term: no interaction, and stumps win. Duration is computed from the yield, which includes the spread, and with it depth 2 wins.

Depth, drawn: parallel curves, then a moving gap





At learning rate 0.05	Round 100	Round 300
stumps	44.2	40.0
depth 2	40.2	38.2
depth 3	38.2	37.1

These lines describe the folds; they do not choose a depth.

Boosting beside Course 4's OLS: cross-validated MAE in bp

Features	OLS (Course 4)	Boosting, stumps	Boosting, depth 2
Without coupon	41.7	40.0	38.2
With coupon	37.2	37.2	37.1

Coupon partly restates the spread (Course 4). With it, what is left for trees to find is small.

Allowed names

fitted spread

the model's spread for these characteristics

residual


Never called


fair value or fair spread

cheap, rich, mispriced

a signal or a trade

Where the two miss: residual plots in bp, without coupon





Without coupon	Misses over 100 bp	Largest miss (bp)	Average residual, 49 bonds above 400 bp
OLS	47	1,701	+133
Boosting, depth 2	43	1,238	+104

How the error by group works

1. Fold residuals

log spread minus the fit that did not see the bond

2. Group the bonds

by years to maturity

3. Average each group

near zero means the pattern is matched

4. Read the shape

a model that misses leaves one

You control


The column and the cut points.

What comes out

A table and a chart of mean residual by group. It judges no bond.

Where the gain comes from: the generator's cap at 10 years

```
oas = BASE_OAS[score] * (0.70 + 0.30 * min(years_to_maturity, 10) / 10) * ...
```



42.3

OLS, bp

40.7


depth 2, bp

39.9

stumps, bp

Score and years only. A straight line in years cannot bend at 10; one tree question, years <= 10, can. Day 12 writes the cap as a feature.

The maturity term: the generator beside the fits



The generator rises to 10 years, then stops. OLS has one slope: too little before 10, too much after. Boosted stumps put their steps where the data bends.

Day 12 writes the cap as a feature and gives OLS the bend by hand.

How the classifier works

1. Start at log-odds

of the default rate

2. Take the gap

outcome minus the current probability

3. Fit a tree to it

the gradient of the log loss

4. Add a fraction

to the log-odds; logistic at the end

You control

Rounds, learning rate, depth, and the share of rows per tree.

What comes out

A model whose predict_proba is the model probability of default in the file.

How the histogram version works

1. Bin each column

at most 255 bins

2. Try bin edges only

far fewer splits per round

3. Grow leaf by leaf

best split first, up to 31 leaves

4. Same rounds

fit the residuals, add a fraction

You control

max_iter, learning_rate, max_leaf_nodes, min_samples_leaf, l2_regularization.

What comes out

The same kind of model, much faster on tens of thousands of rows.

Two names for later

GradientBoostingClassifier

Start at the log-odds of the default rate; fit each tree to outcome minus probability, the gradient; add a fraction to the log-odds. XGBoost and LightGBM (days 8 and 9) build on it.

HistGradientBoostingRegressor

Columns in at most 255 bins; only the bin edges are tried. Trees grown by a number of leaves; missing values taken as they are. Named today, not fitted.

Every setting of GradientBoostingRegressor

Setting	Default	Tune first?
n_estimators	100	tune first
learning_rate	0.1	tune first
max_depth	3	tune first
subsample	1.0	tune first
min_samples_leaf	1	
max_features	None	
loss	'squared_error'	
init	None	
n_iter_no_change	None	


Read it by group

Rounds and learning rate trade against each other. Tree shape decides what a round can learn. Subsample and max_features are a mild brake. The loss decides what the residuals are. 21 settings, read from the signature.

The four to tune first


learning_rate and n_estimators together, max_depth, and subsample. Days 11 to 14 search the shaded rows.

One setting at a time, held out



Depth is where the fitted and held-out lines part. On 615 bonds bigger leaves hurt, and the absolute-error loss is not the lowest even though the metric is an absolute error.

Pairs of settings, and the other two classes



With 615 bonds, trees fitted on half of them lose more than the randomness gives back.

The other two classes

GradientBoostingClassifier: the regressor's settings, except alpha, and the default loss is log loss.

HistGradientBoostingRegressor: max_iter for n_estimators; adds max_bins, l2_regularization, categorical_features, and two constraint settings; min_samples_leaf defaults to 20.

Excel side by side: one round from residuals

Excel side by side (tested in Excel)

`=AVERAGE(B2:B616)`	round 0: 4.8776
`=B2-E2`	residual, column F
`=AVERAGEIFS(F2:F616,A2:A616,"<="&M2)`	left leaf -0.5401
`=AVERAGEIFS(F2:F616,A2:A616,">"&M2)`	right leaf 0.6132
`=E2+$M$1*IF(A2<=$M$2,$M$5,$M$6)`	round 1, column G
`=AVERAGE(ABS(EXP(B2:B616)-EXP(D2:D616)))`	MAE 38.2 bp

No gradient boosting function in Excel. Round 2 repeats the three steps; both rounds equal the library on all 615 bonds.

Save the day: git log -p -1 -- ensemblekit.py

1. Morning

Files as day 6 left them

2. Code

boost_by_hand and mae_bp

3. Results

results.csv, cross-validated

```
model,features,rows,mae_bp,r2
OLS,rating_sector_duration_years_amount,cv,41.7166,0.8799
boosting_stumps,score_sector_duration_years_amount,cv,40.0452,0.8871
boosting_depth_2,score_sector_duration_years_amount,cv,38.1729,0.8999
```

The patch skips the results commit and shows the code commit: + lines only, adding def boost_by_hand and def mae_bp.

The AI check

The docstring is the prompt. The code that comes back runs, and its number looks fine.

1

Docstring

Which rows fit, which rows choose, which rows report: what you asked for.

→

2

Code back

Written for the course in the style of an AI answer. Read it.

→

3

Test first

Assert what the docstring promises. Run it: it fails.

→

4

Fix

Find the rule it broke, fix it, run the test again.

Today: each tree is fitted to y, not the residual: 100 rounds, 4 distinct fitted values.

Code that runs is not the same as code that is right.

What you can do now

- Each round: a small tree on the residuals, a fraction added
- A regression stump is a search for the smallest squared residuals
- boost_by_hand equals GradientBoostingRegressor to 1e-12
- A learning-rate chart describes; it does not choose
- Stumps add one feature at a time; depth 2 adds interactions

Week 2, Day 3 XGBoost, regularization, and early stopping