pfi

Python for Fixed Income

COURSE 3 · MARKET DATA AND TIME SERIES

SQL With sqlite3

WEEK 3 · DAY 1

Created by **Jeff Lenamon**

This course is educational content created in a personal capacity. Nothing here is investment advice or a recommendation to buy or sell any security. All portfolio data is synthetic.

Week 3 opens: the book in a database

Courses 1 and 2 answered every question about the book with pandas. On many desks the same data sits in a database, and SQL is how you ask it. Today the synthetic book goes into one database file.

Every query sits beside its pandas version, and an assert proves the two return the same rows.

No live cells today: everything comes from the course's files, so no FRED key is needed.

Week 3: SQL, AI, and the snapshot

Day 1	**SQL With sqlite3**
Day 2	SQL joins, time series
Day 3	Working with an AI assistant
Day 4	The daily market snapshot
Day 5	The capstone

Why SQL: you already know most of it

Job	pandas	SQL
Pick columns	`holdings[["cusip", "oas"]]`	`SELECT cusip, oas FROM holdings`
Pick rows	`holdings[holdings["oas"] > 200]`	`WHERE oas > 200`
Sort, first five	`.sort_values(...).head(5)`	`ORDER BY oas DESC LIMIT 5`
Group and total	`.groupby("sector").agg(...)`	`GROUP BY sector, COUNT, SUM, AVG`
Keep some groups	`a filter after groupby`	`HAVING`
Join	`pd.merge(...)`	`JOIN`

Assistants write SQL readily, and it runs whether it is right or not. Read it, then check it against pandas.

sqlite3: a database in one file

One file

The whole database is a file the program reads and writes. No server, no password.

Built in

Python ships the sqlite3 module: SQLite 3.50.4 here.

Everywhere

"Likely used more than all other database engines combined."

```
connection.execute("SELECT 7 / 2, 7 / 2.0")
7 / 2 = 3, 7 / 2.0 = 3.5
```

Two whole numbers divide as whole numbers. Write * 1.0 on a count.

SQLite, "Single-file Cross-platform Database" and "Most Widely Deployed and Used Database Engine", sqlite.org (read 2026-10-04).

load_tables: CSV in, counts checked

```
frame = pd.read_csv(csv_path)
frame.to_sql(name, connection, if_exists="replace")
# read the count back and check it
SELECT COUNT(*) FROM {name}
```

A table name cannot be a ? parameter, so only plain names (letters, digits, underscore) are allowed.


Seven tables, each count checked

holdings	200 rows
issuers	150 rows
ratings	18 rows
benchmark	821 rows
trades	374 rows
treasury	35,728 rows
spreads	2,940 rows

```
b'SQLite format 3\x00'
```

A database file is binary and rebuilt in one call: *.db stays in .gitignore.

Wide to long: what melt leaves out



41,160

cells in the wide file: 2,940 dates by 14 tenors

35,728

rows with a yield: the long table keeps only these

Late starters: 1.5 Month has 408 rows, 2 Mo 1,991, 4 Mo 989. A missing yield is a missing row, not a blank.

SELECT, WHERE, ORDER BY, LIMIT

```
SELECT cusip, issuer, market_value
FROM holdings
WHERE sector = ? AND oas > ?
ORDER BY market_value DESC
LIMIT ?
```

`run_query`

One query, a DataFrame back; values through params; the connection closed.


`assert_same_rows`

Sorted by your keys, index reset; text exact, decimals to rtol 1e-12.


Without ORDER BY, a database promises no order: LIMIT 5 alone is five rows, not the first five.

Dates are ISO text, YYYY-MM-DD: year first, so < on text compares in date order. They come back as text; convert with pd.to_datetime.

What WHERE and LIMIT keep



WHERE keeps the dark bars above the dashed line: the rows the query returned.



ORDER BY ... DESC puts the largest first; LIMIT 5 cuts the list after five.

Values go in as ? parameters

Pasted into the SQL with an f-string, a value becomes SQL: a quote can break the query or change it. A ? parameter is sent separately and is only ever a value.


A ticker with a quote, pasted: O'BRN

```
DatabaseError: ... near "BRN": syntax error
```

A value that rewrites the question: NONE' OR '1'='1

```
pasted into the SQL: 200 rows
as a ? parameter:    0 rows
```

This is SQL injection. Only a checked table or column name ever goes into the text.



GROUP BY, then HAVING

```
SELECT sector, COUNT(*) AS bonds
FROM holdings
WHERE oas > ?          -- rows first
GROUP BY sector
HAVING COUNT(*) >= ?   -- then groups
ORDER BY sector
```

The clauses, always in this order


`SELECT`	`FROM`
`WHERE`	`GROUP BY`
`HAVING`	`ORDER BY`
`LIMIT`	

WHERE filters rows before grouping. HAVING filters groups after. A single row has no COUNT.

HAVING COUNT(*) >= 20 keeps 7 of 10 sectors. 46 tests pass at the end of the section.


GROUP BY, drawn

Sector	Bonds	Market value ($)	Avg OAS (bp)
Materials	26	71,701,618	182.42
Financials	26	68,219,672	172.31
Consumer	26	56,629,598	218.88
Telecom	21	55,848,270	182.38
Industrials	20	52,540,745	220.55
Transportation	20	48,822,898	126.50
Health Care	20	38,908,188	141.75
Energy	17	38,830,005	171.59
Technology	12	30,311,760	298.17
Utilities	12	29,006,462	177.92




Styled table: .format is Format Cells, .bar is Data Bars, .background_gradient is Color Scales, .highlight_max is a Top/Bottom rule.

HAVING, drawn



HAVING COUNT(*) >= 20 keeps 7 of 10 sectors. Three sit exactly on the line.



WHERE filters rows before grouping; HAVING filters groups after.

A market-value weighted average in SQL

```
SUM(oas * market_value) / SUM(market_value) AS weighted_oas
```


AVG(oas) gives every bond the same say. The weighted average gives every dollar the same say, and bondmath.weighted_average is the answer key.

180.46

weighted OAS in bp, 200 bonds (synthetic)

185.75

simple AVG(oas) in bp, same bonds



A query that writes AVG where the question said weighted runs, looks plausible, and is wrong.

Excel side by side

SQL	Excel (tested; long ranges shortened)	Energy
COUNT(*) … GROUP BY	`=COUNTIFS($C$2:$C$201,J2)`	17
SUM(market_value)	`=SUMIFS($F$2:$F$201,$C$2:$C$201,J2)`	38,830,005
AVG(oas)	`=AVERAGEIFS($E$2:$E$201,$C$2:$C$201,J2)`	171.5882
WHERE … AND oas > 200	`=COUNTIFS(...,J2,$E$2:$E$201,">200")`	3
weighted OAS	`=SUMPRODUCT((C=J2)*E*F)/SUMIFS(F,C,J2)`	176.3494

WHERE is FILTER; ORDER BY ... DESC LIMIT 5 is TAKE(SORTBY(...,-1),5); HAVING is FILTER on the summary block.

A pivot table does the whole GROUP BY at once: 10 sectors, Grand Total 200 bonds.

Every formula typed into Excel 16.0 build 20527 by a script on 2026-11-02, equal to the SQL and pandas results.

Save the day: the database stays out

```
git check-ignore -v course3.db
.gitignore:5:*.db    course3.db
git status --short --ignored
!! course3.db
```

Committed: four text files

```
.gitignore
marketdata.py
test_marketdata.py
queries.sql
```

Binary, rewritten on every load, rebuilt from the CSVs in one call: the CSVs and the code are the record.

The AI check

The docstring is the prompt. The code that comes back runs, and has one data bug.

1

Docstring

Units, conventions, and what it must never do: what you asked for.

→

2

Code back

Written for the course in the style of an AI answer. Read it.

→

3

Test first

Assert what the docstring promises. Run it: it fails.

→

4

Fix

Find the rule it broke, fix it, run the test again.

Today: "weighted OAS by grade" written as AVG(oas). It runs and returns plausible spreads; bondmath disagrees.

Code that runs is not the same as code that is right.

What you can do now

- A SQLite database in one file, kept out of Git with *.db
- load_tables: CSVs to tables, every row count checked
- SELECT, WHERE, ORDER BY, LIMIT, each proved against pandas
- Every value as a ? parameter, never an f-string
- GROUP BY with HAVING; a weighted OAS that bondmath agrees with

Week 3, Day 2 SQL joins and time series: matching tables, the duplicating join, and dates in SQL