pfi

Python for Fixed Income

COURSE 9 · DEPLOYMENT

The Credit Desk as a Service

WEEK 2 · DAY 3

Created by **Jeff Lenamon**

This course is educational content created in a personal capacity. Nothing here is investment advice or a recommendation to buy or sell any security. All portfolio data is synthetic.

Today: the desk as a service

Today

1. The desk without a key: Course 8 in replay
2. Why a snapshot: size, and what replay answers
3. desk_snapshot: the brief, every exchange hashed
4. desk_app: four endpoints, the refusal first
5. The live switch, and the platform's secrets
6. The guardrail, checked on the served JSON
7. Deploying it: the course's deploy, recorded
8. The deploy log

Nothing is sent

To a model

the brief replays from saved runs

To Vercel

the cloud steps are recorded

The server never holds a key.

Freeze what the desk returned, trace every figure, and serve that.

What the deployed desk serves, and never

Descriptive only	what documents state, the curve between dates, the book's DV01
Every response dated	figures as of 2026-10-02, next year too
A view is refused first	before anything is looked up
No key, synthetic holdings	a real company only as a document's author

What the service serves

Allowed names

the brief as of 2026-10-02

the check table

the saved run

Never called

the desk's view

advice or a call

a recommendation

The desk without a key

```
OpenAI key loaded: False. Mode: replay.
```

59	10	21	53	2
saved exchanges	covenant rows	brief requests	checks passed	checks failed

The run line: where every figure came from

Model gpt-4.1-mini-2025-04-14, temperature 0, seed 42; 21 requests, 39,691 prompt and 6,154 completion tokens;

saved run recorded 2026-10-11; replayed (no key loaded).

The two failures are Course 8's own. A service serves them beside the passes.

Why a snapshot

	Replay service	Snapshot service
Requirements	20	1 (fastapi)
Distributions	94	11
Installed here (Windows)	923.4 MB	9.6 MB
Linux, read by day 4	about 5,716.5 MB	about 9.2 MB

Largest in the replay: torch 452.8 MB, scipy 102.8 MB, transformers 47.9 MB

A question nobody recorded, to the replay

```
LookupError: no saved exchange for request ab75aca0dc68 in day15
```

Vercel's bundle limit is 500 MB. And a replay answers only what was recorded: 3 graded answers.

desk_snapshot: the brief, frozen as data

desk_snapshot.json

25,853 bytes of JSON

as_of 2026-10-02, mode replay

the brief and 55 checks

the run line, the disclaimer

3 graded answers

21 keys, each with a SHA-256

Course 8's input rule, as data

Every figure traces to a file

a figure in the brief

-> names the tool request that computed it

-> which lives in a saved exchange

-> a file whose SHA-256 anyone can recompute

checked in the notebook: 21 of 21

An exchange missing from the folder raises ValueError: a snapshot holds only what was saved.

desk_app: four endpoints, the refusal first

Endpoint	Returns
GET /health	version, as_of, mode
GET /brief	the three sections, as_of
GET /checks	the 55 checks, as_of
POST /ask	see the order on the right

POST /ask, in order

1. a view? 200, refused, the refusal line

2. recorded? 200, its saved answer

3. anything else: 404, not in the saved runs

```
200 refused: True rule: opinion words <- Which of these bonds should the desk buy?
200 refused: True rule: an ordering of securities <- Rank the three issuers' indentures.
200 refused: True rule: opinion words <- Where will the 10-year yield be next month?
200 refused: True rule: a real issuer beside a holding <- Is Lamar a holding in this portfolio?
```

Status 200 for a refusal: the request was understood and answered. A 4xx would call it malformed.

The live switch, and where secrets live

```
nothing set, as on the course's deployments  {'mode': 'replay', 'key_loaded': False}
DESK_MODE live, no key  {'mode': 'replay', 'key_loaded': False}
DESK_MODE live and a key  {'mode': 'live', 'key_loaded': True}
```

The key in any response: no. The settings hold key_loaded, never the key.

On a platform: environment variables, in the project's settings, never in a file.

Vercel: a changed environment variable applies only to new deployments (vercel.com/docs/environment-variables, read 2026-10-12).

Vercel: a Secret is write-only once saved (vercel.com/docs/environment-variables/sensitive-environment-variables, read 2026-10-12).

The course sets neither DESK_MODE nor a key. Going live is your own key, and your own budget.

The guardrail at the API

Served section	Real issuers	Synthetic issuers	CUSIPs	Document ids
macro	0	0	0	0
documents	0	0	0	2
portfolio	0	0	0	0

Course 8's separation checks, as served: 4 of 4 passed.

Nothing served puts a real company beside a holding: checked on the JSON a stranger receives.

Deploying it

pfi-desk-service

```
app.py
bondmath.py
deploykit.py
desk_snapshot.json
requirements.txt (fastapi)
.python-version (3.13)
README.md
```

What the platform printed, masked

```
Recorded 2026-10-12, on the course's account, masked
Directory ~\projects\pfi-desk-service
Detected FastAPI (Output Directory: N/A)
? Created student/pfi-desk-service
Previous build caches not available.
Build Completed in /vercel/output [8s]
? Aliased https://student.vercel.app
? Ready in 21s
```

Vercel Python: project files reachable at build time are bundled (vercel.com/docs/functions/runtimes/python, read 2026-10-12).

The deployed service: /brief and /ask

```
> curl.exe -s -w "`nHTTP status %{http_code}`n" https://student.vercel.app/brief
{"as_of":"2026-10-02","mode":"replay","brief":{"macro":{"text":"The FOMC post-meeting statement o...
HTTP status 200
the deployed /brief is the test client's /brief here, every figure: yes
```

```
> $body = '{"question": "Which of these bonds should the desk buy?"}'; $r = Invoke-WebRequest -Us...
HTTP status 200
X-Desk-Refused: true
{"question":"Which of these bonds should the desk buy?","answer":"REFUSED: this course asks only ...
```

The snapshot travelled with the app; the rule ran on Vercel with no agentkit installed.

Excel side by side: what the recording cost

Excel side by side (tested in Excel)

`B2:B3, tokens of 59 exchanges`	110,907 and 11,833
`C2:C3, prices per token`	0.0000004 and 0.0000016
`=SUMPRODUCT(B2:B3,C2:C3)`	0.0632956000
`=B2*C2+B3*C3`	0.0632956000
`=SUMPRODUCT(B2:B3,D2:D3)`	0 (D2:D3: prices as text)

textkit.usage_cost: 0.0632956000, equal within 1e-12. Type prices as numbers.

The AI check

The docstring is the prompt. The deploy code that comes back runs and looks finished.

1

Docstring

Units, conventions, and what the code must never let through: what you asked for.

→

2

Code back

Written for the course in the style of an AI answer. Read it.

→

3

Test first

Plant the case the docstring promises to catch. Run it: it fails.

→

4

Fix

Find the rule it broke, fix it, run the test again.

Today: the settings keep the key "for debugging", and /health returns them to anyone.

Code that runs is not the same as code that is right.

What you can do now

- Replay the desk with no key; a replay answers only what it recorded
- Ship a snapshot: one requirement, every exchange hashed
- desk_app: dated responses, 404s with a reason, refusals first
- live_settings: a mode and a yes or no, never a value
- The guardrail on the served JSON; 36 tests; the deploy logged

Week 2, Day 4 Streamlit and Gradio front ends