


# Comparing models of irrational behaviour against individual variance

Lenard Dome and Andy Wills

Apr 11, 2022

## XKCD: 2323



## Structure

1. The framework
2. The tools
3. The phenomenon
4. The method
5. The findings

# The framework: *local* model behaviour

- The traditional approach used in all areas of Psychology
- A measure of how well a model accommodates an already observed data pattern

| A measure of how well a model accommodates (reproduces) and already-observed data pattern.

```
if (model_value == human_aggregate):  
    print("Good Model")  
else:  
    print("Bad Model")
```


# The framework: *global* model behaviour

Roberts and Pashler (2000) pointed out three distinct areas not covered by a goodness-of-fit:


1. *prediction* What does the model say will happen?
2. *heterogeneity* Between-subject variability is not explained by goodness-of-fit.
3. *\*a priori\* likelihood* How likely that the model will be a good fit?

We evaluate models on these neglected areas of formal modelling.

# The tools: parameter space partitioning



- *To model behavior, we need to know how models behave* (Pitt, Kim, MNavarro, Myung, 2006)
- MCMC method to define disjointed regions in the parameter space
- Tells us what unobserved results the model predicts


We implemented the technique in an  package:

psp

 R-CMD-check passing downloads 3297 cran v0.1 license GPL (>= 3)




## The tools: g-distance



---

The relationship between these sets will be our measure


## The tools: g-distance



---

Sufficiency of accomodation  $\alpha = \frac{|M \cap H|}{|H|}$


## The tools: g-distance



---

Breadth of prediction  $\beta = \frac{|M \cap H'|}{|H'|}$





*g-distance* is then the distance between our model and an [ideal model in an ideal scenario]

$$g = \sqrt{w_{\alpha}(1 - \alpha)^2 + (1 - w_{\alpha})(0 - \beta)^2},$$

# The phenomenon: the inverse base-rate effect

## Abstract Design

Training	Test
$AB \rightarrow common$ x3	A, B, C
$AC \rightarrow rare$ x1	BC


- Participants overwhelmingly prefer  $BC \rightarrow rare$
- $BC \rightarrow rare$  is observed even when:
  - participants have high accuracy
  - participants have low accuracy
  - stimuli are pictures, colours, symptoms, person characteristics

See Don, Worthy and Livesey (2021)'s excellent paper for a more thorough review.

## Method: ordinal patterns

Ordinal patterns are a qualitative description of a relationship between an independent variable as defined by at least one of the dependent variables.

### Directed Graph



### Inequality Matrices



	$\emptyset$	A	B	BC	C
$\emptyset$		1	1	1	-1
A			0	-1	0
B				-1	0
BC					0
C					

## Method: procedure

### Empirical

- We implemented IBRE in the simplest way possible
- Stopped data collection at 117 participants
- Confirmed group-level results

### Computational

- All models were implemented in `catlearn`  
- Ran PSP for each participant on different ordinal complexities
- Models we tested: EXIT, NNCAG, DGCM

# The findings: results

| The computer was on a figurative 🔥

- There are 3 possible patterns.
- Hmans showed all three.

```
## [[1]]
##      ∅ BC
## ∅ NA -1
## BC NA NA
##
## [[2]]
##      ∅ BC
## ∅ NA 1
## BC NA NA
##
## [[3]]
##      ∅ BC
## ∅ NA 0
## BC NA NA
```

pattern <i>g-distance</i> accomodation prediction				
EXIT	BC	0.47	1.00	0.67
NNCAG	BC	0.43	0.91	0.55
DGCM	BC	0.47	1.00	0.67

## The findings: results (increasing complexity)

- There are 19 possible patterns
- Humans showed 17 of them.

```
## [[1]]
##      ∅   A BC
## ∅  NA  1  1
## A   NA NA -1
## BC NA NA NA
```

pattern <i>g-distance</i> accomodation prediction				
EXIT	BC, A	0.67	0.20	0.41
NNCAG	BC, A	0.61	0.18	0.19
DGCM	BC, A	0.53	0.38	0.42

## The findings: results (increasing complexity more)

- There are 171 possible patterns
- Humans showed 41 of them.
- EXIT showed 70 of them (41%) - independent of trial order.

```
## [[1]]
##      ∅  B BC  C
## ∅  NA  1  1  0
## B  NA NA  0 -1
## BC NA NA NA -1
## C  NA NA NA NA
```

	pattern	<i>g-distance</i>	accomodation	prediction
EXIT	BC, B, C	0.67	0.08	0.14
NNCAG	BC, B, C	0.65	0.09	0.07
DGCM	BC, B, C	0.57	0.20	0.12

# The findings: conclusion

## Methodological

- Developed a novel method to evaluate aspects of computational models often neglected

## Theoretical

- Provided evidence against EXIT, the best model of IBRE
  - *EXIT has an issue of flexibility when trial-order is not accounted for*
- The most adequate model is a non-associative learning model, DGCM
  - *but it suffers from a metatheoretical issue*






# The End



Lenard Dome






*Buy me a coffee*

-  lenard.dome@plymouth.ac.uk
-  @lenarddome
-  @lenarddome



Andy Wills

-  andy.wills@plymouth.ac.uk
-  @ajwills72
-  @ajwills72



UNIVERSITY OF  
PLYMOUTH  
School of Psychology



Economic  
and Social  
Research Council



BRIC

BRAIN RESEARCH & IMAGING CENTRE