

# 给你的礼物: c919b45075}

1.刚开始直接给了一部分flag，扫描目录看到主页index.php

```
[14:00:46] Scanning:  
[14:01:00] 302 - 1KB - /index.php → p1.php  
[14:01:00] 302 - 1KB - /index.php/login/ → p1.php
```

2.直接访问主页用burpsuit抓包，Ctrl+R发送到重发器->发送，看到index.php内容

请求		响应	
美化	Raw	Hex	页面渲染
1 GET /index.php HTTP/1.1			<?php
2 Host: node4.anna.nssctf.cn:28991			header('Location: p1.php');
3 Accept-Language: en-US			highlight_file(__FILE__);
4 Upgrade-Insecure-Requests: 1			if (\$_GET['a'] == 'index') {
5 User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/127.0.6533.100 Safari/537.36			echo substr(getenv('FLAG'), 0, 11);
6 Accept:			}
text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,image/apng,*/*;q=0.8,application/signed-exchange;v=b3;q=0.7			?>
7 Accept-Encoding: gzip, deflate, br			
8 Connection: keep-alive			

3.改请求包，get传参a=index->发送得到flag第一部分

请求		响应	
美化	Raw	Hex	页面渲染
1 GET /index.php?a=index HTTP/1.1			<?php
2 Host: node4.anna.nssctf.cn:28991			header('Location: p1.php');
3 Accept-Language: en-US			highlight_file(__FILE__);
4 Upgrade-Insecure-Requests: 1			if (\$_GET['a'] == 'index') {
5 User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/127.0.6533.100 Safari/537.36			echo substr(getenv('FLAG'), 0, 11);
6 Accept:			}
text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,image/apng,*/*;q=0.8,application/signed-exchange;v=b3;q=0.7			?> NSSCTF{fd62

然后跟随重定向,看到p1内容

## 请求

美化 Raw Hex

```
1 GET /p1.php HTTP/1.1
2 Host: node4.anna.nssctf.cn:28991
3 Accept-Language: en-US
4 Upgrade-Insecure-Requests: 1
5 User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64)
   AppleWebKit/537.36 (KHTML, like Gecko) Chrome/127.0.6533.100
   Safari/537.36
c Accent.
```

## 响应

美化 Raw Hex 页面渲染

```
<?php
header('Location: p2.php');
highlight_file(__FILE__);
if ($_POST['name'] == 'p1') {
    echo substr(getenv('FLAG'), 11, 11);
}
?>
```

4. 将请求方式改成POST，加入请求头Content-Type: application/x-www-form-urlencoded，post传参name=p1

发送得到flag第二部分

## 请求

美化 Raw Hex

```
1 POST /p1.php HTTP/1.1
2 Host: node4.anna.nssctf.cn:28991
3 Accept-Language: en-US
4 Upgrade-Insecure-Requests: 1
5 User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64)
   AppleWebKit/537.36 (KHTML, like Gecko) Chrome/127.0.6533.100
   Safari/537.36
6 Accept:
   text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/
   webp,image/apng,*/*;q=0.8,application/signed-exchange;v=b3;q=0.7
7 Accept-Encoding: gzip, deflate, br
8 Connection: keep-alive
9 Referer: http://node4.anna.nssctf.cn:28991/index.php?a=index
0 Content-Type: application/x-www-form-urlencoded
1 Content-Length: 7
2
3 name=p1
```

## 响应

美化 Raw Hex 页面渲染

```
<?php
header('Location: p2.php');
highlight_file(__FILE__);
if ($_POST['name'] == 'p1') {
    echo substr(getenv('FLAG'), 11, 11);
}
?> 6d22-2c08-4
```

5. 再跟随重定向，看到p2.php内容

## 请求

美化 Raw Hex

```
1 GET /p2.php HTTP/1.1
2 Host: node4.anna.nssctf.cn:28991
3 Accept-Language: en-US
4 Upgrade-Insecure-Requests: 1
5 User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64)
   AppleWebKit/537.36 (KHTML, like Gecko) Chrome/127.0.6533.100
   Safari/537.36
6 Accept:
   text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/
   webp,image/apng,*/*;q=0.8,application/signed-exchange;v=b3;q=0.7
7 Accept-Encoding: gzip, deflate, br
8 Connection: keep-alive
9 Referer: http://node4.anna.nssctf.cn:28991/p1.php
0
```

## 响应

美化 Raw Hex 页面渲染

```
<?php
header('Location: p3.php');
highlight_file(__FILE__);
if ($_COOKIE['name'] == 'p2') {
    echo substr(getenv('FLAG'), 22, 11);
}
?>
```

6. 加入请求头Cookie: name=p2->发送，得到flag第三部分

注意：下面要保持两行空行

## 请求

美化 Raw Hex

```
1 GET /p2.php HTTP/1.1
2 Host: node4.anna.nssctf.cn:28991
3 Accept-Language: en-US
4 Upgrade-Insecure-Requests: 1
5 User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64)
   AppleWebKit/537.36 (KHTML, like Gecko) Chrome/127.0.6533.100
   Safari/537.36
6 Accept:
   text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/
   webp,image/apng,*/*;q=0.8,application/signed-exchange;v=b3;q=0.7
7 Accept-Encoding: gzip, deflate, br
8 Connection: keep-alive
9 Referer: http://node4.anna.nssctf.cn:28991/p1.php
0 Cookie: name=p2
1
```

## 响应

美化 Raw Hex 页面

```
<?php
header('Location: p3.php');
highlight_file(__FILE__);
if ($_COOKIE['name'] ==
    echo substr(getenv(
})
?> bd1-bf54-75
```

7.继续跟随重定向得到最后一部分

## 响应

美化

Raw

Hex

页面渲染

给你的礼物: c919b45075}