

Notes 8

Definition, usage, and examples of the following commands:

cat

- **Definition:**
 - Used to display content of a file.
- **Usage/Formula:**
 - `cat + option + files to display`
- **Example:**
 - Display content of a file located in a specific directory.
 - `cat + ~/Documents/sample_files/Code/helloWorld.py`
 - Display content of a file with line numbers.
 - `cat + -n + ~/Documents/sample_files/Code/helloWorld.py`

tac

- **Definition:**
 - Used to display content of a file in reverse order.
- **Usage/Formula:**
 - `tac + option + files to display`
- **Example:**
 - To display content of a file located in a specific folder:
 - `tac + ~/Documents/Code/helloWorld.py`
 - To display content of multiple files:
 - `tac + ~/Documents/receipts.py + ~/Documents/bills.sh`

head

- **Definition:**
 - It displays the top N number of lines of a given file. By default, it prints the first 10 lines.
- **Usage/Formula:**
 - `head + option + file name`
- **Example:**
 - Display the first 10 lines of a file:
 - `head + ~/Documents/Book/dracula.txt`
 - Display the first 5 lines of a file:
 - `head + -5 + ~/Documents/Book/dracula.txt`
 - Display the first line of multiple files using wildcards:
 - `head + -n +1 + Csv/*.csv Code/*.py`
 - Display the name of the file in the output:
 - `head + -v + -n + 7 + Json/joke.json`

tail

- **Definition:**
 - It displays the last N number of lines of a given file. By default, it prints the last 10 lines.
- **Usage/Formula:**
 - `tail + option + file name`
- **Example:**
 - Display the last 5 lines of a file:
 - `tail + -5 + ~/Documents/sample_files/bills.pdf`
 - Display the first 5 lines of multiple files:
 - `tail + -n 5 + Txt/{dracula,war-and-peace}.txt`
 - Display a given number of bytes instead of lines:
 - `tail + -c 50 + Txt/Dracula.txt`

cut

- **Definition:**
 - Used to extract a specific section of each line of a file and display it to the screen:
- **Usage/Formula:**
 - `cut + option + file name`
- **Example:**
 - Display a list of all users in your system:
 - `cut + -d ':' -f1 + /etc/passwd`
 - Display a list of users in your system with their login shell:
 - `cut + -d ':' -f1,7 + /etc/passwd`
 - Cut a range of bytes per line:
 - `cut + -b 1-5 + usernames.txt`

sort

- **Definition:**
 - Used for sorting files in alphabetical, reverse order, by number and by month. It follows the following rules unless specified otherwise: lines starting with numbers appear first, alphabetical order is followed next, lowercase appears before uppercase.
- **Usage/Formula:**
 - `sort + option + file name`
- **Example:**
 - Sort a file and save the output to a new file:
 - `sort + -o + sorted.lst users.lst`
 - Sort a file in reverse order:
 - `sort + -r + users.txt`
 - Sort a file with numeric data:
 - `sort + -n + codes.lst`
 - Sort and remove duplicate entries:
 - `sort + -u + users.lst`

WC

- **Definition:**
 - Used for printing the number of lines, characters and bytes in a file.

- **Usage/Formula:**
 - `wc + option + file name`
- **Example:**
 - Display the number of characters in a file:
 - `wc + -m + users.txt`
 - Display the number of words in a file:
 - `wc + -w + users.txt`