

# JAXtronomy: A JAX port of lenstronomy

Alan Huang<sup>1</sup>, Simon Birrer<sup>1</sup>, Natalie B. Hogg<sup>2</sup>, Aymeric Galan<sup>3,4</sup>,  
Daniel Gilman<sup>5</sup>, Anowar J. Shajib<sup>5,6,7</sup>, and Nan Zhang<sup>8</sup>

<sup>1</sup> Department of Physics and Astronomy, Stony Brook University, Stony Brook, NY 1794, USA <sup>2</sup> Laboratoire Univers et Particules de Montpellier, CNRS and Université de Montpellier (UMR-5299), 34095 Montpellier, France <sup>3</sup> Max-Planck-Institut für Astrophysik, Karl-Schwarzschild Straße 1, 85748 Garching, Germany <sup>4</sup> Technical University of Munich, TUM School of Natural Sciences, Physics Department, James-Frank-Straße 1, 85748 Garching, Germany <sup>5</sup> Department of Astronomy and Astrophysics, University of Chicago, Chicago, Illinois 60637, USA <sup>6</sup> Kavli Institute for Cosmological Physics, University of Chicago, Chicago, IL 60637, USA <sup>7</sup> Center for Astronomy, Space Science and Astrophysics, Independent University, Bangladesh, Dhaka 1229, Bangladesh <sup>8</sup> Department of Physics, University of Illinois, 1110 West Green St., Urbana, IL 61801, USA

DOI: [10.xxxxxx/draft](https://doi.org/10.xxxxxx/draft)

## Software

- Review
- Repository
- Archive

Editor: [Open Journals](#)

## Reviewers:

- @openjournals

Submitted: 01 January 1970

Published: unpublished

## License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](#)).

## Summary

Gravitational lensing is a phenomenon where light bends around massive objects, resulting in distorted images seen by an observer. Studying gravitationally lensed objects can give us key insights into cosmology and astrophysics, such as constraints on the expansion rate of the universe and dark matter models.

Thus, we introduce JAXtronomy, a re-implementation of the gravitational lensing software package lenstronomy<sup>1</sup> (Birrer, 2021; Birrer & Amara, 2018) using JAX<sup>2</sup>. JAX is a Python library that uses an accelerated linear algebra (XLA) compiler to improve the performance of computing software. Our core design principle of JAXtronomy is to maintain an identical API to that of lenstronomy.

The main JAX features utilized in JAXtronomy are just-in-time-compilation, which can lead to significant reductions in execution time, and automatic differentiation, which allows for the implementation of gradient-based algorithms that were previously impossible. Additionally, JAX allows code to be run on GPUs or parallelized across CPU cores, further boosting the performance of JAXtronomy.

## Statement of need

lenstronomy has been widely applied to numerous science cases, with more than 200 publications making use of the software, and has an increasing number of dependent packages relying on features of lenstronomy. For instance, science cases directly involving lenstronomy include galaxy evolution studies using strong lensing (Anowar J. Shajib et al., 2021; Sheu et al., 2025; Tan et al., 2024) and detailed lens modeling for measuring the Hubble constant using time-delay cosmography by the TDCOSMO collaboration (Birrer, S. et al., 2020; Birrer, Simon & Treu, Tommaso, 2021; Collaboration et al., 2025; Gilman, D. et al., 2020; Millon, M. et al., 2020; Schmidt et al., 2025; A. J. Shajib et al., 2022; ?).

Examples of packages dependent on lenstronomy for general-purpose lensing computations and image modelling include the dolphin package (Anowar J. Shajib et al., 2025) for automated lens modeling, the galight package (Ding et al., 2020) for galaxy morphology measurements,

<sup>1</sup><https://github.com/lenstronomy/lenstronomy>

<sup>2</sup><https://github.com/google/jax>

40 SLSim (Khadka et al, 2025, in prep) for simulating large populations of strong lenses, pyHalo  
41 (Gilman et al., 2019) and mejiro (Wedig et al., 2025) for simulating strong lenses with dark  
42 matter substructure, and PALTAS (Wagner-Carena et al., 2023) for neural network inference  
43 tasks.

44 In many of these applications, computational constraints are the key limiting factor for strong  
45 gravitational lensing science. For example, increased data quality and number of lenses to  
46 analyze makes lens modeling a computational bottleneck, and expensive ray-tracing through  
47 tens of thousands of dark matter substructures limit the amount of images that can be  
48 simulated, especially for the training of neural networks and simulation-based inferences. These  
49 ever-increasing computational costs have lead to the development of several JAX-accelerated  
50 and GPU-accelerated strong-lensing packages, such as gigaLens (Gu et al., 2022), herculens  
51 (Galan et al., 2022), paltax (Wagner-Carena et al., 2024), GLaD (Wang et al., 2025), caustics<sup>3</sup>  
52 (Stone et al., 2024) and Google Research's jaxstronomy<sup>4</sup>.

53 **Why JAXtronomy?**

54 JAXtronomy inherits a wide range of features from lenstronomy that are not offered by any  
55 of the aforementioned JAX-accelerated or GPU-accelerated software. Such features include  
56 lenstronomy's linear amplitude solver, which reduces the number of sampled parameters during  
57 lens modeling, as well as a variety of log likelihood functions and optional punishment terms.  
58 Furthermore, JAXtronomy aims to maintain an identical API to lenstronomy so that packages  
59 dependent on lenstronomy can transition seamlessly to JAXtronomy.

60 **Improvements over lenstronomy in image simulation**

61 The simulation of a lensed image comes in three main steps. The first step begins with a  
62 coordinate grid in the angles seen by the observer. These coordinates are ray-traced through  
63 the deflectors back to the source plane. This process requires the calculation of light ray  
64 deflection angles at each deflector. Second, the surface brightness of the source is calculated  
65 on the ray-traced coordinate grid. This produces a lensed image. Third, the lensed image gets  
66 convolved by the point spread function (PSF) originating from diffraction of the telescope  
67 optics and atmospheric turbulence. Due to the various choices in deflector mass profiles, light  
68 model profiles, grid size, and PSF kernel size, the overall runtime of the pipeline can vary  
69 significantly.

70 In the following sections, we outline the improvements in performance that JAXtronomy has  
71 over lenstronomy for each step in the pipeline. These performance benchmarks were run using  
72 an Intel(R) Xeon(R) Gold 6338 CPU @ 2.00GHz, an NVIDIA A100 GPU, and JAX version  
73 0.7.0.

74 **Deflection angle calculations**

75 Each entry in the table indicates how much faster JAXtronomy is compared to lenstronomy  
76 at computing deflection angles for the corresponding deflector profile and grid size. Some  
77 comparisons vary significantly with values of function arguments, so a range is given rather  
78 than a number.

Deflector Profile	60x60 grid (cpu)	180x180 grid (cpu)	180x180 grid (gpu)
CONVERGENCE	0.4x	1.1x	0.5x
CSE	1.6x	2.6x	2.6x
EPL	5.1x - 15x	9.2x - 17x	37x - 120x

<sup>3</sup><https://github.com/Ciela-Institute/caustics>

<sup>4</sup><https://github.com/google-research/google-research/tree/master/jaxstronomy>

Deflector Profile	60x60 grid (cpu)	180x180 grid (cpu)	180x180 grid (gpu)
EPL (jax) vs EPL_NUMBA	1.4x	3.0x	13x
EPL_MULTIPOLE_M1M3M4	2.1x - 7x	6.4x - 13x	42x - 108x
HERNQUIST	2.0x	3.4x	5.8x
HERNQUIST_ELLIPSE_CSE	3.8x	5.4x	40x
MULTIPOLE	0.9x	1.0x	8.3x - 14x
MULTIPOLE_ELL	1.5x - 2.1x	2.0x - 2.8x	70x
NIE/SIE	0.5x	0.5x	2.0x
NFW	1.6x	3.3x	4.5x
NFW_ELLIPSE_CSE	4.1x	6.7x	31x
PJAFPE	1.0x	1.2x	2.8x
PJAFPE_ELLIPSE_POTENTIAL	1.4x	1.6x	3.1x
SHEAR	0.7x	2.0x	0.9x
SIS	1.4x	3.3x	2.0x
TNFW	2.4x	5.8x	7.5x

79 For small enough grid sizes, JAXtronomy computes deflection angles slower than lenstronomy  
80 when using certain deflector profiles. This is because function call overheads are significantly  
81 higher in JAX than in standard Python, so computations that are already fast in Python  
82 can end up slower in JAX. In these cases, the benefit of using JAX is to have automatic  
83 differentiation for lens modeling.

#### 84 Flux calculations

85 An analogous table for the different light profiles is shown below. The MULTI\_GAUSSIAN  
86 and MULTI\_GAUSSIAN\_ELLIPSE profiles include five GAUSSIAN and GAUSSIAN\_ELLIPSE  
87 components, respectively, highlighting JAX's improved performance in sequential computations.

Light Profile	60x60 grid (cpu)	180x180 grid (cpu)	180x180 grid (gpu)
CORE_SERSIC	2.0x	6.7x	4.2x
GAUSSIAN	1.0x	2.5x	1.3x
GAUSSIAN_ELLIPSE	1.5x	3.6x	2.0x
MULTI_GAUSSIAN	3.7x	11x	7.8x
MULTI_GAUSSIAN_ELLIPSE	4.0x	13x	6.9x
SERSIC	1.0x	1.7x	3.9x
SERSIC_ELLIPSE	1.9x	5.7x	3.2x
SERSIC_ELLIPSE_Q_PHI	1.7x	5.5x	3.3x
SHAPELETS	6.2x	3.4x	15x
(n_max=6)			
SHAPELETS	6.0x	4.5x	17x
(n_max=10)			

#### 88 FFT Convolution

89 We find that FFT convolution using JAX on CPU results in variable performance boosts or  
90 slowdowns compared to lenstronomy (which uses scipy's FFT convolution). On a 60x60  
91 grid, and kernel sizes ranging from 3 to 45, JAX on CPU ranges from being 1.1x to 2.9x faster  
92 than lenstronomy, with no obvious correlation to kernel size. On a 180x180 grid, and kernel  
93 sizes ranging from 9 to 135, JAXtronomy on CPU ranges from being 0.7x to 2.5x as fast as  
94 lenstronomy, with no obvious correlation to kernel size.

95 However, FFT convolution using JAX on GPU is significantly faster than `scipy`. On a 60x60  
96 grid, and kernel sizes ranging from 3 to 45, JAX on GPU ranges from being 1.5x to 3.5x  
97 faster than `lenstronomy`, with JAX performing better at higher kernel sizes. On a 180x180  
98 grid, and kernel sizes ranging from 9 to 135, JAXtronomy on GPU is about 10x to 20x as fast  
99 as `lenstronomy`, again with JAX performing better at higher kernel sizes.

## 100 Improvements over `lenstronomy` in lens modelling

101 The process of lens modelling involves finding best-fit parameters describing a lensed system from  
102 real data. In `lenstronomy`, this typically involves a Particle Swarm Optimizer (PSO) (Kennedy  
103 & Eberhart, 1995) for optimization and Monte Carlo Markov Chains for posterior sampling.  
104 JAXtronomy retains these lens modelling algorithms from `lenstronomy` while benefitting from  
105 the increased performance outlined above.

106 In the following table, we compare JAXtronomy's PSO performance to that of `lenstronomy`  
107 when modeling a lens with an elliptical power-law mass profile, Sersic light profile, and a  
108 quadruply-imaged point source. We use a 100x100 grid and a size 13 PSF kernel. These  
109 benchmarks were performed using the same hardware as in the previous section.

Number of Particles	1 CPU core	64 CPU cores (parallelized)	GPU
64	4x	16x	5x
128	4x	18x	5.5x
256	4.7x	30x	9x
512	4.7x	34x	11x

110 Additionally, using JAX's autodifferentiation, we have implemented the L-BFGS gradient descent  
111 algorithm from the `Optax`<sup>5</sup> library (DeepMind et al., 2020) for optimization. This is a significant  
112 improvement over `lenstronomy`'s PSO, which does not have access to gradient information.  
113 Due to the random nature of the PSO, we do not present a concrete comparison between  
114 `lenstronomy` and JAXtronomy for how long it takes to find best-fit parameters. However, we  
115 note that JAXtronomy can find a good fit within one minute, while `lenstronomy` can take  
116 hours.

## 117 References

- 118 Birrer, S. (2021). Gravitational lensing formalism in a curved arc basis: A continuous  
119 description of observables and degeneracies from the weak to the strong lensing regime.  
120 *The Astrophysical Journal*, 919(1), 38. <https://doi.org/10.3847/1538-4357/ac1108>
- 121 Birrer, S., & Amara, A. (2018). `Lenstronomy`: Multi-purpose gravitational lens modelling  
122 software package. *Physics of the Dark Universe*, 22, 189–201. [https://doi.org/10.1016/j.](https://doi.org/10.1016/j.dark.2018.11.002)  
123 [dark.2018.11.002](https://doi.org/10.1016/j.dark.2018.11.002)
- 124 Birrer, Simon, & Treu, Tommaso. (2021). TDCOSMO - v. Strategies for precise and accurate  
125 measurements of the hubble constant with strong lensing. *Astronomy & Astrophysics*, 649,  
126 A61. <https://doi.org/10.1051/0004-6361/202039179>
- 127 Birrer, S., Shajib, A. J., Galan, A., Millon, M., Treu, T., Agnello, A., Auger, M., Chen, G.  
128 C.-F., Christensen, L., Collett, T., Courbin, F., Fassnacht, C. D., Koopmans, L. V. E.,  
129 Marshall, P. J., Park, J.-W., Rusu, C. E., Sluse, D., Spiniello, C., Suyu, S. H., ... Van de  
130 Vyvere, L. (2020). TDCOSMO - IV. Hierarchical time-delay cosmography – joint inference  
131 of the hubble constant and galaxy density profiles\*. *Astronomy & Astrophysics*, 643, A165.  
132 <https://doi.org/10.1051/0004-6361/202038861>

<sup>5</sup><https://github.com/google-deepmind/optax>

- 133 Collaboration, T., Birrer, S., Buckley-Geer, E. J., Cappellari, M., Courbin, F., Dux, F.,  
 134 Fassnacht, C. D., Frieman, J. A., Galan, A., Gilman, D., Huang, X.-Y., Knabel, S.,  
 135 Langeroodi, D., Lin, H., Millon, M., Morishita, T., Motta, V., Mozumdar, P., Paic, E., ...  
 136 Wong, K. C. (2025). *TDCOSMO 2025: Cosmological constraints from strong lensing time*  
 137 *delays*. <https://arxiv.org/abs/2506.03023>
- 138 DeepMind, Babuschkin, I., Baumli, K., Bell, A., Bhupatiraju, S., Bruce, J., Buchlovsky, P.,  
 139 Budden, D., Cai, T., Clark, A., Danihelka, I., Dedieu, A., Fantacci, C., Godwin, J., Jones,  
 140 C., Hemsley, R., Hennigan, T., Hessel, M., Hou, S., ... Viola, F. (2020). *The DeepMind*  
 141 *JAX Ecosystem*. <http://github.com/google-deepmind>
- 142 Ding, X., Silverman, J., Treu, T., Schulze, A., Schramm, M., Birrer, S., Park, D., Jahnke, K.,  
 143 Bennert, V. N., Kartaltepe, J. S., Koekemoer, A. M., Malkan, M. A., & Sanders, D. (2020).  
 144 The Mass Relations between Supermassive Black Holes and Their Host Galaxies at  $1 < z$   
 145  $< 2$  HST-WFC3. *The Astrophysical Journal*, 888(1), 37. [https://doi.org/10.3847/1538-](https://doi.org/10.3847/1538-4357/ab5b90)  
 146 [4357/ab5b90](https://doi.org/10.3847/1538-4357/ab5b90)
- 147 Galan, A., Vernardos, G., Peel, A., Courbin, F., & Starck, J.-L. (2022). Using wavelets  
 148 to capture deviations from smoothness in galaxy-scale strong lenses. *Astronomy &*  
 149 *Astrophysics*, 668, A155. <https://doi.org/10.1051/0004-6361/202244464>
- 150 Gilman, D., Birrer, S., Nierenberg, A., Treu, T., Du, X., & Benson, A. (2019). Warm dark  
 151 matter chills out: Constraints on the halo mass function and the free-streaming length of  
 152 dark matter with eight quadruple-image strong gravitational lenses. *Monthly Notices of the*  
 153 *Royal Astronomical Society*, 491(4), 6077–6101. <https://doi.org/10.1093/mnras/stz3480>
- 154 Gilman, D., Birrer, S., & Treu, T. (2020). TDCOSMO - III. Dark matter substructure meets  
 155 dark energy. The effects of (sub)halos on strong-lensing measurements of  $H_0$ . *Astronomy*  
 156 *& Astrophysics*, 642, A194. <https://doi.org/10.1051/0004-6361/202038829>
- 157 Gu, A., Huang, X., Sheu, W., Aldering, G., Bolton, A. S., Boone, K., Dey, A., Filipp, A.,  
 158 Jullo, E., Perlmutter, S., Rubin, D., Schlafly, E. F., Schlegel, D. J., Shu, Y., & Suyu, S. H.  
 159 (2022). GIGA-lens: Fast bayesian inference for strong gravitational lens modeling. *The*  
 160 *Astrophysical Journal*, 935(1), 49. <https://doi.org/10.3847/1538-4357/ac6de4>
- 161 Kennedy, J., & Eberhart, R. (1995). Particle swarm optimization. *Proceedings of ICNN'95*  
 162 *- International Conference on Neural Networks*, 4, 1942–1948 vol.4. [https://doi.org/10.](https://doi.org/10.1109/ICNN.1995.488968)  
 163 [1109/ICNN.1995.488968](https://doi.org/10.1109/ICNN.1995.488968)
- 164 Millon, M., Galan, A., Courbin, F., Treu, T., Suyu, S. H., Ding, X., Birrer, S., Chen, G. C.-F.,  
 165 Shajib, A. J., Sluse, D., Wong, K. C., Agnello, A., Auger, M. W., Buckley-Geer, E. J.,  
 166 Chan, J. H. H., Collett, T., Fassnacht, C. D., Hilbert, S., Koopmans, L. V. E., ... Van  
 167 de Vyvere, L. (2020). TDCOSMO - i. An exploration of systematic uncertainties in the  
 168 inference of  $H_0$  from time-delay cosmography. *Astronomy & Astrophysics*, 639, A101.  
 169 <https://doi.org/10.1051/0004-6361/201937351>
- 170 Schmidt, T., Treu, T., Birrer, S., Millon, M., Sluse, D., Galan, A., Shajib, A., Lemon, C.,  
 171 Dux, F., & Courbin, F. (2025). TDCOSMO. XVIII. Strong lens model and time-delay  
 172 predictions for J1721+8842, the first einstein zigzag lens. *Astronomy & Astrophysics*.  
 173 <https://doi.org/10.1051/0004-6361/202449984>
- 174 Shajib, Anowar J., Nihal, N. S., Tan, C. Y., Sahu, V., Birrer, S., Treu, T., & Frieman, J. (2025).  
 175 *dolphin: A fully automated forward modeling pipeline powered by artificial intelligence for*  
 176 *galaxy-scale strong lenses*. <https://arxiv.org/abs/2503.22657>
- 177 Shajib, Anowar J., Treu, T., Birrer, S., & Sonnenfeld, A. (2021). Dark matter haloes of  
 178 massive elliptical galaxies at  $z \sim 0.2$  are well described by the Navarro-Frenk-White  
 179 profile. *Monthly Notices of the Royal Astronomical Society*, 503(2), 2380–2405. <https://doi.org/10.1093/mnras/stab536>
- 180
- 181 Shajib, A. J., Wong, K. C., Birrer, S., Suyu, S. H., Treu, T., Buckley-Geer, E. J., Lin, H., Rusu, C.

- 182 E., Poh, J., Palmese, A., Agnello, A., Auger-Williams, M. W., Galan, A., Schuldt, S., Sluse,  
183 D., Courbin, F., Frieman, J., & Millon, M. (2022). TDCOSMO. IX. Systematic comparison  
184 between lens modelling software programs: Time-delay prediction for WGD 2038–4008.  
185 *Astronomy & Astrophysics*, 667, A123. <https://doi.org/10.1051/0004-6361/202243401>
- 186 Sheu, W., Shajib, A. J., Treu, T., Sonnenfeld, A., Birrer, S., Cappellari, M., Oldham, L. J., &  
187 Tan, C. Y. (2025). Project Dinos II: redshift evolution of dark and luminous matter density  
188 profiles in strong-lensing elliptical galaxies across  $0.1 < z < 0.9$ . *Monthly Notices of the*  
189 *Royal Astronomical Society*, 541(1), 1–27. <https://doi.org/10.1093/mnras/staf976>
- 190 Stone, C., Adam, A., Coogan, A., Yantovski-Barth, M. J., Filipp, A., Setiawan, L., Core,  
191 C., Legin, R., Wilson, C., Barco, G. M., Hezaveh, Y., & Perreault-Levasseur, L. (2024).  
192 Caustics: A python package for accelerated strong gravitational lensing simulations. *Journal*  
193 *of Open Source Software*, 9(103), 7081. <https://doi.org/10.21105/joss.07081>
- 194 Tan, C. Y., Shajib, A. J., Birrer, S., Sonnenfeld, A., Treu, T., Wells, P., Williams, D.,  
195 Buckley-Geer, E. J., Drlica-Wagner, A., & Frieman, J. (2024). Project Dinos I: A joint  
196 lensing-dynamics constraint on the deviation from the power law in the mass profile of  
197 massive ellipticals. *Monthly Notices of the Royal Astronomical Society*, 530(2), 1474–1505.  
198 <https://doi.org/10.1093/mnras/stae884>
- 199 Wagner-Carena, S., Aalbers, J., Birrer, S., Nadler, E. O., Darragh-Ford, E., Marshall, P. J., &  
200 Wechsler, R. H. (2023). From images to dark matter: End-to-end inference of substructure  
201 from hundreds of strong gravitational lenses. *The Astrophysical Journal*, 942(2), 75.  
202 <https://doi.org/10.3847/1538-4357/aca525>
- 203 Wagner-Carena, S., Lee, J., Pennington, J., Aalbers, J., Birrer, S., & Wechsler, R. H.  
204 (2024). A strong gravitational lens is worth a thousand dark matter halos: Inference on  
205 small-scale structure using sequential methods. *The Astrophysical Journal*, 975(2), 297.  
206 <https://doi.org/10.3847/1538-4357/ad6e70>
- 207 Wang, H., Suyu, S. H., Galan, A., Halkola, A., Cappellari, M., Shajib, A. J., & Cernetic, M.  
208 (2025). *GPU-accelerated gravitational lensing & dynamical (GLaD) modeling for cosmology*  
209 *and galaxies*. <https://arxiv.org/abs/2504.01302>
- 210 Wedig, B., Daylan, T., Birrer, S., Cyr-Racine, F.-Y., Dvorkin, C., Finkbeiner, D. P., Huang, A.,  
211 Huang, X., Karthik, R., Khadka, N., Natarajan, P., Nierenberg, A. M., Peter, A. H. G., Pierel,  
212 J. D. R., Tang, X. T., & Wechsler, R. H. (2025). The roman view of strong gravitational  
213 lenses. *The Astrophysical Journal*, 986(1), 42. <https://doi.org/10.3847/1538-4357/adc24f>