

Rust: When the Aliasing Discipline Is Too Strong

Jacques-Henri Jourdan

January 31st, 2024

Abstract from last week

Rust: When the
Aliasing Discipline
Is Too Strong

Jacques-Henri
Jourdan

Unsafe Rust

Unsafe and aliasing
Safe abstractions

Interior mutability

Cell<T>
RefCell<T>
Rc<T>

Last week, we saw many features of the Rust programming language:

- algebraic data types, records;
- various kinds of pointers: `Box<T>`, `&mut T`, `&T`;
- how Rust controls ownership and aliasing, the concept of lifetime;
- traits: Rust's type classes
 - (trait examples: iterators, closures);
- why all that gives control, performance and safety
 - (the notion of zero-cost abstraction).

This week

How to escape the ownership discipline when needed?

- unsafe code behind safe abstractions,
- interior mutability.

Rust: When the
Aliasing Discipline
Is Too Strong

Jacques-Henri
Jourdan

Unsafe Rust

Unsafe and aliasing
Safe abstractions

Interior mutability

Cell<T>
RefCell<T>
Rc<T>

Unsafe Rust

Unsafe and aliasing

Safe abstractions

Interior mutability

`Cell<T>`

`RefCell<T>`

`Rc<T>`

1 Unsafe Rust

- Unsafe and aliasing
- Safe abstractions

2 Interior mutability

- `Cell<T>`
- `RefCell<T>`
- `Rc<T>`

Unsafe

Rust: When the
Aliasing Discipline
Is Too Strong

Jacques-Henri
Jourdan

Unsafe Rust

Unsafe and aliasing
Safe abstractions

Interior mutability

Cell<T>
RefCell<T>
Rc<T>

Despite zero-cost abstractions, the requirement of safety has some costs:

- no loop in memory graph,
- shared ownership: restricted to borrows (statically known lifetime),
- linking to external libraries: not always follow ownership discipline,
- bounds checks for `Vec` accesses.

One can use `unsafe Rust` to avoid these costs.

- A set of features that extend Rust.
- Only available in `unsafe` blocks or `unsafe` functions.
- No guarantee of safety:
 - one should `encapsulate` unsafety behind `safe abstractions`,
 - or mark functions with unsafe behavior as `unsafe`.

Unsafe features

Rust: When the
Aliasing Discipline
Is Too Strong

Jacques-Henri
Jourdan

Unsafe Rust

Unsafe and aliasing
Safe abstractions

Interior mutability

Cell<T>
RefCell<T>
Rc<T>

- Dereference **raw pointers**.
- Call unsafe functions (e.g., accessing **Vec<T>** without bounds checks).
- Implement **unsafe** traits (e.g., **Send** and **Sync**, see next week).

And things we won't discuss:

- Mutate global variables (called **static** variables in Rust)
 - (because that can lead to data races).
- Access **union** types.

Undefined behaviors

Using these features is **unsafe**.

⇒ the compiled program can crash even if type-checked!

It is important to know when a program triggers **undefined behavior**.

This is sometimes **very subtle**.

Rust provides an experimental **reference interpreter**, called **Miri**, which detects **some** undefined behavior.

- Can be used on concrete code for testing.

Still, writing unsafe code should be **reserved to experts**. There is a book dedicated to writing unsafe code: **Rustonomicon**.

So I will not teach this here. Instead, we will see why this is subtle.

Rust: When the
Aliasing Discipline
Is Too Strong

Jacques-Henri
Jourdan

Unsafe Rust

Unsafe and aliasing
Safe abstractions

Interior mutability

Cell<T>
RefCell<T>
Rc<T>

Unsafe and aliasing

Common use of unsafe code: weaken aliasing restrictions.

Raw pointers `*mut T` and `*const T`:

- have **no statically checked aliasing restriction**,
- can coerce from/to borrows (both shared and unique),
- can easily be used to **break any aliasing policy**.

Rust: When the
Aliasing Discipline
Is Too Strong

Jacques-Henri
Jourdan

Unsafe Rust

Unsafe and aliasing
Safe abstractions

Interior mutability

Cell<T>
RefCell<T>
Rc<T>

Unsafe and aliasing

Common use of unsafe code: weaken aliasing restrictions.

Raw pointers `*mut T` and `*const T`:

- have **no statically checked aliasing restriction**,
- can coerce from/to borrows (both shared and unique),
- can easily be used to **break any aliasing policy**.

But the compiler may assume known aliasing properties on borrows to perform some optimizations:

```
fn test_noalias(x: &mut i32, y: &mut i32) -> i32 {  
    // x, y cannot alias: they are unique borrows  
    *x = 42;  
    *y = 37;  
    return *x; // must return 42 -- can be optimized  
}
```

⇒ The programmer should take care of not breaking these aliasing guarantees using raw pointers!

Unsafe and aliasing

Common use of unsafe code: weaken aliasing restrictions.

Raw pointers `*mut T` and `*const T`:

- have **no statically checked aliasing restriction**,
- can coerce from/to borrows (both shared and unique),
- can easily be used to **break any aliasing policy**.

But the compiler may assume known aliasing properties on borrows to perform some optimizations:

```
fn test_unique(x: &mut i32) -> i32 {  
    *x = 42;  
    // unknown_function cannot have an alias to x  
    unknown_function();  
    return *x; // must return 42 -- can be optimized  
}
```

⇒ The programmer should take care of not breaking these aliasing guarantees using raw pointers!

Unsafe and aliasing

Common use of unsafe code: weaken aliasing restrictions.

Raw pointers `*mut T` and `*const T`:

- have **no statically checked aliasing restriction**,
- can coerce from/to borrows (both shared and unique),
- can easily be used to **break any aliasing policy**.

But the compiler may assume known aliasing properties on borrows to perform some optimizations:

```
fn test_shared(x: &i32) -> i32 {  
    let y = *x;  
    // unknown_function cannot have a mutable alias to x  
    unknown_function();  
    return *x + y; // can be optimized to 2*y  
}
```

⇒ The programmer should take care of not breaking these aliasing guarantees using raw pointers!

Undefined behavior and aliasing

Rust: When the
Aliasing Discipline
Is Too Strong

Jacques-Henri
Jourdan

Some rules are needed to tell what one can do with raw pointers.

These rules must be a balance between:

- flexibility for the programmer of unsafe code;
- allowing optimizations.

Choosing these rules is still an **open problem**.

The Miri interpreter implements two sets of rules called **Stacked Borrows** and **Tree Borrows**:

- experimental and imperfect,
- but executable on concrete tests.

Unsafe Rust

Unsafe and aliasing
Safe abstractions

Interior mutability

Cell<T>
RefCell<T>
Rc<T>

Undefined behavior and aliasing

Rust: When the
Aliasing Discipline
Is Too Strong

Jacques-Henri
Jourdan

Some rules are needed to tell what one can do with raw pointers.

These rules must be a balance between:

- flexibility for
- allowing op

If you write unsafe code, you need to follow rules like these.

Choosing these

The Miri interp

Borrows:

- experimental and imperfect,
- but executable on concrete tests.

I told you, writing correct unsafe code is subtle. . .

Unsafe Rust

Unsafe and aliasing

Safe abstractions

Interior mutability

Cell<T>

RefCell<T>

Rc<T>

Safe abstractions

Rust: When the
Aliasing Discipline
Is Too Strong

Jacques-Henri
Jourdan

Unsafe Rust

Unsafe and aliasing

Safe abstractions

Interior mutability

Cell<T>

RefCell<T>

Rc<T>

How to benefit from the power of unsafe code without paying the cost?

Use **libraries** written using unsafe features but with safe interfaces.

Example: **Vec<T>**, resizable arrays:

- fully written in Rust with unsafe features,
- yet, most of the functions exposed by **Vec<T>** are safe!

Example of a safe abstraction: a queue based on a linked list

Rust: When the
Aliasing Discipline
Is Too Strong

Jacques-Henri
Jourdan

Unsafe Rust

Unsafe and aliasing

Safe abstractions

Interior mutability

Cell<T>

RefCell<T>

Rc<T>

Let's say we would like to implement a FIFO queue using a singly linked list.

We need a pointer both at the beginning (for **pop**) and at the end of the list (for **push**).

Aliasing rules are violated, we need unsafe code.

Example of safe abstraction: `Queue<T>`

```
mod queue {
  pub struct Queue<T> {
    head: *mut Node<T>,
    tail: *mut Node<T>
  }
  struct Node<T> {
    elem: T,
    next: *mut Node<T>,
  }

  ...
}
use queue::*;

fn (q: Queue<i32> /* Allowed */) {
  ...
  q.head /* Error */
  ...
  Queue { ... } /* Error */
  ...
  let x : Node<i32> /* Error */ = ... ;
  ...
}
```

We use **modules** as an encapsulation mechanism.

Some elements of the modules are marked with **pub**, they are public.
The other elements are private.

Fields of **struct** are also either public or private.

- `Queue` has no public field: **abstract type**!

1 Unsafe Rust

- Unsafe and aliasing
- Safe abstractions

2 Interior mutability

- `Cell<T>`
- `RefCell<T>`
- `Rc<T>`

Working around aliasing rules

Can we do better than `unsafe`?

On the one hand, Rust aliasing rules are strict;
on the other hand, `unsafe` code seems too subtle to write. . .

Can we do better?

Rust: When the
Aliasing Discipline
Is Too Strong

Jacques-Henri
Jourdan

Unsafe Rust

Unsafe and aliasing
Safe abstractions

Interior mutability

`Cell<T>`
`RefCell<T>`
`Rc<T>`

Working around aliasing rules

Can we do better than `unsafe`?

On the one hand, Rust aliasing rules are strict;
on the other hand, `unsafe` code seems too subtle to write. . .

Can we do better?

We can use **interior mutability**:

- libraries that relax aliasing rules, **safely**,
- written with `unsafe` code, but safely encapsulated!
- Common feature: updating memory using a shared borrow, with appropriate restrictions.
 - (Uses special annotation to disable some optimizations.)

Any idea of an API with interior mutability?

Rust: When the
Aliasing Discipline
Is Too Strong

Jacques-Henri
Jourdan

Unsafe Rust

Unsafe and aliasing

Safe abstractions

Interior mutability

`Cell<T>`

`RefCell<T>`

`Rc<T>`

Cell<T>

```
pub struct Cell<T> { ... }

impl<T> Cell<T> {
    pub fn new(value: T) -> Cell<T> { ... }
    pub fn into_inner(self) -> T { ... }
    pub fn set(&self, val: T) { ... }
    pub fn replace(&self, val: T) -> T { ... }
    pub fn get(&self) -> T where T : Copy { ... }
}
```

Informally, why is this safe?

Cell<T>

```
pub struct Cell<T> { ... }

impl<T> Cell<T> {
    pub fn new(value: T) -> Cell<T> { ... }
    pub fn into_inner(self) -> T { ... }
    pub fn set(&self, val: T) { ... }
    pub fn replace(&self, val: T) -> T { ... }
    pub fn get(&self) -> T where T : Copy { ... }
}
```

Informally, why is this safe?

From `&Cell<T>`, we can never get a (shared or mutable) borrow of the content. Hence, invariants on borrows of `T` cannot be violated.

We can only exchange values of type `T` or get a copy, but no internal borrow.

Cell<T>

```
pub struct Cell<T> { ... }

impl<T> Cell<T> {
    pub fn new(value: T) -> Cell<T> { ... }
    pub fn into_inner(self) -> T { ... }
    pub fn set(&self, val: T) { ... }
    pub fn replace(&self, val: T) -> T { ... }
    pub fn get(&self) -> T where T : Copy { ... }
}
```

Informally, why is this safe?

From `&Cell<T>`, we can never get a (shared or mutable) borrow of the content. Hence, invariants on borrows of `T` cannot be violated.

We can only exchange values of type `T` or get a copy, but no internal borrow.

And what if we **do want** an internal borrow?

RefCell<T> API(1/2)

RefCell, RefMut

```
pub struct RefCell<T> { ... }
pub struct RefMut<'b, T> where T: 'b { ... }

impl<T> RefCell<T> {
    pub fn new(value: T) -> RefCell<T> { ... }
    pub fn into_inner(self) -> T { ... }

    /* Checks there is no borrow. Marks as uniquely borrowed. */
    pub fn borrow_mut<'a>(&'a self) -> RefMut<'a, T> { ... }
}

/* This DerefMut instance means RefMut<'b, T> can be used as &'b mut T */
impl<'b, T> DerefMut for RefMut<'b, T> {
    fn deref_mut<'a>(&'a mut self) -> &'a mut T /* where 'b: 'a */ { ... }
}

/* This Deref instance means RefMut<'b, T> can be used as &'b T */
impl<'b, T> Deref for RefMut<'b, T> {
    type Target = T
    fn deref<'a>(&'a self) -> &'a T /* where 'b: 'a */ { ... }
}

/* Destructor. */
impl<'a, T> Drop for RefMut<'a, T> {
    /* Mark RefCell as not borrowed. */
    fn drop(&mut self) { ... }
}
```

Rust: When the
Aliasing Discipline
Is Too Strong

Jacques-Henri
Jourdan

Unsafe Rust

Unsafe and aliasing
Safe abstractions

Interior mutability

Cell<T>
RefCell<T>
Rc<T>

RefCell<T> Example

Rust: When the
Aliasing Discipline
Is Too Strong

Jacques-Henri
Jourdan

Unsafe Rust

Unsafe and aliasing
Safe abstractions

Interior mutability

Cell<T>
RefCell<T>
Rc<T>

```
fn use_refcell(x : &RefCell<Vec<i32>>) {  
    {  
        let mut v: RefMut<'_, Vec<i32>> = x.borrow_mut();  
        v.push(42); // v can be used just like a unique borrow  
  
        /* Panics: there already is a unique borrow. */  
        /* let v2 = x.borrow_mut().push(16); */  
  
        /* Implicit : v.drop(); */  
    }  
  
    /* The RefMut is dropped, I can create another one: */  
    println!("{}", x.borrow_mut()[0]);  
}
```


RefCell<T> API (2/2)

Ref

...

```
pub struct Ref<'b, T> where T: 'b { ... }
```

```
impl<T> RefCell<T> {
```

```
    ...
```

```
    /* Checks there is no unique borrow. Increments borrow count. */
```

```
    pub fn borrow<'a>(&'a self) -> Ref<'a, T> { ... }
```

```
}
```

```
/* This Deref instance means Ref<'b, T> can be used as &'b T */
```

```
impl<'b, T> Deref for Ref<'b, T> {
```

```
    type Target = T
```

```
    fn deref<'a>(&'a self) -> &'a T /* where 'b: 'a */ { ... }
```

```
}
```

```
/* Destructor. */
```

```
impl<'a, T> Drop for Ref<'a, T> {
```

```
    /* Decrements borrow count. */
```

```
    fn drop(&mut self) { ... }
```

```
}
```

Rust: When the
Aliasing Discipline
Is Too Strong

Jacques-Henri
Jourdan

Unsafe Rust

Unsafe and aliasing

Safe abstractions

Interior mutability

Cell<T>

RefCell<T>

Rc<T>

Soundness

Why is RefCell sound?

Rust: When the
Aliasing Discipline
Is Too Strong

Jacques-Henri
Jourdan

Unsafe Rust

Unsafe and aliasing
Safe abstractions

Interior mutability

Cell<T>
RefCell<T>
Rc<T>

Why is `RefCell` sound?

The aliasing rule (aliasing XOR mutation) is enforced dynamically, through an internal counter.

We can see `RefCell` as a non-concurrent reader/writer lock.

Subtle API question regarding lifetimes

In the standard library:

```
impl<'b, T> RefMut<'b, T> {  
    pub fn map<U, F>(orig: RefMut<'b, T>, f: F) -> RefMut<'b, U>  
        where F: FnOnce(&mut T) -> &mut U  
    { ... }  
}  
  
impl<'b, T> Ref<'b, T> {  
    pub fn map<U, F>(orig: Ref<'b, T>, f: F) -> Ref<'b, U>  
        where F: FnOnce(&T) -> &U  
    { ... }  
}
```


It can be used e.g., to transform a `RefMut<'b, T>` to a `RefMut` to one of the fields of `T`.

Subtle API question regarding lifetimes

In the standard library:

```
impl<'b, T> RefMut<'b, T> {  
    pub fn map<U, F>(orig: RefMut<'b, T>, f: F) -> RefMut<'b, U>  
        where F: FnOnce(&mut T) -> &mut U  
    { ... }  
}  
  
impl<'b, T> Ref<'b, T> {  
    pub fn map<U, F>(orig: Ref<'b, T>, f: F) -> Ref<'b, U>  
        where F: FnOnce(&T) -> &U  
    { ... }  
}
```

It can be used e.g., to transform a `RefMut<'b, T>` to a `RefMut` to one of the fields of `T`.

Exercise: what are the lifetimes of borrows  used in closures?
Give (counter-)examples.

Rc<T>

A pointer to T, with reference counting

```
struct Rc<T> { ... }

impl<T> Rc<T> {
    pub fn new(value: T) -> Rc<T> { ... }
}

/* This Deref instance means Rc<T> can be used as &T */
impl<T> Deref for Rc<T> {
    type Target = T
    fn deref<'a>(&'a self) -> &'a T { ... }
}

impl<T> Clone for Rc<T> {
    /* Copy the pointer, and increment the reference count. */
    fn clone(&self) -> Rc<T> { ... }
}

impl<T> Drop for Rc<T> {
    /* Drop the pointer, decrement the reference count, and recursively
       drop+deallocate if count is 0. */
    fn drop(&mut self) { ... }
}
```

Rust: When the
Aliasing Discipline
Is Too Strong

Jacques-Henri
Jourdan

Unsafe Rust

Unsafe and aliasing
Safe abstractions

Interior mutability

Cell<T>
RefCell<T>
Rc<T>

Rc<T>

A pointer to T, with reference counting

```
struct Rc<T> { ... }

impl<T> Rc<T> {
    pub fn new(value: T) -> Rc<T> { ... }
}

/* This Deref impl
impl<T> Deref for Rc<T> {
    type Target = T;
    fn deref(&'a self) -> &'a T { ... }
}

impl<T> Clone for Rc<T> {
    /* Copy the pointer, not the data
    fn clone(&self) -> Rc<T> { ... }
}

impl<T> Drop for Rc<T> {
    /* Drop the pointer, decrement the reference count, and recursively
    drop+deallocate if count is 0. */
    fn drop(&mut self) { ... }
}
```

This is typically used for implementing **data structures with sharing**.
Example: purely functional maps, BDDs...

Why do I say this is interior mutability?

Rc<T>

A pointer to T, with reference counting

```
struct Rc<T> { ... }

impl<T> Rc<T> {
    pub fn new(value: T) -> Rc<T> { ... }
}

/* This Deref impl
impl<T> Deref for Rc<T> {
    type Target = T;
    fn deref(&'a self) -> &'a T { ... }
}

impl<T> Clone for Rc<T> {
    /* Copy the pointer, not the data
    fn clone(&self) -> Rc<T> { ... }
}

impl<T> Drop for Rc<T> {
    /* Drop the pointer, decrement the reference count, and recursively
    drop+deallocate if count is 0. */
    fn drop(&mut self) { ... }
}
```

This is typically used for implementing **data structures with sharing**.
Example: purely functional maps, BDDs...

Interior mutability is limited to the reference count.

Rust: When the
Aliasing Discipline
Is Too Strong

Jacques-Henri
Jourdan

Unsafe Rust

Unsafe and aliasing

Safe abstractions

Interior mutability

Cell<T>

RefCell<T>

Rc<T>

Getting mutable references

Rust: When the
Aliasing Discipline
Is Too Strong

Jacques-Henri
Jourdan

A priori, an `Rc<T>` can be aliased, so we don't have a `DerefMut` instance.

But we have:

```
impl<T> Rc<T> {  
    /* Checks the count is equal to 1. */  
    pub fn get_mut(this: &mut Rc<T>) -> Option<&mut T> { ... }  
  
    /* Clone-on-write: clone the content to a fresh location if the count is not 1. */  
    pub fn make_mut(this: &mut Rc<T>) -> &mut T  
        where T : Clone { ... }  
}
```

Of course, this prevents mutation and aliasing.

How would you get a functionality close to an OCaml's `ref` type?

Unsafe Rust

Unsafe and aliasing

Safe abstractions

Interior mutability

`Cell<T>`

`RefCell<T>`

`Rc<T>`

Getting mutable references

Rust: When the
Aliasing Discipline
Is Too Strong

Jacques-Henri
Jourdan

A priori, an `Rc<T>` can be aliased, so we don't have a `DerefMut` instance.

But we have:

```
impl<T> Rc<T> {  
    /* Checks the count is equal to 1. */  
    pub fn get_mut(this: &mut Rc<T>) -> Option<&mut T> { ... }  
  
    /* Clone-on-write: clone the content to a fresh location if the count is not 1. */  
    pub fn make_mut(this: &mut Rc<T>) -> &mut T  
        where T : Clone { ... }  
}
```

Of course, this prevents mutation and aliasing.

How would you get a functionality close to an OCaml's `ref` type?

Answer: `Rc<RefCell<T>>`.

Unsafe Rust

Unsafe and aliasing

Safe abstractions

Interior mutability

Cell<T>

RefCell<T>

Rc<T>

A note on performances

Rust: When the
Aliasing Discipline
Is Too Strong

Jacques-Henri
Jourdan

Unsafe Rust

Unsafe and aliasing

Safe abstractions

Interior mutability

Cell<T>

RefCell<T>

Rc<T>

Reference counting is sometimes considered slow.

This is because it usually requires a lot of updates to the reference counts (ex. parameter passing, assignments to a variable. . .)

In Rust, we can mix reference counting and borrowing:

- Use borrows when doing a read-only traversal of a data structure.
- Increment the count only when creating a new long-lived reference.

This gives **better control**, and **better performances**.

A question for next course

Rust: When the
Aliasing Discipline
Is Too Strong

Jacques-Henri
Jourdan

Unsafe Rust

Unsafe and aliasing

Safe abstractions

Interior mutability

Cell<T>

RefCell<T>

Rc<T>

The next course will focus on support for parallelism (i.e., multicore programs).

What do you think is needed in Rust to guarantee the safety of multicore Rust programs?