

MPRI 2.4

GADTs

François Pottier



2024

Untyped expressions

Consider a tiny language of expressions $t ::= k \mid (t, t) \mid \pi_i t$:

```
type expr =  
| EInt  of int  
| EPair of expr * expr  
| EFst  of expr  
| ESnd  of expr
```

Expressions include integer constants, pairs, and projections.

Untyped values

A straightforward interpreter for this language uses a type of all values:

```
type value =  
| VInt of int  
| VPair of value * value
```

This is an algebraic data type. Thus every value carries a [tag](#).

Runtime tests

These tags are used in **runtime tests** that can cause **runtime errors**.

```
let as_pair (v : value) : value * value =  
  match v with  
  | VPair (v1, v2) ->  
    v1, v2  
  | _ ->  
    assert false (* runtime error! *)
```

An untyped interpreter

Here, interpreting a pair projection operation involves a runtime test.

```
let rec eval (e : expr) : value =  
  match e with  
  | EInt x ->  
    VInt x  
  | EPair (e1, e2) ->  
    VPair (eval e1, eval e2)  
  | EFst e ->  
    fst (as_pair (eval e))  
  | ESnd e ->  
    snd (as_pair (eval e))
```

This is **necessary** because this interpreter accepts untyped expressions.

Typed expressions

Examples

Tagless
interpretersRuntime type
descriptionsA well-typed
type-checker
Printf & friends

Metatheory

Conclusion

Let us impose a **simple type discipline** on expressions.

```

type _ expr =
| EInt   :          int ->      int expr
| EPair  : 'a expr * 'b expr -> ('a * 'b) expr
| EFst   :      ('a * 'b) expr ->   'a expr
| ESnd   :      ('a * 'b) expr ->   'b expr

```

This type definition encodes the following type discipline:

$$\Gamma \vdash k : \text{int} \qquad \frac{\Gamma \vdash t_1 : T_1 \quad \Gamma \vdash t_2 : T_2}{\Gamma \vdash (t_1, t_2) : T_1 \times T_2} \qquad \frac{\Gamma \vdash t : T_1 \times T_2}{\Gamma \vdash \pi_i t : T_i}$$

A **meta-level** abstract syntax tree (AST) of type `'a expr` represents an **object-level** expression of type `'a`.

Typed values

Let us similarly impose a type discipline on values:

```
type _ value =
| VInt   :                int ->      int value
| VPair  : 'a value * 'b value -> ('a * 'b) value
```

Values are still tagged (for now), but runtime tests become unnecessary...

Look Ma, no runtime test!

Only one branch is now necessary. A second branch would be **dead**.

```
let as_pair : type a b . (a * b) value -> a value * b value
= function
  | VPair (v1, v2) ->
    v1, v2
  (* In this branch, we would learn [a * b = int], *)
  (* which is contradictory. *)
  (* | _ -> . *)
```

In OCaml, destructing a GADT requires a type annotation in this style.

A typed interpreter

Evaluating an expression of type T yields a value of type T .

```

let rec eval : type a . a expr -> a value
= function
  | EInt x ->
    (* We learn [a = int] so returning [VInt _] is OK. *)
    VInt x
  | EPair (e1, e2) ->
    (* For some types [a1] and [a2], we learn [a = a1 * a2] *)
    (* and we can assume [e1 : a1 expr] and [e2 : a2 expr]. *)
    VPair (eval e1, eval e2)
  | EFst e ->
    fst (as_pair (eval e))
  | ESnd e ->
    snd (as_pair (eval e))

```

The type of the interpreter reflects the **subject reduction** property.
 it amounts to **checking the proof** of subject reduction!

A typed, tagless interpreter

Evaluating an expression of type T yields a **meta-level value** of type T .

```

let rec eval : type a . a expr -> a
= function
  | EInt x ->
    (* We learn [a = int] so returning an integer is OK. *)
    x (* no tagging! *)
  | EPair (e1, e2) ->
    (* For some types [a1] and [a2], we learn [a = a1 * a2] *)
    (* and we can assume [e1 : a1 expr] and [e2 : a2 expr]. *)
    (eval e1, eval e2) (* no tagging! *)
  | EFst e ->
    fst (eval e) (* no untagging! *)
  | ESnd e ->
    snd (eval e) (* no untagging! *)

```

The type of the interpreter reflects the **subject reduction** property.
 it amounts to **checking the proof** of subject reduction!

Polymorphic recursion

`eval` involves **polymorphic recursion**:
the fact that `eval` is polymorphic
is exploited in the definition of `eval` itself.

For example, when applied to an expression of type `a expr`,
`eval` calls itself recursively with an expression of type `a1 expr`.

Polymorphic recursion is naturally available in System F (with *let rec*).
In OCaml, Haskell, etc., a type annotation is required.

Mycroft, **Polymorphic type schemes and recursive definitions**, 1984.

Going further

Our tiny expressions are **closed**: the typing judgement is $\vdash t : T$.

When expressions involve variables, one needs a type $(\text{'g'}, \text{'a'}) \text{ expr}$ whose definition encodes the typing judgement $\Gamma \vdash t : T$.

This is reasonably easy if variables are encoded as de Bruijn indices.

Bird, Paterson, **de Bruijn notation as a nested datatype**, 1999.

Runtime type descriptions

Examples

Tagless
interpretersRuntime type
descriptionsA well-typed
type-checker

Printf & friends

Metatheory

Conclusion

A **value** of type `'a ty` is a runtime description of the **type** `'a`.

```
type _ ty =
| TyInt   : int ty
| TySum   : 'a ty * 'b ty -> ('a, 'b) sum ty
| TyPair  : 'a ty * 'b ty -> ('a * 'b) ty
```

The binary sum type `('a, 'b) sum` is defined as follows:

```
type ('a, 'b) sum = Left of 'a | Right of 'b
```

It is also available in the standard library module **Either**.

An example of a runtime type description

Examples

Tagless
interpreters

Runtime type descriptions

A well-typed
type-checker
Printf & friends

Metatheory

Conclusion

```
let example : (int * int) ty =  
  TyPair (TyInt, TyInt)
```

The value `example` is a runtime description of the type `int * int`.

This value has no other type.

This type has no other inhabitant: `(int * int) ty` is a [singleton type](#).

Applications

Although **inspecting a type** at runtime is impossible, as types are erased, **inspecting a runtime description of a type** is possible.

In other words, although the type $\forall X. X \rightarrow X$ has only **one** inhabitant, the type $\forall X. \text{Ty } X \rightarrow X \rightarrow X$ has **more than one**.

This lets us write **polymorphic, type-directed** functions, an activity that is sometimes known as **generic programming**.

Show

MPRI 2.4
Generalized
Algebraic
Data Types

François
Pottier

Examples

Tagless
interpreters

Runtime type
descriptions

A well-typed
type-checker
Printf & friends

Metatheory

Conclusion

Here is a polymorphic, type-directed **conversion of a value to a string**.

```
let rec show : type a . a ty -> a -> string =
  fun ty x ->
    match ty with
    | TyInt ->
      string_of_int x
    | TySum (ty1, ty2) ->
      begin match x with
      | Left x1 -> "left(" ^ show ty1 x1 ^ ")"
      | Right x2 -> "right(" ^ show ty2 x2 ^ ")"
      end
    | TyPair (ty1, ty2) ->
      let (x1, x2) = x in
      "(" ^ show ty1 x1 ^ ", " ^ show ty2 x2 ^ ")"
```

In each branch, **we learn something** about the type of x .

Show

It is more concise and looks better to deconstruct both arguments at once.

```
let rec show : type a . a ty -> a -> string =
  fun ty x ->
    match ty, x with
    | TyInt, x ->
      string_of_int x
    | TySum (ty1, _), Left x1 ->
      "left(" ^ show ty1 x1 ^ ")"
    | TySum (_, ty2), Right x2 ->
      "right(" ^ show ty2 x2 ^ ")"
    | TyPair (ty1, ty2), (x1, x2) ->
      "(" ^ show ty1 x1 ^ ", " ^ show ty2 x2 ^ ")"
```

The OCaml type-checker reads patterns from left to right
so deconstructing (ty, x) works but deconstructing (x, ty) does not.

Show

MPRI 2.4
Generalized
Algebraic
Data Types

François
Pottier

Examples

Tagless
interpreters

Runtime type
descriptions

A well-typed
type-checker
Printf & friends

Metatheory

Conclusion

Here is a polymorphic, type-directed **equality test**.

```
let rec equal : type a . a ty -> a -> a -> bool =
  fun ty x y ->
    match ty, x, y with
    | TyInt, x, y ->
      Int.equal x y
    | TySum (ty1, _), Left x1, Left y1 ->
      equal ty1 x1 y1
    | TySum (_, ty2), Right x2, Right y2 ->
      equal ty2 x2 y2
    | TySum _, Left _, Right _
    | TySum _, Right _, Left _ ->
      false
    | TyPair (ty1, ty2), (x1, x2), (y1, y2) ->
      equal ty1 x1 y1 && equal ty2 x2 y2
```

Connections between GADTs and type classes

Eq and **Show** are typical examples of **type classes** in Haskell.

Here, a somewhat similar effect is achieved using GADTs.

Upcoming lecture on type classes (PED).

Hinze, Jeuring, Löh,

Comparing Approaches to Generic Programming in Haskell, 2006.

Connections between GADTs and type classes

A **fixed** set of type class instances can be compiled down to a GADT.

If a Haskell program contains three instances of the class **Show**,
for integers, products, and sums,
then compiling type classes to GADTs
would produce (roughly) the function `show` of the previous slide.

Pottier and Gauthier,

Polymorphic typed defunctionalization and concretization, 2006.

A fixed set of **functions** can also be compiled down to a GADT.

– See above paper and next week's lecture!

Connections between GADTs and type classes

A limitation of this compilation scheme is that a GADT describes a **fixed** universe of types whereas type classes are **open-ended**.

The Holy Grail is to propose a language where **a type of the representations of all types** (including itself!) can be defined.

Chapman, Dagand, McBride, Morris,
The Gentle Art of Levitation, 2010.

Untyped expressions

We have a type of raw (untyped) expressions:

```
module Raw = struct
  type expr =
    | EInt   of int
    | EPair  of expr * expr
    | EFst   of expr
    | ESnd   of expr
end
```

This is an ordinary algebraic data type.

Typed expressions and type descriptions

Examples

Tagless
interpretersRuntime type
descriptionsA well-typed
type-checker

Printf & friends

Metatheory

Conclusion

We also have a type 'a expr of well-typed expressions:

```
type _ expr =
| EInt   :                int ->      int expr
| ...
```

and a type 'a ty of runtime type descriptions:

```
type _ ty =
| TyInt   :                int ty
| ...
```

Question

MPRI 2.4
Generalized
Algebraic
Data Types

François
Pottier

Examples

Tagless
interpreters
Runtime type
descriptions
A well-typed
type-checker
Printf & friends

Metatheory

Conclusion

Can we write a simple **type inferencer**
that accepts an untyped expression
and **either fails or returns a typed expression**?

```
exception IllTyped
let rec infer : Raw.expr -> ???
= function
  | Raw.EInt i ->
    (TyInt, EInt i)
  | ...
```

What should its **result type** be?

A type inferencer

We need an **existential type** $\exists X. \text{Ty } X \times \text{Expr } X$.

```
type typed_expr =  
| TypedExpr : 'a ty * 'a expr -> typed_expr
```

A type inferencer

Examples

Tagless
interpretersRuntime type
descriptionsA well-typed
type-checker

Printf & friends

Metatheory

Conclusion

We can now write the type inferencer:

```
let rec infer : Raw.expr -> typed_expr =
  function
  | Raw.EInt i ->
      TypedExpr (TyInt, EInt i)
  | Raw.EFst e ->
      let TypedExpr (ty, e) = infer e in
      begin match ty with
      | TyPair (ty1, ty2) -> TypedExpr (ty1, EFst e)
      | _ -> raise IllTyped
      end
  end
```

Exercise: write the two missing cases (**EPair** and **ESnd**).

A type-checker

Can we **check** whether an expression has a certain expected type?

We would like to write something like this:

```
let check (type a) (e : Raw.expr) (expected : a ty) : a expr =
  let TypedExpr (inferred, e) = infer e in
  if inferred = expected then
    e
  else
    raise IllTyped
```

But **this code is not well-typed**. Why?

expected has type $a \text{ ty}$.

inferred has type $b \text{ ty}$

where b is an unknown type introduced by deconstructing **TypedExpr**.

They **cannot be compared** using homogeneous equality $=$.

Even if they could, e has type $b \text{ expr}$

whereas a result of type $a \text{ expr}$ is required.

The equality GADT

The solution involves the **type equality GADT**.

```
type (_, _) eq =  
  | Equal: ('a, 'a) eq
```

The type `('a, 'b) eq` has at most one inhabitant.

If it has one then this inhabitant must be **Equal**
and the types `'a` and `'b` must be the same.

For example, the type `(int, int) eq` has one inhabitant, namely **Equal**.
The type `(int, bool) eq` has no inhabitant.

The equality GADT

```
type (_, _) eq =
| Equal: ('a, 'a) eq
```

The data constructor `Equal` has polymorphic type:

$$\forall \alpha. (\alpha, \alpha) \text{eq}$$

which can also be understood as a **constrained** polymorphic type:

$$\forall \alpha \beta. (\alpha = \beta) \Rightarrow (\alpha, \beta) \text{eq}$$

Any color the customer wants, as long as it's black. – Henry Ford

A heterogeneous type equality test

This lets us express a **heterogenous** type equality test:

```
let rec equal : type a b . a ty -> b ty -> (a, b) eq =
  fun ty1 ty2 ->
    match ty1, ty2 with
    | TyInt, TyInt ->
      Equal
    | TyPair (ty1a, ty1b), TyPair (ty2a, ty2b) ->
      let Equal = equal ty1a ty2a in
      let Equal = equal ty1b ty2b in
      Equal
    | -, - ->
      raise IllTyped
```

When `equal ty1 ty2` succeeds, we **learn** that the runtime type descriptions `ty1` and `ty2` describe the same static type.

Exercise: write the missing case.

A type-checker

We can now write the type-checker:

```
let check (type a) (e : Raw.expr) (expected : a ty) : a expr =  
  let TypedExpr (inferred, e) = infer e in  
  let Equal = equal inferred expected in  
  e
```

Exercise: make sure that you understand why this code is well-typed.

Putting the pieces together

Given an arbitrary untyped expression in our tiny language, we can now **infer** its type, **evaluate** it, and **show** its value, whatever its type may be.

```
let () =  
  let e = Raw.(EPair (EInt 42, EInt 0)) in  
  let TypedExpr (ty, e) = infer e in  
  let v = eval e in  
  Printf.printf "%s\n!" (show ty v)
```

This program prints:

```
(42, 0)
```


Putting the pieces together

Here is
a second example
(of a different type!):

```
let () =  
  let e = Raw.(EFst (EPair (EInt 42, EInt 0))) in  
  let TypedExpr (ty, e) = infer e in  
  let v = eval e in  
  Printf.printf "%s\n%" (show ty v)
```

This program prints:

42

Printf in OCaml

`printf` takes a “format string” followed with a number of arguments:

```
# open Printf;;  
# printf "%d * %s = %d\n" 2 "12" 24;;  
2 * 12 = 24  
- : unit = ()
```

The number and type of these arguments *depends* on the format string.

Printf in OCaml

Examples

Tagless
interpretersRuntime type
descriptionsA well-typed
type-checker

Printf & friends

Metatheory

Conclusion

A format string is actually **not** a string: it is a **data structure**.

```
# open CamlinternalFormatBasics;;
# let desc : _ format6 = "%d * %s = %d\n";;
val desc :
  (int -> string -> int -> 'a, 'b, 'c, 'd, 'd, 'a) format6 =
  Format
    (Int (Int_d, No_padding, No_precision,
      String_literal (" * ",
        String (No_padding,
          String_literal (" = ",
            Int (Int_d, No_padding, No_precision,
              Char_literal ('\n', End_of_format)))))),
      "%d * %s = %d\n")
```

Printf in OCaml

This data structure has the shape of a list:

```
Int (Int_d, No_padding, No_precision,  
String_literal ( " * ",  
String (No_padding,  
String_literal ( " = ",  
Int (Int_d, No_padding, No_precision,  
Char_literal ( '\n' ,  
End_of_format ) ) ) ) ) )
```

`End_of_format` is “nil”; the other constructors are “cons” constructors.

`Int` and `String` correspond to “holes” `%d` and `%s`.

`String_literal` and `Char_literal` correspond to literal pieces of string.

An algebraic data type of descriptors

Examples

Tagless
interpretersRuntime type
descriptionsA well-typed
type-checker

Printf & friends

Metatheory

Conclusion

Can we define our own algebraic data type of formats, or **descriptors**?

```
type desc =  
  | Nil  
  | Lit of string * desc  
  | Int of desc
```

An algebraic data type of descriptors

Examples

Tagless
interpretersRuntime type
descriptionsA well-typed
type-checker

Printf & friends

Metatheory

Conclusion

Or, in this alternative syntax:

```
type desc =  
| Nil : desc  
| Lit : string * desc -> desc  
| Int : desc -> desc
```

An algebraic data type of descriptors

Examples

Tagless
interpretersRuntime type
descriptionsA well-typed
type-checker

Printf & friends

Metatheory

Conclusion

Or, in this alternative syntax:

```
type desc =
| Nil  :          desc
| Lit  : string * desc -> desc
| Int  : desc      -> desc
```

Now, please define `fprintf` so that `fprintf` emit `desc <args>`

- emits output via the function `emit : string -> unit`,
- obeys `desc`,
- expects arguments `<args>` whose number and type satisfy `desc`.

`fprintf` should have type `(string -> unit) -> desc -> ??? -> unit`.

Expressing the type of printf

The type desc \rightarrow ??? \rightarrow `unit` does not make sense.

The number of and type of the arguments ??? *depends* on the descriptor.

We seem to need a *dependent type* $(d : \text{desc}) \rightarrow \text{shape } d$

- where shape would be a function of descriptors to types,
- but OCaml does not have that.

Instead, let's use a plain function type $\text{'shape } \text{desc} \rightarrow \text{'shape}$

- where the definition of $\text{'shape } \text{desc}$ as a GADT encodes the correspondence between descriptors and shapes.

Descriptors form a *typed language* and `fprintf` is an *interpreter* for it!

A GADT of descriptors

We want `fprintf` : `(string -> unit) -> 'a desc -> 'a`.

```

type desc =
  | Nil      :                               desc
  | Lit      :      string *                desc ->   desc
  | Int      :                               desc ->   desc

```

We must turn the type `desc` into a GADT.

A GADT of descriptors

We want `fprintf` : `(string -> unit) -> 'a desc -> 'a`.

```

type _ desc =
  | Nil      :                                ?? desc
  | Lit      :      string * ?? desc ->      ?? desc
  | Int      :              ?? desc ->      ?? desc

```

We parameterize the type `desc`.

A GADT of descriptors

We want `fprintf` : (`string` -> `unit`) -> 'a desc -> 'a.

```

type _ desc =
  | Nil   :                               unit desc
  | Lit   :          string * ?? desc ->    ?? desc
  | Int   :                ?? desc ->      ?? desc

```

`Nil` requires no action; the corresponding shape is `unit`.

A GADT of descriptors

We want `fprintf` : `(string -> unit) -> 'a desc -> 'a`.

```

type _ desc =
  | Nil   :                               unit desc
  | Lit   :          string * 'a desc ->    'a desc
  | Int   :                ?? desc ->      ?? desc

```

`Lit` (`s`, `d`) requires printing `s` and interpreting `d`.

If `d` has shape `'a` then `Lit` (`s`, `d`) has shape `'a` as well.

A GADT of descriptors

We want `fprintf` : `(string -> unit) -> 'a desc -> 'a`.

```
type _ desc =
  | Nil   :                               unit desc
  | Lit   :          string * 'a desc ->      'a desc
  | Int   :          'a desc -> (int -> 'a) desc
```

`Int d` requires consuming an integer argument and interpreting `d`.

If `d` has shape `'a` then `Int d` has shape `int -> 'a`.

We can in fact replace `Int` with a more general constructor `Hole`...

A GADT of descriptors

We want `fprintf` : (`string` -> `unit`) -> `'a` desc -> `'a`.

```
type _ desc =
  | Nil      :                               unit desc
  | Lit      :          string * 'a desc ->      'a desc
  | Hole     : ('data -> string) * 'a desc -> ('data -> 'a) desc
```

We now allow a hole of arbitrary type `'data`.

We require a conversion function of type `'data -> string`.

Implementing fprintf

```

let fprintf (type a) emit (desc : a desc) : a =
  let rec eval : type a . a desc -> a =
    function
    | Nil ->
      ???
    | Lit (s, desc) ->
      ???
    | Hole (to_string, desc) ->
      ???

  in eval desc

```

Recall

```

| Nil : unit desc

```

Implementing fprintf

```
let fprintf (type a) emit (desc : a desc) : a =
  let rec eval : type a . a desc -> a =
    function
    | Nil ->
      ??? (* We learn [a = unit]. *)
    | Lit (s, desc) ->
      ???
    | Hole (to_string, desc) ->
      ???

  in eval desc
```

Recall

```
| Nil : unit desc
```


Implementing fprintf

```
let fprintf (type a) emit (desc : a desc) : a =
  let rec eval : type a . a desc -> a =
    function
    | Nil ->
      () (* We learn [a = unit]. *)
    | Lit (s, desc) ->
      ???
    | Hole (to_string, desc) ->
      ???

  in eval desc
```

Recall

```
| Lit : string * 'a desc -> 'a desc
```

Implementing fprintf

```
let fprintf (type a) emit (desc : a desc) : a =
  let rec eval : type a . a desc -> a =
    function
    | Nil ->
      ()
    | Lit (s, desc) ->
      ??? (* We learn no new type equality. *)
    | Hole (to_string, desc) ->
      ???

  in eval desc
```

Recall

```
| Lit : string * 'a desc -> 'a desc
```

Implementing fprintf

```
let fprintf (type a) emit (desc : a desc) : a =
  let rec eval : type a . a desc -> a =
    function
    | Nil ->
      ()
    | Lit (s, desc) ->
      emit s; eval desc
    | Hole (to_string, desc) ->
      ???

  in eval desc
```

Recall

```
| Hole : ('data -> string) * 'a desc -> ('data -> 'a) desc
```

Implementing fprintf

```

let fprintf (type a) emit (desc : a desc) : a =
  let rec eval : type a . a desc -> a =
    function
    | Nil ->
      ()
    | Lit (s, desc) ->
      emit s; eval desc
    | Hole (to_string, desc) ->
      ??? (* We learn [a = data -> b] *)
          (* [to_string : data -> string; desc : b desc] *)
  in eval desc

```

Recall

```

| Hole : ('data -> string) * 'b desc -> ('data -> 'b) desc

```

Implementing fprintf

```

let fprintf (type a) emit (desc : a desc) : a =
  let rec eval : type a . a desc -> a =
    function
    | Nil ->
      ()
    | Lit (s, desc) ->
      emit s; eval desc
    | Hole (to_string, desc) ->
      fun x -> emit (to_string x); eval desc
      (* [x] has type [data]; [eval desc] has type [b] *)
  in eval desc
  (* and [data -> b] is [a] *)

```

Recall

```

| Hole : ('data -> string) * 'b desc -> ('data -> 'b) desc

```

Using fprintf

Voilà! From fprintf, we get printf.

```
let printf desc =  
  let emit = print_string in  
  fprintf emit desc
```

Its type is 'a desc -> 'a.

Using fprintf

To construct descriptors, some sugar is needed.

```
module Sugar = struct
  let nil = Nil
  let lit s desc = Lit (s, desc)
  let d desc = Hole (string_of_int, desc)
  let s desc = Hole (Fun.id, desc)
end
```

Using `fprintf`

Examples

Tagless
interpretersRuntime type
descriptionsA well-typed
type-checker

Printf & friends

Metatheory

Conclusion

To construct descriptors, some sugar is needed.

```
module Sugar = struct
  let nil = Nil
  let lit s desc = Lit (s, desc)
  let d desc = Hole (string_of_int, desc)          (* %d *)
  let s desc = Hole (Fun.id, desc)                 (* %S *)
end
```

For example,

```
let desc =                                     (* "%d * %S = %d\n" *)
  d @@ lit " * " @@ s @@ lit " = " @@ d @@ lit "\n" @@ nil
```

`@@` is OCaml's low-priority **application operator**.

Using `fprintf`

```
let desc = (* "%d * %s = %d\n" *)
  d @@ lit " * " @@ s @@ lit " = " @@ d @@ lit "\n" @@ nil
```

Try this in the OCaml REPL (read-eval-print-loop):

```
# let () = printf desc 2 "12" 24;;
2 * 12 = 24
```

Implementing sprintf

Can we implement sprintf, which returns a string?

```
let naive_sprintf desc args =
  let b = Buffer.create 128 in
  let emit = Buffer.add_string b in
  fprintf emit desc args;
  Buffer.contents b
```

This is accepted but is **not** what we want.

Its (inferred) type is ('a -> 'b) desc -> 'a -> **string**.

We want sprintf to accept **a variable number of arguments**, not just one.

Implementing sprintf

In fact, we cannot write the desired type of `sprintf`.

Whereas `fprintf` has type `desc -> ??? -> unit`
which we have encoded as `'a desc -> 'a`,
we want `sprintf` to have type `desc -> ??? -> string`.

How can this be expressed?

A more general type of descriptors

Examples

Tagless
interpretersRuntime type
descriptionsA well-typed
type-checker

Printf & friends

Metatheory

Conclusion

We must equip ourselves with a **more general** type of descriptors.

```

type _ desc =
  | Nil   :                                     unit desc
  | Lit   :          string * 'a          desc ->      'a desc
  | Hole  : ('data -> string) * 'a          desc ->      ('data -> 'a      ) desc

```

A more general type of descriptors

Examples

Tagless
interpretersRuntime type
descriptionsA well-typed
type-checker

Printf & friends

Metatheory

Conclusion

We must equip ourselves with a **more general** type of descriptors.

```
type (_, _) desc =
  | Nil   :                               ('r, 'r) desc
  | Lit   :          string * ('a, 'r) desc -> ('a, 'r) desc
  | Hole  : ('data -> string) * ('a, 'r) desc ->
                                     ('data -> 'a, 'r) desc
```

In the type `('a, 'r) desc`,

- `'a` is the **shape**, as before,
- `'r` is the **eventual return type** of this shape.
 - it can be **unit** for `fprintf` and **string** for `sprintf`;
 - a descriptor can be polymorphic in `'r`.

Implementing fprintf, again

We can now give fprintf a **more general** type. We parameterize it with:

- `emit : string -> unit`
- `finished : unit -> r` — **new**
- `desc : (a, r) desc`

`fprintf emit finished desc` has type `a`.

`a` must in fact be a function type whose eventual return type is `r`.

`fprintf emit finished desc <args>` must eventually return a value of type `r`, which it obtains by calling `finished()`.

Implementing printf, again

```

let fprintf (type a r) emit (finished : unit -> r)
    (desc : (a, r) desc) : a =
  let rec eval : type a . (a, r) desc -> a =
    function
    | Nil ->
      (* We have [a = r] so [finished()] has type [a]. *)
      finished()
    | Lit (s, desc) ->
      emit s; eval desc
    | Hole (to_string, desc) ->
      fun x -> emit (to_string x); eval desc
  in eval desc

```

Implementing printf and sprintf

We can now implement `printf` and `sprintf`, among other variations:

```
let printf desc =  
  let emit = print_string  
  and finished () = () in  
  fprintf emit finished desc  
  
let sprintf desc =  
  let b = Buffer.create 128 in  
  let emit = Buffer.add_string b  
  and finished () = Buffer.contents b in  
  fprintf emit finished desc
```

We get

```
val printf : ('a, unit) desc -> 'a  
val sprintf : ('a, string) desc -> 'a
```


Using printf and sprintf

```
let desc () = (* "%d * %s = %d\n" *)
  d @@ lit " * " @@ s @@ lit " = " @@ d @@ lit "\n" @@ nil
```

Try this in the OCaml REPL (read-eval-print-loop):

```
# let () = printf (desc()) 2 "12" 24;;
2 * 12 = 24
# let (s : string) = sprintf (desc()) 2 "12" 24;;
val s : string = "2 * 12 = 24\n"
```

Here, we make desc a (constant) function in order to work around the [value restriction](#). See upcoming lecture on mutable state (GS).

Danvy et al.'s approach

Danvy, Keller and Puech (2015) view formats as **trees** instead of **lists**.

```
type (_, _) desc =
  | Lit   : string -> ('a, 'a) desc
  | Hole  : ('data -> string) -> ('data -> 'a, 'a) desc
  | Seq   : ('a, 'b) desc * ('b, 'c) desc -> ('a, 'c) desc
```

The type `('a, 'r) desc` has the same meaning as earlier.

Lit and **Hole** no longer play the role of list “cons” constructors.

Seq is a binary concatenation constructor, whose type says:

*If 'a is a multi-arrow type whose eventual return type is 'b and
if 'b is a multi-arrow type whose eventual return type is 'c then
'a is a multi-arrow type whose eventual return type is 'c.*

Danvy et al.'s approach

Danvy et al. write `kprintf` in [continuation-passing style](#):

```
let rec kprintf
: type a r . (a, r) desc -> (string -> r) -> a =
  fun desc finished ->
    match desc with
    | Lit s ->
      finished s
    | Hole to_string ->
      fun x -> finished (to_string x)
    | Seq (desc1, desc2) ->
      kprintf desc1 @@ fun s1 ->
        kprintf desc2 @@ fun s2 ->
          finished (s1 ^ s2)
```

Exercise (easy): define `printf`, `sprintf`, and `fprintf` using `kprintf`.

Exercise (harder): define `fprintf` directly.

Do not use string concatenation `^`.

System F +GADTs

System F +GADTs was defined by Xi, Chen and Chen (2003).

Xi, Chen, Chen,
Guarded Recursive Datatype Constructors, 2003.

Pottier and Gauthier,
Polymorphic typed defunctionalization and concretization, 2006.

System F +GADTs: terms

The syntax of terms is extended with constructor applications and case analysis constructs:

$$\begin{array}{lcl}
 t & ::= & \dots \\
 & | & K\ t \\
 & | & \text{case } t \text{ of } \bar{c} \\
 c & ::= & K\ \bar{X}\ x \mapsto t
 \end{array}$$

Each branch in a case construct is a **clause** c .

System F +GADTs: the typing judgement

Examples

Tagless
interpreters
Runtime type
descriptions
A well-typed
type-checker
Printf & friends

Metatheory

Conclusion

Recall the typing judgement of System F :

$$\Gamma \vdash t : T$$

In System F +GADTs, must we change the shape of this judgement?

We must extend it with a conjunction of **equality hypotheses**.

$$\Gamma \mid C \vdash t : T$$

This means: under Γ , **assuming the constraint C is true**, t has type T .

Equality constraints are given by $C, D ::= \text{True} \mid \text{False} \mid T = T \mid C \wedge C$.

In a well-formed judgement, every variable or type variable in C, t, T is introduced by Γ .

System F +GADTs: type declarations

Examples

Tagless
interpreters
Runtime type
descriptions
A well-typed
type-checker
Printf & friends

Metatheory

Conclusion

We assume that a family of type constructors F is given.

- for simplicity, we assume they have arity 1.

The syntax of types includes applications of type constructors:

$$T := X \mid T \rightarrow T \mid T + T \mid T \times T \mid 0 \mid 1 \mid F T$$

We assume that a family of data constructors K is given.

- for simplicity, we assume they have arity 1.

We assume that each data constructor has a closed **type scheme**:

$$K : \forall \bar{X}. D \Rightarrow T_1 \rightarrow F T_2$$

Example

For example, the equality GADT *eq* could be a type constructor:

$$F ::= \dots \mid eq$$

Equal could be a data constructor:

$$K ::= \dots \mid Equal$$

whose type scheme would be:

$$Equal : \forall \alpha \beta. \alpha = \beta \Rightarrow unit \rightarrow eq (\alpha \times \beta)$$

This is a **constrained type scheme** – remember Henry Ford.

System $F+$ GADTs: an auxiliary judgement

For readability, we introduce the auxiliary judgement

$$K \leq D \Rightarrow T_1 \rightarrow F T_2$$

whose definition is the following:

$$\frac{K : \forall \bar{X}. D \Rightarrow T_1 \rightarrow F T_2}{K \leq D[\bar{T}/\bar{X}] \Rightarrow T_1[\bar{T}/\bar{X}] \rightarrow F T_2[\bar{T}/\bar{X}]}$$

This judgement means that $D \Rightarrow T_1 \rightarrow F T_2$ is
a **valid monomorphic constrained type** for K .

For example, we have

$$\frac{\text{Equal} : \forall \alpha \beta. \alpha = \beta \Rightarrow \text{unit} \rightarrow \text{eq} (\alpha \times \beta)}{\text{Equal} \leq \text{int} = \text{int} \Rightarrow \text{unit} \rightarrow \text{eq} (\text{int} \times \text{int})}$$

System F +GADTs: the typing judgement

Examples

Tagless
interpreters
Runtime type
descriptions
A well-typed
type-checker
Printf & friends

Metatheory

Conclusion

The shape of the typing judgement is now $\Gamma \mid C \vdash t : T$.

This means: under Γ , **assuming the constraint C is true**, t has type T .

$$\begin{array}{c}
 \text{VAR} \\
 \hline
 \Gamma \mid C \vdash x : \Gamma(x)
 \end{array}
 \qquad
 \begin{array}{c}
 \text{ABS} \\
 \hline
 \frac{\Gamma; x : T_1 \mid C \vdash t : T_2}{\Gamma \mid C \vdash \lambda x. t : T_1 \rightarrow T_2}
 \end{array}
 \qquad
 \begin{array}{c}
 \text{APP} \\
 \hline
 \frac{\Gamma \mid C \vdash t_1 : T_1 \rightarrow T_2 \quad \Gamma \mid C \vdash t_2 : T_1}{\Gamma \mid C \vdash t_1 t_2 : T_2}
 \end{array}$$

$$\begin{array}{c}
 \text{TABS} \\
 \hline
 \frac{\Gamma; X \mid C \vdash t : T \quad X \# C}{\Gamma \mid C \vdash \Lambda X. t : \forall X. T}
 \end{array}
 \qquad
 \begin{array}{c}
 \text{TAPP} \\
 \hline
 \frac{\Gamma \mid C \vdash t : \forall X. T}{\Gamma \mid C \vdash t T' : T[T'/X]}
 \end{array}$$

The rules of System F are unchanged, except a constraint is transported.

System F_{+} GADTs: the typing judgement,
continued

Examples

Tagless
interpreters
Runtime type
descriptions
A well-typed
type-checker
Printf & friends

Metatheory

Conclusion

The typing rule for a **data constructor application** is straightforward:

$$\text{DCon} \quad \frac{\begin{array}{c} K \leq D \Rightarrow T_1 \rightarrow F T_2 \\ C \Vdash D \\ \Gamma \mid C \vdash t : T_1 \end{array}}{\Gamma \mid C \vdash K t : F T_2}$$

We write $C \Vdash D$ when **C entails D** (see next slide).

For example, we have

$$\frac{\begin{array}{c} \text{Equal} \leq \text{int} = \text{int} \Rightarrow \text{unit} \rightarrow \text{eq} (\text{int} \times \text{int}) \\ \text{True} \Vdash \text{int} = \text{int} \quad \Gamma \mid \text{True} \vdash () : \text{unit} \end{array}}{\Gamma \mid \text{True} \vdash \text{Equal} () : \text{eq} (\text{int} \times \text{int})}$$

On the other hand, $\Gamma \mid \text{True} \vdash \text{Equal} () : \text{eq} (\text{int} \times \text{bool})$ **cannot** be proved because $\text{True} \Vdash \text{int} = \text{bool}$ does not hold.

System F +GADTs: entailment

Let ρ denote a total mapping of type variables to closed types.

We write $\rho \vdash C$ to mean that ρ satisfies C or ρ is a solution of C :

$$\rho \vdash \text{True} \qquad \frac{\rho(T_1) = \rho(T_2)}{\rho \vdash T_1 = T_2} \qquad \frac{\rho \vdash C_1 \quad \rho \vdash C_2}{\rho \vdash C_1 \wedge C_2}$$

The entailment $C \Vdash D$ holds if every solution of C is a also solution of D :

$$\frac{\forall \rho. \rho \vdash C \Rightarrow \rho \vdash D}{C \Vdash D}$$

Entailment is decidable.

System F +GADTs: entailment

For example,

$True$	entails	$int = int$	
$\alpha = int$	entails	$int = \alpha$	
$\alpha = int \wedge \alpha = \beta$	entails	$\beta = int$	
$\alpha \times \beta = int \times bool$	entails	$\alpha = int \wedge \beta = bool$	
$\alpha \times \beta = int \times bool$	entails	$\alpha \times \alpha = int \times int$	
$int = bool$	entails	$False$	
$F \ T = F' \ T'$	entails	$False$	if $F \neq F'$
$False$	entails	$T = T'$	

System $F+$ GADTs: the typing judgement,
continued

Examples

Tagless
interpreters
Runtime type
descriptions
A well-typed
type-checker
Printf & friends

Metatheory

Conclusion

Type-checking a **case analysis** construct is straightforward:

$$\text{CASE} \quad \frac{\begin{array}{c} \Gamma \mid C \vdash t : T_1 \\ \forall c \in \bar{c}. \quad \Gamma \mid C \vdash c : T_1 \rightarrow T_2 \\ \bar{c} \text{ is exhaustive} \end{array}}{\Gamma \mid C \vdash \text{case } t \text{ of } \bar{c} : T_2}$$

A **clause** takes the form $c ::= K \bar{X} x \mapsto t$.

\bar{c} is exhaustive if it contains a clause for every data constructor K .

System $F+$ GADTs: the typing judgement,
continued

When a clause is entered, **new constraints appear** locally.

CLAUSE

$$\frac{\begin{array}{c} K : \forall \bar{X}. D \Rightarrow T_1 \rightarrow F T_2 \\ (\Gamma; \bar{X}; x : T_1) \mid (C \wedge D \wedge F T_2 = F' T'_2) \vdash t : T' \\ \bar{X} \# C, T'_2, T' \end{array}}{\Gamma \mid C \vdash K \bar{X} x \mapsto t : F' T'_2 \rightarrow T'}$$

For example,

$$\frac{\begin{array}{c} \text{Equal} : \forall \alpha \beta. \alpha = \beta \Rightarrow \text{unit} \rightarrow \text{eq} (\alpha \times \beta) \\ (\Gamma; \alpha; \beta; x : \text{unit}) \mid (\text{True} \wedge \alpha = \beta \wedge \text{eq} (\alpha \times \beta) = \text{eq} (T \times U)) \vdash t : T' \end{array}}{\Gamma \mid \text{True} \vdash \text{Equal} \alpha \beta x \mapsto t : \text{eq} (T \times U) \rightarrow T'}$$

so the branch t is type-checked under the assumption
 $\text{eq} (\alpha \times \beta) = \text{eq} (T \times U)$, which entails $T = U$.

The type-checker **can assume** $T = U$ while type-checking t .

System F +GADTs: the typing judgement,
continued

Examples

Tagless
interpreters
Runtime type
descriptions
A well-typed
type-checker
Printf & friends

Metatheory

Conclusion

There remains to introduce a typing rule that **exploits** the hypothesis C :

$$\text{CONVERSION} \quad \frac{\Gamma \mid C \vdash t : T \quad C \Vdash T = T'}{\Gamma \mid C \vdash t : T'}$$

This rule is **not** syntax-directed.

One can imagine a variant of the system where conversion is explicit.
System FC is the core language of the Glasgow Haskell compiler.

Sulzmann, Chakravarty, Peyton Jones, Donnelly,
System F with Type Equality Coercions, 2007.

System $F+$ GADTs: the typing judgement,
continued

Examples

Tagless
interpreters
Runtime type
descriptions
A well-typed
type-checker
Printf & friends

Metatheory

Conclusion

Another rule can exploit the hypothesis C when this hypothesis is *False*:

$$\frac{\begin{array}{c} \text{CONTRADICTION} \\ C \Vdash \text{False} \end{array}}{\Gamma \mid C \vdash t : T}$$

Ex falso, quod libet.

In particular, if $C \Vdash \text{False}$ then $\Gamma \mid C \vdash \text{absurd} : T$.

In OCaml, *absurd* is written `.` and is used to indicate a dead branch.

System F +GADTs: type soundness

Exercise: write down the omitted details (e.g., the reduction rule for *case*), then prove Subject Reduction and Progress.

An affair to remember

The fundamental feature of GADTs is to let a **value** serve as a witness of an equality between two **types**.

Therefore, a **runtime test** (a case analysis) **can reveal type information**, even though types do not exist at runtime: **type erasure** is still possible.

GADTs allow simulating some uses of **dependent types**.

Without GADTs, one could live with ordinary algebraic data types: more **tags**, more (redundant) **runtime tests**, more **dead branches**.

With GADTs, one can gain space, time, elegance and static assurance.

Beyond GADTs

GADTs allow reasoning about equalities between types, but the idea can be generalized by allowing constraints to be **formulae in a more expressive logic**, as long as entailment remains decidable.

For instance, Xi's "Dependent ML" exploits Presburger arithmetic formulae to reason about integers, with applications to array bounds checking, balanced binary trees, etc.