

To Infinity and Beyond: coinduction¹

February 10, 2021

¹Freely inspired from Andreas Abel's "Coprograms Programming Infinite Objects by Observations"

Representation of Infinite Datastructures

Functional encoding (strict languages: Scheme, ML)

- **thunk** computation with an abstraction
`fun () -> ...`
- **force** computation with an application of `()`

Usual datatype (lazy language: Haskell)

- Laziness allows any datatype to be infinite
- Program with pattern-matching: “Just Be Careful”

Final semantics

- Reacts to (a finite number of) *observations*
- Infinite structure = coinductive datatype

What not to do²

```
CoInductive Stream: Type :=  
  cons: nat -> Stream -> Stream
```

```
zeros: Stream  
zeros = cofix (cons 0)
```

```
force: Stream -> Stream  
forces = case s of cons x y => cons x y
```

```
eq: (s: Stream) -> s = force s  
eq s = case s of cons x y => refl
```

```
eqzeros: zeros = cons 0 zeros  
eqzeros = eq zeros
```

²Let's see how things unfold, McBride'09

“Understand coinduction not
through **construction**, but
through **observations**”

Familiar example: functions

- A function is a black box
- Observation: apply it to an argument (*experiment*) and observe its result (*observation*)
- Application is the defining principle of functions
- λ -abstraction is *derived*, secondary to application
- Typical semantic view of functions

Example: infinite objects

Principles

- A coinductive object is a black box
- Finite set of experiments (*projections*) we can perform
- The object is determined by the observations we make

Example

```
class type ['a] stream =  
  object  
    method hd: 'a  
    method tl: 'a stream  
  end
```

- `hd`, `tl`: only 2 experiments we can make on a stream
- a `stream` is defined by the results of these experiments

Defining infinite objects

Defining a cofixpoint

```
class ones : [int] stream =  
  object  
    method hd = 1  
    method tl = new ones  
  end
```

Defining the “constructor”

```
class ['a] cons (x: 'a)(s: 'a stream): ['a] stream =  
  object  
    method hd = x  
    method tl = s  
  end
```

Defining infinite objects

```
class interval (i: int) : [int] stream =  
  object  
    method hd = i  
    method tl = new interval (i+1)  
  end  
  
class nat : [int] stream = interval 0  
  
let rec take (n: int)(s: 'a stream): 'a list =  
  if n = 0 then  
    []  
  else  
    s#hd :: take (n-1) s#tl
```


Combinators on infinite objects

```
class ['b] map (f: 'a -> 'b)(s: 'a stream):  
    ['b] stream =
```

```
object
```

```
    method hd = f s#hd
```

```
    method tl = new map f s#tl
```

```
end
```

```
class ['a, 'b] zip (s1: 'a stream)(s2: 'b stream):  
    ['a * 'b] stream =
```

```
object
```

```
    method hd = (s1#hd, s2#hd)
```

```
    method tl = new zip s1#tl s2#tl
```

```
end
```

```
class ['a, 'b, 'c] zipWith (op: 'a -> 'b -> 'c)  
    (s1: 'a stream)(s2: 'b stream): ['c] stream =  
    ['c] map (fun (x, y) -> op x y) (new zip s1 s2)
```

Categorical perspective

Let $\mathcal{F} \in \mathbb{C} \Rightarrow \mathbb{C}$ be an endofunctor.

An \mathcal{F} -algebra consists of

- A carrier $A \in |\mathbb{C}|$
- A morphism $\alpha \in \mathbb{C}(|\mathcal{F}| A, A)$

The *initial algebra* is an \mathcal{F} -coalgebra

$(\mu\mathcal{F}, \text{constr} \in \mathbb{C}(|\mathcal{F}| (\mu\mathcal{F}), \mu\mathcal{F}))$ such that for any \mathcal{F} -algebra (A, α) we have

$$\begin{array}{ccc} |\mathcal{F}| (\mu\mathcal{F}) & \xrightarrow{\mathcal{F}^{\rightarrow} (\text{fix } \alpha)} & |\mathcal{F}| A \\ \parallel \text{constr} & & \alpha \downarrow \\ \mu\mathcal{F} & \xrightarrow{\text{fix } \alpha} & A \end{array}$$

Reduction: $\text{fix } \alpha (\text{constr } as) = \alpha (\mathcal{F}^{\rightarrow} (\text{fix } \alpha) as)$

Categorical perspective

Let $\mathcal{F} \in \mathbb{C} \Rightarrow \mathbb{C}$ be an endofunctor.

An \mathcal{F} -coalgebra consists of

- A carrier $A \in |\mathbb{C}|$
- A morphism $\alpha \in \mathbb{C}(A, |\mathcal{F}| A)$

The *terminal coalgebra* is an \mathcal{F} -coalgebra

$(\nu\mathcal{F}, \text{force} \in \mathbb{C}(\nu\mathcal{F}, |\mathcal{F}| (\nu\mathcal{F})))$ such that for any \mathcal{F} -coalgebra (A, α) we have

$$\begin{array}{ccc} A & \xrightarrow{\text{cofix } \alpha} & \nu\mathcal{F} \\ \alpha \downarrow & & \parallel \text{force} \\ |\mathcal{F}| A & \xrightarrow{\mathcal{F}^\rightarrow (\text{cofix } \alpha)} & |\mathcal{F}| (\nu\mathcal{F}) \end{array}$$

Reduction: $\text{force} (\text{cofix } \alpha \ a) = \mathcal{F}^\rightarrow (\text{cofix } \alpha) (\alpha \ a)$

Example: stream

$$\mathcal{F} X = \mathbb{N} \times X$$

$$\text{nstream} = \nu \mathcal{F}$$

$$\alpha () = (1, ())$$

$$\text{ones} = \text{cofix } \alpha ()$$

$$\begin{array}{ccc} \text{unit} & \xrightarrow{\text{cofix } \alpha} & \text{nstream} \\ \alpha \downarrow & & \downarrow \text{hd,tl} \\ \mathbb{N} \times \text{unit} & \xrightarrow{\text{id} \times (\text{cofix } \alpha)} & \mathbb{N} \times \text{nstream} \end{array}$$

Fibonacci

Recurrence equation:

fib	0	1	1	2	3	5	8	...
fib#tl	1	1	2	3	5	8	13	...
zipWith (+)	1	2	3	5	8	13	21	...

```
class fib: [int] stream =  
  object  
    method hd = 0  
    method tl =  
      object  
        method hd = 1  
        method tl = new zipWith (+) (new fib) (new fib#tl)  
      end  
    end  
  end
```

Conclusion

Positive	Negative
'a option	'a -> 'b
'a list	'a stream
type	object
constructor	methods / copatterns
pattern-matching	projection
algebra	coalgebra