

Miles Studio – Event CSV Remapper

Provides a way to sync events to external definitions

Miles Studio provides a CSV Remapper that allows for Events in Miles Studio to be exported and reimported with updates to the Sources the Events reference. This system also allows for new Events to be created by duplicating existing Events and then altering the assigned Sources, as well as renaming old events.

To use, select any number of events to export, then go to Tools / Event CSV Remapper. The list of selected events will be displayed under the **Export** tab. Press the Export button in the lower right and select a destination filename.

Format

The CSV will output with a line for headers, and then one line for each Source.

Event Folder	Old Event Name	New Event Name	Action Index	Source Tree Path	Old Source Name	New Source Name
Bank/folder	MyEvent	MyEvent	0	state[0].layer[0].selector[1]	MySource	MySource
			0	state[0].layer[0].selector[2]	MySource2	MySource2

Most of the output data is used by Miles during reimport to find the original event. The only fields that can be changed are NewEventName and NewSourceName. Note that when there are multiple sources for one event the first three fields are left blank after the first source.

- **NewEventName** – Changing this will cause a new event to be create that is an exact duplicate of the old name, or if desired, rename the existing event. If NewSourceName is also different, the new event will have its sources updated as well.
- **NewSourceName** – Changing this will simply update the existing event to use the new source, replacing the one referenced by OldSourceName.

Adding New Sources

New sources can be added to an existing event by adding a new line to the CSV file. This is the only time that the number of lines can be changed during the export/import process. **The new line must**

have the same SourceTreePath as another line. This line determines where the new source will be added. In the above example, if another line were added such that the file looked like:

Event Folder	Old Event Name	New Event Name	Action Index	Source Tree Path	Old Source Name	New Source Name
Bank/folder	MyEvent	MyEvent	0	state[0].layer[0].selector[1]	MySource	MySource
			0	state[0].layer[0].selector[2]	MySource2	MySource2
			0	state[0].layer[0].selector[2]	MySource2	MySource3

This would result in the event MyEvent adding another Source (MySource3) to the selector to its first voice (action index 0). Note that if this would be the second source on the event, then the first three fields must be blank. For example, if Miles exported:

Event Folder	Old Event Name	New Event Name	Action Index	Source Tree Path	Old Source Name	New Source Name
Bank/folder	MyEvent	MyEvent	0	state[0].layer[0].selector[0]	MySource	MySource

Then when adding a source, the result would be:

Event Folder	Old Event Name	New Event Name	Action Index	Source Tree Path	Old Source Name	New Source Name
Bank/folder	MyEvent	MyEvent	0	state[0].layer[0].selector[0]	MySource	MySource
			0	state[0].layer[0].selector[0]	MySource	MySource2

Importing

To import the altered CSV, go to Tools / Event CSV Remapper, and select the Import tab along the top. Load the CSV by clicking the Load button, and Miles will parse the file and report errors. Errors are reported by highlighting the incorrect field in red, and hovering the mouse over the cell will describe the error in a tooltip. A reload button on the right allows for rapid iteration when errors occur.

Fields that are changed are highlighted in blue.

Update Existing – This will not create any new events. Any changed event names will rename the old event. Sources are updated as well.

Create New – This will only create new events – old events will be neither renamed, nor will their sources be updated!