



Smart Car Washing System IoT.



Leonardo Tassinari,
Michele Olivieri
December 1, 2023

Contents

1	Circuit	2
2	Software Architecture	2
3	FSM diagrams	2
3.1	General diagram	2
3.2	Tasks	2

1 Circuit

The circuit schematic is as follows:

Device	pinout
Temperature sensor	A1
Pir	2
L1	7
L2	6
L3	5
Servo	3
Sonar trig	11
Ssonar echo	12

Since the servo motor might draw more current than the 150mA offered by arduino pins it's advisable to feed the servo with external power. All the elements attached to the power line create noise that hinder the analog temperature sensor's readings.

To dampen this effect it is possible to add decoupling capacitors (10-100 uF) to filter a bit those variation.

2 Software Architecture

The program is managed by a synchronous scheduler, it is triggered by a timer and launches non cooperative tasks. Each task period has been chosen accordingly to its operative requirements, and is a multiple of the base period of the scheduler. Some empiric tests have been made to ensure that no overrun happens in any scenario. The work tree of the program is divided in: Sensors and actuators, containing interfaces (abstract classes) and implementations for the devices. System, containing the scheduler and the task interface, Task, containing all the tasks.

3 FSM diagrams

3.1 General diagram

3.2 Tasks

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.