

## logistic\_regression

2022-07-31

2) Complete data model is logistic regression & probability to be missing depends  
## only on Y

WTS: If probability to be missing depends ONLY on Y and NOT on X, and missing

data is confined to either Y or X (will confine to just X in our case), then

LD is more efficient (and generates unbiased regression coefficients)

```
create.data <- function(beta_0 = 0, beta_1 = 1, beta_2 = 2, n = 200){  
  x1 = rnorm(n)           # some continuous variables  
  x2 = rnorm(n)  
  z = beta_0 + beta_1*x1 + beta_2*x2      # Here, B_0 = 1, B_1 = 2.  
  pr = 1/(1+exp(-z))      # pass through an inv-logit (sigmoid) function to  
                          # to constrain to [0,1];  
  Y = rbinom(n,1,pr)  
  data = as.data.frame(cbind(Y, x1, x2))  
}
```

```
data <- create.data()  
data
```

relative to multiple imputation.

##	Y	x1	x2
## 1	0	-0.966659885	-2.30957503
## 2	0	0.413768780	-0.35886034
## 3	1	0.625555293	0.91329839
## 4	1	-0.634437081	0.77801411
## 5	1	-0.411279070	0.17687392
## 6	1	0.653376668	0.04989277
## 7	0	-0.302163166	0.84027267
## 8	0	-0.961532540	0.57986432
## 9	1	-0.618665710	0.19497418
## 10	0	0.371382321	-0.27025280
## 11	0	-0.247532764	0.21515521
## 12	0	-0.336329901	-1.54203475
## 13	0	0.004056327	-1.20576957
## 14	1	0.501081401	-0.08893358
## 15	0	-0.705540562	0.81210662
## 16	0	-0.615832638	-1.49450713
## 17	0	-0.184008211	0.42901230
## 18	0	0.837940652	0.12833079

```

## 19 0 0.819690630 -1.65803739
## 20 1 1.193642780 0.45329521
## 21 0 0.131278195 -0.07680205
## 22 1 0.805655229 0.99438741
## 23 1 0.712021082 -0.45203549
## 24 0 -1.668358308 -0.73304524
## 25 1 -0.059996743 -0.17020636
## 26 1 -0.205635252 1.99482164
## 27 1 0.836106896 0.88067690
## 28 0 0.489556921 -0.87502948
## 29 0 0.081252159 0.62764734
## 30 0 0.573302732 -0.90715594
## 31 0 0.396522310 -0.97039127
## 32 0 -0.526714514 -1.43092381
## 33 0 -1.489086229 -1.04769958
## 34 1 0.199621396 0.72281435
## 35 1 -1.318658086 0.41581700
## 36 0 1.383108592 -2.26498937
## 37 0 -1.943089866 0.07178334
## 38 1 0.099457934 2.35648059
## 39 0 -1.324434346 -0.36506795
## 40 1 -0.226716268 1.57156326
## 41 1 1.431418131 0.62070354
## 42 1 -0.994008415 0.91063067
## 43 1 1.120606779 1.43643495
## 44 0 -0.562196836 -0.69743081
## 45 1 -0.050548584 -0.40461823
## 46 0 -1.550956583 -1.79793843
## 47 1 -0.174718664 0.19612777
## 48 1 -0.859068201 1.24072430
## 49 0 -0.587036200 -0.32485174
## 50 0 0.330046965 -0.44403283
## 51 1 0.760163954 1.22764755
## 52 1 -0.242811734 -0.01933909
## 53 1 -0.202576667 1.26579044
## 54 0 -0.659421534 0.34978793
## 55 1 0.539414626 -0.18295850
## 56 0 -0.103844212 0.21223964
## 57 1 -0.070973340 0.93250886
## 58 1 0.608006967 0.61739200
## 59 1 0.816535792 -0.02100856
## 60 0 0.313248555 0.35740752
## 61 1 -0.842362405 1.15403657
## 62 1 -1.179652440 2.41894796
## 63 1 1.711935199 1.01551253
## 64 0 -0.995255839 0.80895930
## 65 1 -0.552176050 0.53940675
## 66 0 -0.937066644 -0.19451250
## 67 1 1.044179939 0.18922335
## 68 0 0.225420362 -0.61670594
## 69 1 1.357948148 1.31805898
## 70 1 -0.093994899 0.01796951
## 71 0 0.871702776 -0.96894692
## 72 1 -0.980833465 0.98703436

```

```

## 73 1 0.507160051 0.10652636
## 74 0 0.099785200 -1.04094519
## 75 0 -0.901693333 0.20505689
## 76 0 -0.474255501 0.81822973
## 77 1 -1.043705425 0.99069077
## 78 1 -0.066003670 -0.05117990
## 79 1 0.121017966 0.58687541
## 80 1 -0.927557854 0.82505239
## 81 1 1.882859880 0.14422974
## 82 0 -0.626589089 0.11977845
## 83 1 0.204913693 0.23228225
## 84 1 1.399639217 0.83592291
## 85 1 0.610669709 1.28622751
## 86 1 -1.032985271 0.84659221
## 87 1 0.610046615 0.49394264
## 88 1 -0.372750275 0.45289534
## 89 0 -1.852423425 -0.73920195
## 90 1 0.886502879 0.74559819
## 91 1 -1.605507687 0.26776339
## 92 1 1.430078936 -1.43723950
## 93 1 -0.825435322 0.57927628
## 94 0 -0.474063027 -0.64280691
## 95 1 0.364598734 0.44762296
## 96 1 -2.068827387 1.15646894
## 97 0 0.604965343 -0.10149201
## 98 1 1.664206419 1.17033305
## 99 0 3.006618174 -0.09340858
## 100 0 0.198483401 -0.13611669
## 101 0 -0.643154225 -0.91269666
## 102 1 0.380278493 -0.28972030
## 103 1 -0.342182660 1.66679690
## 104 1 -1.022550555 0.54557690
## 105 0 -0.701967158 -1.12266377
## 106 1 0.126428672 0.63422318
## 107 0 -0.754764707 -0.51448471
## 108 1 0.365500539 0.81788112
## 109 0 0.059043981 0.36176285
## 110 0 -1.319651434 -0.65364493
## 111 0 -1.003563365 0.25706587
## 112 1 -0.660043247 -0.96055065
## 113 1 -0.362333178 2.29510606
## 114 1 1.137560612 1.15000704
## 115 1 1.258399090 0.59349911
## 116 1 1.505411120 2.15324517
## 117 1 1.022761137 1.10726405
## 118 0 -1.825587532 -0.04005304
## 119 1 0.245271007 0.12504483
## 120 0 -0.980823074 -0.01020598
## 121 0 0.986570794 -0.63860904
## 122 0 0.237813573 -2.05281443
## 123 0 -1.144811313 -1.36318111
## 124 1 0.212885586 0.52330532
## 125 0 0.987571627 0.01222115
## 126 1 -1.394156827 1.94532269

```

```

## 127 1 1.022251100 0.76855727
## 128 1 0.024525765 2.05479104
## 129 1 -0.186578030 0.06152101
## 130 0 -1.001470233 0.12837315
## 131 0 -0.785422908 -0.97552050
## 132 0 0.196825432 -0.85247983
## 133 1 -0.054953309 -0.69265294
## 134 0 2.077601949 -1.81831686
## 135 1 1.426131206 -0.21936592
## 136 0 -0.555480101 -0.34634251
## 137 1 1.944718884 -0.60826573
## 138 1 0.979450033 -0.47398293
## 139 1 1.871309322 -1.07512152
## 140 0 1.266717348 -0.88023290
## 141 1 -2.084122862 0.89738962
## 142 0 0.540317118 0.12602731
## 143 0 -1.722405449 -0.38593160
## 144 1 -0.183612906 0.14154569
## 145 0 -1.549367430 1.25234242
## 146 1 0.839690457 1.38309788
## 147 1 -1.115205057 0.77043387
## 148 0 -0.624486404 -2.06144113
## 149 1 1.634785826 0.39421843
## 150 0 -0.593964265 0.21605605
## 151 1 -0.365565264 0.44858699
## 152 0 -1.834391845 0.69863639
## 153 0 -0.689952058 0.24297540
## 154 0 -1.152356629 -2.09228231
## 155 0 0.108724563 1.07316920
## 156 0 -0.864380572 -0.65370281
## 157 0 -1.709152705 0.88971305
## 158 0 -1.647813901 -0.93443328
## 159 1 0.989625220 0.73508761
## 160 1 0.454098344 1.27747736
## 161 1 1.528591966 -0.40259252
## 162 1 0.038031337 1.75088627
## 163 0 -0.133959651 1.64630400
## 164 1 0.403917167 -0.06826208
## 165 1 0.702442407 -0.61543383
## 166 0 0.583063061 0.46794728
## 167 1 -0.599556423 1.06156384
## 168 0 -0.332641845 0.12696376
## 169 0 0.103207262 1.17420495
## 170 1 1.899675543 0.01472493
## 171 0 0.624631634 -0.86251490
## 172 1 0.501530110 0.07305673
## 173 0 -2.086114468 0.38383323
## 174 0 -0.912478380 0.71835592
## 175 1 -0.824903866 1.70229069
## 176 0 0.327485867 -0.92420976
## 177 0 -0.726021208 -0.63387890
## 178 0 -0.382031725 -0.30999654
## 179 1 0.421218814 0.16144099
## 180 1 -0.982807465 0.25897670

```

```
## 181 0 -1.098778333 -0.11839672
## 182 0 -1.359567301 -0.37002376
## 183 1 -0.040439502 0.15147097
## 184 0 0.270764019 -0.81552772
## 185 1 -0.622974273 -0.32375970
## 186 0 -0.967619896 -1.25477543
## 187 0 -1.830583436 -0.60669061
## 188 0 -0.172838444 -1.25541822
## 189 0 -0.916393519 1.51207787
## 190 1 -0.382614988 0.52010339
## 191 1 -0.600311480 -0.16327685
## 192 0 0.809542254 -0.22956870
## 193 0 -1.240968437 -0.66415987
## 194 0 0.398639061 -0.37865741
## 195 1 0.284672138 0.14290382
## 196 0 -0.849677920 0.62723631
## 197 0 -1.996663105 0.81319568
## 198 1 0.485311316 0.38141688
## 199 1 -0.290281048 2.48959665
## 200 0 -1.001175429 -0.58261810
```

## Add Missingness

```
# probability of missingness is greater for x1/x2 if Y == 1.
MNAR.make.missing <- function(data, probab_missing_larger = 0.2,
                               probab_missing_smaller = 0.6){
  # Setting up the randomness categories for missingness in x1, x2,
  higher <- data %>% filter(Y == 1) %>% select(x1)
  rx1_larger <- rbinom(nrow(higher), 1, probab_missing_larger)
  rx1_smaller <- rbinom(nrow(data) - nrow(higher), 1, probab_missing_smaller)
  rx2_larger <- rbinom(nrow(higher), 1, probab_missing_larger)
  rx2_smaller <- rbinom(nrow(data) - nrow(higher), 1, probab_missing_smaller)
  rx1 <- c(rx1_larger, rx1_smaller)
  rx2 <- c(rx2_larger, rx2_smaller)
  data <- data %>%
    arrange(desc(Y)) %>%
    cbind(rx1, rx2)
  # Implementing the missingness in x1, X_3, X_4
  data <- data %>% mutate(x1 = case_when(rx1 == 1 ~ as.numeric(NA),
                                         rx1 == 0 ~ as.numeric(data$x1))) %>%
    mutate(x2 = case_when(rx2 == 1 ~ as.numeric(NA),
                          rx2 == 0 ~ as.numeric(data$x2)))
  # Remove setup variables
  data <- select(data, -c(rx1, rx2))
  data
}
```

## Multiple Imputation

```
# Simulate multiple imputation, obtaining estimates and 95% confidence interval.
simulate_MI2 <- function(runs = 100) {
  res <- array(NA, dim = c(3, runs, 3))
}
```

```

times <- array(NA, dim = c(runs, 1, 1))
dimnames(res) <- list(c("Intercept", "x1", "x2"),
                      as.character(1:runs), c("estimate", "2.5%", "97.5%"))
sim_dataset <- as.data.frame(create.data(n = 1000))
for (run in 1:runs){
  # Note that time is only measured for the MI/imp steps
  # (i.e. filtering, predicting)
  missingness_sim_dataset <- MNAR.make.missing(sim_dataset, 0.2, 0.8)
  start_time <- Sys.time()
  imp_MI <- mice(missingness_sim_dataset, print = FALSE)
  fit <- with(imp_MI, glm(Y ~ x1 + x2, family = "binomial"))
  end_time <- Sys.time()
  tab <- summary(pool(fit), "all", conf.int = TRUE)
  res[1, run, ] <- as.numeric(tab[1, c("estimate", "2.5 %", "97.5 %")])
  res[2, run, ] <- as.numeric(tab[2, c("estimate", "2.5 %", "97.5 %")])
  res[3, run, ] <- as.numeric(tab[3, c("estimate", "2.5 %", "97.5 %")])

  times[run, 1, 1] <- as.numeric(end_time - start_time)
}
list(res, times)
}

# Run 100 iterations
res_MI2 <- simulate_MI2(100)

# Obtain confidence intervals & estimates for all coefficients, intercept.
apply(res_MI2[[1]], c(1, 3), mean, na.rm = TRUE)

##           estimate      2.5%      97.5%
## Intercept 0.1002261 -0.4251241 0.6255763
## x1        1.1277327  0.1873987 2.0680666
## x2        2.2181855  1.0932241 3.3431469

# Mean time for the multiple imputation instances
times <- res_MI2[[2]]
mean(times)

## [1] 0.2416485

Multiple_Imputation <- mean(times)

# Evaluating imputation method performance for estimating
# all parameters of interest.
res <- res_MI2[[1]]
true <- c(0, 1, 2)
Raw_Bias <- rowMeans(res[, "estimate"]) - true
Percent_Bias <- 100 * abs((rowMeans(res[, "estimate"]) - true) / true)
Coverage_Rate <- rowMeans(res[, "2.5%"] < true & true < res[, "97.5%"])
Average_Width <- rowMeans(res[, "97.5%"] - res[, "2.5%"])
RMSE <- sqrt(rowMeans((res[, "estimate"] - true)^2))
MI_measures <- data.frame(Raw_Bias, Percent_Bias, Coverage_Rate, Average_Width, RMSE)
knitr::kable(round(MI_measures, 3), align = "ccccc") %>% kable_styling()

```

	Raw_Bias	Percent_Bias	Coverage_Rate	Average_Width	RMSE
Intercept	0.100	Inf	1.00	1.051	0.170
x1	0.128	12.773	0.98	1.881	0.309
x2	0.218	10.909	0.99	2.250	0.360

## Listwise Deletion

```
# Simulate listwise deletion, obtaining estimates and 95% confidence interval.

simulate_LD <- function(runs = 100){
  res <- array(NA, dim = c(3, runs, 3))
  dimnames(res) <- list(c("Intercept", "x1", "x2"),
                        as.character(1:runs), c("estimate", "2.5%", "97.5%"))
  times <- array(NA, dim = c(runs, 1, 1))
  sim_dataset <- as.data.frame(create.data(n = 1000))
  # Note that time is only measured for the LD/imp steps (i.e. filtering, predicting)
  for (run in 1:runs){
    missingness_sim_dataset <- MNAR.make.missing(sim_dataset, 0.2, 0.5)
    start_time <- Sys.time()
    filtered_sim_dataset <- missingness_sim_dataset %>%
      select(Y, x1, x2) %>%
      filter(!is.na(x1), !is.na(x2))

    fit <- with(filtered_sim_dataset, glm(Y ~ x1 + x2, family = "binomial"))
    end_time <- Sys.time()
    times[run, 1, 1] <- as.numeric(end_time - start_time)
    # loop over each variable. Note we do the imputation just ONCE b/c LD is
    # deterministic.
    for (var in 1:3){
      edges <- as.numeric((confint.default(fit))[var,])
      estimate <- as.numeric(fit$coefficients)[var]
      interval <- c(estimate, edges)
      res[var, run, ] <- interval
    }
  }
  list(res, times)
}

result_LD <- simulate_LD(100)

# Obtain confidence intervals & estimates for all coefficients, intercept.
apply(result_LD[[1]], c(1, 3), mean, na.rm = TRUE)

##           estimate      2.5%      97.5%
## Intercept 0.9067962 0.6193571 1.194235
## x1        1.1459560 0.8061650 1.485747
## x2        2.2936344 1.8077398 2.779529

# Evaluating imputation method performance for estimating
# all parameters of interest.
res <- result_LD[[1]]
true <- c(0, 1, 2)
Raw_Bias <- rowMeans(res[, "estimate"]) - true
```

	Raw_Bias	Percent_Bias	Coverage_Rate	Average_Width	RMSE
Intercept	0.907	Inf	0.00	0.575	0.913
x1	0.146	14.596	0.93	0.680	0.208
x2	0.294	14.682	0.89	0.972	0.361

	average-runtime
Multiple Imputation	0.2416485
ListwiseDeletion	0.0073440

```
Percent_Bias <- 100 * abs((rowMeans(res[, "estimate"]) - true) / true)
Coverage_Rate <- rowMeans(res[, "2.5%"] < true & true < res[, "97.5%"])
Average_Width <- rowMeans(res[, "97.5%"] - res[, "2.5%"])
RMSE <- sqrt(rowMeans((res[, "estimate"] - true)^2))
LD_measures <- data.frame(Raw_Bias, Percent_Bias, Coverage_Rate, Average_Width, RMSE)
knitr::kable(round(LD_measures, 3), align = "cccc") %>% kable_styling()
```

```
# Mean time for 100 instances of LD
times_LD <- result_LD[[2]]
ListwiseDeletion <- mean(times_LD)
```

```
mean_times <- as.data.frame(rbind(Multiple Imputation, ListwiseDeletion), col.names = "average_runtime")
colnames(mean_times) <- "average-runtime"
mean_times
```

```
##                average-runtime
## Multiple Imputation    0.241648512
## ListwiseDeletion      0.007343969
```

```
knitr::kable(mean_times) %>% kable_styling(full_width = F)
```