

# Vim Quick Reference

## MOVEMENT

### By Line

|                      |   |
|----------------------|---|
| <b>G</b>             | go to end of file                           |
| <b>nG</b>            | go to line <i>n</i>                         |
| <b>0, \$</b>         | begin, end of a line                        |
| <b>^</b> or <b>_</b> | first non-blank char on line                |
| <b>+</b> , <b>-</b>  | first non-blank char on next, previous line |

### By Screen

|                       |   |
|-----------------------|---|
| <b>Ctrl-F, Ctrl-B</b> | scroll forward, back one full screen      |
| <b>Ctrl-D, Ctrl-U</b> | scroll forward, back half a screen        |
| <b>Ctrl-E, Ctrl-Y</b> | scroll screen up, down by one line        |
| <b>H, M, L</b>        | go to top, middle, bottom of screen       |
| <b>zJ, z-</b>         | position line with cursor at top / bottom |
| <b>z, zz</b>          | position line with cursor at middle       |

### By Window

|                                 |                             |
|---------------------------------|-----------------------------|
| <b>:sp(lit)</b>                 | split window horizontally   |
| <b>:vsp(lit)</b>                | split window vertically     |
| <b>ctrl-ww</b>                  | move cursor between windows |
| <b>ctrl-w &gt;, ctrl-w &lt;</b> | horizontally resize window  |
| <b>:hide</b>                    | hide current window         |

### By Buffer

|                              |                           |
|------------------------------|---------------------------|
| <b>:ls, :buffers</b>         | list buffers              |
| <b>:b, &lt;ctrl-^&gt;</b>    | switch between buffers    |
| <b>:bn, n-&lt;ctrl-^&gt;</b> | switch to buffer <i>n</i> |
| <b>&lt;ctrl-^&gt;</b>        | buffer switch             |

### By Character

|                   |                       |
|-------------------|-----------------------|
| <b>h, j, k, l</b> | left, down, up, right |
|-------------------|-----------------------|

### Marking Position on Screen

|           |  |
|-----------|--|
| <b>mp</b> | mark current position(line) as <i>p</i> (a..z) |
| <b>`p</b> | move to marker line <i>p</i>                   |
| <b>'p</b> | move to first char on marker line <i>p</i>     |

### Miscellaneous Movement

|                           |   |
|---------------------------|---|
| <b>fm, Fm, tm, Tm</b>     | fwd, bkd to/before and after character <i>m</i> |
| <b>w, W</b>               | move to next word                               |
| <b>b, e, B, E</b>         | move to beginning, end of word                  |
| <b>), (, ][, [[, ], {</b> | next, previous sentence, section, paragraph     |
| <b>%</b>                  | go to matching parenthesis ( ), { }, [ ]        |

## EDITING TEXT

### Entering Text

|                       |  |
|-----------------------|--|
| <b>~</b>              | toggle character case                                  |
| <b>O, o</b>           | open line to enter above, below current line           |
| <b>A, a</b>           | append after line, after cursor                        |
| <b>I, i</b>           | insert before line, before cursor                      |
| <b>r</b>              | replace character under cursor                         |
| <b>cm, cc</b>         | change <i>m</i> characters, a line (del & ins.)        |
| <b>J</b>              | join end of line with next line                        |
| <b>.</b>              | repeat last cmd of text editing                        |
| <b>U</b>              | undo changes on current line                           |
| <b>u</b>              | undo last command                                      |
| <b>:r f</b>           | insert text from external file <i>f</i> (paste a file) |
| <b>:r!(shell cmd)</b> | insert shell command output                            |

### Cut, Copy, Paste

|                   |  |
|-------------------|--|
| <b>dm, dd</b>     | delete <i>m</i> characters, the whole line     |
| <b>d%, y%</b>     | delete/yank a block of { }, [ ], or [ ]        |
| <b>D</b>          | delete until end of line                       |
| <b>x, X</b>       | delete character under, before cursor          |
| <b>ym</b>         | yank to buffer ( <i>m</i> is movement)         |
| <b>yy, Y</b>      | yank current line to buffer                    |
| <b>p, P</b>       | paste from buffer after, before cursor         |
| <b>"bdd, "byy</b> | cut, yank line to named buffer <i>b</i> (a..z) |
| <b>"bp</b>        | paste from named buffer <i>b</i>               |

### Indentation

|                          |   |
|--------------------------|---|
| <b>==</b>                | indent the line <i>correctly</i>                      |
| <b>=%</b>                | indent a block of { }, [ ] or [ ] <i>correctly</i>    |
| <b>gg=G</b>              | indent entire buffer/file <i>correctly</i>            |
| <b>n&gt;&gt;, n&gt;m</b> | indent <i>n</i> lines ( <i>m</i> is movement)         |
| <b>n&lt;&lt;, n&lt;m</b> | un-indent left <i>n</i> lines ( <i>m</i> is movement) |
| <b>&gt;%, &lt;%</b>      | indent a block of { }, [ ] or [ ]                     |
| <b>&gt;'a</b>            | indent from marker 'a' to current line                |
| <b>:retab</b>            | correct tabs (tabs -> spaces)                         |

### Searching and Replacing

|                       |   |
|-----------------------|---|
| <b>/w</b>             | search forward for <i>w</i>               |
| <b>?w</b>             | search backward for <i>w</i>              |
| <b>n, N</b>           | repeat search in same, opposite direction |
| <b>:s/old/new/g</b>   | replace all occurrences on the line       |
| <b>:%s/old/new/g</b>  | replace all occurrences in file           |
| <b>:%s/old/new/gc</b> | same as above, with confirmation          |
| <b>&amp;</b>          | repeat replacement operation              |

### Miscellaneous

|                                  |                              |
|----------------------------------|------------------------------|
| <b>^G</b>                        | show status                  |
| <b>/ &lt;ctrl-f&gt; , :his /</b> | list vi search history       |
| <b>:his</b>                      | list vi command history      |
| <b>:set ft=c</b>                 | set to use C-style file type |

## Combinations

|                         |   |
|-------------------------|---|
| <b>d^, d\$, dW, dw</b>  | delete to line beginning, end, Word, word     |
| <b>d3l, x3</b>          | delete 3 characters after cursor, inclusively |
| <b>i + Ctrl-V + Tab</b> | insert a tab                                  |

### Regional Copy/Paste/Delete (1)

|                 |   |
|-----------------|---|
| <b>dG, yG</b>   | delete/yank until end of file                     |
| <b>dnG, ynG</b> | delete/yank from current line until line <i>n</i> |
| <b>ndd, nyy</b> | delete/yank <i>n</i> lines                        |

### Regional Copy/Paste/Delete (2)

- (1) At region start line, type **"ma"** to set marker "a".
- (2) At region end line, use **:'a,y b** to yank the region from marker "a" to current line into buffer "b".  
Note: **'a** means from marker **"a"**, **.** means current line, **b** is buffer "b". Use **:'a,d b** to delete region and save a copy into buffer "b".
- (3) At the desired line, use **:pu b** to paste the content of buffer "b".

|                                  |  |
|----------------------------------|--|
| <b>d2h, X2</b>                   | delete 2 characters before cursor, exclusively |
| <b>c^, c\$, cW, cw, c3l, c2h</b> | change (delete and insert)                     |

|                       |   |
|-----------------------|---|
| <b>dL, yL</b>         | delete/yank until bottom line on screen         |
| <b>:n,m,d, :n,m,y</b> | delete/yank from line <i>n</i> to line <i>m</i> |
| <b>:n.,d, :n.,y</b>   | delete/yank until current line                  |