

**Sheet 8 of 8 | 320 × 260 × 18 mm hardwood**



|           |                                      |
|-----------|--------------------------------------|
| PROJECT   | CSM V3 — Circular Sock Machine       |
| PART      | Wood Upper Deck V1.0                 |
| SIZE      | 320 × 260 × 18 mm                    |
| MATERIAL  | Hardwood (walnut/maple/Baltic birch) |
| FINISH    | Sanded smooth, oiled or sealed       |
| TOLERANCE | ±1.0 mm (holes), ±2 mm (outline)     |
| REV       | V1.0                                 |
| DATE      | 2026-06-05                           |
| QTY       | 1 piece                              |

## HOLE LIST

| # | X     | Y     | Drill | Use                      |
|---|-------|-------|-------|--------------------------|
| 1 | +150  | -120  | Ø5.5  | upright SE               |
| 2 | +150  | +120  | Ø5.5  | upright NE               |
| 3 | -150  | -120  | Ø5.5  | upright SW               |
| 4 | -150  | +120  | Ø5.5  | upright NW               |
| 5 | +63.6 | +63.6 | Ø5.5  | plate NE (PCD180 @ 45°)  |
| 6 | -63.6 | +63.6 | Ø5.5  | plate NW (PCD180 @ 135°) |
| 7 | -63.6 | -63.6 | Ø5.5  | plate SW (PCD180 @ 225°) |
| 8 | +63.6 | -63.6 | Ø5.5  | plate SE (PCD180 @ 315°) |
| — | 0     | 0     | Ø170  | cam ring through-hole    |

**TOTAL: 9 holes (8× Ø5.5 + 1× Ø170)**

## NOTES

- Hole tolerance  $\pm 1$  mm acceptable
- Cam-ring hole can be jigsawed if no  $\varnothing 170$  hole saw
- Sand all edges before assembly
- Bolt: M5  $\times$  35 mm through wood into  
T-nut (upright) or M5 insert (plate)
- Dry-fit before any glue/finish