

Outliers and Hallucinations: Contributions to Robust Community Detection and Language Model Alignment

Leonardo Martins Bianco

Supervisors:

Christine Keribin (Université Paris-Saclay, LMO)

Zacharie Naulet (Université Paris-Saclay, INRAE)

Jessica Hoffmann (Google DeepMind)

December 4, 2025

Thesis progress



Thesis progress



Thesis progress



Thesis progress



Overview

Part I: Contributions to Robust Community Detection

Robust Estimation for the SBM


Part II: Contributions to Language Model Alignment

Reducing Hallucinations with Synthetic Hallucinations

Decoding-time Realignment of Language Models

Motivation

- ❖ *Adjacency matrix:*
symmetric $A \in \{0, 1\}^{n \times n}$



Jazz collaborations in New York, Chicago,
and elsewhere [2]

Motivation


- ❖ *Adjacency matrix:*
symmetric $A \in \{0, 1\}^{n \times n}$
- ❖ *Community detection [1]:*
group similar nodes,
sensitive to *outliers*



Clustering of the Jazz collaborations

Motivation

- ❖ *Adjacency matrix:* symmetric $A \in \{0, 1\}^{n \times n}$
- ❖ *Community detection* [1]: group similar nodes, sensitive to *outliers*
- ❖ *Robust algorithm:* accurate results despite outliers



Clustering of the Jazz collaborations


The Stochastic Block Model [3]

$Z_i \rightarrow$ community of node i

$K \rightarrow$ nb. of communities

$\pi_k \rightarrow$ size of community k

$\Gamma_{kl} \rightarrow$ connectivity k, l



The Stochastic Block Model [3]

$Z_i \rightarrow$ community of node i


$K \rightarrow$ nb. of communities

$\pi_k \rightarrow$ size of community k

$\Gamma_{kl} \rightarrow$ connectivity k, l

$(Z, A) \sim \text{SBM}_K(\pi, \Gamma)$


$$\begin{cases} \mathbb{P}(Z_i = k) = \pi_k \\ \mathbb{P}(A_{ij} = 1 | Z_i = k, Z_j = l) = \Gamma_{kl} \end{cases}$$



The Corrupted Stochastic Block Model [4]

Adversary creates outliers:

1. $(Z, A_{\text{pure}}) \sim \text{SBM}_K(\pi, \Gamma)$
2. Adversary arbitrarily changes edges of γn nodes
3. Corrupted A is observed



Research question

- ❖ **Problem:** estimate Γ under *worst-case* adversary
- ❖ For $K = 1$, solved by Acharya et al. [5]

Research question:

How to robustly estimate Γ for $K > 1$?

Results

- ❖ Idea: find subgraph $S = S_1 \cup \dots \cup S_K$ excluding outliers

$$\Rightarrow \hat{\Gamma} = \left(\sum_{i \in S_k j \in S_l} A_{ij} \right) / |S_k||S_l| \quad \text{is a good estimator}$$

Results

- ❖ Idea: find subgraph $S = S_1 \cup \dots \cup S_K$ excluding outliers

$$\Rightarrow \hat{\Gamma} = \left(\sum_{i \in S_k j \in S_l} A_{ij} \right) / |S_k||S_l| \text{ is a good estimator}$$

- ❖ **Contribution:** extend bound in Acharya et al. [5] to $K > 1$

Theorem [6]. Let S be a subgraph clustered into S_1, \dots, S_K , Ω_k the nodes in community k , \mathcal{I} the inliers. Let $\hat{\Gamma} = (\sum_{i \in S_k j \in S_l} A_{ij}) / |S_k||S_l|$ and $\hat{Q}(S)_{ij} = \hat{\Gamma}_{S(i)S(j)}$. Then,


$$\|\Gamma - \hat{\Gamma}\|_1 \lesssim \frac{\|A_S - \hat{Q}(S)\|_{\text{op}}}{\min_{1 \leq k \leq K} |\Omega_k \cap S_k \cap \mathcal{I}|}$$

Results

- ❖ Idea: find subgraph S excluding worst outliers
- ❖ **Contribution:** extend bound in Acharya et al. [5] to $K > 1$
- ❖ **Contribution** (`SUBSEARCH`, [6]): finding S by optimizing $c(S) := \|A_S - \hat{Q}(S)\|_{\text{op}}$ via Simulated Annealing
- ❖ **Contribution:** github.com/leobianco/robust_estim_sbm

SUBSEARCH: Subgraph Search via Simulated Annealing


Explore the space \mathcal{S} of subgraphs
 $S \subset G$ of size $(1 - \gamma)n$, to minimize
 $c(S) = \|A_S - \hat{Q}(S)\|_{\text{op}}$



SUBSEARCH: Subgraph Search via Simulated Annealing

Explore the space \mathcal{S} of subgraphs
 $S \subset G$ of size $(1 - \gamma)n$, to minimize
 $c(S) = \|A_S - \hat{Q}(S)\|_{\text{op}}$


- ① **Initialize:** random subgraph S_0 ,
high temperature T_0



SUBSEARCH: Subgraph Search via Simulated Annealing

Explore the space \mathcal{S} of subgraphs
 $S \subset G$ of size $(1 - \gamma)n$, to minimize
 $c(S) = \|A_S - \hat{Q}(S)\|_{\text{op}}$

- ① **Initialize:** random subgraph S_0 ,
high temperature T_0
- ② **Propose $S_{\text{candidate}}$:** swap
 $i \in S_{\text{current}}$ with $j \notin S_{\text{current}}$




SUBSEARCH: Subgraph Search via Simulated Annealing

Explore the space \mathcal{S} of subgraphs
 $S \subset G$ of size $(1 - \gamma)n$, to minimize
 $c(S) = \|A_S - \hat{Q}(S)\|_{\text{op}}$

- ① **Initialize:** random subgraph S_0 ,
high temperature T_0

- ② **Propose $S_{\text{candidate}}$:** swap
 $i \in S_{\text{current}}$ with $j \notin S_{\text{current}}$

- ③ **Accept or reject:** compute
 $\Delta = c(S_{\text{current}}) - c(S_{\text{candidate}})$,
accept with probability
 $\min(1, \exp(\Delta/T_t))$



SUBSEARCH: Subgraph Search via Simulated Annealing


Explore the space \mathcal{S} of subgraphs
 $S \subset G$ of size $(1 - \gamma)n$, to minimize
 $c(S) = \|A_S - \hat{Q}(S)\|_{\text{op}}$

- ① **Initialize:** random subgraph S_0 ,
high temperature T_0

- ② **Propose $S_{\text{candidate}}$:** swap
 $i \in S_{\text{current}}$ with $j \notin S_{\text{current}}$

- ③ **Accept or reject:** compute
 $\Delta = c(S_{\text{current}}) - c(S_{\text{candidate}})$,
accept with probability
 $\min(1, \exp(\Delta/T_t))$

- ④ **Cool down:** $T_{t+1} = c T_t$, $c \approx 1$



SUBSEARCH: Subgraph Search via Simulated Annealing


Explore the space \mathcal{S} of subgraphs
 $S \subset G$ of size $(1 - \gamma)n$, to minimize
 $c(S) = \|A_S - \hat{Q}(S)\|_{\text{op}}$

- ① **Initialize:** random subgraph S_0 ,
high temperature T_0


- ② **Propose $S_{\text{candidate}}$:** swap
 $i \in S_{\text{current}}$ with $j \notin S_{\text{current}}$

- ③ **Accept or reject:** compute
 $\Delta = c(S_{\text{current}}) - c(S_{\text{candidate}})$,
accept with probability
 $\min(1, \exp(\Delta/T_t))$


- ④ **Cool down:** $T_{t+1} = c T_t$, $c \approx 1$



Results





Results



Results

Parameters: $n = 200$, $K = 2$, $\gamma = 0.3$.




Results


Parameters: $n = 200, K = 2, \gamma = 0.3$.



- Community 1
- Community 2
- Detected Outliers
- FP / FN Outliers



Results



Discussion

- ❖ **Main takeaway:** “exploring” the space of subgraphs \Rightarrow find subgraphs avoiding outliers
- ❖ Perspective # 1: can we rigorously prove robustness?
- ❖ Perspective # 2: can we provide faster rates?

Overview

Part I: Contributions to Robust Community Detection

Robust Estimation for the SBM

Part II: Contributions to Language Model Alignment

Reducing Hallucinations with Synthetic Hallucinations

Decoding-time Realignment of Language Models

Motivation

- ❖ Chatbots based on Transformers [7]
- ❖ Hallucinations \approx false information, out of topic, rambling, toxic...
- ❖ How to mitigate them?

The image shows a screenshot of a news article from Ars Technica. The header features the Ars Technica logo and navigation links for 'biz & it', 'tech', 'science', 'policy', 'cars', 'gaming & culture', and 'store'. Below the header, a green banner reads 'BLAME GAME —'. The main title of the article is 'Air Canada must honor refund policy invented by airline's chatbot'. A subtitle below the title states 'Air Canada appears to have quietly killed its costly chatbot support.' The author is listed as 'ASHLEY BELANGER - 2/16/2024, 5:12 PM'. To the right of the text is a photograph of an Air Canada Boeing 777 aircraft in flight, set against a backdrop of mountains under a pinkish sunset sky.

Background on Language Models

- ❖ *Vocabulary* \mathcal{V} = set of *tokens* (“pieces of words”)
- ❖ Language model

$$\pi_\theta : x = (\text{token}_1, \dots, \text{token}_L) \mapsto \pi_\theta(\cdot | x) = \text{proba. over } \mathcal{V}$$

Background on Language Models

- ❖ *Vocabulary* \mathcal{V} = set of *tokens* (“pieces of words”)
- ❖ Language model

$$\pi_\theta : x = (\text{token}_1, \dots, \text{token}_L) \mapsto \pi_\theta(\cdot | x) = \text{proba. over } \mathcal{V}$$

- ❖ Autoregressive generation: *prompt* $x \rightarrow \text{response } y$

$$y_1 \sim \pi_\theta(\cdot | x)$$

$$y_2 \sim \pi_\theta(\cdot | x, y_1)$$


$$\vdots$$

$$y_t \sim \pi_\theta(\cdot | x, y_{<t})$$

Background on Language Models

Pre-training: given a dataset \mathcal{D}_{pre} , find θ minimizing


$$\ell(\theta; \mathcal{D}_{\text{pre}}) = - \sum_{x \in \mathcal{D}_{\text{pre}}} \sum_{i=1}^{|x|} \log \pi_\theta(x_{i+1} \mid x_{\leq i})$$




Background on Language Models

SFT: given a dataset \mathcal{D}_{SFT} , find θ minimizing

$$\ell(\theta; \mathcal{D}_{\text{SFT}}) = - \sum_{x \in \mathcal{D}_{\text{SFT}}} \sum_{i=1}^{|x|} \log \pi_\theta(x_{i+1} \mid x_{\leq i})$$



Retrieval Augmented Generation: NPOV Task [8]



Background on Language Models

Alignment to human preferences via Reinforcement Learning [9]:

1. Train a reward model R on \mathcal{D}_{RM}




Background on Language Models

Alignment to human preferences via Reinforcement Learning [9]:

1. Train a reward model R on \mathcal{D}_{RM}
2. Update the writer model π_{SFT}


$$\pi_\beta \in \arg \max_{\pi} \mathbb{E}_{\substack{x \sim \mathcal{D}_{\text{RL}} \\ y \sim \pi(y|x)}} [R(x, y)] - \beta \text{KL}(\pi \| \pi_{\text{SFT}})$$



Background on Language Models

Parameter-efficient RL \Rightarrow Low-Rank Adaptation (LoRA) [10]:

$$\theta = \theta_{\text{SFT}} + \underbrace{AB}_{\text{low rank}}$$



Background on Language Models

Evaluation via *autorater*:

Below are examples where an expert identifies when the neutral natural language rewriting of arguments used to answer a user query contains additional arguments not present in the original list.

User query:{user_query}


Pro arguments provided:{perspective_1}

Con arguments provided:{perspective_2}

Neutral point-of-view answer to user query, rewriting the provided arguments in natural language:{npov_response}

Expert linguist review: the rewriting of the provided arguments contains additional arguments not present in the original list (Yes/No):

{answer}



Research questions

Problem: \mathcal{D}_{RM} is costly, time-consuming, and error-prone to get

Research questions

Problem: \mathcal{D}_{RM} is costly, time-consuming, and error-prone to get

→ Synthetic hallucinations are cheap, fast, error-free

Research question #1:

Can synthetic hallucinations be used instead?

Creating Synthetic Hallucinations [8]

Pros:

1. Studies show marijuana is a safe drug
2. Legalization boosts the economy

Cons:

1. Marijuana is a gateway drug
2. Legalization brings costs

Neutral answer:

“Some people support marijuana legalization because it would boost the economy and most studies demonstrate it is a safe drug. Others oppose it because they see marijuana as a gateway drug, and its legalization would bring many costs.”

Creating Synthetic Hallucinations [8]

Pros:

1. Studies show marijuana is a safe drug
2. Legalization boosts the economy

Cons:

1. Marijuana is a gateway drug
2. Legalization brings costs

Neutral answer:


“Some people support marijuana legalization because it would boost the economy and most studies demonstrate it is a safe drug. Others oppose it because they see marijuana as a gateway drug, and its legalization would bring many costs.”

Creating Synthetic Hallucinations [8]

	<i>Train</i>	<i>Validation</i>	<i>Test</i>	<i>Total</i>
Non-hallucinated	335	117	126	578
Organic hallucinations	85	30	46	161
Synthetic hallucinations	303	98	67	468
.....
Samples	723	245	239	1207
Topics	30	14	28	72

Results

<i>SFT baseline (%)</i>	<i>Organic hallucinations (%)</i>	<i>Synthetic hallucinations (%)</i>
10.2	3.0	0.74



Example of Hallucination Removed

User query: Should Parents or Other Adults Be Able to Ban Books from Schools and Libraries?

Pros

- ❖ Keeping books with inappropriate content out of libraries protects kids but doesn't stop people from reading those books or prevent authors from writing them.
- ❖ Parents have the right to decide what material their children are exposed to and when.

Cons

- ❖ People can better understand the world and their position in it by reading works that are regularly criticized.
- ❖ Books are a portal to different life experiences and reading encourages empathy and social-emotional development.

Neutral point-of-view answer (SFT):

This is a very controversial topic. Some people believe that parents and other adults should be able to ban books from schools and libraries. They say that **this would protect children from inappropriate content**. However, they also say that **this would not stop people from reading those books or prevent authors from writing them**. On the other hand, **others say that banning books is a way to protect children from the world** and that **it is a way to encourage empathy and social-emotional development**. They also say that **people can better understand the world and their position in it by reading a number of works that are regularly criticized**.

Example of Hallucination Removed

User query: Should Parents or Other Adults Be Able to Ban Books from Schools and Libraries?

Pros

- ❖ Keeping books with inappropriate content out of libraries protects kids but doesn't stop people from reading those books or prevent authors from writing them.
- ❖ Parents have the right to decide what material their children are exposed to and when.

Cons

- ❖ People can better understand the world and their position in it by reading works that are regularly criticized.
- ❖ Books are a portal to different life experiences and reading encourages empathy and social-emotional development.

Neutral point-of-view answer (PE-RL):

I don't know what to make of this. Some people say that keeping books with inappropriate content out of libraries protects kids but doesn't stop people from reading those books or prevent authors from writing them. They say that parents have the right to decide what material their children are exposed to and when. Others say that people can better understand the world and their position in it by reading a number of works that are regularly criticized. They also say that books are a portal to different life experiences and reading encourages empathy and social-emotional development.

Research questions

Problem: coefficient β is expensive to tune via grid-search

Research question #2:

Can we adjust regularization strength without retraining?

Closed-form solution

- ❖ Closed-form solution to alignment objective [11]:

$$\pi_{\beta}(y|x) = \frac{\pi_{\text{SFT}}(y|x) \exp\left(\frac{1}{\beta}R(x,y)\right)}{\sum_{y'} \pi_{\text{SFT}}(y'|x) \exp\left(\frac{1}{\beta}R(x,y')\right)}$$

Closed-form solution

- ❖ Closed-form solution to alignment objective [11]:

$$\pi_{\beta}(y|x) = \frac{\pi_{\text{SFT}}(y|x) \exp\left(\frac{1}{\beta}R(x,y)\right)}{\sum_{y'} \pi_{\text{SFT}}(y'|x) \exp\left(\frac{1}{\beta}R(x,y')\right)}$$

- ❖ For $\beta' = \beta/\lambda$, after some algebra:

$$\pi_{\beta/\lambda}(y|x) = \frac{\pi_{\text{SFT}}(y|x) \left(\frac{\pi_{\beta}(y|x)}{\pi_{\text{SFT}}(y|x)}\right)^{\lambda}}{\sum_{y'} \pi_{\text{SFT}}(y'|x) \left(\frac{\pi_{\beta}(y'|x)}{\pi_{\text{SFT}}(y|x)}\right)^{\lambda}}$$

Closed-form solution

- ❖ Closed-form solution to alignment objective [11]:

$$\pi_{\beta}(y|x) = \frac{\pi_{\text{SFT}}(y|x) \exp\left(\frac{1}{\beta}R(x,y)\right)}{\sum_{y'} \pi_{\text{SFT}}(y'|x) \exp\left(\frac{1}{\beta}R(x,y')\right)}$$

- ❖ For $\beta' = \beta/\lambda$, after some algebra:

$$\pi_{\beta/\lambda}(y|x) = \frac{\pi_{\text{SFT}}(y|x) \left(\frac{\pi_{\beta}(y|x)}{\pi_{\text{SFT}}(y|x)}\right)^{\lambda}}{\sum_{y'} \pi_{\text{SFT}}(y'|x) \left(\frac{\pi_{\beta}(y'|x)}{\pi_{\text{SFT}}(y|x)}\right)^{\lambda}}$$

- ❖ Idea: change $y, y' \rightarrow$ current trajectory $\{y_i\}_{i=1,\dots,t}$, fit π_{β}

Results

- ❖ Approximate realigned model at β/λ [12]:

$$\hat{\pi}_{\beta/\lambda}(y_t|x, y_{$$

Results

- ❖ Approximate realigned model at β/λ [12]:

$$\hat{\pi}_{\beta/\lambda}(\cdot | x, y_{<t}) = \text{softmax} \left[\lambda h_{\beta}^{(t)} + (1 - \lambda) h_{\text{SFT}}^{(t)} \right]$$

where $h_{\text{SFT}}^{(t)}$ and $h_{\beta}^{(t)}$ are the logits

$$\begin{cases} \pi_{\text{SFT}}(\cdot | x, y_{<t}) &= \text{softmax}(h_{\text{SFT}}^{(t)}) \\ \pi_{\beta}(\cdot | x, y_{<t}) &= \text{softmax}(h_{\beta}^{(t)}) \end{cases}$$

Results

Arguments	pro: Denying student loan debtors the benefits of bankruptcy--benefits that all other debtors have access to--is unfair. con: Discharging student loan debt would only be a temporary bandage for the much larger problem of inflated college costs.
Response $\lambda=0.011$	[...] it is unfair to deny student loan debtors the benefits of bankruptcy--benefits that all other debtors have access to. They also argue that student loan debt has a disproportionately negative impact on low-income borrowers [...]. However, [...] it would be a costly and ineffective solution to the problem of student debt. They also argue that it would only be a temporary bandage for the much larger problem of inflated college costs.
Response $\lambda=2$	[...] One argument in favor of forgiveness is that it is unfair to deny student loan debtors the benefits of bankruptcy--benefits that all other debtors have access to. However, one argument against forgiveness is that it would only be a temporary bandage for the much larger problem of inflated college costs.
Response: $\lambda=5$	Denying student loan debtors the benefits of bankruptcy--benefits that all other debtors have access to--is unfair. Discharging student loan debt would only be a temporary bandage for the much larger problem of inflated college costs.

Discussion

- ❖ **Main takeaway:** efficient hallucination reduction using PE-RL with synthetic data and DeRA hyperparameter optimization.
- ❖ **Code:** github.com/leobianco/perl_hallucination
- ❖ Perspectives: other tasks (summarization), models (Mistral, Qwen), synthetic hallucinations schemes (LLMs)

Thank you!

References I

- [1] Emmanuel Abbe. Community detection and stochastic block models, 2023. URL <https://arxiv.org/abs/1703.10146>.
- [2] Pablo M Gleiser and Leon Danon. Community structure in jazz. *Advances in complex systems*, 6(04):565–573, 2003.
- [3] Paul W. Holland, Kathryn Blackmond Laskey, and Samuel Leinhardt. Stochastic blockmodels: First steps. *Social Networks*, 5(2):109–137, 1983. ISSN 0378-8733. doi: [https://doi.org/10.1016/0378-8733\(83\)90021-7](https://doi.org/10.1016/0378-8733(83)90021-7). URL <https://www.sciencedirect.com/science/article/pii/0378873383900217>.
- [4] Allen Liu and Ankur Moitra. Minimax rates for robust community detection. In *2022 IEEE 63rd Annual Symposium on Foundations of Computer Science (FOCS)*, pages 823–831. IEEE, 2022.
- [5] Jayadev Acharya, Ayush Jain, Gautam Kamath, Ananda Theertha Suresh, and Huanyu Zhang. Robust estimation for random graphs. In Po-Ling Loh and Maxim Raginsky, editors, *Proceedings of Thirty Fifth Conference on Learning Theory*, volume 178 of *Proceedings of Machine Learning Research*, pages 130–166. PMLR, 02–05 Jul 2022. URL <https://proceedings.mlr.press/v178/acharya22a.html>.
- [6] Leonardo Martins Bianco, Christine Keribin, and Zacharie Naulet. Subsearch: Robust estimation and outlier detection for stochastic block models via subgraph search, 2025. URL <https://arxiv.org/abs/2506.03657>.

References II

- [7] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Proceedings of the Conference on Neural Information Processing Systems*, volume 30, 2017.
- [8] Tyler A. Chang, Katrin Tomanek, Jessica Hoffmann, Nithum Thain, Erin van Liemt, Kathleen Meier-Hellstern, and Lucas Dixon. Detecting hallucination and coverage errors in retrieval augmented generation for controversial topics, 2024. URL <https://arxiv.org/abs/2403.08904>.
- [9] Paul Christiano, Jan Leike, Tom B. Brown, Miljan Martic, Shane Legg, and Dario Amodei. Deep reinforcement learning from human preferences, 2023. URL <https://arxiv.org/abs/1706.03741>.
- [10] Edward J. Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. Lora: Low-rank adaptation of large language models, 2021. URL <https://arxiv.org/abs/2106.09685>.
- [11] Daniel M. Ziegler, Nisan Stiennon, Jeffrey Wu, Tom B. Brown, Alec Radford, Dario Amodei, Paul Christiano, and Geoffrey Irving. Fine-tuning language models from human preferences, 2020. URL <https://arxiv.org/abs/1909.08593>.
- [12] Tianlin Liu, Shangmin Guo, Leonardo Bianco, Daniele Calandriello, Quentin Berthet, Felipe Llinares, Jessica Hoffmann, Lucas Dixon, Michal Valko, and Mathieu Blondel. Decoding-time realignment of language models, 2024. URL <https://arxiv.org/abs/2402.02992>.

References III

- [13] Ilias Diakonikolas, Gautam Kamath, Daniel Kane, Jerry Li, Ankur Moitra, and Alistair Stewart. Robust estimators in high dimensions without the computational intractability, 2019.