School of Computation, Information and Technology
Technical University of Munich

Increasing Reward Quality and Density for Verifiable Rewards

Ana Carolina Ramos Cunha Leonhard Driesch Leonard Evers

School of Computation, Information and Technology
Technical University of Munich

ana.cunha@tum.de leo.driesch@tum.de ge95gih@mytum.de

Abstract: Reinforcement learning for large language models on verifiable tasks (mathematics, code, and other domains with binary correctness checks) suffers from reward sparsity: only the final outcome receives a signal, leaving credit assignment across long chains of thought unresolved. We investigate a Master/Novice framework that compares a strong policy to a structurally matched but capacity-reduced *Novice*, obtained by tensor disentanglement of the Master's MLP weights, and asks whether their per-token divergence identifies the steps that deserve credit. We contribute (i) the conceptual framework and its central, testable hypothesis; (ii) an end-to-end `NoviceModel` pipeline that scales tensor disentanglement to Qwen3.5-4B and bakes Novices at any rank fraction from a single checkpoint; and (iii) a hypothesis-first causal evaluation on MATH-500. Three intervention designs of increasing strength, namely, handing generation over to the Novice, perturbing single tokens, and corrupting whole reasoning steps, consistently fail to reject the null: disagreement positions carry no more outcome leverage than depth-matched control positions. The only reliable effect is local: disagreement positions are more fragile in the immediate continuation, and this effect survives controlling for Master entropy. We report these negative results precisely, characterize a coherence cliff that constrains usable Novice ranks, and discuss what they imply for divergence-based reward densification.

Keywords: reinforcement learning, verifiable rewards, credit assignment, tensor disentanglement

1 Introduction

Large language models (LLMs) trained with reinforcement learning often receive only a sparse, verifiable reward at trajectory end (correct or incorrect) while intermediate tokens receive no direct feedback. This *reward sparsity* impedes sample efficiency and credit assignment: the policy cannot tell which reasoning steps were load-bearing and which were routine (Cui et al., 2025).

Recent work densifies rewards without human step labels by exploiting structure already present in the task or the model: partial test-case success in code (Wang et al., 2026), implicit process rewards trained from outcome labels alone (Cui et al., 2025), teacher–student divergence in distillation (Xu et al., 2026), and the observation that a minority of high-entropy "forking" tokens concentrates most of the learning signal in RLVR (Wang et al., 2025).

This paper explores a complementary idea: construct a weaker *Novice* from the same base weights as the *Master* via tensor disentanglement, compare their next-token distributions on successful Master rollouts, and upweight positions where the two diverge, on the premise that such steps rely on knowledge the Novice lacks and therefore deserve higher credit. Unlike an externally trained reward model, the Novice shares architecture and tokenizer with the Master and offers a continuous knob (the retained rank fraction) for how weak the comparator should be. Figure 1 summarizes the approach and its outcome.

Our contributions are of three kinds. *Conceptually*, we formalize the Master/Novice framework and reduce its promise to a single testable hypothesis: divergence positions have higher causal leverage on the final outcome than matched non-divergence positions. *Methodologically*, we implement an end-to-end `NoviceModel` pipeline. It disentangles, saves/loads, bakes to a chosen rank, and finally generates. This pipeline is validated from MLP-scale prototypes through Qwen3.5-4B, together with a ladder of three causal intervention designs for testing per-token credit signals before committing to RL training. *Empirically*, we characterize the disentanglement and Novice-quality landscape (learning-rate sweep, MMLU rank sweep, a generation-level coherence cliff) and report a consistent, statistically quantified negative result on the central hypothesis, alongside one genuine positive: a local fragility effect at disagreement positions that is not explained by Master entropy alone.




Figure 1: What we did and what we found: **(1)** compress a strong model's (*Master's*) MLP weights into a weakened copy, the *Novice*; **(2)** let the Novice re-predict the Master's correct MATH-500 solutions and mark the disagreements (*flips*); **(3)** damage solutions at flips versus at depth-matched normal positions and let the Master finish. **(4)** *Takeaway:* the answer breaks equally often either way (shown: whole-step damage; all three experiments agree), so flips mark where the Novice's missing capacity acts — not where the outcome is decided — and this divergence signal cannot densify the reward.

2 Related Work

We group prior work by where the dense signal comes from: the *task* (verifiable structure) or the *model* (internal statistics). For each line of work we focus on its relation to our approach; we refer to the original papers for full results.

2.1 Dense rewards from verifiable task structure

VeRPO (Wang et al., 2026) densifies code-RL rewards using partial test-case success. Its central observation is cautionary: the naive dense signal (the raw test-suite pass rate) can *underperform* sparse outcome rewards, because redundant easy tests dominate the reward by sheer count (a *cardinality bias*). VeRPO corrects this with a dynamically calibrated per-test weighting and re-anchors the result to the end-to-end outcome, outperforming outcome-only GRPO and RM-based baselines without a learned reward model. We selected it both as the clearest instance of extracting density from the *verifier* side and for its lesson that denser is not automatically better. This same lesson motivates our causal validation of the divergence signal before any training. This approach as a whole differs from ours in scope and granularity: the signal exists only where partial success is measurable (currently code) and is assigned per turn, whereas a Master/Novice comparator is task-agnostic and per token.

PRIME (Cui et al., 2025) obtains per-token process rewards without step labels by training an outcome reward model whose log-ratio to a reference policy is reinterpreted as an implicit process reward, updated online alongside the policy. It substantially improves sample efficiency over outcome-only RL on math and code. PRIME is the closest point of comparison for our goal (token-level credit from outcome supervision only); the difference is that PRIME *learns* its dense signal, whereas we test whether a fixed, training-free capacity-reduced copy of the policy can supply one.

2.2 Token-importance signals inside the model

High-entropy minority tokens. Wang et al. (2025) show that in RLVR most chain-of-thought tokens are low-entropy "followers," while a minority of high-entropy forking tokens carries the learning signal: restricting policy gradients to the top 20% highest-entropy tokens matches or exceeds full-gradient training. We selected this work because Master entropy is the natural single-model baseline that any two-model divergence signal must beat; our experiments therefore control for entropy explicitly.

TIP (Xu et al., 2026) studies on-policy distillation and identifies informative tokens along two axes, student entropy and teacher-student divergence: entropy-only selection is structurally blind to positions where the student is confidently wrong, and training on under 10% of tokens, from the low-entropy, high-divergence region alone, nearly

matches full-token distillation. TIP is the closest conceptual relative of our hypothesis in the sense that divergence between a strong and a weak model marks important tokens, but it operates in distillation, where the teacher's distribution is the training target itself. Whether the same signal identifies *outcome-critical* steps for RL credit assignment is exactly the question our experiments address; our negative results suggest the transfer is not automatic.

Compared with all four, the Master/Novice comparator requires no additional training, no task-specific verifier beyond the outcome check, and applies to any domain with verifiable answers; the price, as our results show, is that the signal it produces must be validated causally rather than assumed.

3 Methodology

3.1 Setup and hypothesis

We treat autoregressive generation as a Markov decision process: state s_t is the prompt plus generated prefix $y_{<t}$, action a_t is the next token, and the reward is binary verifiable correctness at episode end. The **Master** is the full-capacity policy π_M. The **Novice** is π_N, derived from the same checkpoint by truncating disentangled MLP factors to a rank fraction $\rho \in (0, 1]$, the share of each layer's internal rank that is kept (defined precisely in Section 3.2); ρ=1 reproduces the Master and smaller ρ yields a weaker Novice. On a Master rollout $\tau = (y_1, \ldots, y_T)$ that reaches a correct answer, per-token divergence is

$$\delta_t = D\big(\pi_M(\cdot \mid y_{<t}),\, \pi_N(\cdot \mid y_{<t})\big), \tag{1}$$

where D measures how different the two next-token distributions are, for example the Kullback–Leibler (KL) or Jensen–Shannon divergence, both of which grow as the distributions move apart; or, in the discrete limit used throughout our experiments, D reduces to the *top-1 flip* indicator

$$\mathrm{flip}_t = \mathbb{1}\big[\arg\max \pi_N(\cdot \mid y_{<t}) \neq y_t\big], \tag{2}$$

i.e., whether the Novice would have emitted a different token at position t. The top-1 flip is one instantiation of the framework, chosen for the experiments because it is parameter-free and directly interpretable; the framework itself is agnostic to the divergence measure. This setup, where the full policy generates while its truncated counterpart re-scores the same states, instantiates the *Observer pattern* of the weight-matrix disentanglement (WMD) introspection framework (Till, 2026), and the top-1 flip corresponds to its discrete *behavioral disagreement* indicator.

The intended use of δ_t is as a shaping signal that concentrates credit on high-divergence steps of verified-correct rollouts. Before such a signal enters any RL objective, however, its premise must hold. We therefore state it as an explicit hypothesis:

H1 (outcome leverage). *Positions where the Novice diverges from the Master have a larger causal effect on final-answer correctness than depth-matched positions where the two agree.*

All credit-assignment experiments in this paper are direct causal tests of H1 at increasing intervention strength. We deliberately do not evaluate any RL training run: if H1 fails, divergence-weighted advantages cannot concentrate gradient where the outcome is decided, and the training experiment would be uninformative.

3.2 Constructing the Novice via weight matrix disentanglement

The Novice must be *policy-preserving*: it should retain as much of the Master's behavior as a given rank budget permits, so that its remaining disagreements are attributable to missing capacity rather than to a lossy construction. The classical route, truncated SVD of each weight matrix, treats the matrix as a flat 2D array and ignores the multi-dimensional structure of neural weights. We instead use *Weight Matrix Disentanglement* (WMD) (Till, 2026), following the Master/Novice framework of Till (sebis/TUM), which adapts tensor disentanglement from numerical linear algebra (Wei et al., 2025) to neural network layers.

Let $X \in \mathbb{R}^{lr \times bc}$ be a decoder-MLP weight matrix whose row and column counts are each written as a product of two integers, lr split into the near-balanced pair (l, r) and bc into (b, c); this lets the flat matrix be read as a four-index tensor rather than a 2D array, which is what exposes the multi-dimensional structure that plain SVD ignores. Writing M for the reshape of X into the 4th-order tensor $\mathcal{X} \in \mathbb{R}^{l \times r \times b \times c}$ and P for the index permutation $(l, r, b, c) \to (l, c, r, b)$, WMD re-bipartitions the tensor with the operator

$$A \equiv M^{-1} \circ P \circ M\colon\ \mathbb{R}^{lr \times bc} \to \mathbb{R}^{lc \times rb}, \tag{3}$$

exposing cross-dimensional correlations that the flat matricization hides. A learnable orthogonal *gauge* $Q \in O(lr)$ (here $O(lr)$ is the orthogonal group, the $lr \times lr$ matrices with $Q^\top Q = I$; the word *gauge* signals that Q is later undone by $Q^\top$ during reconstruction, so it re-expresses the layer's coordinates without changing the layer itself) is applied to the row space before re-bipartitioning, and is optimized to concentrate the spectrum of $A(QX)$ in its leading singular directions, i.e., to make a few large singular values carry most of the energy. For a target rank k, the optimal disentangler minimizes the energy of the discarded singular tail:

$$Q_k^* \;=\; \arg\min_{Q \in O(lr)} \sum_{i>k} \sigma_i^2\big(A(QX)\big). \tag{4}$$

The tail sum $\sum_{i>k} \sigma_i^2$ is exactly the squared error of replacing $A(QX)$ by its best rank-k approximation, so a gauge that shrinks it makes the layer more compressible. Because A is an isometry (a norm-preserving map) and Q is orthogonal, the total singular energy of $A(QX)$ is invariant, so (4) directly minimizes the Frobenius reconstruction error (the sum of squared entrywise differences) between the original and truncated layer; the identity gauge Q=I recovers plain SVD truncation, so the optimized gauge is never worse. The rank-k Novice weight is reconstructed by inverting the pipeline,

$$\widetilde{X}^{(k)} \;=\; Q^{*\top} A^{-1}\big(\mathrm{trunc}_k(A(Q^* X))\big), \tag{5}$$

and the per-layer rank is set by a single global rank fraction: $k(\rho) = \max(1, \lceil \rho\, m \rceil)$, where $m = \min(lc, rb)$ is the largest possible rank of $A(QX)$. Thus ρ is literally the fraction of singular directions kept, and the outer max with 1 guarantees at least one is retained.

The optimization problem (4) admits a closed-form gradient that reuses one SVD of $A(QX)$ per step (Wei et al., 2025), and can be solved by Riemannian first- and second-order methods or by alternating minimization between Q and the low-rank factors. Our pipeline (vendored from the reference disentanglement code) accelerates this optimization by roughly 30–50× per layer through three stacked changes: Adam on a Cayley-parameterized orthogonal Q, reuse of the gradient's SVD within each step, and 32-bit floating-point precision throughout (Appendix A); truncation cost stays within ∼10% of the double-precision reference. Layers are independent, so all MLP projections are processed in parallel and their factors streamed to disk. These optimizations are what made it feasible to construct the Novice at the 4B scale used in our experiments.

WMD also supplies the theoretical link between Novice construction and the divergence signal of Section 3.1: for a policy and its rank-k truncated counterpart, the per-state KL divergence is bounded by the discarded singular tail, $D_{\mathrm{KL}}\big(\pi_M(\cdot \mid s) \,\|\, \pi_N(\cdot \mid s)\big) \le \frac{L}{2} \sum_{i>k} \sigma_i^2\big(A(Q^*X)\big)$ with L a network-wide Fisher-information Lipschitz constant, a fixed factor that converts discarded weight energy into a bound on how much the output distribution can change and so measures the policy's sensitivity to perturbing its weights. At the rank the gauge was optimized for, the optimized gauge yields the tightest such bound (Till, 2026). Two properties of our pipeline determine how this applies to the Novices used below. First, baking truncates the *stored factors* of $A(Q^*X)$ before inverting the reshape, exactly the construction in (5), so the bound itself holds at every bake rank ρ, with the tail read directly off the stored spectrum. Second, because (4) depends on k, the *tightness* guarantee is rank-specific: a Novice baked at a different ρ than the gauge was optimized for inherits a valid but not provably minimal bound. We verify empirically that the gauge's advantage transfers across ranks in our checkpoint (Section 5.1). WMD rather than plain SVD thus keeps the observed Master/Novice divergence dominated by genuinely missing capacity rather than by avoidable truncation error.

3.3 The `NoviceModel` pipeline

The `NoviceModel` wrapper owns the full lifecycle: load a base causal LM, swap MLP linears, run disentanglement, persist factors to disk (monolithic or per-layer sharded checkpoints with a manifest), bake to any ρ via (5), and delegate `generate()` to the underlying `PreTrainedModel`, preserving compatibility with the key/value cache that makes autoregressive decoding efficient. Concretely, for Qwen3.5-4B's `down_proj` (one of the three MLP projection matrices in each decoder layer, here $X \in \mathbb{R}^{2560\times 9216}$) the factorization is $(l, r, b, c) = (40, 64, 96, 96)$, so that $40 \times 64 = 2560$ and $96 \times 96 = 9216$ recover the matrix dimensions; then $Q \in O(2560)$, $A(QX) \in \mathbb{R}^{3840\times 6144}$, and $m = 3840$; baking at ρ=0.25 keeps k=960 singular directions. The stored per-layer factors (Q, U, s, V_h), namely the gauge together with the singular vectors and values U, s, V_h of $A(Q^*X)$, retain the full decomposition, so one disentanglement run yields Novices at every ρ by cheap re-truncation. Sharded checkpoints are loaded and baked one layer at a time, keeping peak memory near a single model. An equality test confirms that a Novice baked at ρ=1 reproduces the base model's logits. The pipeline was validated incrementally on toy weight matrices, MNIST- and CIFAR-scale MLPs, a small GPT-2-style transformer, Qwen3.5-0.8B-Base, and finally Qwen3.5-4B, the model used in all experiments below.

4 Experiments

4.1 Models, data, and grading

Models. Master: `Qwen/Qwen3.5-4B` (full rank). Novice: the disentangled checkpoint of the same model (gauge optimized at ρ=0.1), baked at ρ=0.25; the bake-rank choice is justified empirically in Section 5.1.

Data. MATH-500 (`HuggingFaceH4/MATH-500`), problems 0–49, prompted via the chat template with the standard instruction to place the final answer in `\boxed{}`. All decoding is greedy; Master rollouts are capped at 512 new tokens in E1 and 700 in E2/E3 (under greedy decoding the shared prefixes are identical, and the same 23 problems are solved), which sufficed for most rollouts to terminate naturally. Greedy decoding makes every experiment deterministic up to the fixed sampling seed used for control selection.

Grading. A balanced-brace `\boxed{}` extractor with LaTeX-normalizing equality (fraction, spacing, and delimiter normalization; numeric fallback). The Master solved 23/50 problems; all credit-assignment experiments operate on these 23 verified-correct rollouts. Across them, the Novice is teacher-forced on the Master's tokens and flips are recorded at every generated position (10,895 scored tokens; flip rate 12.3%). The disentangled factor checkpoint is publicly available, and Appendix A collects all remaining reproduction details (seeds, prompts, evaluation configuration); code and per-trial artifacts are available from the authors.

4.2 Novice characterization experiments

Learning-rate selection. Disentanglement quality is sensitive to the optimizer learning rate; a sweep on a representative Qwen3.5-0.8B MLP layer selects 10^{-3}, used for all subsequent disentanglement runs (Appendix B).

MMLU rank sweep. Novice quality as a function of ρ is measured with `lm-eval` on MMLU, 5-shot, limited to 5 questions per subtask (a fixed-budget subset; the same protocol at every rank, so relative comparisons are unaffected by the limit).

Generation coherence. Because MMLU scores likelihood ranking rather than generation, we separately inspect greedy free-running generations of the Novice at $\rho \in \{0.1, 0.25, 0.5, 0.75\}$ on MATH-500 prompts.

4.3 Intervention experiments

All three experiments compare *flip* positions against *depth-matched non-flip controls*. The *depth* of a position is its relative location within the generated part of the rollout, from 0 (first generated token) to 1 (last). Depth matching is essential because an intervention late in a rollout is much easier to recover from, since most of the correct solution is already in place; how far into a rollout an intervention occurs in fact dominates its effect (Section 5.2), so comparisons at unmatched depths would be confounded. Controls are drawn once per flip with a fixed random seed.

E1: Release-from-here. At a chosen position p the Novice takes over: it receives the Master's prefix $y_{<p}$ and free-runs greedily to completion (budget: remaining rollout length plus 48 tokens); the completed trajectory is graded. This mirrors the deployment ("Actor") pattern of the WMD framework (Till, 2026), in which the truncated policy drives the rollout. Release positions are selected as follows. Within each rollout, all flips are ranked by their *confidence gap*: the probability the Novice assigns to its own preferred token minus the probability it assigns to the Master's token at that position. A near-zero gap means a borderline disagreement, a large gap a confident one. We release at the 5 most confident flips per rollout, since these are the flips most likely to matter if H1 is true; selecting them biases the test toward finding an effect, which makes a null result more conclusive. Each selected flip is then paired with the not-yet-used non-flip position closest to it in depth, and every control is used at most once. With 23 rollouts and 5 pairs each, this yields $23 \times 5 = 115$ pairs, i.e., 230 Novice free-runs; five pairs per rollout balance per-problem coverage against generation cost. If H1 holds, releasing at a flip should derail the answer more often than at its matched control.

E2: Single-token perturbation. E1 is a coarse test: after the handoff, a whole weak model free-runs in both arms, so the effect of the single position is diluted by the long shared continuation. E2 instead perturbs exactly one token and lets the *Master* continue. It reuses the same 5 flip/control pairs per rollout as E1, and each of the 115 pairs produces three trials, one per arm: `flip_novice` splices the Novice's token at the flip position, `flip_rank2` splices the Master's own second most probable token at the same flip position, and `control_rank2` splices the second most probable token at the matched control position. The second-choice token is used because it exists at every position and is a perturbation of comparable strength in both groups. Comparing the two `rank2` arms therefore isolates the *position* effect under an identical perturbation type, while comparing the two flip arms isolates the effect of the Novice's *specific* token at an identical (hence entropy-matched) position. In total this gives $23 \times 5 \times 3 = 345$ trials, 115 per arm.

Three metrics are recorded per trial. (i) *Local disruption*: the mean drop in the log-probability the Master assigns to its own next K=8 tokens when the perturbed prefix replaces the clean one, in nats per token (a nat is the natural-logarithm unit of information, so a drop of one nat means the Master finds its own continuation a factor of e less likely); K=8 is long enough to capture the immediate continuation while keeping the metric local. (ii) *Answer log-probability drop*: the same drop evaluated on the Master's answer tokens (the `\boxed{}` content), with the reasoning between the perturbation and the answer teacher-forced, i.e., held fixed; this isolates the part of the perturbation's effect that reaches the outcome. Trials whose perturbed position lies after the answer span have no answer tokens left to score and are excluded from this metric. (iii) A binary *answer-break* outcome: whether the Master, free-running greedily from the perturbed prefix, no longer reaches the correct answer; since each free-run is a full generation, this is evaluated on a random subset of 90 of the 345 trials to bound compute. Because flips concentrate at positions where the Master itself is uncertain, and perturbing an uncertain position disturbs the continuation more for purely mechanical reasons, all position comparisons are additionally adjusted for entropy by ordinary least squares, $y = \beta_0 + \beta_1\,\mathrm{isflip} + \beta_2\,H_M$, where isflip indicates whether the position is a flip and H_M is the Shannon entropy (in nats) of the Master's next-token distribution at the perturbed position. The regression is fitted over the two `rank2` arms only, so that both groups received the identical perturbation type; β_1 then estimates the difference between a flip and a control position at equal entropy.

E3: Span perturbation. Single tokens may be the wrong granularity for reasoning. E3 corrupts an entire reasoning step, simplified here as a newline-delimited token span. Spans shorter than 4 tokens are discarded as trivial fragments. It then lets the Master free-run to the answer, so the downstream reasoning may adapt. Steps are ranked by *flip density*, the fraction of their tokens that are flips; per rollout the 3 densest steps are paired with depth-matched low-density steps (three per rollout, for the same coverage-cost balance as in E1), giving $23 \times 3 = 69$ step pairs. Arms mirror E2: generic corruption (per-position second-choice tokens) of a flip-dense step, generic corruption of a control step, and replacement of the flip-dense step by the *Novice's version* of it (its preferred token at every position), for $69 \times 3 = 207$ trials in total, 69 per arm. The primary metric is the binary answer-break rate of the Master's free-run, evaluated on 150 of the 207 trials; the teacher-forced answer drop and the entropy-adjusted regression (with the step's mean entropy as covariate) are reported as in E2, where one step pair without answer tokens after the span is excluded.

Statistical analysis. We attach a standard test to each comparison so that a null result can be quantified rather than merely asserted. Every rate is reported with a 95% Wilson confidence interval (CI). E1's flip and control arms are *paired*, since each flip has its own depth-matched control, and are compared with McNemar's exact test; E2 and E3 treat their free-run arms as *independent* groups, compared with Fisher's exact test, whose *odds ratio* is above 1 when the flip arm broke the answer more often. For the regression coefficients β_1 and β_2 we report the estimate, its standard error (SE), and the t-value (estimate divided by SE); at our sample sizes $|t| \gtrsim 2$ corresponds to $p \lesssim 0.05$. Appendix D explains each test and why it matches the design. In every case a small p-value, a t-value past this threshold, or a CI that excludes the no-

effect value would signal a real effect; as the next section shows, we observe none of these.

5 Results

5.1 Novice characterization

Gauge quality across bake ranks. The checkpoint's gauge was optimized at ρ=0.1 while the interventions bake at ρ=0.25, so the KL bound's tightness is not guaranteed at the bake rank (Section 3.2). Measured on the stored spectra, the advantage transfers: the optimized gauge's reduction of discarded tail energy relative to identity-gauge (plain SVD) truncation is large, if heterogeneous across layers, and essentially rank-independent between ρ=0.1 and ρ=0.25 (Appendix C).

MMLU vs. rank. On Qwen3.5-4B (5-shot, 5 questions per subtask), accuracy stays near the base model's 0.737 down to $\rho \approx 0.5$, then degrades monotonically to 0.42 at ρ=0.1: still above the 0.25 random baseline (Figure 2).

Coherence cliff. Free-running generation tells a sharper story than likelihood-based MMLU: at ρ=0.1 every inspected generation collapses into degenerate repetition, while at $\rho \geq 0.25$ generations are fluent, structured solutions. Consistently, the Novice's teacher-forced flip rate on Master rollouts falls from 44.0% at ρ=0.1 (disagreement smeared over half the tokens, i.e., noise) to 12.3% at ρ=0.25 (concentrated disagreement). We therefore run all interventions at ρ=0.25, the sharpest coherent operating point: the Novice is far weaker than the Master generatively (released on the Master's own trajectories it completes them correctly only 26% of the time; E1 below), yet its disagreements are attributable to specific positions rather than global incoherence.




Figure 2: MMLU accuracy vs. Novice rank fraction on Qwen3.5-4B (`lm-eval`, 5-shot, 5 questions per subtask). Accuracy is preserved until $\rho \approx 0.5$, then degrades; note that at ρ=0.1 the Novice still scores above chance on likelihood ranking even though its free-running generation is degenerate.

5.2 Intervention experiments

Table 1 summarizes the outcome-level results of all three experiments; Table 2 reports E2's graded per-token metrics.

Table 1: Outcome-level intervention results. E1 reports the Novice's completion success rate after taking over at the given position (H1 predicts *lower* success at flips). E2/E3 report the rate at which the Master's free-run no longer reaches the correct answer after the perturbation (H1 predicts *higher* break rates at flips). No comparison is significant; exact tests in the text.

Exp.	Arm	Rate	Count
E1 (success↑)	release at flip	0.261	30/115
	release at control	0.270	31/115
E2 (break↓)	flip, Novice token	0.241	7/29
	flip, rank-2 token	0.100	3/30
	control, rank-2	0.194	6/31
E3 (break↓)	flip-dense step	0.151	8/53
	control step	0.176	9/51
	flip-dense, Novice version	0.152	7/46

Table 2: E2 graded metrics (means over 115 trials per arm). Local disruption differs between flip and control positions; the answer-tied drop is negligible for every arm. H_M: mean Master entropy at the perturbed position, confirming that flips sit at high-entropy positions, hence the entropy-adjusted analyses in the text.

E2 arm	Local disr. (nats/tok)	Answer drop (nats/tok)	H_M
flip, Novice token	2.56	0.0009	0.41
flip, rank-2	2.55	0.0009	0.41
control, rank-2	1.60	0.0013	0.08

E1: no release-point effect. Success after handing over at a flip was 30/115 (0.261; Wilson 95% CI $[0.189, 0.348]$) versus 31/115 (0.270; CI $[0.197, 0.357]$) at depth-matched controls; the two intervals almost entirely overlap, and the paired difference is only +0.009. Because the design is paired, the informative comparison is within pairs: in 108 of the 115 pairs both releases had the same outcome (concordant), and the seven discordant pairs split 4 (control succeeded, flip failed) versus 3 (the reverse). McNemar's exact test, which evaluates only these discordant pairs, gives $p = 1.00$: a 4-versus-3 split is exactly what chance would produce, so the arms are statistically indistinguishable. Success is instead governed by release depth (Figure 3): in the deepest quartile of release positions both arms succeed at ≈ 0.7, in the earliest at $\approx$ 0–0.1; the earlier the Novice takes over, the more of the solution it must produce itself. H1 is not supported at this granularity.




Figure 3: E1 (release-from-here). Left: Novice completion success after taking over at flip vs. depth-matched control positions (115 pairs): no difference. Right: success by release-depth quartile (bin 0 = earliest quarter of the rollout). Both arms rise identically with depth: the outcome is governed by how much of the Master's trajectory the Novice inherits, not by whether the release point is a flip.

E2: a local but not an outcome effect. Perturbing at a flip disrupts the Master's immediate continuation substantially more than at a matched control (2.55 vs. 1.60 nats/token, Table 2), a raw gap of +0.94. Flips sit at higher-entropy positions (H_M 0.41 vs. 0.08), and entropy independently predicts disruption ($\beta_2 = 0.97$, SE 0.36, $t = 2.69$), but the flip effect survives the adjustment: $\beta_1 = 0.62$, SE 0.26, $t = 2.35$ (n=230, the two `rank2` arms), which clears the $|t| \approx 2$ threshold and is therefore unlikely to be sampling noise. The raw gap thus decomposes into roughly 0.32 nats attributable to the entropy difference between the groups (β_2 times the mean-entropy difference) and 0.62 nats associated with flip status itself; consistently, the flip>control ordering also holds within every entropy tercile (the positions split into thirds from lowest to highest entropy). The effect does not reach the outcome, however: the answer-tied drop is ∼0.001 nats/token in *every* arm, with no flip effect ($\beta_1 = -0.0002$, SE 0.0017, $t = -0.14$, i.e., essentially zero standard errors from no effect, n=225; 5 trials whose perturbed position lies after the answer span are excluded), and the free-run answer-break subset shows no coherent ordering (7/29, 3/30, and 6/31 broken answers per arm; Fisher's exact test on the two `rank2` arms gives an odds ratio of 0.46 with $p = 0.47$, numerically even in the direction opposite to H1, and no pairwise comparison approaches significance). The Novice's specific token adds nothing over the Master's own second choice at the same position: the paired difference is +0.017 nats/token locally (Novice larger in only 18% of pairs) and +0.0001 on the answer metric (11% of pairs).

E3: no step-level effect. Corrupting a flip-dense reasoning step broke the final answer in 8/53 free-runs (0.151; CI [0.079, 0.271]) versus 9/51 (0.176; CI [0.096, 0.303]) for depth-matched low-disagreement steps. Fisher's exact test gives an odds ratio of 0.83, which is below 1 and so has the flip-dense step breaking the answer slightly *less* often than the control, the opposite of what H1 predicts, with $p = 0.80$, far from any significance threshold. Replacing a flip-dense step by the Novice's own version of it was indistinguishable from generic corruption of the same step (7/46 vs. 8/53; Fisher $p = 1.00$; on the paired answer-drop metric the Novice version was larger in only 10% of step pairs). The entropy-adjusted answer-drop OLS is likewise null ($\beta_1 = -0.0018$, SE 0.0023, $t = -0.79$, n=137). Notably, the Master recovered the correct answer after whole-step corruption in 84% of all trials (126/150), independent of the step's flip density.

6 Discussion

6.1 What the results mean for H1

Across three intervention designs of increasing strength, we consistently fail to reject the null. Particularly noteworthy is E3, whose free-running outcome metric gives downstream reasoning every chance to amplify a corrupted step. Where the Novice disagrees with the Master is, causally, not where the outcome is decided: flip positions and flip-dense steps are no more outcome-critical than depth-matched controls, and the Novice's specific alternatives are no more damaging than the Master's own second choices. We conclude that naive top-1-flip divergence, used as a per-token or per-step credit weight, would not concentrate learning where it matters, and an RL run built on it would most likely reproduce a uniform-weighting baseline at extra cost.

Two genuine findings survive alongside the negative. First, disagreement positions are *locally* special: perturbations there disrupt the immediate continuation about 60% more than at matched positions, beyond what Master entropy explains. Divergence therefore does measure something real about where the truncated capacity acts. It just measures local fragility, not outcome leverage. Second, the Master is strikingly robust on MATH-500: even corrupting an entire reasoning step leaves the final answer intact 84% of the time. Only a small minority of steps is load-bearing, and identifying them evidently requires more than capacity-difference signals.

On the relation to entropy: our data do *not* show that entropy is a sufficient credit signal either. Entropy predicted local disruption, but neither entropy nor flips predicted the outcome-tied metrics: on those, everything was null. The correct summary is that divergence and entropy are correlated, each carries independent *local* information, and neither, in our setting, identifies outcome-critical positions. This is consistent with the interpretation of high-entropy tokens as *forks* whose importance is realized over many rollouts during training (Wang et al., 2025), rather than as counterfactually decisive positions within a single trajectory.

6.2 Why the hypothesis may fail

The premise behind H1 conflates two notions of importance: a step can be hard *for a weaker model to produce* without being critical *to the outcome*. Much of what extra MLP capacity buys appears to be fluency and confidence at delicate positions, which is exactly what the local-disruption effect detects. Meanwhile the mathematically decisive content is either redundantly encoded across the

trajectory (the Master re-derives it after corruption) or concentrated in a few steps that flips do not preferentially mark. TIP's setting (Xu et al., 2026) explains why the same signal can still be valuable in distillation: there, "hard for the weaker model" *is* the training target, with no causal claim being needed. For RL credit assignment, our results show that the causal claim must be established separately, and here it fails.

6.3 Outlook

The infrastructure result stands independently of the negative: Master/Novice pairs can be produced repeatably at 4B scale, with rank fraction as a smooth, characterized control knob and a documented coherent operating range. Given H1's failure, we see three defensible directions: (i) aggregate rather than pointwise use of divergence (e.g., trajectory-level divergence mass as a difficulty or novelty signal); (ii) combining divergence with signals whose training-time value is established, such as entropy-based token selection (Wang et al., 2025), where divergence's independent local information may still help; and (iii) learned dense-reward approaches in the PRIME family (Cui et al., 2025), against which any future training-free comparator should be benchmarked. Any of these should be preceded by the same kind of causal validation we applied here.

7 Limitations

Our conclusions are bounded by the setting: one Master (Qwen3.5-4B), one Novice family (MLP-only disentanglement with the gauge optimized at ρ=0.1, evaluated chiefly at ρ=0.25, where the truncation bound's tightness is verified empirically on sampled layers rather than guaranteed), one dataset (MATH-500; 23 Master-correct rollouts), greedy decoding, and top-1 flips as the divergence instantiation. The gauge optimization was stopped after 40 compute-bounded steps with the cost still decreasing (Figure 4), so a fraction of the observed divergence may be avoidable truncation error rather than missing capacity, although the optimized gauge already clearly outperforms plain SVD at both ranks (Appendix C). The binary outcome metrics have modest power ($\sim$50–115 per arm; the reported CIs are correspondingly wide), though the consistency of the null across three designs and both graded and binary metrics argues against a large hidden effect. The regression standard errors treat positions as independent although they are clustered within the 23 rollouts, so the local-fragility t-statistic should be read as approximate. The MMLU sweep uses a fixed 5-question-per-subtask budget, adequate for relative comparisons across ρ but not for absolute benchmark claims. The answer-tied drop metric teacher-forces intervening reasoning and is thus conservative by design; the free-run metrics in E1/E3 are the complementary, unconstrained tests. Finally, continuous divergence measures (e.g., Jensen–Shannon mass aggregated per trajectory), sampled rather than greedy rollouts, and other Novice constructions remain untested and are natural follow-ups.

8 Conclusion

We formalized the Master/Novice framework for densifying verifiable rewards, built and validated the tensor-disentanglement pipeline that makes it practical at 4B scale, and subjected its central premise to a ladder of three causal intervention tests on MATH-500. The premise did not hold: top-1 disagreement between Master and Novice does not mark outcome-critical positions or steps (McNemar p=1.00; Fisher p=0.80), and the Novice's specific token choices carry no more leverage than generic perturbations. What disagreement does mark robustly, and beyond Master entropy, is local fragility of the immediate continuation. We report this negative result with exact statistics because it de-scopes an otherwise attractive idea: dense rewards from a training-free capacity-reduced comparator cannot be assumed to target the right tokens, and causal validation of any proposed credit signal should precede RL integration. The released pipeline, the coherence-cliff characterization, and the three reusable intervention designs are intended to make exactly that validation cheap for future signals.

AI-Use Statement

AI assistants were used for limited drafting and coding assistance during this project. Boilerplate and auxiliary code (e.g., plotting, evaluation harness glue) may have been generated with an LLM, and LLM tools were used to assist with editing and restructuring the manuscript. All content was reviewed, modified, and verified by the authors, who take full responsibility for the final work.

References

Ganqu Cui, Lifan Yuan, Zefan Wang, Hanbin Wang, Yuchen Zhang, Jiacheng Chen, Wendi Li, Bingxiang He, Yuchen Fan, Tianyu Yu, Qixin Xu, Weize Chen, Jiarui Yuan, Huayu Chen, Kaiyan Zhang, Xingtai Lv, Shuo Wang, Yuan Yao, Xu Han, Hao Peng, Yu Cheng, Zhiyuan Liu, Maosong Sun, Bowen Zhou, and Ning Ding. Process reinforcement through implicit rewards. *arXiv preprint arXiv:2502.01456*, 2025.

Tristan Till. On agent introspection via policy-preserving weight matrix disentanglement. Working paper, sebis, Technical University of Munich, 2026.

Longwen Wang, Yirui Liu, Xuan'er Wu, Xiaohui Hu, Yuankai Fan, Kaidong Yu, Qizhen Weng, Wei Xi, and Xuelong Li. Beyond binary: Turning partial success into dense verifiable rewards for reinforcement learning in code generation. *arXiv preprint arXiv:2601.03525*, 2026.

Shenzhi Wang, Le Yu, Chang Gao, Chujie Zheng, Shixuan Liu, Rui Lu, Kai Dang, Xiong-Hui Chen, Jianxin Yang, Zhenru Zhang, Yuqiong Liu, An Yang, Andrew Zhao, Yang Yue, Shiji Song, Bowen Yu, Gao Huang, and Junyang Lin. Beyond the 80/20 rule: High-entropy minority tokens drive effective reinforcement learning for LLM reasoning. *arXiv preprint arXiv:2506.01939*, 2025.

Julia Wei, Alec Dektor, Chungen Shen, Zaiwen Wen, and Chao Yang. Numerical optimization for tensor disentanglement. *arXiv preprint arXiv:2508.19409*, 2025.

Yuanda Xu, Hejian Sang, Zhengze Zhou, Ran He, Zhipeng Wang, and Alborz Geramifard. TIP: Token importance in on-policy distillation. *arXiv preprint arXiv:2604.14084*, 2026.

A Reproducibility details

Table 3 collects every hyperparameter and configuration value used in the paper; the paragraphs below add only the details that need explanation rather than lookup.

Table 3: All hyperparameters and configuration values. Together with the published factor checkpoint, these settings specify every experiment in the paper; settings not listed use the released code's defaults.

Disentanglement (published checkpoint)	
Master / base model	`Qwen/Qwen3.5-4B`
Factor checkpoint	`leodriesch/novice-qwen3.5-4b-rf0.1` (Hugging Face Hub)
Factored layers	96 MLP linears (32 decoder layers × {gate, up, down})
Gauge optimization rank	$\rho = 0.1$
Optimizer, learning rate	Adam (Cayley-parameterized, fp32), 10^{-3}
Steps per layer	40 (compute-budget cutoff; Figure 4)
Bake rank, all interventions	$\rho = 0.25$
Data and decoding	
Dataset	MATH-500 (`HuggingFaceH4/MATH-500`), test split, problems 0–49
Decoding	greedy; rollouts capped at 512 new tokens (E1) / 700 (E2, E3)
Model precision	bfloat16
Prompt format	chat template, thinking mode disabled
Interventions	
Seed for controls and subsets	0 (Python `random.Random`)
E1 releases	5 flip/control pairs per rollout; budget = remainder + 48 tokens
E2 perturbations	same 5 pairs; local window $K = 8$; free-run subset 90 of 345
E3 spans	3 pairs per rollout; min. 4 tokens; free-run subset 150 of 207
MMLU evaluation	
Harness	`lm-eval`, task `mmlu`
Protocol	5-shot, 5 questions per subtask, batch size 1, max. length 2048

Checkpoint. The disentangled factors are stored sharded (one `*.factors.pt` file per linear plus a manifest), together with the per-step tuning trace (cost, entropy, effective rank per matrix); Figure 4 shows the run's cost trajectories for all 96 matrices. The step count was set by our compute budget, not by convergence: longer optimization would likely improve the factors further.

Implementation. The Cayley transform expresses the orthogonal gauge Q through unconstrained parameters that an ordinary optimizer can update freely while keeping Q exactly orthogonal; its backward pass is far cheaper than that of the matrix exponential it replaces, whose autograd gradient requires a Fréchet-derivative computation. Combined with reusing the gradient's SVD within each step and 32-bit precision, this yields the 30–50× per-layer speed-up reported in Section 3.2.

Prompting. Problems are formatted with the model's chat template, with the instruction "Please reason step by step, and put your final answer within `\boxed{}`." appended to the problem statement.

Seeds and subsampling. All randomness beyond greedy decoding, i.e., the selection of depth-matched control positions and steps and of free-run subsets, uses Python's `random.Random` with seed 0; free-run subsets are drawn uniformly without replacement via `rng.sample`.

B Learning-rate sweep

Disentanglement quality is sensitive to the optimizer learning rate. We swept $\{5\times10^{-4}, 10^{-3}, 5\times10^{-3}, 7\times10^{-3}, 10^{-2}, 2\times10^{-2}, 5\times10^{-2}\}$ for 200 steps on a representative Qwen3.5-0.8B MLP layer, tracking reconstruction cost (the discarded singular energy of (4), so lower is better) and effective rank (a soft count of how many singular directions carry meaningful energy). Small rates converge slowly; rates $\geq 10^{-2}$ diverge (reconstruction cost increases). A mid-range rate near 10^{-3} minimizes cost while reaching a stable effective rank (Figure 5). All disentanglement runs in the paper use this regime.

C Gauge quality across bake ranks

Relative to identity-gauge (plain SVD) truncation in the same bipartition, the optimized gauge reduces the discarded tail energy to 0.60× (ρ=0.1) and 0.58× (ρ=0.25) on `layers.0.down_proj`, and to 0.026× and 0.025× on




Figure 4: Disentanglement cost per optimization step for all 96 MLP matrices of the published ρ=0.1 run (thin lines: individual matrices; thick lines: per-projection medians). `gate_proj` and `up_proj` compress by more than an order of magnitude, while `down_proj` barely improves: the layer heterogeneity of the gauge advantage (Appendix C) is already visible during optimization. Cost is still decreasing when the run stops at the 40-step compute budget, so the gauges are not fully converged.

`layers.31.up_proj`. The advantage is large, heterogeneous across layers, and essentially independent of the bake rank, supporting the use of the ρ=0.1-optimized gauge for Novices baked at ρ=0.25 (Section 5.1).

D Statistical tests

This appendix explains the tests used in Section 5.2 and why each matches its design. The *Wilson* 95% confidence interval is the range of true rates consistent with the observed counts; it is preferred over the textbook (Wald) interval because it stays well-behaved for proportions near 0 or 1 and for small samples. *McNemar's exact test* suits E1's paired design: it looks only at the pairs whose two arms gave different outcomes (the discordant pairs) and asks whether one arm wins more often than a coin flip would predict. *Fisher's exact test* suits E2 and E3, whose free-run arms are independent groups: it operates on the two-by-two table of arm versus outcome, summarizes the association as an odds ratio, and returns an exact p-value that remains valid at small counts. For regression coefficients, the standard error (SE) quantifies the estimate's uncertainty, and the t-value (estimate divided by SE) counts how many standard errors the estimate lies from zero.




Figure 5: Learning-rate sweep for tensor disentanglement (Qwen3.5-0.8B MLP layer, 200 steps). Mid-range rates balance convergence speed and stability; large rates diverge.