



In the above example the fields singleSRC and size will be shown after the addImage checkbox field, when addImage has been activated.

## Sub palettes with selects

Instead of reacting to a checkbox, you can also define different sub palettes depending on different value for a select input field:

```
// contao/dca/tl_example.php
$GLOBALS['TL_DCA']['tl_example'] = [
    'palettes' => [
        '__selector__' => ['selectField'],
        'default' => '{title_legend},title,alias,selectField',
    ],
    'subpalettes' => [
        'selectField_value1' => 'field1,field2',
        'selectField_value2' => 'field3,field4',
    ],
];
```

In this case the sub palette key needs to be in the form of <a href="fieldValue">fieldValue</a>. Depending on the field's value, the appopriate sub palette will be inserted.

Q Search...

Getting Started

Data Container Array

Framework

Reference

Config

List

Hooks

Config

Services

Fields

Palettes

Commands

Callbacks

## Sorting

```
食
// contao/dca/tl_example.php
$GLOBALS['TL_DCA']['tl_example']['list']['sorting'] = [
    // ...
];
```

Key	Value	Description
mode	Sorting mode (integer)	<ul> <li>0 Records are not sorted</li> <li>1 Records are sorted by a fixed field</li> <li>2 Records are sorted by a switchable field</li> <li>3 Records are sorted by the parent table</li> <li>4 Displays the child records of a parent record (see style sheets module)</li> <li>5 Records are displayed as tree (see site structure)</li> <li>6 Displays the child records within a tree structure (see articles module)</li> </ul>
		1 Sort by initial letter ascending 2 Sort by initial letter descending