

→ C managed-edition.wip/contao/install













Update the database

Update the database

Please note that the update assistant only handles tables starting with t1_.

Create tables


- ✓ Select all
- ✓ CREATE TABLE tl_remember_me (
 id INT UNSIGNED AUTO_INCREMENT NOT NULL,
 series BINARY(32) NOT NULL COMMENT '(DC2Type:binary_string)',
 value BINARY(64) NOT NULL COMMENT '(DC2Type:binary_string)',
 lastUsed DATETIME NOT NULL,
 expires DATETIME DEFAULT NULL,
 class VARCHAR(100) NOT NULL,
 username VARCHAR(200) NOT NULL,
 INDEX series (series),
 UNIQUE INDEX value (value),
 PRIMARY KEY(id)
) DEFAULT CHARACTER SET utf8mb4 COLLATE utf8mb4_unicode_ci ENGINE = InnoDB

Change columns

- ✓ Select all
- ✓ ALTER TABLE tl_article CHANGE stop stop VARCHAR(10) DEFAULT '' NOT NULL
- ALTER TABLE tl article CHANGE start start VARCHAR(10) DEFAULT '' NOT NULL

Update database

- Import a template
- Create an admin user
- ▼ Installation complete



→ C managed-edition.wip/contao/install













Update the database

Update the database

Please note that the update assistant only handles tables starting with t1_.

Create tables

- ✓ Select all
- ✓ CREATE TABLE tl_remember_me (
 id INT UNSIGNED AUTO_INCREMENT NOT NULL,
 series BINARY(32) NOT NULL COMMENT '(DC2Type:binary_string)',
 value BINARY(64) NOT NULL COMMENT '(DC2Type:binary_string)',
 lastUsed DATETIME NOT NULL,
 expires DATETIME DEFAULT NULL,
 class VARCHAR(100) NOT NULL,
 username VARCHAR(200) NOT NULL,
 INDEX series (series),
 UNIQUE INDEX value (value),
 PRIMARY KEY(id)
) DEFAULT CHARACTER SET utf8mb4 COLLATE utf8mb4_unicode_ci ENGINE = InnoDB

Change columns

- ✓ Select all
- ✓ ALTER TABLE tl_article CHANGE stop stop VARCHAR(10) DEFAULT '' NOT NULL
- ALTER TABLE tl article CHANGE start start VARCHAR(10) DEFAULT '' NOT NULL

Update database

- Import a template
- Create an admin user
- ▼ Installation complete

Suchindex aufbauen auf der CLI