Allowed HTML tags

<a><abbr><acronym><address><area><article><aside><audio><b><bdi><bdo><big><blockquote>
<button><captic

Here you can enter a list of allowed HTML tags that will not be stripped.

Allowed HTML attributes

Key	Value
*	aria-*,class,data-*,dir,hidden,id,itemid,itemprop,itemref,itemscope,itemtype,lang,style,title,trans
a	download,href,hreflang,referrerpolicy,rel,target
area	alt,coords,download,href,hreflang,rel,shape,target
audio	autoplay,controls,crossorigin,loop,muted,preload,src
col	span
colgroup	span
details	open
img	alt,crossorigin,decoding,height,ismap,loading,referrerpolicy,sizes,src,srcset,usemap,width
map	name
ol	reversed,start,type
source	media,sizes,src,srcset,type
style	media

Save | Save and close

```
class Input

    /**
     * Encode a string using the input encoding algorithm
     */
    public static function encodeInput(string $value, InputEncodingMode $mode, bool $
    {
        // Normalize newlines
        $value = preg_replace('(\r\n?)', "\n", $value);

        // Replace null bytes with U+FFFD Replacement Character
        $value = str_replace("\0", "\u{FFFD}", $value);

        $value = match ($mode)
        {
            InputEncodingMode::encodeAll => str_replace(
                array('#', '<', '>', '(', ')', '\\', '=', '"', "'"),
                array('&#35;', '&#60;', '&#62;', '&#40;', '&#41;', '&#92;', '&#61;',
                $value,
            ),
            InputEncodingMode::sanitizeHtml => static::stripTags($value, Config::get(
            InputEncodingMode::encodeLessThanSign => str_replace('<', '&#60;', $value
            InputEncodingMode::encodeNone => $value,
```