Status	Finished
Started	Wednesday, 21 October 2026, 11:16 PM
Completed	Wednesday, 21 October 2026, 11:22 PM
Duration	5 mins 57 secs
Grade	**14.00** out of 15.00 (**93.33**%)

Question **1**

Correct

Mark 1.00 out of 1.00

What will be the Output of the following code?
dl={1:10, 2:20, 3:30, 4:40}
d2={5:50, 6:60, 7:70}
dl.update (d2)
print (dl)

a. {1:10, 2: 20, 4: 40, 5: 50, 6: 60, 7: 70}

b. {1: 10, 2: 20, 3: 30, 4: 40, 5: 50, 6: 60, 7: 70} ✓

c. [1: 10, 2: 20, 3: 30, 4: 40, 5: 50, 6: 60, 7: 70]

d. [(1, 10), (2, 20), (3, 30), (4, 40), (5, 50)]

Question **2**

Correct

Mark 1.00 out of 1.00

Which of the following is used to delete an element from Dictionary?

a. remove

b. None of the mentioned

c. pop ✓

d. delete

Question **3**

Correct

Mark 1.00 out of 1.00

To obtain the number of entries in dictionary which command is used?

a. size(d)

b. d.size()

c. d.len()

d. len(d) ✓

Question **4**

Correct

Mark 1.00 out of 1.00

The key-value pair in dictionary is called _____.

a. pair item
b. paired value
c. value
d. item ✓

Question **5**

Correct

Mark 1.00 out of 1.00

Dictionaries in python are _____.

a. Mutable data type
b. Non-Mutable data type
c. Both Mutable data type and Mapping data type ✓
d. Mapping data type

Question **6**

Correct

Mark 1.00 out of 1.00

Following statement return values in the form of: D1.keys() # D1 is a dictionary

a. list ✓
b. string
c. dictionary
d. tuple

Question **7**

Correct

Mark 1.00 out of 1.00

1,2,3 are the _____ in the following dictionary. D = {1 : "One", 2 : "Two", 3 : "Three"}

a. Values
b. Keys ✓
c. Items
d. None of the mentioned

Question **8**

Correct

Mark 1.00 out of 1.00

Traversing a dictionary can be done using _____.

- a. loop ✓
- b. None of the mentioned
- c. jump statement
- d. if statement

Question **9**

Correct

Mark 1.00 out of 1.00

Both keys and values are unique in dictionary.

- a. True
- b. False ✓

Question **10**

Correct

Mark 1.00 out of 1.00

What does the following code print?

```
names = {'Janice': 5, 'Emily': 3, 'John': 7, 'Eleanor': 2}
list_o_names = []
names['Emily'] += 10
names['Erik'] = 22

for name in names:
    if names[name] > 5:
        list_o_names.append(name)
print(list_o_names)
```

- a. ['Janice', 'Emily', 'John']
- b. ['Janice', 'Emily', 'John', 'Eleanor']
- c. ['Janice', 'John', 'Erik']
- d. ['Emily', 'John', 'Erik'] ✓

Question **11**

Correct

Mark 1.00 out of 1.00

Which of the following function create a dictionary from a sequence of key-value pairs

a. create
b. dict ✓
c. dictionary
d. convert

Question **12**

Correct

Mark 1.00 out of 1.00

Suppose d = {"john":40, "peter":45}, to delete the entry for "john" what command do we use?

a. d.delete("john":40)
b. d.delete("john")
c. del d["john"] ✓
d. del d("john":40)

Question **13**

Correct

Mark 1.00 out of 1.00

_____ datatype fall under mapping.

a. String
b. List
c. Tuple
d. Dictionary ✓

Question **14**

Correct

Mark 1.00 out of 1.00

All elements in dictionary are separated by _____.

a. Colon (
b. Comma(,) ✓
c. dot(.)
d. Semicolon(;)

Question **15**

Incorrect

Mark 0.00 out of 1.00

What will be the output of the following Python code snippet?

```
a={}
a['a']=1
a['b']=[2,3,4]
print(a)
```

a. {'b': [2], 'a': [3]}

b. {'b': [2, 3, 4], 'a': 1}

c. {'b': [2], 'a': 1} ✕

d. Error