AQUARIUM

Aquarium Installation Guide

Setting up a new Aquarium server, step by step

Updated 2026-11-01

Contents

About this guide

1. What you need before you start

- 1.1 A server
- 1.2 Two domain names (DNS)
- 1.3 Ports
- 1.4 Accounts you will need later

2. Installing Aquarium

- 2.1 Log in to the server
- 2.2 Get Aquarium and check the server
- 2.3 Run the installer
- 2.4 What the installer does
- 2.5 When it finishes

3. First owner setup

4. The Get ready checklist

5. Adding AI model providers and API keys

6. Inviting people

7. Connecting Gmail, Google Calendar and Drive (Google OAuth)

- Step A — create the Google client (owner, once, about 10 minutes)
- Step B — connect a Google account (each person)
- Email polling for Gmail

8. Connecting other mailboxes (IMAP / SMTP)

- Email polling for IMAP / SMTP mailboxes
- The assistant's mailbox tool

9. Messaging channels

- 9.1 Telegram
- 9.2 WhatsApp
- 9.3 Other platforms

10. Extra tools, VPN and network folders

11. Backups

- 11.1 Offsite backups (from the app — recommended)
- 11.2 Local backups (from the server)

12. Updating Aquarium

- 12.1 Servers installed from a git clone
- 12.2 Servers installed from a release

13. Troubleshooting

13.1 First step: run the doctor

13.2 Services

13.3 Common problems

14. Security notes

About this guide

This guide is for the person who sets up and looks after an Aquarium server (the **operator**). You do not need to be a developer. You do need to be comfortable typing commands into a Linux terminal over SSH.

When you finish, you will have:

- an Aquarium server running on its own virtual machine (VM),
- a web address where your team signs in (the **app**, for example `https://home.example.com`),
- a second web address for the operator dashboard (for example `https://dash.example.com`),
- an **owner** account with two-factor login, an AI model key, and backups.

All host names in this guide are examples. Replace `home.example.com`, `dash.example.com` and `203.0.113.10` with your own values.

> **Words used in this guide**
>
> - **Owner** — the one person who can change everything in an Aquarium.
> - **Admin, member, viewer** — the other roles (see the User Guide).
> - **agent-home** — the Aquarium web app your team uses in the browser.
> - **Dashboard** — a secondary console for the operator.
> - **Profile** — one independent assistant (its own memory, skills and conversations). Most servers have one, called `default`.

1. What you need before you start

1.1 A server

Item	Minimum	Recommended
Operating system	Ubuntu 24.04 LTS (64-bit, x86_64), fresh install	same
CPU	4 vCPU	8 vCPU
Memory (RAM)	8 GB	16 GB
Disk	80 GB (the installer refuses to start with less than 25 GB free)	160 GB SSD
Network	a public IPv4 address	same
Access	SSH login as `root`, or a user that can run `sudo`	SSH key login

Notes:

- The automated install test uses a 4 vCPU / 8 GB / 80 GB cloud VM, so this is the smallest size known to work. Choose the recommended size for a team.
- The server needs outbound internet access during installation (Ubuntu packages, Docker images, GitHub, the Hugging Face embedding model of about 2.3 GB) and afterwards (your AI provider, Google, Telegram and so on).
- Use a **dedicated** VM. The installer turns on the firewall, creates service accounts and takes over ports 80 and 443.

1.2 Two domain names (DNS)

Aquarium is reached through two names. Both must point at the server's public IP address **before** you install, so that free HTTPS certificates can be issued automatically (by Caddy, using Let's Encrypt).

Name (example)	Used for	DNS record
`home.example.com`	the app (agent-home) your team uses	`A` record → `203.0.113.10`
`dash.example.com`	the operator dashboard	`A` record → `203.0.113.10`

How to check: on your own computer run `nslookup home.example.com` and confirm it shows the server's IP address. DNS changes can take up to an hour.

> **No domain yet?** You can install without domains. Aquarium then listens only on the server itself (`http://127.0.0.1:3100`) and you reach it through an SSH tunnel. You can add a domain later from the first-run setup page (step 5, "Web address").

1.3 Ports

Port	Open to the internet?	Why
22 (SSH)	yes	so you can log in
80 (HTTP)	yes	certificate checks and redirect to HTTPS
443 (HTTPS)	yes	the app and the dashboard
everything else	**no**	internal services listen on `127.0.0.1` only

The installer configures the Ubuntu firewall (`ufw`) for you: it allows only SSH, 80 and 443. If your cloud provider has its own firewall, open the same three ports there.

1.4 Accounts you will need later

You can collect these after the installation:

- **An AI model provider account and API key** (required) — for example OpenRouter, Anthropic, OpenAI, DeepSeek or Google Gemini.
- **A Google account that can create Google Cloud projects** (optional) — for Gmail, Google Calendar and Google Drive.
- **Email server details** (optional) — for non-Gmail mailboxes over IMAP/SMTP.
- **A Telegram account** and/or **a dedicated WhatsApp phone number** (optional).
- **S3-compatible storage** such as Backblaze B2 or Amazon S3 (strongly recommended) — for offsite backups.

2. Installing Aquarium

Installing takes three commands and about 20–35 minutes, most of it spent downloading.

2.1 Log in to the server

```
ssh root@203.0.113.10
```

2.2 Get Aquarium and check the server

```
git clone https://github.com/leolau/aquarium.git && cd aquarium
./install-aquarium.sh --check
```

`--check` is a read-only **preflight**. It changes nothing and does not need `sudo`. It checks the operating system, CPU, memory, free disk, ports 80/443 and DNS. Fix anything it reports:

- It **fails** when another program already uses port 80 or 443. Caddy needs both ports to get the HTTPS certificates.
- It **warns** when a domain name does not resolve yet, or points at a different server. Fix the DNS record (section 1.2) and wait before you install with that domain.

2.3 Run the installer

```
sudo ./install-aquarium.sh
```

When you run it from a clone, the installer installs **that clone**: it is copied to `/opt/data/hermes-agent` together with its git history. Nothing else is downloaded from GitHub Releases. `--from-checkout` does the same thing explicitly.

The questions it asks (once)

The first time you run it in a terminal, the installer asks for the instance settings, checks them, and saves them in `/etc/aquarium/aquarium.conf`:

Setting	Option	Environment variable	Default
Organisation name	`--org-name`	`AQUARIUM_ORG_NAME`	`Aquarium`
App host name (agent-home)	`--home-domain`	`AQUARIUM_HOME_DOMAIN`	none: no HTTPS, local only

Setting	Option	Environment variable	Default
Dashboard host name	`--dashboard-domain`	`AQUARIUM_DASHBOARD_DOMAIN`	none
Owner login	`--owner-id`	`AQUARIUM_OWNER_ID`	`admin`
Owner email (contact for the HTTPS certificates)	`--owner-email`	`AQUARIUM_OWNER_EMAIL`	none

If a setting is given in more than one place, this order wins: command-line option, then environment variable, then the saved `aquarium.conf`, then your answer to the question, then the default.

Without questions (for scripts): `--yes` never asks. Defaults fill in anything you leave out:

```
sudo ./install-aquarium.sh --yes --org-name "Example Org" \
  --home-domain home.example.com --dashboard-domain dash.example.com \
  --owner-email it@example.com
```

Running it again is safe. Re-runs read `/etc/aquarium/aquarium.conf` and ask nothing. Existing secrets, data and `config.yaml` are kept. To change a setting later (for example to add a domain), edit `/etc/aquarium/aquarium.conf` or pass the option, then run `sudo ./install-aquarium.sh` again.

Other ways to install

Option	What it installs	Use it for
(none, run from a clone) or `--from-checkout`	the clone you are in (not signature-checked)	a new instance from a git clone
`--version v1.2.0`	exactly that signed GitHub release	installing a known, verified version
`--channel stable` / `--channel beta`	the newest signed release on that channel (beta includes release candidates)	release-based servers
`--from-branch develop`	a fresh git checkout of a branch (not signature-checked)	development and test servers only

Releases are verified before they are installed. The installer checks a cryptographic signature (cosign) and a checksum, and stops if either does not match. Installs from a clone are not signature-checked, so only use a clone you trust.

Without a clone: the script can also be piped straight from GitHub. It then installs the newest stable release:

```
curl -fsSL https://raw.githubusercontent.com/leolau/aquarium/develop/install-aquarium.sh \
  | sudo AQUARIUM_HOME_DOMAIN=home.example.com \
         AQUARIUM_DASHBOARD_DOMAIN=dash.example.com \
         bash -s -- --channel stable
```

More settings

Setting	Default	Meaning
`AQUARIUM_ROOT`	`/opt/data`	where data and settings live. **Keep the default** if you want to update with `aquarium-update.sh` (section 12): git updates only work with `/opt/data`.
`AQUARIUM_SKIP_EMBED_MODEL=1`	off	do not download the 2.3 GB search model now (faster, but memory search needs it later)

2.4 What the installer does

You do not need to do any of this by hand; it is listed so you know what is on the server:

1. Checks the server (Ubuntu, root, at least 25 GB free disk).
2. Installs system packages, Docker, Node.js 22, `uv` (Python), and Caddy (web server with automatic HTTPS). Turns on automatic Ubuntu security updates, the firewall, and a 4 GB swap file if there is none. Warns about weak SSH settings (it never changes SSH itself).
3. Creates two service accounts: `hermes` (runs Aquarium) and `hermes-tools` (runs the commands the assistant types, so they cannot read Aquarium's secrets).
4. Generates all passwords and keys and stores them in `/opt/data/aquarium-secrets.env` (readable by root only).
5. Copies your clone into place (or downloads and verifies the release).
6. Starts a private, self-hosted Supabase database (Docker), creates the database tables and the first owner.
7. Installs the local embedding service (used to search memory).
8. Installs the services, starts them, configures Caddy for your two domains, and runs health checks.

Running the installer again is safe: it keeps existing secrets, data and settings.

2.5 When it finishes

At the end the installer prints health checks and a summary, for example:

```
==> Health checks
  ok    service hermes-embed active
  ok    service hermes-dashboard active
  ok    service hermes-gateway active
  ok    service app-mcp active
  ok    service agent-home active
  ok    supabase containers healthy
  ok    postgres reachable (pooler)
  ok    agent-home :3100/login
  ok    dashboard :9119
  ok    embedding :8791
  ok    https://home.example.com/login

Aquarium installed for Example Org (home.example.com).
  Owner setup : open this one-time link within 24 hours to set the owner's email and
password:
                https://home.example.com/setup#token=…
                New link (cancels the old one): sudo -u hermes -H bash -c '…hermes setup-
link …'
  Settings    : /etc/aquarium/aquarium.conf (domains, owner; re-runs reuse it)
  Secrets     : /opt/data/aquarium-secrets.env (root only); service env files in
/etc/aquarium/*.env (root only)
  Models      : add your model provider API key(s) (e.g. OPENROUTER_API_KEY=...) to
                /opt/data/hermes-home/.env, then: systemctl restart hermes-gateway hermes-
dashboard
  Health      : sudo aquarium doctor    Logs: sudo aquarium logs [service]
  Update      : sudo /opt/data/hermes-agent/scripts/aquarium-update.sh develop
```

- Every line should say `ok`. If any line says `FAIL`, see Troubleshooting.
- **Copy the Owner setup link now.** It works once and expires after 24 hours. Treat it like a password: whoever opens it first becomes the owner.
- **Secrets** (database passwords, keys) are in `/opt/data/aquarium-secrets.env` and `/etc/aquarium/*.env`, readable by root only. `aquarium.conf` and the clone contain nothing secret.

3. First owner setup

Open the setup link from the installer in your browser. The **Set up Aquarium** page takes about 5 minutes and has five steps.

1. **Owner account.** Enter your work email and a password of at least 12 characters (a short sentence works well). This email and password are your login from now on. The same password is also set for the operator dashboard.
2. **Two-factor login (recommended).** Leave it on. After you press *Finish setup* the page shows a QR code: scan it with an authenticator app (Google Authenticator, Microsoft Authenticator, 1Password…), type the 6-digit code, then **save the recovery codes** somewhere safe. Each recovery code lets you in once if you lose your phone.
3. **AI model.** Choose a provider (OpenRouter, Anthropic, OpenAI, DeepSeek or Google), paste your API key and press **Test**. Aquarium sends one short message; you should see "✓ Works". You can skip this and add the key later.
4. **Region and language.** Check the time zone (used for reminders and schedules).
5. **Web address (optional).** If you installed without a domain, type the name you want to use and press **Check**. Aquarium tells you whether the name points at the server and whether HTTPS is ready.

Press **Finish setup**. You land on the **Get ready** checklist (section 4).

The link expired or was lost

Create a new link on the server (a new link cancels the old one):

```
sudo -u hermes -H bash -c 'set -a; . /opt/data/hermes.env; set +a; \
  /opt/data/hermes-agent/.venv/bin/hermes setup-link --origin https://home.example.com'
```

Signing in later

Go to `https://home.example.com/login`, enter your email and password, then the 6-digit code from your authenticator app.

4. The Get ready checklist

Everything starts empty after a fresh install. **Settings → Get ready** is a checklist of what is set up and what is left. Each item shows *Done*, *Needs attention* or *Not started*, has a **Set up** button that opens its settings inline, and a **Test** button. **Test everything** checks all items at once.

Group	Item	Who
Basics	Owner account and two-factor login	owner
Basics	AI model provider key	owner, admins
Basics	People and roles	owner, admins
Your connections	Google (Gmail, Calendar, Drive)	each person
Your connections	WhatsApp	each person
Your connections	Telegram	each person
Your connections	Email (IMAP / SMTP)	each person
Your connections	Extra tools (MCP servers)	each person
Your connections	Office network: VPN and network folders	each person
Keep it safe	Backups	owner
Keep it safe	Security basics	owner, admins

"Your connections" are personal: every person gets their own list and sets up their own. Owner and admins only see *whether* each person is set up, never their keys, messages or files.

The rest of this chapter walks through each item.

5. Adding AI model providers and API keys

Aquarium needs at least one AI model provider before the assistant can answer.

From the app (recommended):

1. Open **Settings → Get ready → AI model provider key → Set up**, or open **Models** from the menu (System group).
2. Choose the provider and paste the API key from the provider's website.
3. Press **Test**. The key is checked with the provider before it is saved and is never shown again.

On the **Models** page the owner and admins can also choose which model is used for the main chat and for background tasks, add backup models, and see 30-day usage.

From the server (alternative): API keys are secrets and live in the profile's `.env` file. Add a line such as `OPENROUTER_API_KEY=…` to `/opt/data/hermes-home/.env`, then restart:

```
sudo systemctl restart hermes-gateway hermes-dashboard
```

Only put secrets (keys, tokens, passwords) in `.env`. Every other setting belongs in `config.yaml`.

6. Inviting people

1. Open **Users** (System group of the menu).
2. Enter the person's email, display name and role (admin, member or viewer). You cannot make someone owner here; ownership is changed on the server.
3. Aquarium shows a **one-time activation link**. Copy it and send it to the person. It is shown only once; if it is lost, make a new one (the old one stops working).
4. The person opens the link and chooses their own password. Nobody else ever sees it.

To add many people at once, use **CSV import** with the columns `email,display,role`. Aquarium previews every row before you apply it and shows the activation links in order.

If someone forgets their password, they press **Can't sign in?** on the login page; an administrator then gets a one-time link to hand over.

7. Connecting Gmail, Google Calendar and Drive (Google OAuth)

Google only lets an app read Gmail, Calendar and Drive if the app is registered in Google Cloud. Each Aquarium registers its **own** Google client, so your data never passes through anyone else's account. This has two steps.

Step A — create the Google client (owner, once, about 10 minutes)

Open **Settings → In&Out → Google** (or Get ready → Google → Set up). The page lists six steps, each with a button that opens the right Google Cloud page. Tick each step when you finish it.

1. **Create a Google Cloud project**, for example named "Aquarium". Use a Google account that can create projects (a Workspace admin is best).
2. **Turn on the Google APIs:** Gmail, Calendar, Drive, People, Sheets, Docs.
3. **Set up the consent screen** (Google Auth Platform → Branding): app name, support email, developer contact email. - *Audience:* choose **Internal** if everyone uses your company's Google Workspace. Otherwise choose **External**, add your colleagues as test users, then press **Publish app** so connections don't expire after 7 days. - Your team will see "Google hasn't verified this app". That is expected for your own company's app: click *Advanced → Go to Aquarium*.
4. **Add the permissions (scopes):** Data access → Add or remove scopes → paste the scopes Aquarium shows (use **Copy all**) → Update → Save.
5. **Create the OAuth client:** Clients → Create client → Application type **Desktop app** → name "Aquarium" → Create → **Download JSON**.
6. **Give the client to Aquarium:** drop the downloaded `client_secret_….json` file on the page (or paste the client ID and secret) and press **Save and test**. You should see "✓ Google accepted this client".

If you chose *Web application* instead of *Desktop app*, add `http://localhost:4321` under *Authorized redirect URIs*.

Step B — connect a Google account (each person)

1. Open **Settings → In&Out → Connected accounts**.
2. Choose which services to enable (Email, Calendar, Drive, Full workspace).
3. Open the Google consent link, sign in, and approve.
4. The browser ends on a `localhost` address that does not load — this is expected. Copy the whole address from the browser's address bar and paste it back into Aquarium.
5. Aquarium shows which Google account and permissions were granted. Check it is the right account.

Email polling for Gmail

For a Google account connected with the Mail permission, the owner sees an **Email polling** switch next to it in Connected accounts. When it is on, Aquarium regularly checks that inbox and files new mail into the person's Inbox for triage. Without the Mail permission, email polling stays off.

8. Connecting other mailboxes (IMAP / SMTP)

For mailboxes that are not Gmail (Microsoft 365/Outlook, your hosting provider, your company mail server):

1. Open **Settings → In&Out → Email (IMAP / SMTP) → Add mailbox**.
2. Choose a provider preset (Gmail, Outlook or Other). Presets fill in the server names and ports.
3. Enter the email address, user name, incoming server (IMAP), outgoing server (SMTP), ports, security (SSL/TLS or STARTTLS) and the password. *Gmail and Outlook need an app password when 2-step sign-in is on.*
4. Press **Save and test**. Aquarium logs in to both servers; no mail is sent. The mailbox shows *Working*, *Needs attention* (with the reason) or *Not tested yet*.

Each mailbox is private to the person who added it. The password is stored on the server and never shown again (leave the field empty when editing to keep it).

Email polling for IMAP / SMTP mailboxes

IMAP/SMTP mailboxes get the same install-wide polling as Gmail. The **owner** sees an **Email polling** checkbox under each of their own mailboxes in **Settings → In&Out → Email (IMAP / SMTP)**. It is hidden from everyone else.

- Tick it to add the mailbox to the server's email poller. The first time, the hint "(adds a poller entry for this mailbox)" appears next to it.
- The poller logs in with the mailbox's saved password and sends new mail through the full email pipeline (triage, to-dos and escalations), the same way as Gmail polling.
- The password stays in the credential store. It is never copied into the poller's settings file.
- Untick it to stop polling.

The checkbox only appears when the server has an email poller configuration.

The assistant's mailbox tool

The assistant has a built-in `email_mailbox` tool. With it, each person can ask the assistant to list, search, read, send, reply to, file and flag mail in the mailboxes **they** saved. It only ever uses the mailboxes of the person it is working for, and it logs in without showing the password to the model or the terminal. It asks the person to confirm recipients and content before it sends anything.

9. Messaging channels

9.1 Telegram

Each person can have their own Telegram bot that answers only them.

1. In Telegram, message **@BotFather**, send `/newbot`, answer the questions and copy the token it gives you (looks like `123456789:AA…`).
2. In Aquarium open **Settings → In&Out → Telegram**, paste the token and press **Save and test**.
3. Press **Link my Telegram account**, open the link, press **Start** in Telegram, then come back and press **Check**.

From then on the bot answers only that Telegram account. Owner and admins can also link Telegram user IDs to members in **Telegram links** in the same section; messages from unlinked IDs are treated as anonymous.

9.2 WhatsApp

WhatsApp works through a "bridge" linked to a phone, like WhatsApp Web.

1. Open **Settings → In&Out → WhatsApp**, type a name for the phone (lowercase letters, digits and hyphens, e.g. `work`) and press **Add bridge**.
2. On the phone: WhatsApp → Settings → Linked devices → Link a device, and scan the QR code shown in Aquarium.
3. Press **Send test** to send yourself a message.

Use a **dedicated business phone number**. Aquarium reads and sends messages as that number, and WhatsApp may block numbers that behave like bots. On the server each bridge runs as a service named `hermes-wa-bridge@<name>`.

9.3 Other platforms

The Aquarium messaging gateway (`hermes-gateway`) is based on Hermes Agent, which also supports Discord, Slack, Signal, Matrix and other platforms. These are configured on the server rather than in the app; see the Hermes messaging documentation in `website/docs/user-guide/messaging/` of the repository.

10. Extra tools, VPN and network folders

- **Tools & Integrations** (Settings): the MCP servers and tool groups the assistant can use. Owner and admins can enable, disable, test, remove, and re-authenticate (for example Canva). Members and viewers can view them.
- **Your own tools** (Get ready → Extra tools): each person can add their own MCP servers (for example Notion), visible only to them.
- **Office network (VPN):** Settings → In&Out → Private networks. Add a Fortinet SSL-VPN login so Aquarium can reach files on an office file server; then add network folders under Files.
- **What each role can use** (Settings → Tools & Integrations): which tool groups and files each role's assistant may use.
- **Menu** (Settings): which launcher items each role sees.
- **Websites behind a login:** the built-in `auth-web-crawler` skill lets people have the assistant sign in to a website and read it (see the User Guide). No setup is needed. Logins are kept in the credential store (`web-login/<site>`). Like every web tool, it refuses private and intranet addresses (`10.x`, `192.168.x`, `localhost`). If people need it for intranet sites, set `security.allow_private_urls: true` in the profile's `config.yaml` (`/opt/data/hermes-home/config.yaml`) and restart `hermes-gateway` and `hermes-dashboard`.

11. Backups

There are two layers of backup. Set up both.

11.1 Offsite backups (from the app — recommended)

1. Open **Settings → Get ready → Backups → Set up** (owner only).
2. Choose the storage: Backblaze B2, Amazon S3 or other S3-compatible storage. Enter the bucket name, key ID and secret key (and the storage address for "other").
3. Choose **Back up every night**, the time, and how many days to keep copies.
4. Press **Save and test**, then **Run first backup**.
5. **Save the backup key** that is shown. Copies are encrypted with it, and you need it to open them if the server is lost. It is shown only once.
6. Press **Restore test**. It unpacks the latest copy into a scratch area and compares it; your live data is not touched.

The checklist warns when the last good copy is more than two days old or a restore test failed.

11.2 Local backups (from the server)

```
sudo aquarium backup                 # encrypted backup to /var/backups/aquarium/
sudo aquarium backup --to /mnt/usb   # somewhere else
sudo aquarium restore <file> --test  # check a backup opens, change nothing
sudo aquarium restore <file> --yes   # put a backup back (takes a safety backup first)
```

The backup key is `/etc/aquarium/backup.key`. **Keep a copy of it off the server**, together with `/opt/data/aquarium-secrets.env`, in a password manager. Without the key a backup cannot be opened.

12. Updating Aquarium

12.1 Servers installed from a git clone

```
sudo /opt/data/hermes-agent/scripts/aquarium-update.sh           # the branch that was
installed
sudo /opt/data/hermes-agent/scripts/aquarium-update.sh develop   # or name a branch
```

The script fetches the branch from the clone's `origin`. It refuses to run if there are local edits that would be overwritten. It then rebuilds what changed, restarts the services and checks them.

> **Limit:** this git update path only works when Aquarium was installed with the default data folder `/opt/data`. If you installed with a different `AQUARIUM_ROOT`, update by running `git pull` in your own clone and then `sudo ./install-aquarium.sh` again.

`git pull` + re-running `sudo ./install-aquarium.sh` also works on default installs. It copies the updated clone and rebuilds.

12.2 Servers installed from a release

Check what is installed and whether an update is available:

```
sudo aquarium status
```

Install the newest release on your channel:

```
sudo aquarium update                    # newest on the configured channel
sudo aquarium update --version v1.3.0   # a specific release
sudo aquarium update --channel beta     # switch to the beta channel
```

`aquarium update` makes a backup first. It then downloads and verifies the signed release, switches to it, restarts the services and runs health checks. If the checks fail, it rolls back to the previous release automatically. On a release install, `aquarium-update.sh` hands over to `sudo aquarium update`.

13. Troubleshooting

13.1 First step: run the doctor

```
sudo aquarium doctor
```

It checks everything and prints a plain-language **Fix:** line under each problem. **Settings → Get ready → Security basics → Test** runs read-only security checks from the app.

13.2 Services

Service	What it does	Listens on (local only)
`agent-home`	the web app	127.0.0.1:3100
`hermes-dashboard`	the AI layer API and operator dashboard	:9119 (closed by firewall)
`hermes-gateway`	messaging (Telegram, WhatsApp, email…), schedules	—
`app-mcp`	tools for apps the assistant builds	127.0.0.1:9220/9221
`hermes-embed`	local embedding model for memory search	127.0.0.1:8791
`hermes-wa-bridge@<name>`	one per linked WhatsApp phone	—
`caddy`	HTTPS for your two domains	80, 443
Docker `supabase-*`	the database (Postgres) and its services	127.0.0.1:5432/8000

Useful commands:

```
sudo aquarium status                    # version and the state of every service
sudo systemctl status agent-home        # one service in detail
sudo systemctl restart hermes-gateway   # restart one service
sudo aquarium logs                      # recent logs of all services
sudo aquarium logs gateway -f           # follow one service's log
sudo journalctl -u agent-home -n 200    # the same with journalctl
sudo docker ps                          # database containers (all should be "healthy")
```

Quick health checks from the server:

```
curl -sf -o /dev/null http://127.0.0.1:3100/login && echo app ok
curl -s -o /dev/null -w '%{http_code}\n' http://127.0.0.1:9119/   # 200, 302 or 401 is
fine
```

13.3 Common problems

Symptom	Likely cause	What to do
`--check` fails on port 80 or 443	another web server (e.g. nginx, apache) is running	stop and disable it, then re-run `--check`
`--check` warns about DNS	the domain does not point at this server yet	fix the A record, wait, re-run `--check`
Installer stops with "need >= 25 GB free disk"	disk too small	use a bigger disk
`aquarium-update.sh` says "git updates support AQUARIUM_ROOT=/opt/data only"	installed with a non-default data folder	`git pull` in your clone and re-run `sudo ./install-aquarium.sh`
`https://home.example.com` does not load; certificate errors	DNS does not point at the server yet, or ports 80/443 closed at the cloud firewall	check `nslookup`, open 80/443, then `sudo systemctl restart caddy`
Health check `FAIL` for one service	the service did not start	`sudo aquarium logs <service>`; fix, then re-run the installer (it is safe)
"This setup link is not valid"	expired (24 h) or already used	create a new link (section 3)
The assistant does not answer	no model key, or the key is wrong	Get ready → AI model → Test; check the provider account has credit
Google: "redirect_uri_mismatch"	client type is Web application	use Desktop app, or add `http://localhost:4321` as redirect URI
Google connection stops after 7 days	consent screen is External and not published	press **Publish app** in Google Cloud
Mailbox "Needs attention"	wrong password, or app password required	create an app password at your mail provider and edit the mailbox
WhatsApp bridge "stopped" or QR old	phone unlinked or bridge stuck	press **Restart**, or **Rebind** to scan a new QR

Symptom	Likely cause	What to do
Lost the owner's two-factor phone	—	sign in with a recovery code, then turn two-factor off and on again

14. Security notes

- **Keep the setup link, activation links and backup key private.** Each one grants access.
- **Turn on two-factor login** for the owner and every admin.
- **Only ports 22, 80 and 443** should be reachable from the internet. Do not open 3100, 5432, 8000, 9119 or other internal ports.
- **Use SSH keys**, not passwords, for server login. The installer warns about weak SSH settings but never changes them for you.
- **Secrets live in root-only files:** `/opt/data/aquarium-secrets.env`, `/etc/aquarium/*.env`, `/etc/aquarium/backup.key`. Do not copy them into chat, email or tickets.
- **The assistant's commands run as a separate account** (`hermes-tools`) that cannot read Aquarium's secrets or database passwords.
- **Personal connections stay personal.** Each person's Google, email, WhatsApp, Telegram, tools and VPN are visible and usable only by them.
- **Updates are signed.** Only install releases through the installer or `aquarium update`, which verify the signature.
- **Automatic security updates** for Ubuntu are turned on by the installer. Reboot the server from time to time when Ubuntu asks for it.
- **Removing Aquarium:** `sudo aquarium uninstall` (keeps data unless you add `--purge-data`).