Vibrant EMR HL7 Order (ORM^O01) - Field Reference

Version 2 (2026-10). Describes what Vibrant's order intake actually reads. Fields not listed under a segment are ignored; you may send them, but they have no effect.

Example message

```
MSH|^~\&|EPIC|CLINIC001|IN OFFICE|LC|202501220952||ORM^O01|MSG20250122095201001|P|2.5|
PID|1|PAT123456|||Smith^John^Michael||19850315|M|||123 Main Street^^Anytown^CA^90210||5551234567|||||||john.smith@email.
com|
IN1|1|C|
ORC|NW|ORD20250122001|||||||||1234567890^Johnson^Robert^^^^^^N|
OBR|1|ORD20250122001||VAREQUISTION463^Gut Zoomer 5.0^L|||202501220951||||N||Not Specified^||0|1234567890^Johnson^Robert^
^^^^^N|||FASTING|
DG1|1||K59.00|
DG1|2||R19.7|
OBR|2|ORD20250122001||VATEST70^Vitamin D, 25-OH^L|||202501220951||||N||Not Specified^||0|1234567890^Johnson^Robert^^^^^^
N|||NON-FASTING|
DG1|3||E55.9|
```

The test codes above are real, orderable codes. For your menu, use only codes from the current Vibrant compendium.

MSH - Message Header

Field	Example	Meaning
MSH-3	`EPIC`	Sending application.
MSH-4	`CLINIC001`	Sending facility. Not used for routing unless your onboarding contact tells you otherwise.
MSH-5	`IN OFFICE`	Fixed value. Send as shown. Not read.
MSH-6	`LC`	Fixed value. Send as shown. Not read.
MSH-7	`202501220952`	Message date/time, YYYYMMDDHHMM.
MSH-9	`ORM^O01`	Message type.
MSH-10	`MSG20250122095201001`	Message control ID. Must be unique per message: a control ID that already produced an order is not processed again.
MSH-11 / MSH-12	`P` / `2.5`	Send as shown. Not read.

PID - Patient

Field	Example	Meaning
PID-2	`PAT123456`	Your patient ID.
PID-5	`Smith^John^Michael`	`Last^First^Middle`.
PID-7	`19850315`	Date of birth, YYYYMMDD.
PID-8	`M`	Gender, M/F/U.
PID-10		Race (optional).
PID-11	`123 Main Street^^Anytown^CA^90210`	`Street^^City^State^ZIP`.
PID-13	`5551234567`	Phone.

Field	Example	Meaning
PID-16		Marital status (optional).
PID-19	(empty)	**SSN only.** Leave empty unless you are sending an SSN. Anything here is stored as the SSN.
PID-20	`john.smith@email.com`	**Patient email.** The only field email is read from.

Patients are matched within the practice on first name, last name, gender and date of birth. PID-3 and PID-18 are not read.

IN1 - Who pays

Field	Example	Meaning
IN1-2	`C`	`C` = charge the practice's default payment method on file. Any other value, or no IN1 segment = the patient receives a payment link.

Insurance is not billed through the HL7 order.

ORC - Common Order

Field	Example	Meaning
ORC-1	`NW`	New order.
ORC-2	`ORD20250122001`	Your order number.
ORC-12	`1234567890^Johnson^Robert^^^^^^N`	Ordering provider (XCN), see below.

Ordering provider (ORC-12, same value in OBR-16)

Component	Example	Meaning
1	`1234567890`	**Provider NPI.** This is what identifies the order. (A value of 7 digits or fewer is read as a Vibrant customer ID instead.)
2	`Johnson`	Family name. Used in error messages only.
3	`Robert`	Given name. Used in error messages only.
9	`N`	Identifier type. Not read.

The provider must have a Vibrant account **and** be set up on your integration before their orders are accepted. Orders from a provider who is not set up are held as "customer not found".

OBR - One per test

Field	Example	Meaning
OBR-2	`ORD20250122001`	Same as ORC-2.
OBR-4	`VAREQUISTION463^Gut Zoomer 5.0^L`	`Code^Name^L`. Only component 1 (the code) is used. The code must exist in the current compendium and be orderable, otherwise the order is held.
OBR-7	`202501220951`	Collection date/time, YYYYMMDDHHMM. Used as the sample's collection time. Leave empty to use the time we receive the file.
OBR-11	`N`	Send as shown. Not used.

Field	Example	Meaning
OBR-15	`0`	Send as shown. Not read.
OBR-16		Same XCN as ORC-12.
OBR-19	`FASTING`	FASTING / NON-FASTING. Optional; currently informational only.

Code formats: `VAREQUISTION...` (panels), `VATEST...` (individual tests), `discountpanel...` (bundles), `VACP...` (custom panels).

DG1 - Diagnosis codes

Field	Example	Meaning
DG1-1	`1`	Sequence number.
DG1-3	`K59.00`	ICD-10 code (component 1 is read).

All DG1 segments in the message apply to the whole order. Grouping them under a specific OBR is not preserved.

File handling

- Place each order as one `.hl7` file in the order folder agreed for your integration. Files are picked up every 15 minutes.
- **A file name is processed only once.** To resend a corrected order, use a new file name and a new MSH-10.

Set at onboarding, not in the HL7

- Kit delivery / draw location (kit shipped to the patient, or supplied by the office): set per provider.
- Order summary PDF: on request, a PDF is placed on your SFTP for every order we receive, in a folder you choose.
- Result delivery (ORU^R01) folder and format.