

## Lesson 5

### Cairo Language part 2

#### Builtins revisited

Builtins are predefined optimized low-level execution units which are added to the Cairo CPU board to perform predefined computations which are expensive to perform in vanilla Cairo

The available builtins are

1. output - to output values, these are seen by the verifier.
2. signature - to allow checking of ecdsa signatures.
3. bitwise - to carry out bitwise operations on felts
4. pedersen - to supply the pedersen hash function.
5. range check - to compare integers and check they fall in a certain range.

They have their own area of memory set aside for their use, and hence need implicit arguments in functions.

To use the builtins you need to specify them at the beginning of your program, for example

```
%builtins output pedersen range_check ecdsa bitwise
```

#### Implicit argument example

```
// Use the output builtin.
%builtins output

// Import the serialize_word() function.
from starkware.cairo.common.serialize import serialize_word

func main{output_ptr: felt*}() {
    tempvar x = 10;
    tempvar y = x + x;
    tempvar z = y * y + x;
    serialize_word(x);
    serialize_word(y);
    serialize_word(z);
}
```

```
    return ();  
}
```

From [documentation](#)

```
from starkware.cairo.common.cairo_builtins import HashBuiltin  
  
func hash2{hash_ptr: HashBuiltin*}(x, y) -> (z: felt) {  
    // Create a copy of the reference and advance hash_ptr.  
    let hash = hash_ptr;  
    let hash_ptr = hash_ptr + HashBuiltin.SIZE;  
    // Invoke the hash function.  
    hash.x = x;  
    hash.y = y;  
    // Return the result of the hash.  
    // The updated pointer is returned automatically.  
    return (z=hash.result);  
}
```

The curly braces declare `hash_ptr` as an *implicit argument*. This automatically adds an argument **and** a return value to the function. If you're using the high-level `return` statement, you don't have to explicitly return `hash_ptr`. The Cairo compiler just returns the current binding of the `hash_ptr` reference.

## Revoked references

The compiler substitutes a reference with the thing it refers to, but it may find a situation where it doesn't know how to do this.

For example is we have

```
let a = [ap -1];
```

and later in our code we use `a`, it will substitute that with `[ap -1]`

In order to do this, it needs to understand how `ap` will change, and it may not be able to do this unambiguously.

From the [documentation](#)

"If there is a label or a call instruction between the definition of a reference that depends on `ap` and its usage, the reference may be *revoked*, since the compiler may not be able to compute the change of `ap` (as one may jump to the label from another place in the program, or call a function that might change `ap` in an unknown way)."

The way to solve this is to use local variables which depend on `fp` rather than `ap` for example

```
local a = 13
```

in order to use local variables we must explicitly add

```
alloc_locals;
```

---

## Loops / Recursion

---

Although loops are possible in Cairo, they are restricted in what they can do and so instead we use recursion.

Loops will be fully supported in Cairo v 1.0

For an example of recursion see the [cairo playground Recursion challenge](#)

## Error Messages / Scope Attributes

See [documentation](#)

Scope attributes are specified for a code block by surrounding it with the `with_attr` statement

```
with_attr attribute_name("Attribute value"){  
    # Code block.  
}
```

The attribute value must be a string, and can refer to local variables only. Referring to a variable is done by putting the variable name inside curly brackets (e.g., `"x must be positive. Got: {x}."`).

At present, only one attribute is supported by the Cairo runner: `error_message`. It allows the user to annotate a code block with an informative error message. If a runtime error originates from a code wrapped by this attribute, the VM will automatically add the corresponding error message to the error trace.

## Strings

---

Strings are not natively supported as a datatype, since everything fundamentally is a felt.

We can create string [literals](#)

```
[ap] = 'hello';
```

which the compiler encodes into a felt

```
[ap] = 0x68656c6c66;
```

There is a utility scripts to convert strings into a felt in our [repo](#)

## Useful Libraries

---

Import the libraries using this format

```
from starkware.cairo.common.bitwise import bitwise_operations
```

## 1. `Math.cairo`

- `assert_not_zero()`.
- `assert_not_equal()`.
- `assert_nn()`.
- `assert_le()`.
- `assert_lt()`.
- `assert_nn_le()`.
- `assert_in_range()`.
- `assert_le_250_bit()`.
- `split_felt()`.
- `assert_le_felt()`.
- `abs_value()`.
- `sign()`.
- `unsigned_div_rem()`.
- `signed_div_rem()`.

## 2. Common Library

- `alloc`.
- `bitwise`.
- `cairo_builtins`.
  - This has structs
    - `BitwiseBuiltin`
    - `HashBuiltin`
    - `SignatureBuiltin`
- `default_dict`.
- `dict`.
- `dict_access`.
- `find_element`.
- `set`.

## 3. Bool comparison of felts

- `equal`
- `either`
- `both`
- `neither`
- `not`

#### 4. Uint256

This has a struct to hold the values and 2 operations on the values

- `Uint256`
- `uint256_add()`
- `uint256_mul()`

The value is split into 2 parts high and low with

Low = least significant u251, High. =. most significant u251

We need the implicit argument `range_check_ptr` for the functions.

Functions include

- `uint256_check`
- `uint256_add`
- `uint256_mul`
- `uint256_sqrt`
- `uint256_lt`
- `uint256_le`
- `uint256_unsigned_div_rem`

See the repo for others

Example of using Uint256 in Cairo

```
%builtins output range_check

from starkware.cairo.common.uint256 import (uint256_add, Uint256,
uint256_mul)
from starkware.cairo.common.serialize import serialize_word

func main{output_ptr : felt*, range_check_ptr}(){
    alloc_locals;
    local num1 : Uint256 = Uint256(low=0,high=10);
    local num2 : Uint256= Uint256(low=0,high=3);
    let (local mul_low : Uint256, local mul_high : Uint256) =
uint256_mul(num1, num2);
    serialize_word(mul_high.low);
    return ();
}
```

#### 5. Felt Packing

The idea of this library is to be able to store multiple smaller felts into one bigger felt.

As an example it is possible to store 62 felt of size 8 bits (0-255) into one unique felt.

