

Technical & Product Blueprint

Implementation Checkpoint

Update to the September 2026 pre-documentation

Checkpoint date: 6 September 2026

1. Executive checkpoint

The project has advanced from a visual/architectural proof into a working private SaaS foundation. Real user registration, email verification, login sessions, protected routes, mandatory onboarding, multi-tenant workspace structures and a real Fanvue OAuth connector are now implemented or actively being validated.

- Private GitHub repository remains the source of truth; main branch is used for the demo deployment.
- The demo is deployed at `demo.maconfeccoes.com.br` with environment-specific production variables.
- The login and onboarding flow are functional in production.
- Fanvue consent is opening successfully; callback and account-persistence flow are in active validation.
- The login visual direction now includes a premium technology hero background in `public/monitor_hero.png`.

2. Current implementation status

Area	Status	Notes
Project / Git	Operational	Private repository connected; checkpoint work is on main.
Next.js / TypeScript	Operational	Next.js 16.3.4 build passes locally.
Internationalization	Operational foundation	en-US, pt-BR, es-ES and fr-FR routing/messages are present; newer onboarding/auth strings still need translation cleanup.
PostgreSQL / Neon	Operational	Prisma 8 contract workflow verified against the active database.
Authentication	Operational	Sign-up, Argon2 password hashing, email verification, login and HttpOnly session cookie are implemented.
Protected app area	Operational foundation	Authenticated /app route exists; full dashboard remains pending.
Onboarding	Implemented visually	Welcome, Workspace, Creators and Platforms steps exist. Workspace/creator onboarding persistence still needs completion.
PlatformAccount model	Operational	Database model added and synchronized to Neon.

Fanvue OAuth	In validation	Authorization page opens and consent works. Token exchange was corrected to client_secret_basic. Latest known blocker is OAuth state mismatch when environments are mixed.
Vault / media	Pending	Not yet implemented.
Scheduler / queue / workers	Pending	Not yet implemented.
Analytics	Pending	Planned; product implementation deferred.

3. Authentication & security implementation

- User sign-up API validates input with Zod.
- Passwords are hashed using Argon2id.
- New accounts are created as PENDING until email verification succeeds.
- Email verification tokens are generated securely, hashed before persistence and expire after a limited window.
- Transactional email uses Resend with the verified maconfeccoes.com.br sending domain.
- Login creates a server-side Session record and sets an HttpOnly cookie named creator_session.
- Protected routes resolve the session by hashing the cookie token and validating user/session status and expiration.
- Login attempts and audit-log structures are present.
- 2FA/TOTP, recovery flow UX, rate limiting and logout/session-management UX remain future work.

4. Mandatory onboarding flow

Users with an incomplete workspace onboarding state are routed to a mandatory onboarding flow before the main workspace.

- Step 1 - Welcome / setup introduction.
- Step 2 - Workspace configuration (name, operation type, timezone).
- Step 3 - Creator setup (individual creator or agency-managed creator list).
- Step 4 - Platform connections, with at least one verified connection required.
- Step 5 - Connection check / finish (still to be implemented).

Onboarding state is stored at Workspace level through onboardingStatus and onboardingCompletedAt. The current Workspace and Creator forms still need persistence APIs.

5. Platform connector layer - Fanvue

Fanvue is the first real connector selected for the POC because it exposes an official OAuth/API path.

- Fanvue developer app created using a KYC-verified Creator account.
- App type configured as off-platform with the temporary demo domain.
- Production redirect URI: <https://demo.maconfeccoes.com.br/api/platforms/fanvue/callback>.
- OAuth start route generates cryptographically random state and PKCE verifier/challenge values.
- Temporary OAuth values are stored in HttpOnly cookies.
- Callback validates state and PKCE before token exchange.

- Fanvue requires client_secret_basic for the current OAuth client; callback was corrected accordingly.
- Access and refresh tokens are designed to be encrypted with AES-256-GCM before database persistence.
- PlatformAccount stores external account identity, connection status, token expiry, verification timestamps and error fields.
- Unsupported connectors remain INTEGRATION_PENDING; Fanvue is AVAILABLE.

Latest known test state: Fanvue consent opened successfully and the creator accepted authorization. A subsequent callback reported FANVUE_OAUTH_STATE_INVALID. The most likely cause observed during testing was starting the OAuth flow from localhost while Fanvue returned to the production demo domain. The next validation must run entirely as demo -> Fanvue -> demo, with a single Connect click.

6. Production deployment findings

- Hostinger initially kept an older successful deployment online because a newer commit failed during build.
- The build failure was caused by RESEND_API_KEY not being available to the build environment at that time.
- After production environment variables were configured, the same commit deployed successfully.
- The production database initially lacked public.platformAccount; Prisma db update synchronized the schema.
- APP_URL must be environment-specific: localhost locally and the demo domain on Hostinger.
- FANVUE_REDIRECT_URI in production must exactly match the redirect registered in Fanvue.
- Hostinger may expose 0.0.0.0:3000 internally; external redirects must be built from APP_URL instead of request.url.

7. Environment separation

Variable	Local development	Demo / production
APP_URL	http://localhost:3000	https://demo.maconfeccoes.com.br
FANVUE_REDIRECT_URI	Local HTTPS callback to be configured later	https://demo.maconfeccoes.com.br/api/platforms/fanvue/callback
DATABASE_URL	Active Neon database	Same active Neon database for current demo
RESEND_API_KEY	Local secret	Hostinger environment secret
FANVUE_CLIENT_ID	Local config/secret	Hostinger environment config/secret
FANVUE_CLIENT_SECRET	Local secret	Hostinger environment secret
FANVUE_TOKEN_ENCRYPTION_KEY	Local secret	Hostinger environment secret

Secrets must never be committed to Git. The .env file remains local; production values live in the hosting environment.

8. Database model additions

- Workspace.onboardingStatus - current onboarding stage.
- Workspace.onboardingCompletedAt - completion marker.
- PlatformAccount.workspaceId / creatorId - tenant and creator ownership.
- PlatformAccount.platform / status - connector identity and connection state.

- External account identifiers and display information.
- Encrypted access/refresh token fields and token expiration.
- lastVerifiedAt, lastSyncAt, lastErrorCode and lastErrorMessage.

Connection states are designed around DISCONNECTED, CONNECTING, CONNECTED, ERROR, EXPIRED and REVOKED.

9. Visual design checkpoint

The premium dark direction remains approved. A new technology-focused login hero was generated and saved as public/monitor_hero.png. It uses an exploded-view workstation concept with media cards, data layers and distribution cues.

- Dark navy/graphite foundation.
- Subtle cyan/violet lighting.
- Technology and creator-workflow imagery without third-party brand logos.
- Intended for the left side of the split login page under a dark overlay.

10. Current project structure additions

```
creator-platform/
├─ app/
│  └─ [locale]/
│     └─ app/page.tsx
│     └─ login/page.tsx
│     └─ onboarding/
│        └─ page.tsx
│        └─ workspace/page.tsx
│        └─ creators/page.tsx
│        └─ platforms/page.tsx
│     └─ sign-up/page.tsx
│     └─ verify-email/page.tsx
├─ api/
│  └─ auth/
│     └─ platforms/
│        └─ fanvue/
├─ public/
│  └─ monitor_hero.png
├─ src/lib/
├─ src/prisma/
└─ docs/
```

11. Immediate next steps

1. Run a clean Fanvue OAuth test entirely in production: demo -> Fanvue -> demo.
2. Confirm PlatformAccount is persisted with status CONNECTED and the card shows a verified connection.
3. Implement token refresh and connection re-verification.
4. Persist Workspace and Creator onboarding form data to the database.

5. Create onboarding connection-check and finish steps; set onboardingCompletedAt.
6. Replace the /app placeholder with the first real internal workspace/dashboard shell.
7. Implement logout and basic session management.
8. Finish translation coverage for all newly added auth/onboarding messages.
9. Begin Media Vault model and upload strategy after the first connector is proven.
10. Implement scheduler, queue and worker execution for the POC distribution test.

12. POC success gate

The core success criterion remains unchanged: upload or select one media asset once, schedule it for at least one real connected platform, execute the publication through the connector, and store a verifiable final status.

- Authentication and tenant foundation: largely proven.
- Real connector authorization: partially proven; final persistence confirmation pending.
- Media Vault: pending.
- Scheduler/worker publication: pending.
- Investor-ready end-to-end distribution demonstration: not yet complete.