

Orgs

The orgs index is responsible for holding details related to organizations. API Clients can use these endpoints to find orgs, follow and update their details.

Methods

Get Orgs

Retrieves orgs from the collection, ordering them by number of followers.

```
GET /orgs?name=xyz
```

- Request:
 - Query parameters(optional)
 - name: can be used to search an org by its name
 - Body: none
- Response:
 - Success:
 - Status code: 200
 - Content-Type: application/json
 - Body example:

```
{
  "status": "success",
  "body": [
    {
      "_id": "5f2d643c2004be5f80ec1bd2",
      "following": {},
      "followers": {
        "5f2d64442004be5f80ec1bd3": "volunteer"
      },
      "name": "New org",
      "description": "description",
      "phone": "123456789",
      "siteLink": "www.org.pt",
      "facebookLink": "www.facebook.com",
      "linkedinLink": "www.linkedin.com",
      "nrFollowing": 0,
      "nrFollowers": 1
    },
    {
      "_id": "5f2d64382004be5f80ec1bd0",
      "following": {
        "5f2d893272d0185bf0b94b7a": "volunteer",
        "5f2d64442004be5f80ec1bd3": "volunteer"
      },
      "followers": {},
      "name": "New org",
```

```
        "description": null,
        "phone": null,
        "siteLink": null,
        "facebookLink": null,
        "linkedinLink": "www.linkedin.com",
        "mail": null,
        "nrFollowing": 0,
        "nrFollowers": 0
    }
]
}
```

Get org by id

Retrieves a specific org

```
GET /orgs/:org_id
```

- Request:
 - Path parameters:
 - org_id: id of org
 - Body: none
- Response:
 - Success:
 - Status code: 200
 - Content-Type: application/json
 - Body example:

```
{
  "status": "success",
  "body": {
    "_id": "5f2d64382004be5f80ec1bd0",
    "following": {
      "5f2d893272d0185bf0b94b7a": "volunteer",
      "5f2d64442004be5f80ec1bd3": "volunteer"
    },
    "followers": {},
    "name": "New org",
    "description": "description",
    "phone": "918312733",
    "siteLink": "www.pt.org",
    "facebookLink": "www.facebook.org",
    "linkedinLink": "www.linkedin.com",
    "mail": "mail@mail.org",
    "nrFollowing": 0,
    "nrFollowers": 0
  }
}
```

Update org

Updates the org's fields. Requires authentication by the org.

PUT /auth/orgs/:org_id

- Request:
 - Path parameters:
 - Org_id: id of org
 - Body example:

```
{
  "description": "new description",
  "linkedinLink": "www.linkedin.com/abc"
}
```

- Response:
 - Success:
 - Status code: 201
 - Content-Type: application/json
 - Body example:

```
{
  "status": "success",
  "body": {
    "message": "Profile updated",
    "success": true
  }
}
```

Follow org

Follows/unfollows an org. Requires authentication.

PUT /auth/orgs/:org_id/follow

- Request:
 - Path parameters:
 - org_id: id of org
 - Body: none
- Response:
 - Success:
 - Status code: 201
 - Content-Type: application/json
 - Body example:

```
{  
  "status": "success",  
  "body": {  
    "message": "Follow was changed.",  
    "success": true  
  }  
}
```